Attachment B; Specifications
RFx #3000006180; Freezer Repairs for DOC/Avoyelles Correctional Center

Bohn Model BZN035L6D or equal
Air-Cooled Condensing Units, 460/3/60 Voltage,
½ - 6 HP Horizontal Air Discharge, Indoor, Compressor type Scroll,
Operating Range – Low Temperature, R-404A/507, Microchannel

Performance Data: Compressor P/N ZF11K4E-TFD, Ambient Temperature 95°F,
Suction Temp -10°F, Capacity (BTUH) 15,860

Electrical Ratings: Compressor RLA 6.4, Compressor LRA 44.0,
Fan Motor Qty 2, Motor HP 1/15, Fan Motor FLA 1.0,
Air Defrost / Beacon II – MCA 15.0 and MOPD 15,
Electric Defrost – MCA 15.0 and MOPD 15

Physical Data: Height 19-1/4 in., Depth 28-1/4 in., Width 37-3/4 in., Approx Net Weight 217 lbs., Receiver 90% Full 14.0 lbs., Sound Data dBA 73

Bohn LET160BK or equal
Walk-in Unit Coolers, 208-230/1/60 Voltage,
Low Profile, Electric Defrost, FPI 6

Performance Data: Rating Point 10°F TD-20°F SST, Capacity (BTUH) 16,000, CFM 2,600

Electrical Ratings: PSC Motor, 4 fans, Motor HP 1/15, Motor Voltage 208-230/1/60, Motor Watts 364, Motor Amps 2.0, Defrost Heater Voltage 208-230/1/60, Defrost Heater Watts 3,600, Defrost Heater Amps 15.7

Physical Data: Height 15 in., Depth 14.7/8 in., Length 77 ½ in., Approx. Weight 81 lbs.

Connections Data (in.): Coil Inlet OD 1/2, Coil Inlet ODF -, Suction ID 1 1/8, External Equalizer OD ¼, Drain MPT 3/4.