ATTACHMENT B

SPECIFICATIONS

NEW TRIPLE DUAL AXLE, GOOSENECK TRAILER AND SHALL MEET OR EXCEED THE FOLLOWING SPECIFICATIONS:

GVWR: MINIMUM 43,000 LBS - MAXIMUM 47,000 LBS

GCWR: MINIMUM 33,000 LBS - MAXIMUM 37,000 LBS

DECK LENGTH: MINIMUM 23'- MAXIMUM 27'

DECK WIDTH: 8' 6" WIDE

DECK HEIGHT: MINIMUM 33" - MAXIMUM 40" (UNLOADED)

DOVETAIL LENGTH: MINIMUM 4' - MAXIMUM 5'

FRAME: 14 INCH WIDE 22LBS/FT. FLANGE H-BEAM

ANTI-TWIST: 4 .5" SCH.40 TORQUE TUBE RUNS LENGTH OF TRAILER & 3" X 4" TUBE FRAME TRUSS

FLOOR BRACES: 4" CHANNEL CROSSMEMBERS

RAMPS: 5 FT. FOLD OVER SELF CLEANING DOZER RAMPS WITH SPRING ASSIST

AXLES: QTY (3)

BRAKES: ELECTRIC BRAKES ON ALL 3 AXLES

JACKS: PAIR OF 2 SPEED DROP LEG

STEPS: (2) ONE ON EACH SIDE IN FRONT

PLUG: 7 WAY RV STYLE

SUSPENSION: MINIMUM 58,000 LBS – MAXIMUM 62,000 LBS RATED

HITCH: 3" ADJUSTABLE GOOSENECK 40,000 LBS. COUPLER

SAFETY CHAINS: 5/8" GRADE 80 HEAVY DUTY

SAFETY: ELECTRIC BRAKE-AWAY SAFETY DEVICE

FLOOR: 2" X 8" TREATED WOOD

FLOOR OVER AXLES: 1/4" DIAMOND PLATE STEEL

TIRES: 235/17.5R16, 16 PLY

WHEELS: 8 HOLE 17.5" DUAL RIMS

SPARE: FULL SIZE SPARE INCLUDED

SPARE MOUNT: STORAGE MOUNT IN TONGUE

TOOLBOX: MOUNTED UNDER TONGUE LIGHTS: RUBBER MOUNTED SEALED BEAM LED LIGHTS CONSPICUITY: REFLECTIVE TAPE AS REQUIRED BY DOTD COATING: PRIMER AND PAINTED BLACK

** UNIT PRICE TO INCLUDE COST FOR FREIGHT AND ALL DOCUMENTATION

** REGISTRATION FEES SHOULD NOT BE INCLUDED IN PRICING AS LDWF WILL DO THIS PROCESS.