

# STATE OF LOUISIANA DEPARTMENT OF TRANSPORTATION AND DEVELOPMENT TECHNICAL SPECIFICATIONS FOR

#### HYDRAULIC POWER UNIT, TRAILER MOUNTED

### SERIES NO. 205-000 EQUIPMENT SPECIFICATION 205-000A

**REV. 1/20/2023** 

#### **GENERAL**

This specification sets forth the minimum requirements for a trailer mounted hydraulic power unit to power a DOTD owned MKT V-2ESC vibratory hammer.

Equipment shall be new, a production model of current manufacture, and must meet all state and Federal safety and emission standards in effect at time of order.

#### REPRESENTATIVE SPECIFICATIONS

A Fast Flow Pumps, 125 HP Hydraulic Power Unit, with appropriate options and standard features, was used to develop these specifications and establish equivalency evaluation criteria.

Equipment of similar style, type, character, quality, features, and purpose conforming to the following detailed requirements/specifications will be considered. For evaluation purposes, bidders proposing an exception/equivalent option/feature to those specified herein, may be required to provide manufacturer/product information (catalogue sheets, detailed specifications, pictures, etc.). This information will be evaluated against the minimum requirements of this specification. Proposed submittals that are determined not to be equivalent to the established criteria will be rejected.

#### **DELIVERY & ACCEPTANCE**

Vendor shall perform a test run of each unit to verify that all features and capabilities are operating properly at time of delivery. Documentation of testing may be required prior to acceptance by the Department.

Unit(s) must be delivered completely assembled (including all components, accessories, etc.) and ready for operation without any additional preparation including, but not limited to, ensuring all fluid levels are at their full mark, fuel tank(s) is full, all necessary lubrication has been performed, etc.


Any unit delivered under this specification is subject to rejection if there is evidence of poor workmanship, by either the vendor or the original manufacturer. Noted defects and/or nonconformance findings may be corrected by the vendor. Corrections must be completed and approved by the Equipment Engineer or his representative prior to final acceptance.

Unit(s) shall be delivered "on the ground;" DOTD will not unload nor provide any unloading equipment to the vendor/delivery driver in order to offload the unit(s).

**NOTE:** The Department will have space available for equipment to be unloaded.

#### EACH UNIT MUST BE SUPPLIED WITH THE FOLLOWING DOCUMENTATION AT TIME OF DELIVERY:

- 1. Notarized Bill of Sale
- 2. Original Certificate of Origin (MSO), (no photocopy)





- 3. Dealer's Service Policy
- 4. Owner's/Operator's Manual(s)
  - a. One (1) Hardcopy
  - b. One (1) Digital Copy
    - i. Acceptable Formats: PDF delivered via USB "Flash Drive", or E-mail
- 5. Service Manual(s)
  - a. One (1) Hardcopy
  - b. One (1) Digital Copy
    - i. Acceptable Formats: PDF delivered via USB "Flash Drive", or E-mail
- 6. Build Sheet(s) as applicable
  - a. One (1) Hardcopy
  - b. Build sheets should be written in plain language (not company specific codes) and include, at a minimum, all standard & optional features of the delivered unit.

**NOTE:** Invoices will not be processed for payment until the unit(s) have been inspected by the Equipment Engineer or their representative and deemed in compliance with the specifications.

#### **BID SUBMITTALS**

Any additions, deletions, or variations from the specifications should be noted in the "Bidder's Exceptions" page of this specification. Exceptions that are noted to be less than a minimum requirement will not be accepted.

Any additions, deletions or variations from the manufacturer's standard published specifications should be noted on the "Bidder's Exceptions" page of this specification. Unless otherwise noted, any items appearing in the manufacturer's standard published specifications furnished by the Bidder are assumed to be included in the Bidder's submittal.

Bidder should note on their submittal any installation(s) to the equipment that will be performed by the vendor instead of the manufacturer.

Failure to note any specification exceptions, manufacturer specification alterations, and/or vendor installations prior to award may result in rejection of the equipment at the time of delivery.

THE NUMBER OF DELIVERY DAYS AFTER RECEIPT OF ORDER (ARO) MAY BE USED AS A FACTOR IN THE AWARD.

EQ. SPEC. **205-000A** REV. 1/20/2023



1.

## **EQUIPMENT SPECIFICATIONS**


#### **NOTICE TO BIDDERS**

Bidder should review the detailed "Equipment Specification" completely and respond to the compliance question at the end of each section by marking "X", in the space provided, for "Yes" or "No". Mark "Yes" to indicate that the equipment bid meets the section exactly as specified. Mark "No" if there are exceptions to any part of that section. Exceptions/deviations to any part of the specification are to be detailed on the "Bidder's Exceptions" page of this specification.

IN ORDER TO BE CONSIDERED FOR AWARD, BIDDER SHOULD RETURN THIS SPECIFICATION, COMPLETED IN FULL, WITH THEIR BID SUBMITTAL.

1.4.2. Hydraulic tank: 120 gallons

te: All values listed below are minimums unless noted otherwise.	
Hydraulic Power Unit	
1.1. Engine	
1.1.1. 125 HP, turbocharged diesel	
1.1.2. 4 Cylinder, liquid cooled	
1.1.3. 3.0 L displacement	
<b>1.1.4.</b> Electric start with weather safe battery box	
1.1.5. Hourmeter and Tachometer	
Comply:YesNo	
<b>1.2.</b> Pump	
<b>1.2.1.</b> Operating pressure 2500 - 3300 PSI	
<b>1.2.2.</b> 0 - 50 GPM (minimum)	
Comply:YesNo	
1.3. Hydraulics System	
1.3.1. Single circuit variable flow	
<b>1.3.1.1.</b> Hydraulic power unit controls must provide a continuous flow of fluid at the desired flow rate and/or pressure set by the operator. The attached hammer has its own controls.	
<b>1.3.2.</b> 12 volt dual fan hydraulic cooler	
<b>1.3.3.</b> 5000 PSI hydraulic gauges	
<b>1.3.4.</b> Double fuel and hydraulic filtration	
1.3.5. Pressure relief valve	
Comply:YesNo	
1.4. Capacities	
1.4.1. Fuel tank: 120 gallons	
<b>1.4.1.1.</b> Drain plugs	






# **EQUIPMENT SPECIFICATIONS**

**1.4.2.1.** Oversized clean out port and drain plugs **1.4.2.2.** Port for case drain line connection, ¾"

Comply:YesNo
1.5. Trailer
1.5.1. Power coated frame
1.5.2. Single torsion axle (7,000 lb. capacity)
1.5.3. DOT registered and approved for highway towing
1.5.4. Stop, turn, tail, and marker lights
1.5.5. Front and rear transport rings
1.5.6. Heavy duty center point lift
1.5.7. 2 5/16" ball hitch, fully adjustable
1.5.8. Jackstand
1.5.9. Safety chains
<b>1.5.10.</b> 10 ply trailer tires
<b>1.5.11.</b> Spare tire
Comply:YesNo
<b>1.6.</b> Dimensions
1.6.1.1. Length: 17 ft. overall length(max)
<b>1.6.1.2.</b> Weight: 7,000 lbs. (max, fully loaded)
Comply:YesNo
· · · ——
1.7. Accessories
1.7.1. Integrated hydraulic hose reel(s) capable of holding supply, return, and drain hoses (at least 50' of each hose)
<b>1.7.2.</b> Hoses
<b>1.7.2.1.</b> Two (2) 1" x 50' with -20 JIC female on each end
<b>1.7.2.2.</b> One (1) ¾" x 50' with -12 JIC female on each end
1.7.3. Hydraulic oil level and temperature gauges
Comply:YesNo
1.8. Paint
1.8.1. Manufacturers standard colors
Comply:YesNo





## **BIDDER'S EXCEPTIONS**

<b>Instructions:</b> Bidder should note all exceptions in space provided below. List the detail number from the aforementioned specification in the column to the left and the exception in the column to the right. Responses may be typed or hand-written. Handwritten responses must be legible. If additional space is needed, please print a duplicate copy of this sheet. "Bidder's Exceptions" page(s) should be returned with the bid submittal.	
Examples:	
1.6	Engine has 325 horsepower
1.18.3	Batteries have 2000 CCA combined.
2.2.8	Crossmembers are 4" channel on 12" centers.
Spec./Detail Reference	Exception
	·