State of Louisiana Department of Transportation and Development

APPROVED MATERIALS LIST

AGGREGATES

Aggregates from the following sources have demonstrated the capability to conform to the quality requirements of Section 1003 of the Department's Standard Specifications for Roads and Bridges, except as noted.

See 'Endnotes' and 'Notes' at the end of each section.

Water Absportion = 0.5%

Updated = 8/22/2017

A. CHERT GRAVEL AND SILICA SANDS

Chert gravels on this list have a Friction Rating of III when used as a coarse aggregate for Asphaltic Concrete. Friction Ratings are defined in Subsection 1003.06

A-1. IN-STATE PRODUCER/SUPPLIERS - BY DISTRICT

A-	·1. IIV-5 I	ATE PRODUCER/SUPPLIERS - BY DISTRICT
District 03		
APS00006160	(A309)	Dupont Sand, LLC-Carencro, LA
<u>Material</u>		Approved Uses
Sand Only		Granular Material for Subbase
Carencro		Special Embankment (non-plastic)
Spec. Gravity-	SSD = 2.62	Asphaltic Concrete
Water Absport	ion = 0.5%	Portland Cement Concrete
Updated = 8/22/2017		
APS00006550	(A308)	L & W Sand Pit, LLC-Carencro, LA
<u>Material</u>		Approved Uses
Sand Only		Granular Material for Subbase
Carencro		Special Embankment (non-plastic)
Spec. Gravity-	SSD = 2.62	Asphaltic Concrete
Water Absporti	ion = 0.5%	Portland Cement Concrete
Updated = 8/22/2017		
APS00007310	(A310)	Vermillion Shell & Limestone Co. IncMaurice, LA
<u>Material</u>		Approved Uses
Sand Only		Granular Material for Subbase
Maurice		Special Embankment (non-plastic)
Spec. Gravity-	SSD = 2.62	Asphaltic Concrete
Water Absporti	ion = 0.5%	Portland Cement Concrete
Updated = 8/22/2017		
APS00011660	(A311)	Perero Co. DBA-DND Landscape - Broussard, LA
<u>Material</u>		Approved Uses
Sand Only		Granular Material for Subbase
Broussard		Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62		Asphaltic Concrete
Water Absportion = 0.5%		Portland Cement Concrete
Updated = 8/22/2017		
APS00011760	(A312)	Lafayette Sand & Fill - Lafayette, LA
<u>Material</u>		Approved Uses
Sand Only		Granular Material for Subbase
Carencro		Special Embankment (non-plastic)
Spec. Gravity-	SSD = 2.62	Asphaltic Concrete

Portland Cement Concrete

				~ ~
	ist	ric	\+ /	ソソ
	ı 🥆 ı			רו
$\boldsymbol{-}$	ıvı		/L \	ノン

District 03	
APS00012000	Red Hawk Materials - Maurice, LA
<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Maurice	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete
Updated = 8/22/2017	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
APS00012170	Red Hawk Materials, LLC - Carencro, LA
<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Carencro	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete
Updated = 8/22/2017	
APS00012630	Glenn Lege Construction - Youngsville
<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
Water Absportion = 0.5%	Asphaltic Concrete
Updated = 1/12/2024	
APS00015080	B & D Materials, LLC - Parks, LA
<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
Water Absportion = 0.5%	Asphaltic Concrete
Updated = 4/7/2022	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of
	Class F fly ash and GGBFS with a minimum of 50% replacement)
District 04	
APS00006830 (A428)	MRH Sand & Gravel-Benton, LA
Material	Approved Uses
Gravel	Granular Material for Subbase
Benton	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.60	Asphaltic Surface Treatment
Water Absportion = 1.0%	Asphaltic Concrete
Sand	(Friction Rating = III - Coarse Agg. Only)
Benton	Portland Cement Concrete
Spec. Gravity-SSD = 2.62	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
Water Absportion = 0.5%	

			^ 4
1.1	ıctr	10t	04
-	เอน	IUL	UH

APS000070)00 (A427)	South Land Sand-Ringgold, LA	
<u>Material</u>		Approved Uses	
Gravel Only		Base & Surface Course	
Ringgol	d	Granular Material for Subbase	
Spec. C	Gravity-SSD = 2.60	Asphaltic Surface Treatment	
Water A	Absportion = 1.0%	Asphaltic Concrete	
Updated = 8/25/2017		(Friction Rating = III - Coarse Agg. Only)	

APS00011330 (A429) Blount Brothers Construction, Inc. -Shreveport, LA

Portland Cement Concrete

<u>Material</u>	Approved Uses	
Sand Only	Granular Material for Subbase	
Blout Bros. Pit	Special Embankment (non-plastic)	
Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
Water Absportion = 0.5%	Portland Cement Concrete	

Updated = 8/22/2017

APS00011910 Hat Creek Dirt Pit - Bossier City, LA

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
Water Absportion = 0.5%	Asphaltic Concrete
Updated = 2/17/2017	Portland Cement Concrete

APS00012310 SiteWurx Sand - Sibley, LA

IV	<u>laterial</u>	Approved Uses	
Sand Only		Granular Material for Subbase	
	Sibley - 164 Pit	Special Embankment (non-plastic)	
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
	Water Absportion = 0.5%	Portland Cement Concrete	

Updated = 8/22/2017

APS00012660 Skyplex Trucking -Bentley, LA

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Wallace Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete
Updated = 8/22/2017	

District 05

APS00006000 (A509) Century Ready Mix - West Monroe, LA

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Jonesboro Road	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete
11. 1. 1. 1. 0/00/0047	

			~ -
- 1)	ıctı	rict	114
\boldsymbol{L}	เอเ	IIUL	Vι

	District 05			
	APS00007270 ((A502)	Martin Marietta - Perryville,LA	
	<u>Material</u>		Approved Uses	
	Gravel		Base & Surface Course	
	Perryville		Granular Material for Subbase	
	Spec. Gravity-SS	5D = 2.54	Special Embankment (non-plastic)	
	Water Absportion	1 = 1.7%	Asphaltic Surface Treatment	
	Sand		Asphaltic Concrete	
	Perryville		(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SS		Portland Cement Concrete	
	Water Absportion	n = 0.5%		
	Updated = 8/22/2017			
	APS00014950		Star Silica LLC West Monroe, LA	
	<u>Material</u>		Approved Uses	
	Sand Only		Base & Surface Course	
	Spec. Gravity-SS	5D = 2.62	Granular Material for Subbase	
	Water Absportion	n = 0.5%	Special Embankment (non-plastic)	
	Updated = 11/24/2021		Asphaltic Surface Treatment	
			Asphaltic Concrete	
			(Friction Rating = III - Coarse Agg. Only)	
			Portland Cement Concrete - Gravel Only	
	APS00015510		G & W Sand & Gravel, LLC West Monroe	
	<u>Material</u>		Approved Uses	
	Sand Only		Granular Material for Subbase	
Spec. Gravity-SSD = 2.62			Special Embankment (non-plastic)	
	Water Absportion = 0.5%		Asphaltic Concrete	
	Updated = 6/20/2023		Portland Cement Concrete	
			(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)	
	District 07			
	APS00006130 ((A712)	DSD Energy Services-Oakdale, LA	
	<u>Material</u>		Approved Uses	
	Sand Only		Granular Material for Subbase	
	Oakdale Pit		Special Embankment (non-plastic)	
	Spec. Gravity-SS	5D = 2.62	Asphaltic Concrete	
	Water Absportion	n = 0.5%	Portland Cement Concrete	
	Updated = 8/22/2017			
	APS00006520 ((A710)	Kinder Sand CoKinder, LA	
	<u>Material</u>		Approved Uses	
	Sand Only		Granular Material for Subbase	
	Kinder		Special Embankment (non-plastic)	
	Spec. Gravity-SS	5D = 2.62	Asphaltic Concrete	
	Water Absportion	n = 0.5%	Portland Cement Concrete	
Updated = 8/22/2017			(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	

Updated = 8/3/2022

APS00007320 (A709) Village Sand, IncKinder, LA Material Approved Uses Sand Only Granular Material for Subbase Indian Village Asphaltic Concrete Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00012100 Lake Area Materials, LLC - DeRidder Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.54 Granular Material for Subbase Water Absportion = 1.7% Special Embankment (non-plastic) Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Asphaltic Concrete Water Absportion = 0.5% Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Updated = 4/13/2017 Asphaltic Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.5% Asphaltic Concrete Asphaltic Concrete Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Asphaltic Concrete	Material Approved Uses Sand Only Granular Material for Subbase Indian Village Asphaltic Concrete Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Water Absportion = 0.5% Updated = 8/22/2017 APS00012100 Lake Area Materials, LLC - DeRidder Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.54 Granular Material for Subbase Water Absportion = 1.7% Special Embankment (non-plastic) Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Asphaltic Concrete Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APPROVED Uses Sand Only Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses	District 07			
Sand Only Granular Material for Subbase	Indian Village	APS00007320 (A709)	Village Sand, IncKinder, LA		
Indian Village Asphaltic Concrete Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00012100 Lake Area Materials, LLC - DeRidder Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.54 Granular Material for Subbase Water Absportion = 1.7% Special Embankment (non-plastic) Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Asphaltic Concrete Water Absportion = 0.5% (Friction Rating = IIII - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Approved Uses Gravel Base & Surface Course Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Material Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	Indian Village Asphaltic Concrete Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 8/22/2017 APS00012100 Lake Area Materials, LLC - DeRidder Material Approved Uses Spec. Gravity-SSD = 2.54 Water Absportion = 1.7% Special Embankment (non-plastic) Asphaltic Concrete Water Absportion = 0.5% Updated = 3/21/2017 Apsonution = 0.5% Updated = 3/21/2017 Apsonution = 0.5% Updated = 3/21/2017 APS00012190 Elite Sand - Longville, LA Material Approved Uses Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Asphaltic Surface Treatment Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Sand Approved Uses Gravel Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Base & Surface Course Gravel Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	<u>Material</u>	Approved Uses		
Spec. Gravity-SSD = 2.62 Portland Cement Concrete	Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00012100 Lake Area Materials, LLC - DeRidder Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.54 Granular Material for Subbase Water Absportion = 1.7% Special Embankment (non-plastic) Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Asphaltic Concrete Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Concrete Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Caravity-SD = 2.62 Portland Cement Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Orosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 0.5% Granular Material for Su	Sand Only	Granular Material for Subbase		
Water Absportion = 0.5% Updated = 8/22/2017 APS00012100 Lake Area Materials, LLC - DeRidder Material Gravel Spec. Gravity-SSD = 2.54 Water Absportion = 1.7% Special Embankment (non-plastic) Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Updated = 4/13/2017 Portland Cement Concrete Approved Uses Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Asphaltic Surface Tourse Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Asphaltic Surface Treatment	Water Absportion = 0.5% Updated = 8/22/2017 APS00012100 Lake Area Materials, LLC - DeRidder Material Spec. Gravity-SSD = 2.54 Spec. Gravity-SSD = 2.54 Water Absportion = 1.7% Special Embankment (non-plastic) Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/22/2017 Approved Uses Sand Only Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Approved Uses Sand Only Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 4/13/2017 Approved Uses Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.5% Asphaltic Concrete Approved Uses Gravel Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 0.5% Updated = 4/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	Indian Village	Asphaltic Concrete		
Updated = 8/22/2017	Apsonular	Spec. Gravity-SSD = 2.62	Portland Cement Concrete		
Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.54 Granular Material for Subbase Water Absportion = 1.7% Special Embankment (non-plastic) Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Asphaltic Concrete Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	APS00012100 Lake Area Materials, LLC - DeRidder Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.54 Water Absportion = 1.7% Special Embankment (non-plastic) Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Welter Absportion = 0.5% Aproved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Water Absportion = 0.5% Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Concrete Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Spec. Gravity-SSD = 2.65 Granular Material for Subbase	Water Absportion = 0.5%			
Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.54 Granular Material for Subbase Water Absportion = 1.7% Special Embankment (non-plastic) Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Asphaltic Concrete Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.54 Granular Material for Subbase Water Absportion = 1.7% Special Embankment (non-plastic) Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Asphaltic Concrete Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD	Updated = 8/22/2017			
Gravel Base & Surface Course Spec. Gravity-SSD = 2.54 Granular Material for Subbase Water Absportion = 1.7% Special Embankment (non-plastic) Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Asphaltic Concrete Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	Gravel Base & Surface Course Spec. Gravity-SSD = 2.54 Granular Material for Subbase Water Absportion = 1.7% Special Embankment (non-plastic) Sand Asphaltic Concrete Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Spec. Gravity-SSD = 2.55 Granular Material for Subbase Spec. Gravity-SSD = 2.55 Granular Material for Subbase Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Spec. Gravity-SSD = 2.55 Granular Material for Subbase Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	APS00012100	Lake Area Materials, LLC - DeRidder		
Spec. Gravity-SSD = 2.54 Water Absportion = 1.7% Special Embankment (non-plastic) Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Asphaltic Concrete Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Asphaltic Surface Treatment	Spec. Gravity-SSD = 2.54 Water Absportion = 1.7% Special Embankment (non-plastic) Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Asphaltic Concrete Water Absportion = 0.5% Updated = 3/21/2017 APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Apshaltic Concrete Water Absportion = 0.5% Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Approved Uses Special Embankment (non-plastic) Approved Uses Asphaltic Concrete Updated = 4/13/2017 Aproved Uses Gravel Base & Surface Course Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Asphaltic Surface Treatment Asphaltic Concrete Pippin Pit Fippin Pit Spec. Gravity-SSD = 2.62 Applatic Surface Treatment Asphaltic Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Granular Material for Subbase Spec. Gravity-SSD = 2.55 Granular Material for Subbase Spec. Gravity-SSD = 2.62 Fortland Cement Concrete Fippin Pit Fippin Pit Firction Rating = III - Coarse Agg. Only) Approved Uses Gravel Base & Surface Course Granular Material for Subbase Spec. Gravity-SSD = 2.55 Granular Material for Subbase Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	<u>Material</u>	Approved Uses		
Water Absportion = 1.7% Special Embankment (non-plastic) Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Asphaltic Concrete Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	Water Absportion = 1.7% Special Embankment (non-plastic) Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Asphaltic Concrete Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Sand Asphaltic Surface Treatment Sand Asphaltic Surface Treatment Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Portland Cement Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Spec. Gravity-SSD = 2.55 Granular Material for Subbase Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	Gravel	Base & Surface Course		
Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Asphaltic Concrete Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.62 Asphaltic Concrete Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Sand Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Base & Surface Course Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Spec. Gravity-SSD = 2.55 Granular Material for Subbase Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	Spec. Gravity-SSD = 2.54	Granular Material for Subbase		
Spec. Gravity-SSD = 2.62 Asphaltic Concrete Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Sand Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Gravel Base & Surface Course Gravity-SSD = 2.55 Granular Material for Subbase Spec. Gravity-SSD = 2.55 Granular Material for Subbase Spec. Gravity-SSD = 2.55 Granular Material for Subbase Spec. Gravity-SSD = 2.55 Special Embankment (non-plastic)	Water Absportion = 1.7%			
Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	Water Absportion = 0.5% (Friction Rating = III - Coarse Agg. Only) Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Sand Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Spec. Gravity-SSD = 2.55 Granular Material for Subbase Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 0.5% Valuer Absportion = 0.5% Approved Uses Gravel Base & Surface Course Water Absportion = 1.0% Special Embankment (non-plastic)				
Updated = 3/21/2017 Portland Cement Concrete APS00012190 Elite Sand - Longville, LA Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	Updated = 3/21/2017		·		
APS00012190 Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Sand Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	•	, , , , , , , , , , , , , , , , , , , ,		
MaterialApproved UsesSand OnlyGranular Material for SubbaseSpec. Gravity-SSD = 2.62Special Embankment (non-plastic)Water Absportion = 0.5%Asphaltic ConcreteUpdated = 4/13/2017Portland Cement ConcreteAPS00012390Gator Aggregates - Deridder, LAMaterialApproved UsesGravelBase & Surface CoursePippin PitGranular Material for SubbaseSpec. Gravity-SSD = 2.53Special Embankment (non-plastic)Water Absportion = 2.2%Asphaltic Surface Treatment	Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Sand Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	Updated = 3/21/2017	Portland Cement Concrete		
Sand Only Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	Sand Only Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Sand Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	APS00012190	Elite Sand - Longville, LA		
Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	Spec. Gravity-SSD = 2.62 Special Embankment (non-plastic) Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Sand Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	<u>Material</u>	Approved Uses		
Water Absportion = 0.5% Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Concrete Portland Cement Concrete Portland Cement Concrete Approved Uses Special Embankment Approved Uses Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment	Water Absportion = 0.5% Asphaltic Concrete Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Sand Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	<u>-</u>	Granular Material for Subbase		
Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	Updated = 4/13/2017 Portland Cement Concrete APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Sand Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	•			
APS00012390 Gator Aggregates - Deridder, LA Material Approved Uses Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	APS00012390 Gator Aggregates - Deridder, LA Material Gravel Base & Surface Course Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Sand Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	•	•		
MaterialApproved UsesGravelBase & Surface CoursePippin PitGranular Material for SubbaseSpec. Gravity-SSD = 2.53Special Embankment (non-plastic)Water Absportion = 2.2%Asphaltic Surface Treatment	MaterialApproved UsesGravelBase & Surface CoursePippin PitGranular Material for SubbaseSpec. Gravity-SSD = 2.53Special Embankment (non-plastic)Water Absportion = 2.2%Asphaltic Surface TreatmentSandAsphaltic ConcretePippin Pit(Friction Rating = III - Coarse Agg. Only)Spec. Gravity-SSD = 2.62Portland Cement ConcreteWater Absportion = 0.5%Updated = 8/22/2017APS00014360Arcosa Aggregates - Anacoco Plant 1391-MerryvilleMaterialApproved UsesGravelBase & Surface CourseSpec. Gravity-SSD = 2.55Granular Material for SubbaseWater Absportion = 1.0%Special Embankment (non-plastic)	Updated = 4/13/2017	Portland Cement Concrete		
Gravel Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	Base & Surface Course	APS00012390			
Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	Pippin Pit Granular Material for Subbase Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Sand Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	<u>Material</u>			
Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment	Spec. Gravity-SSD = 2.53 Special Embankment (non-plastic) Water Absportion = 2.2% Asphaltic Surface Treatment Sand Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	Gravel	Base & Surface Course		
Water Absportion = 2.2% Asphaltic Surface Treatment	Water Absportion = 2.2% Asphaltic Surface Treatment Sand Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	• •			
·	Sand Asphaltic Concrete Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	· · · · · · · · · · · · · · · · · · ·			
Sand Asphaltic Concrete	Pippin Pit (Friction Rating = III - Coarse Agg. Only) Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	·	·		
	Spec. Gravity-SSD = 2.62 Portland Cement Concrete Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)		·		
, , ,	Water Absportion = 0.5% Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	• •	, ,		
,	Updated = 8/22/2017 APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	•	Portland Cement Concrete		
•	APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville Material Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	•			
·	MaterialApproved UsesGravelBase & Surface CourseSpec. Gravity-SSD = 2.55Granular Material for SubbaseWater Absportion = 1.0%Special Embankment (non-plastic)	•			
APS00014360 Arcosa Aggregates - Anacoco Plant 1391-Merryville	Gravel Base & Surface Course Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)	APS00014360	Arcosa Aggregates - Anacoco Plant 1391-Merryville		
	Spec. Gravity-SSD = 2.55 Granular Material for Subbase Water Absportion = 1.0% Special Embankment (non-plastic)				
	Water Absportion = 1.0% Special Embankment (non-plastic)				
·	· · · · · · · · · · · · · · · · · · ·	•			
	Sand Asphaltic Surface Treatment	·			
Sand Asphaltic Surface Treatment	0 0 1 00 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		•		
•		•	·		
Spec. Gravity-SSD = 2.62 Asphaltic Concrete		Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)		
Spec. Gravity-SSD = 2.62 Asphaltic Concrete	Water Absortion = () 5% (Friction Rating = III - Coarse Agg (Only)	Vialet Absportion = 0.576	(i house rading – in Obarso ragg. Offiny)		

Portland Cement Concrete

District 07	
APS00014370	Arcosa Aggregates - Indian Village Plant 1284
<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
Water Absportion = 0.5%	Asphaltic Concrete
Updated = 7/29/2022	Portland Cement Concrete
APS00014470	Merryville Aggregate, LLC - Evans, LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.56	Granular Material for Subbase
Water Absportion = 1.2%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = $2/12/2021$	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
APS00014890	Magic Sand and Gravel - Longville
<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
Water Absportion = 0.5%	Asphaltic Concrete
Updated = 5/7/2024	
APS00014960	Arcosa Aggregates - West Merryville, LA
<u>Material</u>	Approved Uses
Sand Only	Base & Surface Course
Spec. Gravity-SSD = 2.62	Granular Material for Subbase
Water Absportion = 0.5%	Special Embankment (non-plastic)
Updated = 7/17/2023	Asphaltic Surface Treatment
	Asphaltic Concrete
	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete
APS00015140	Arcosa Aggregates - Plant LA 1343 - DeRidder
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.57	Granular Material for Subbase
Water Absportion = 0.7%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 5/4/2022	Portland Cement Concrete

			~~
1)	ıctr	ict	$^{\prime}$
-	เอน	IUL	w

	District 08			
	APS00007150 (A	\844)	Tanner Heavy Equipment Co-Leesville, LA	
	<u>Material</u>		Approved Uses	
	Sand Only		Granular Material for Subbase	
	Tanner Pit #2		Special Embankment (non-plastic)	
	Spec. Gravity-SSD		Asphaltic Concrete	
	Water Absportion = 0.5%		Portland Cement Concrete	
	Updated = 8/25/2017			
	APS00007300 (A	\822)	Martin Marietta - Woodworth, LA	
<u>Material</u>			Approved Uses	
	Gravel		Granular Material for Subbase	
	Spec. Gravity-SSD		Special Embankment (non-plastic)	
	Water Absportion =	= 1.7%	Asphaltic Surface Treatment	
	Sand		Asphaltic Concrete	
	Spec. Gravity-SSD		(Friction Rating = III - Coarse Agg. Only)	
	Water Absportion =	= 0.5%	Portland Cement Concrete	
	Updated = 8/22/2017		(Gravel from this source contains an unusual amount of hematite iron ore, if used in Portland Cement Concrete, the hematite content cannot exceed 2%)	
	APS00011680 (A	\847)	Larry Grayson & Son Trucking, LLC -Forest Hill, LA	
	<u>Material</u>		Approved Uses	
	Gravel		Granular Material for Subbase	
	Ahtus Melder Rd P		Special Embankment (non-plastic)	
	Spec. Gravity-SSD		Asphaltic Surface Treatment	
	Water Absportion =	= 1.0%	Asphaltic Concrete	
	Sand		(Friction Rating = III - Coarse Agg. Only)	
	Ahtus Melder Rd P		Portland Cement Concrete	
	Spec. Gravity-SSD = 2.62 Water Absportion = 0.5%			
	Updated = 8/22/2017			
	•	١٥ (٥)	D: 100 ((: 0 110 D 14	
	APS00011710 (A	\849)	Diamond B Construction Co.,LLC - Boyce, LA	
	<u>Material</u>		Approved Uses	
	Sand Only		Granular Material for Subbase	
	Hot Wells / Garder		Special Embankment (non-plastic)	
	Spec. Gravity-SSD		Asphaltic Concrete	
	Water Absportion =	= 0.5%	Portland Cement Concrete	
	Updated = 8/22/2017			
	APS00011720 (A	\850)	Diamond B Construction Co., LLC Woodworth, LA	
	<u>Material</u>		Approved Uses	
	Sand Only		Granular Material for Subbase	
	Woodworth Pit		Special Embankment (non-plastic)	
	Spec. Gravity-SSD		Asphaltic Concrete	
	Water Absportion =	= 0.2%	Portland Cement Concrete	
	Updated = 5/7/2024		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)	

			\sim
1 1	istr	101	112
	1511	11.11	W

APS00014440	Cenla Materials - Forest Hill, LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.55	Granular Material for Subbase
Water Absportion = 1.5%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 8/25/2020	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)

District 58

APS00007130	(A914)	Swim Enterprises-Columbia, LA
/ \li \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	(/ () ()	OWILL ELICIPIES OCIALIDIA, EX

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Columbia	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete

Updated = 8/22/2017

APS00007290 (A913) Martin Marietta - Jena, LA

	Approved Uses
	Base & Surface Course
	Granular Material for Subbase
. Gravity-SSD = 2.55	Special Embankment (non-plastic)
r Absportion = 1.5%	Asphaltic Surface Treatment
	Asphaltic Concrete
	(Friction Rating = III - Coarse Agg. Only)
Gravity-SSD = 2.62	Portland Cement Concrete
r Absportion = 0.5%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
r	Absportion = 1.5% Gravity-SSD = 2.62

Updated = 8/22/2017

APS00011810 (A916) Amberg Construction - Olla, LA

<u>Materia</u>	<u>l</u>	Approved Uses
Gravel		Base & Surface Course
	Aimwell	Granular Material for Subbase
	Spec. Gravity-SSD = 2.53	Special Embankment (non-plastic)
	Water Absportion = 2.2%	Asphaltic Surface Treatment
Sand		Asphaltic Concrete
	Aimwell	(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete
	Water Absportion = 0.5%	

					_
	ist	ris	^+	_	u
	ı 🥆 I	111	- 1	- 1	\boldsymbol{n}
_	ıvı		_	$\mathbf{\mathcal{C}}$	v

APS00015030	Amberg Construction, LLC Olla
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.52	Granular Material for Subbase
Water Absportion = 1.8%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 4/7/2022	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
APS00015090	D & J Construction Co., LLC - Aimwell, LA
<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
Water Absportion = 0.5%	Asphaltic Concrete
Updated = 4/7/2022	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
District C4	-

District 61

APS00002200 (A628) Bear Industries - Port Allen, LA

<u>Material</u>	Approved Uses	
Sand Only	Asphaltic Concrete	
Port Allen		
Spec. Gravity-SSD = 2.62		
Water Absportion = 0.5%		

Updated = 8/22/2017

APS00005950 (A646) Bunch Sand and Gravel #1 - Clinton, LA

<u>Materi</u>	i <u>al</u>	Approved Uses	
Gravel		Base & Surface Course	
	Pit #1	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.55	Special Embankment (non-plastic)	
	Water Absportion = 1.3%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
	Pit #1	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
	Water Absportion = 0.5%		

Updated = 7/26/2018

District 61

APS0	0006180	(A636)	Feliciana Farms, IncSt. Francisville, LA
<u>Materia</u>	<u>l</u>		Approved Uses
Gravel			Base & Surface Course
	Bayou Sara		Granular Material for Subbase
	Spec. Gravity-S	SSD = 2.54	Special Embankment (non-plastic)
	Water Absporti	ion = 1.7%	Asphaltic Surface Treatment
Sand			Asphaltic Concrete
	Bayou Sara		(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-S	SSD = 2.62	Portland Cement Concrete
	Water Absporti	ion = 0.5%	
Lindatas	J 0/22/2017		

Updated = 8/22/2017

APS00006400 (A632) Hooper Road Dirt Pit-Baton Rouge, LA

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Baton Rouge	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete
Lla data d 0/00/0047	

Updated = 8/22/2017

APS00007010 (A640) Southern Aggregates, LLC-Norwood, LA

<u>Material</u>		Approved Uses	
Gravel		Base & Surface Course	
	Felps	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.53	Special Embankment (non-plastic)	
	Water Absportion = 2.2%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
	Felps	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
	Water Absportion = 0.5%		

Updated = 8/22/2017

APS00011640 (A644) Fleniken Sand & Gravel Inc - Clinton, LA

<u>Material</u>		Approved Uses	
Gravel		Granular Material for Subbase	
	Acme Pit	Special Embankment (non-plastic)	
	Spec. Gravity-SSD = 2.52	Asphaltic Surface Treatment	
	Water Absportion = 1.9%	Asphaltic Concrete	
Sand		(Friction Rating = III - Coarse Agg. Only)	
	Acme Pit	Portland Cement Concrete	
	Spec. Gravity-SSD = 2.62		
	Water Absportion = 0.5%		

Updated = 7/26/2018

		~ 4
 istr	ı^t	ムコ
ווכו	11 71	() I

District 61	
APS00011650 (A645)	Dolese Bros-St.HelenaSand&Gravel - Pine Grove, LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
St. Helena S&G Pit	Granular Material for Subbase
Spec. Gravity-SSD = 2.54	Special Embankment (non-plastic)
Water Absportion = 1.6%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
St. Helena S&G Pit	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
Updated = 6/3/2020	
APS00011920	Regional Sand & Gravel - Clinton, LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Highway 960 Pit	Granular Material for Subbase
Spec. Gravity-SSD = 2.50	Special Embankment (non-plastic)
Water Absportion = 3.0%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Highway 960 Pit	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
Updated = 8/22/2017	
APS00012530	Dennis Stewart Equipment Rental,Inc Baton Rouge,LA
<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Joor Road Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete
Updated = 8/22/2017	
APS00012910	South Louisiana Fill Materials, LLC - Darrow, LA
<u>Material</u>	Approved Uses
Sand Only	Asphaltic Concrete
Spec. Gravity-SSD = 2.62	
Water Absportion = 0.5%	
Updated = 1/5/2024	
APS00014150	Lionel Boudreaux Trucking, LLC - St. Francisville
<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
Water Absportion = 0.5%	Asphaltic Concrete
Updated = 10/16/2019	Portland Cement Concrete

	•			\sim	4
1)	101	tri	<u></u> ∩t	: 6	1
	1.7		l , I		

ADC0004.44.00	Lieu Enternisee III C. Che annuali Carriera I A
APS00014180	Ivey Enterprises, LLC - Greenwell Springs, LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.48	Granular Material for Subbase
Water Absportion = 2.7%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 10/16/2019	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
APS00014850	Superior Sand & Gravel - Plant 1 - Clinton, LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.57	Granular Material for Subbase
Water Absportion = 0.8%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 10/5/2021	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend c Class F fly ash and GGBFS with a minimum of 50% replacement)
APS00014860	Superior Sand & Gravel - Plant 2 - Clinton
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.51	Granular Material for Subbase
Water Absportion = 2.5%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 10/5/2021	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend c Class F fly ash and GGBFS with a minimum of 50% replacement)
APS00015000	Barriere Construction Co. LLC - Map Pit
<u>Material</u>	Approved Uses
Sand Only	Base & Surface Course
Spec. Gravity-SSD = 2.62	Granular Material for Subbase
Water Absportion = 0.5%	Special Embankment (non-plastic)
Updated = 3/28/2022	Asphaltic Surface Treatment
	Asphaltic Concrete
	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete - Gravel Only

	: - 4.	.: - (04
	ICTI	rict	h
\boldsymbol{L}	เอเ	IUL	v

District 61	
APS00015150	Arcosa Aggregates - Plant LA 1342 - Clinton Pit
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.52	Granular Material for Subbase
Water Absportion = 2.2%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 8/3/2022	Portland Cement Concrete
APS00015490	South Louisiana Fill Materials LLC - Convent
<u>Material</u>	Approved Uses
Sand Only	Asphaltic Concrete
Spec. Gravity-SSD = 2.62	
Water Absportion = 0.5%	
Updated = 1/5/2024	
APS00015520	Superior Sand & Gravel - Plant 3 - Greenwell Sprgs
<u>Material</u>	Approved Uses
Sand Only	Base & Surface Course
Spec. Gravity-SSD = 2.62	Granular Material for Subbase
Water Absportion = 0.5%	Special Embankment (non-plastic)
Updated = 9/19/2023	Asphaltic Surface Treatment
	Asphaltic Concrete
	Portland Cement Concrete - Gravel Only
APS00016130	Magnolia Sand Gravel Soil - Denham Springs
<u>Material</u>	Approved Uses
Sand Only	Base & Surface Course
Spec. Gravity-SSD = 2.65	Granular Material for Subbase
Water Absportion = 0.2%	Special Embankment (non-plastic)
Updated = 12/4/2024	Asphaltic Surface Treatment
	Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete - Gravel Only
A DC0004C4.40	·
APS00016140	Convent Minority Material Supplier LLC #2
<u>Material</u>	Approved Uses
Sand Only	Base & Surface Course
Spec. Gravity-SSD = 2.65	Granular Material for Subbase
Water Absportion = 0.1%	Special Embankment (non-plastic)
Updated = 12/4/2024	Asphaltic Surface Treatment Asphaltic Concrete
	· · · · · · · · · · · · · · · · · · ·
	(Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete
	mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)

District 61

APS00016210	Ivey Dirt & Aggregates - Greenwell Springs
<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Spec. Gravity-SSD = 2.65	Special Embankment (non-plastic)
Water Absportion = 0.2%	Asphaltic Concrete
Updated = 12/4/2024	

District 62

APS00005700 (AX04)	Accardo Materials, Inc-Franklinton,LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Isabel	Granular Material for Subbase
Spec. Gravity-SSD = 2.57	Special Embankment (non-plastic)
Water Absportion = 1.0%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Isabel	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)

Updated = 8/22/2017

APS00005870 (AY06) Lakeview Sand & Gravel - Bogalusa, LA

<u>Materia</u>	<u>al</u>	Approved Uses
Gravel		Base & Surface Course
	Bogalusa	Granular Material for Subbase
	Spec. Gravity-SSD = 2.47	Special Embankment (non-plastic)
	Water Absportion = 3.5%	Asphaltic Surface Treatment
Sand		Asphaltic Concrete
	Bogalusa	(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete
	Water Absportion = 0.5%	

Updated = 8/22/2017

APS00005990 (AY10) Cash Sand & Gravel, Inc.-Denham Springs, LA

<u>Materi</u>	<u>al</u>	Approved Uses	
Gravel		Base & Surface Course	
	Easterly Plant	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.54	Special Embankment (non-plastic)	
	Water Absportion = 1.5%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
	Easterly Plant	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
	Water Absportion = 0.5%		

Updated = 7/26/2018

		\sim
 ıctr	10t	62
เอเเ	11 71	\cup

APS00006060	Crawford Aggregate Industr-Pine Grove,LA - Jenkins
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Jenkins Lane	Granular Material for Subbase
Spec. Gravity-SSD = 2.54	Special Embankment (non-plastic)
Water Absportion = 1.7%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Jenkins Lane	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
Updated = $6/3/2020$	

(AX71) Daley Sand & Gravel, Inc.-Roseland, LA APS00006100

<u>Material</u>	Approved Uses
Sand Only	Base & Surface Course
Roseland	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
Water Absportion = 0.5%	Asphaltic Surface Treatment
Roseland	Asphaltic Concrete
Updated = 5/7/2024	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)

(AY17) Brownstone Sand & Gravel - Franklinton, LA APS00006170

<u>Materia</u>	<u>l</u>	Approved Uses
Gravel		Base & Surface Course
	Enon Plant - Franklinton	Granular Material for Subbase
	Spec. Gravity-SSD = 2.54	Special Embankment (non-plastic)
	Water Absportion = 1.7%	Asphaltic Surface Treatment
Sand		Asphaltic Concrete
	Enon Plant - Franklinton	(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete - Gravel Only
	Water Absportion = 0.5%	

Updated = 10/26/2021

(AY24) Florida Parishes Aggregate-Fluker, LA APS00006190

<u>Materia</u>	<u>ll</u>	Approved Uses
Gravel		Base & Surface Course
	Kent Pit - Fluker	Granular Material for Subbase
	Spec. Gravity-SSD = 2.56	Special Embankment (non-plastic)
	Water Absportion = 1.2%	Asphaltic Surface Treatment
Sand		Asphaltic Concrete
	Kent Pit - Fluker	(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete
	Water Absportion = 0.5%	

District 62

APS00006240 (AX91)	Gillman Enterprises, LLC-Independence, LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Independence	Granular Material for Subbase
Spec. Gravity-SSD = 2.52	Special Embankment (non-plastic)
Water Absportion = 2.5%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Independence	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	
Updated = 8/24/2017	
APS00006350 (AY14)	Hard Rock Sand & Gravel LLC - Franklinton, LA - #2
<u>Material</u>	Approved Uses

<u>Mater</u>	<u>ial</u>	Approved Uses	
Grave	ıl	Base & Surface Course	
	#2 - Franklinton	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.54	Special Embankment (non-plastic)	
	Water Absportion = 1.7%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
	#2 - Franklinton	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
	Water Absportion = 0.5%		

Updated = 8/24/2017

APS00006360 (AX89) Hard Rock Sand & Gravel, LLC-Mt. Hermon, LA

<u>Mater</u>	<u>ial</u>	Approved Uses	
Grave	l	Base & Surface Course	
	Mt. Hermon	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.55	Special Embankment (non-plastic)	
	Water Absportion = 1.5%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
	Mt. Hermon	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
	Water Absportion = 0.5%		

Updated = 8/24/2017

APS00006450 (AX72) Industrial Aggregates, LLC-Franklinton, LA-Pine CI

<u>Materia</u>	<u>l</u>	Approved Uses	
Gravel		Base & Surface Course	
	Spec. Gravity-SSD = 2.53	Granular Material for Subbase	
	Water Absportion = 2.2%	Special Embankment (non-plastic)	
Sand		Asphaltic Surface Treatment	
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
Updated	d = 8/24/2017	Portland Cement Concrete	

District 62

APS00006510 (AX	68) K	& C Gravei-independence,LA	
<u>Material</u>		Approved Uses	
Sand Only		Granular Material for Subbase	
Spec. Gravity-SSD =	2.62	Special Embankment (non-plastic)	
Water Absportion = 0	5%	Asphaltic Concrete	
Updated = 8/24/2017		Portland Cement Concrete	

APS00006590 (AY03) Lafarge - Holcim Aggregates - Honey Island

<u>Material</u>	Approved Uses		
Sand Only	Base & Surface Course		
Honey Island	Special Embankment (non-plastic)		
Spec. Gravity-SSD = 2.62	Asphaltic Surface Treatment		
Water Absportion = 0.5%	Asphaltic Concrete		
Honey Island	(Friction Rating = III - Coarse Agg. Only)		
Updated = 9/20/2023	Portland Cement Concrete		

APS00006600 (AY01) Lafarge Aggregates-Bogalusa,LA

Approved Uses
Base & Surface Course
Granular Material for Subbase
Special Embankment (non-plastic)
Asphaltic Surface Treatment
Asphaltic Concrete
(Friction Rating = III - Coarse Agg. Only)
Portland Cement Concrete

Updated = 8/24/2017

APS00006670 (AX43) Lon Land Gravel Co.-Mt Hermon, LA

<u>Mater</u>	<u>rial</u>	Approved Uses	
Grave	el	Base & Surface Course	
	Franklinton	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.53	Special Embankment (non-plastic)	
	Water Absportion = 2.2%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
	Franklinton	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
	Water Absportion = 0.5%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	

District 62

APS00	0006770	(A135)	Me	ars Sand & Gravel-Denham Springs,LA
<u>Material</u>				Approved Uses
Gravel				Granular Material for Subbase
	Dennis Mills			Special Embankment (non-plastic)
5	Spec. Gravity-S	SSD = 2.53		Asphaltic Surface Treatment
\	Water Absporti	on = 2.0%		Asphaltic Concrete
Sand				(Friction Rating = III - Coarse Agg. Only)
	Dennis Mills			Portland Cement Concrete
5	Spec. Gravity-S	SSD = 2.62		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
\	Water Absporti	on = 0.5%		
Updated :	= 6/3/2020			

APS00006850 (AY12) P & J Sand & Gravel, LLC-Independence, LA

<u>Materia</u>	<u>l</u>	Approved Uses
Gravel		Base & Surface Course
	Independence	Granular Material for Subbase
	Spec. Gravity-SSD = 2.48	Special Embankment (non-plastic)
	Water Absportion = 3.5%	Asphaltic Surface Treatment
Sand		Asphaltic Concrete
	Independence	(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete
	Water Absportion = 0.5%	

Updated = 8/24/2017

APS00006920 (AX29) Ram Industries-Mt. Hermon, LA

<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Franklinton	Granular Material for Subbase
Spec. Gravity-SSD = 2.55	Special Embankment (non-plastic)
Water Absportion = 1.5%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Franklinton	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
Updated = 8/24/2017	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)

APS00006990 (AX69) Smith Sand & Gravel-Franklinton, LA

<u>Materia</u>	<u>l</u>	Approved Uses
Gravel		Base & Surface Course
	Franklinton	Granular Material for Subbase
	Spec. Gravity-SSD = 2.52	Special Embankment (non-plastic)
	Water Absportion = 2.5%	Asphaltic Surface Treatment
Sand		Asphaltic Concrete
	Franklinton	(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete
	Water Absportion = 0.5%	

District 62

APS0	0007030	(AY26)	Southern Aggregates, LLC-DenhamSprings,LA-Plant7
<u>Material</u>	<u>[</u>		Approved Uses
Gravel			Base & Surface Course
	Plant #7		Special Embankment (non-plastic)
	Spec. Gravity-S	SSD = 2.52	Asphaltic Surface Treatment
	Water Absporti	on = 1.8%	Asphaltic Concrete
Sand			(Friction Rating = III - Coarse Agg. Only)
	Plant #7		Portland Cement Concrete
	Spec. Gravity-S	SSD = 2.62	
	Water Absporti	on = 0.5%	
المساسية	7/00/0040		

Updated = 7/26/2018

APS00007140 (AX96) T & D Sand & Gravel, LLC-Independence, LA

<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Amite	Granular Material for Subbase
Spec. Gravity-SSD = 2.53	Special Embankment (non-plastic)
Water Absportion = 2.2%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Amite	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	

Updated = 8/24/2017

APS00007490 (AB98) Willis Sand & Gravel-Bogalusa, LA

<u>Material</u>	Approved Uses
Gravel	Granular Material for Subbase
Sun	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.52	Asphaltic Surface Treatment
Water Absportion = 2.5%	Asphaltic Concrete
Sand	(Friction Rating = III - Coarse Agg. Only)
Sun	Portland Cement Concrete
Spec. Gravity-SSD = 2.62	
Water Absportion = 0.5%	

Updated = 8/24/2017

APS00011340 (AY29) BMS, LLC - Amite, LA

<u>Mater</u>	<u>ial</u>	Approved Uses Base & Surface Course	
Grave	l		
	Amite Pit	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.52	Special Embankment (non-plastic)	
	Water Absportion = 2.5%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
	Amite Pit	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
	Water Absportion = 0.5%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	
Updated = 8/22/2017		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	

District 62

APS00011	410	(AX75)	Hard	Rock Sand & Gravel LLC - Franklinton, LA - #1
<u>Material</u>			<u>A</u>	approved Uses
Gravel			В	ase & Surface Course
#1 Fra	nklinton		G	Granular Material for Subbase
Spec.	Gravity-	SSD = 2.51	S	pecial Embankment (non-plastic)
Water	Absport	ion = 2.5%	Д	sphaltic Surface Treatment
Sand			А	sphaltic Concrete
#1 Fra	nklinton		(1	Friction Rating = III - Coarse Agg. Only)
Spec. (Gravity-	SSD = 2.62	P	ortland Cement Concrete
Water	Absport	ion = 0.5%		Gravel from this source is potentially deleterious in Portland Cement Concrete nixes, requires 30% Class F fly ash or 50% slag to mitigate)
Updated = 8/24	/2017		,	Sand from this source is potentially deleterious in Portland Cement Concrete nixes, requires 30% Class F fly ash or 50% slag to mitigate)

APS00011460 (AY30) Hunt Gravel - Franklinton, LA

<u>Materia</u>	<u>ll</u>	Approved Uses		
Gravel		Base & Surface Course		
	Franklinton	Granular Material for Subbase		
	Spec. Gravity-SSD = 2.51	Special Embankment (non-plastic)		
	Water Absportion = 2.5%	Asphaltic Surface Treatment		
Sand		Asphaltic Concrete		
	Franklinton	(Friction Rating = III - Coarse Agg. Only)		
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete		
	Water Absportion = 0.5%			

Updated = 8/24/2017

APS00011520 (AY31) Industrial Mining Plant 5 - Tickfaw, LA

<u>Materia</u>	<u>l</u>	Approved Uses		
Gravel		Base & Surface Course		
	Black Cat Pit	Granular Material for Subbase		
	Spec. Gravity-SSD = 2.50	Special Embankment (non-plastic)		
	Water Absportion = 3.0%	Asphaltic Surface Treatment		
Sand		Asphaltic Concrete		
	Black Cat Pit	(Friction Rating = III - Coarse Agg. Only)		
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete		
	Water Absportion = 0.5%			

Updated = 8/25/2017

APS00011700 (AY34) Madden Roseland, LA Gravel Pit - Roseland, LA

<u>Material</u>		Approved Uses	
Gravel		Base & Surface Course	
F	ormerly Diamond B	Granular Material for Subbase	
S	Spec. Gravity-SSD = 2.52	Special Embankment (non-plastic)	
V	Vater Absportion = 2.1%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
F	ormerly Diamond B	(Friction Rating = III - Coarse Agg. Only)	
S	Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
V	Vater Absportion = 0.5%	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)	
F	ormerly Diamond B		

Formerly Diamond E

Updated = 1/26/2023

District 62

APS0	00011790	(AY32)	Southern Aggregates - Amite, LA - #9	
<u>Materia</u>	<u>l</u>		Approved Uses	
Gravel			Granular Material for Subbase	
	Plant #9		Special Embankment (non-plastic)	
	Spec. Gravity-S	SSD = 2.52	Asphaltic Surface Treatment	
	Water Absporti	on = 2.3%	Asphaltic Concrete	
Sand			(Friction Rating = III - Coarse Agg. Only)	
	Plant #9		Portland Cement Concrete	
	Spec. Gravity-S	SSD = 2.62		
	Water Absporti	on = 0.5%		

Updated = 8/6/2018

APS00011800 (AY33) Bunch's Sand and Gravel #2 - Greensburg, LA

<u>Materia</u>	<u>l</u>	Approved Uses		
Gravel		Granular Material for Subbase		
	Pit #2	Special Embankment (non-plastic)		
	Spec. Gravity-SSD = 2.53	Asphaltic Surface Treatment		
	Water Absportion = 1.8%	Asphaltic Concrete		
Sand		(Friction Rating = III - Coarse Agg. Only)		
	Pit #2	Portland Cement Concrete		
	Spec. Gravity-SSD = 2.62			
	Water Absportion = 0.5%			

Updated = 7/26/2018

APS00011940 Baldwin Redi-Mix Co. Inc.-Greensburg,H&LIsland Pit

<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.53	Granular Material for Subbase
Water Absportion = 1.8%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 7/26/2018	Portland Cement Concrete

APS00012340 River Road Rock - Franklinton, LA

<u>Materia</u>	<u>ıl</u>	Approved Uses Base & Surface Course	
Gravel			
	Mt. Hermon Pit	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.53	Special Embankment (non-plastic)	
	Water Absportion = 2.2%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
	Mt. Hermon Pit	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
	Water Absportion = 0.5%	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	

District 62

District 62	
APS00012420	Tate Construction, LLC - Franklinton, LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Tate Pit	Granular Material for Subbase
Spec. Gravity-SSD = 2.52	Special Embankment (non-plastic)
Water Absportion = 2.5%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Tate Pit	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	
Updated = 8/24/2017	
APS00012510	Industrial Aggregates, LLC - Covington, LA - #2
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Enon Plant #2	Granular Material for Subbase
Spec. Gravity-SSD = 2.55	Special Embankment (non-plastic)
Water Absportion = 1.5%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Enon Plant #2	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
Updated = 8/24/2017	
APS00012620	Industrial Aggregates - Franklinton, LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Pine Cliff Pit	Granular Material for Subbase
Spec. Gravity-SSD = 2.50	Special Embankment (non-plastic)
Water Absportion = 2.5%	Asphaltic Surface Treatment

<u>Material</u>		Approved 03c3	
(Gravel	Base & Surface Course	
	Pine Cliff Pit	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.50	Special Embankment (non-plastic)	
	Water Absportion = 2.5%	Asphaltic Surface Treatment	
5	Sand	Asphaltic Concrete	
	Pine Cliff Pit	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
	Water Absportion = 0.5%		

APS00013080	Northern Sand & Gravel	, L.L.C Independence
711 000010000	Tiortifori Garia & Clavor	, L.L.O. Illaopoliaolioc

<u>Materia</u>	<u>I</u>	Approved Uses	
Gravel		Base & Surface Course	
	Spec. Gravity-SSD = 2.50	Granular Material for Subbase	
	Water Absportion = 2.4%	Special Embankment (non-plastic)	
Sand		Asphaltic Surface Treatment	
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
Updated	d = 4/29/2020	Portland Cement Concrete	

District 62
APS00013250
<u>Material</u>
Gravel

/	11 0. 0 2 020. 00.1100, 220 1.10.11.111.11
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.53	Granular Material for Subbase
Water Absportion = 1.7%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 10/22/2021	Portland Cement Concrete - Gravel Only

APS00013390 L & C Gravel, LLC - Plant #6 - Fluker

<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.53	Granular Material for Subbase
Water Absportion = 1.9%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 9/12/2019	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)

APS00014300 Southern Aggregates, LLC Plant 31 - Franklinton

<u>Material</u>	Approved Uses	
Gravel	Granular Material for Subbase	
Spec. Gravity-SSD = 2.55	Special Embankment (non-plastic)	
Water Absportion = 1.5%	Asphaltic Surface Treatment	
Sand	Asphaltic Concrete	
Spec. Gravity-SSD = 2.62	(Friction Rating = III - Coarse Agg. Only)	
Water Absportion = 0.5%	Portland Cement Concrete	
Updated = 7/16/2020	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	

APS00014350 Barriere Construction Co., LLC - Independence, LA

<u>Material</u>		Approved Uses
Gravel		Base & Surface Course
	Spec. Gravity-SSD = 2.52	Granular Material for Subbase
	Water Absportion = 2.5%	Special Embankment (non-plastic)
Sand		Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated	= 7/15/2020	Portland Cement Concrete
		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)

$\overline{}$		rict	\sim
	101	~I~+	
	1 🥆 1 1		n

District 62	
APS00014410	Arcosa Aggregates - Pearl River Plant 1725
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.48	Granular Material for Subbase
Water Absportion = 3.3%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 8/3/2022	Portland Cement Concrete
APS00014780	Cash Sand & Gravel, Inc Kemp Plant -D.S., LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.52	Granular Material for Subbase
Water Absportion = 2.1%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 10/5/2021	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
APS00014990	Barriere Construction Co. LLC - Miley Pit
APS00014990 Material	Barriere Construction Co. LLC - Miley Pit Approved Uses
Material Gravel	•
Material Gravel Spec. Gravity-SSD = 2.51	Approved Uses Base & Surface Course Granular Material for Subbase
Material Gravel Spec. Gravity-SSD = 2.51 Water Absportion = 2.2%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic)
Material Gravel Spec. Gravity-SSD = 2.51 Water Absportion = 2.2% Sand	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment
Material Gravel Spec. Gravity-SSD = 2.51 Water Absportion = 2.2% Sand Spec. Gravity-SSD = 2.62	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete
Material Gravel Spec. Gravity-SSD = 2.51 Water Absportion = 2.2% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)
Material Gravel Spec. Gravity-SSD = 2.51 Water Absportion = 2.2% Sand Spec. Gravity-SSD = 2.62	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete
Material Gravel Spec. Gravity-SSD = 2.51 Water Absportion = 2.2% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)
Material Gravel Spec. Gravity-SSD = 2.51 Water Absportion = 2.2% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of
Material Gravel Spec. Gravity-SSD = 2.51 Water Absportion = 2.2% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 2/22/2022	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
Material Gravel Spec. Gravity-SSD = 2.51 Water Absportion = 2.2% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 2/22/2022 APS00015160	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) Arcosa Aggregates - Plant LA 1349 - Pearl River Approved Uses Base & Surface Course
Material Gravel Spec. Gravity-SSD = 2.51 Water Absportion = 2.2% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 2/22/2022 APS00015160 Material Gravel Spec. Gravity-SSD = 2.49	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) Arcosa Aggregates - Plant LA 1349 - Pearl River Approved Uses Base & Surface Course Granular Material for Subbase
Material Gravel Spec. Gravity-SSD = 2.51 Water Absportion = 2.2% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 2/22/2022 APS00015160 Material Gravel	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) Arcosa Aggregates - Plant LA 1349 - Pearl River Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic)
Material Gravel Spec. Gravity-SSD = 2.51 Water Absportion = 2.2% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 2/22/2022 APS00015160 Material Gravel Spec. Gravity-SSD = 2.49 Water Absportion = 3.5% Sand	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) Arcosa Aggregates - Plant LA 1349 - Pearl River Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment
Material Gravel Spec. Gravity-SSD = 2.51 Water Absportion = 2.2% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 2/22/2022 APS00015160 Material Gravel Spec. Gravity-SSD = 2.49 Water Absportion = 3.5% Sand Spec. Gravity-SSD = 2.62	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) Arcosa Aggregates - Plant LA 1349 - Pearl River Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete
Material Gravel Spec. Gravity-SSD = 2.51 Water Absportion = 2.2% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 2/22/2022 APS00015160 Material Gravel Spec. Gravity-SSD = 2.49 Water Absportion = 3.5% Sand	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) Arcosa Aggregates - Plant LA 1349 - Pearl River Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment

<u>/ (U</u>	A-1. IN-STATE PRODUCER/SUPPLIERS - BY DISTRICT		
	District 62		
	APS00015170	Arcosa Aggregates - Plant LA 1341 - Independence	
	<u>Material</u>	Approved Uses	
	Gravel	Base & Surface Course	
	Spec. Gravity-SSD = 2.50	Granular Material for Subbase	
	Water Absportion = 2.5%	Special Embankment (non-plastic)	
	Sand	Asphaltic Surface Treatment	
	Spec. Gravity-SSD = 2.62	2 Asphaltic Concrete	
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
	Updated = 5/4/2022	Portland Cement Concrete	
	APS00015200	Arcosa Aggregates - Plant LA 1345 - Franklinton	
	<u>Material</u>	Approved Uses	
	Gravel	Base & Surface Course	
	Spec. Gravity-SSD = 2.49	Granular Material for Subbase	
	Water Absportion = 2.5%	Special Embankment (non-plastic)	
	Sand	Asphaltic Surface Treatment	
	Spec. Gravity-SSD = 2.62	·	
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
	Updated = 5/4/2022	Portland Cement Concrete	
	APS00015210	Arcosa Aggregates - Plant LA 1340 - Denham Springs	
	<u>Material</u>	Approved Uses	
	Gravel	Base & Surface Course	
	Spec. Gravity-SSD = 2.52	2 Granular Material for Subbase	
	Water Absportion = 2.1%	Special Embankment (non-plastic)	
	Sand	Asphaltic Surface Treatment	
	Spec. Gravity-SSD = 2.62	2 Asphaltic Concrete	
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
	Updated = 5/4/2022	Portland Cement Concrete	
	APS00015410	Crawford Aggregate Industries - Cross Pit	
	<u>Material</u>	Approved Uses	
	Sand Only	Base & Surface Course	
	Spec. Gravity-SSD = 2.62	Granular Material for Subbase	
	Water Absportion = 0.5%	· · · · · · · · · · · · · · · · · · ·	
	Updated = 5/23/2023	Asphaltic Surface Treatment	
		Asphaltic Concrete	

(Friction Rating = III - Coarse Agg. Only)

(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of

Class F fly ash and GGBFS with a minimum of 50% replacement)

Portland Cement Concrete

 . ~ +		t 62
 ı Cı I	, 11 J	-
 		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \

	District 02	
	APS00015460	Louisiana Aggregate Materials, LLC-DenhamSprings
	<u>Material</u>	Approved Uses
Sand Only		Base & Surface Course
	Spec. Gravity-SSD = 2.62	Granular Material for Subbase
	Water Absportion = 0.5%	Special Embankment (non-plastic)
	Updated = 12/22/2023	Asphaltic Surface Treatment
		Asphaltic Concrete
		(Friction Rating = III - Coarse Agg. Only)
		Portland Cement Concrete
		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
	APS00015650	Accardo Mining, LLC Bogalusa
	<u>Material</u>	Approved Uses
	Sand Only	Base & Surface Course
	Spec. Gravity-SSD = 2.62	Granular Material for Subbase
	Water Absportion = 0.5%	Special Embankment (non-plastic)
	Updated = 10/9/2023	Asphaltic Surface Treatment
		Asphaltic Concrete
		(Friction Rating = III - Coarse Agg. Only)
		Portland Cement Concrete - Gravel Only
	APS00015670	Candies Excavation, Inc Folsom
	<u>Material</u>	Approved Uses
	Sand Only	Granular Material for Subbase
	Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
	Water Absportion = 0.5%	Asphaltic Concrete
	Updated = 1/12/2024	
	APS00015680	A-1 Aggregates - KSB Holdings, LLC - Mt. Hermon
	<u>Material</u>	Approved Uses
	Sand Only	Base & Surface Course
	Spec. Gravity-SSD = 2.62	Granular Material for Subbase
	Water Absportion = 0.5%	Special Embankment (non-plastic)
	Updated = 1/12/2024	Asphaltic Surface Treatment
		Asphaltic Concrete
		(Friction Rating = III - Coarse Agg. Only)
		Portland Cement Concrete - Gravel Only
	APS00015890	M & M Gravel - Franklinton
	<u>Material</u>	Approved Uses
	Sand Only	Base & Surface Course
	Spec. Gravity-SSD = 2.62	Granular Material for Subbase
	Water Absportion = 0.5%	Special Embankment (non-plastic)
	Updated = 3/14/2024	Asphaltic Surface Treatment
		Asphaltic Concrete
		(Friction Rating = III - Coarse Agg. Only)
		Portland Cement Concrete - Gravel Only

		\sim
 ıctı	rict	に つ
ווכו	11171	\mathbf{U}

APS00015980	River Road Materials, LLC Franklinton	
<u>Material</u>	Approved Uses	
Sand Only	Base & Surface Course	
Spec. Gravity-SSD = 2.62	Granular Material for Subbase	
Water Absportion = 0.5%	Special Embankment (non-plastic)	
Updated = 5/7/2024	Asphaltic Surface Treatment	
	Asphaltic Concrete	
	(Friction Rating = III - Coarse Agg. Only)	
	Portland Cement Concrete - Gravel Only	
. =		

APS00016070	BearCo Construction, LLC Franklinton
-------------	--------------------------------------

<u>materiai</u>	Approved Uses
Sand Only	Base & Surface Course
Spec. Gravity-SSD = 2.63	Granular Material for Subbase
Water Absportion = 4.2%	Special Embankment (non-plastic)
Updated = 9/10/2024	Asphaltic Surface Treatment
	Asphaltic Concrete
	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)

A-2. OUT-OF-STATE PRODUCERS/SUPPLIERS

Out of State

A DO00005700	(40 4 4 1)		
APS00005730	(ASAN)	Alabama Sand and Gravel-Prattville, Al	

<u>Material</u>		Approved Uses
Gravel		Base & Surface Course
	Billingsley Pit	Granular Material for Subbase
	Spec. Gravity-SSD = 2.63	Special Embankment (non-plastic)
	Water Absportion = 0.8%	Asphaltic Surface Treatment
Sand		Asphaltic Concrete
	Billingsley Pit	(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete
	Water Absportion = 0.5%	

Updated = 8/24/2017

APS00005740 (ASAV) Alliance Sand and Gravel, LLC-Phil Campbell, AL

<u>Material</u>	Approved Uses
Sand Only	Special Embankment (non-plastic)
Phil Campbell Pit	Asphaltic Concrete
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	

Out of State

APS00005750	(ASAK)	Allstate Deatsville, LLC-Deatsville, AL
-------------	--------	---

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Deatsville Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete

Updated = 8/24/2017

APS00005780 (ABAO) Arkansas Gravel Company, Inc.-Hampton, AR

<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Bradshaw Mine	Granular Material for Subbase
Spec. Gravity-SSD = 2.56	Special Embankment (non-plastic)
Water Absportion = 1.2%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Bradshaw Mine	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	

Updated = 8/24/2017

APS00005790 (AB76) B & B Gravel & Trucking Co.-Bearden, AR

<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.55	Granular Material for Subbase
Water Absportion = 1.5%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 8/24/2017	Portland Cement Concrete

APS00005830 (ASAR) Baldwin Sand & Gravel-Crystal Springs, MS

<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Crystal Springs Pit	Granular Material for Subbase
Spec. Gravity-SSD = 2.57	Special Embankment (non-plastic)
Water Absportion = 1.0%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Crystal Springs Pit	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
Updated = 8/24/2017	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)

Out of State

APS00005920	(ASAM)	Blackwell Aggregates, IncNicholson, MS	
<u>Material</u>		Approved Uses	
Gravel		Base & Surface Course	
Jackson Landin	g Pit	Granular Material for Subbase	
Spec. Gravity-S	SSD = 2.48	Special Embankment (non-plastic)	
Water Absportion	on = 3.5%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
Jackson Landin	g Pit	(Friction Rating = III - Coarse Agg. Only)	
Spec. Gravity-S	SSD = 2.62	Portland Cement Concrete	
Water Absportion	on = 0.5%		
Updated = 8/24/2017			
APS00005930	(AB31)	Blain Sand & Gravel, IncNatchez, MS	
<u>Material</u>		Approved Uses	
Gravel		Granular Material for Subbase	

Grav	vel	Granular Material for Subbase
	Coverhill Pit	Special Embankment (non-plastic)
	Spec. Gravity-SSD = 2.57	Asphaltic Surface Treatment
	Water Absportion = 1.0%	Asphaltic Concrete
Sand	d	(Friction Rating = III - Coarse Agg. Only)
	Coverhill Pit	Portland Cement Concrete
	Spec. Gravity-SSD = 2.62	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
	Water Absportion = 0.5%	

Updated = 8/24/2017

APS00005940 (AA57) Blain Sand & Gravel, Inc.-Crystal Springs, MS

<u>Material</u>	Approved Uses	
Gravel	Base & Surface Course	
Spec. Gravity-SSD = 2.54	Granular Material for Subbase	
Water Absportion = 1.7%	Special Embankment (non-plastic)	
Sand	Asphaltic Surface Treatment	
Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
Updated = $8/24/2017$	Portland Cement Concrete	

APS00006030 Cossatot Rock, LLC-Lockesburg, AR

<u>Material</u>	Approved Uses	
Gravel	Base & Surface Course	
Old Deirks Hwy Pit	Granular Material for Subbase	
Spec. Gravity-SSD = 2.54	Special Embankment (non-plastic)	
Water Absportion = 1.7%	Asphaltic Surface Treatment	
Sand	Asphaltic Concrete	
Old Deirks Hwy Pit	(Friction Rating = III - Coarse Agg. Only)	
Spec. Gravity-SSD = 2.59	Portland Cement Concrete	
Water Absportion = 1.0%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	
Updated = 8/24/2017	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	

Οu	ıt	Ωf	St	ate
\sim	IL.	VI.	-	alt

Out of State			
APS00006110	(AA80)	Dickerson & Bowen Riverside Gravel-Tylertown, MS	
<u>Material</u>		Approved Uses	
Gravel		Base & Surface Course	
McComb		Granular Material for Subbase	
Spec. Gravity-		Special Embankment (non-plastic)	
Water Absport	ion = 4.0%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
McComb		(Friction Rating = III - Coarse Agg. Only)	
Spec. Gravity-		Portland Cement Concrete	
Water Absport	ion = 0.5%		
Updated = 8/24/2017	. .		
APS00006200	(ASAT)	Foley Materials CoPhenix City, AL- Plant 501	
Material		Approved Uses	
Sand Only		Granular Material for Subbase	
Plant 501		Special Embankment (non-plastic)	
Spec. Gravity-		Asphaltic Concrete	
Water Absport	100 = 0.5%	Portland Cement Concrete	
Updated = 8/24/2017	(1.0.1.N)		
APS00006210	(ASAJ)	Foley Materials CoPhenix City, AL- Plant 505	
<u>Material</u>		Approved Uses	
Sand Only		Granular Material for Subbase	
Plant 505		Special Embankment (non-plastic)	
Spec. Gravity-		Asphaltic Concrete	
Water Absport	100 = 0.5%	Portland Cement Concrete	
Updated = 8/24/2017	/ A O A I \	Facility Count of Country AD	
APS00006230	(ASAI)	Fouke Sand & Gravel, LLC-Fouke, AR	
<u>Material</u>		Approved Uses	
Gravel	CCD 0.04	Base & Surface Course	
Spec. Gravity-		Granular Material for Subbase	
Water Absport	1011 = 0.0%	Special Embankment (non-plastic) Asphaltic Surface Treatment	
Spec. Gravity-	SSD - 2 62	Asphaltic Concrete	
Water Absport		(Friction Rating = III - Coarse Agg. Only)	
Updated = 8/24/2017	1011 - 0.070	Portland Cement Concrete	
APS00006260	(ABAK)	Green Brothers Gravel CoHazlehurst, MS	
Material	(/	Approved Uses	
Gravel		Base & Surface Course	
#22		Granular Material for Subbase	
Spec. Gravity-	SSD = 2.50	Special Embankment (non-plastic)	
Water Absport	ion = 3.0%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
#22		(Friction Rating = III - Coarse Agg. Only)	
Spec. Gravity-	SSD = 2.62	Portland Cement Concrete	

Water Absportion = 0.5%

Updated = 8/24/2017

Page 30 of 59 - 12/26/2024 11:14:52 AM

Out of State

APS	00006270	(ABAL)	Green Brothers Gravel CoCrystalSprings, MS	
<u>Materia</u>	<u>al</u>		Approved Uses	
Gravel			Base & Surface Course	
	#65		Granular Material for Subbase	
	Spec. Gravity-	SSD = 2.50	Special Embankment (non-plastic)	
	Water Absport	ion = 3.0%	Asphaltic Surface Treatment	
Sand			Asphaltic Concrete	
	#65		(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-	SSD = 2.62	Portland Cement Concrete	
	Water Absport	ion = 0.5%		

Updated = 8/24/2017

APS00006290 (ASAW) Hallet Materials-Porter,TX

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Porter Plant	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.63	Asphaltic Concrete
Updated = 8/24/2017	Portland Cement Concrete

APS00006300 (ASAU) Hammett Gravel Company, Inc.-Bentonia, MS

	<u>Material</u> Gravel		Approved Uses Base & Surface Course	
	•	Yazoo City Operation	Granular Material for Subbase	
		Spec. Gravity-SSD = 2.56	Special Embankment (non-plastic)	
	,	Water Absportion = 1.2%	Asphaltic Surface Treatment	
	Sand		Asphaltic Concrete	
	•	Yazoo City Operation	(Friction Rating = III - Coarse Agg. Only)	
		Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
	•	Water Absportion = 0.5%		

Updated = 8/24/2017

APS00006310 (AA70) Hanson Aggregates-Bearden, AR

<u>Material</u>		Approved Uses	
Gravel		Base & Surface Course	
	Eagle Mills	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.57	Special Embankment (non-plastic)	
	Water Absportion = 1.0%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
	Eagle Mills	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
	Water Absportion = 0.5%		

Out of State

APS00006320 (A092)	Heidelberg Materials - Little River Plant
<u>Material</u>	Approved Uses
Sand Only	Base & Surface Course
Little River F.K.A. Hanson	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
Water Absportion = 0.5%	Asphaltic Surface Treatment
Little River F.K.A. Hanson	Asphaltic Concrete
Updated = 5/22/2023	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete

APS00006420 (AB07) Huey Stockstill, LLC - Picayune, MS - 12 Oaks

<u>Material</u>	Approved Uses	
Gravel	Base & Surface Course	
12 Oaks Pit	Granular Material for Subbase	
Spec. Gravity-SSD = 2.47	Special Embankment (non-plastic)	
Water Absportion = 3.5%	Asphaltic Surface Treatment	
Sand	Asphaltic Concrete	
12 Oaks Pit	(Friction Rating = III - Coarse Agg. Only)	
Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
Water Absportion = 0.5%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	
11-1-1-1-0/04/0047		

Updated = 8/24/2017

APS00006430 (AB26) Huey P. Stockstill, LLC -Picayune, MS - Pine Grove

<u>Material</u>	Approved Uses	
Gravel	Base & Surface Course	
Pine Grove Pit	Granular Material for Subbase	
Spec. Gravity-SSD = 2.53	Special Embankment (non-plastic)	
Water Absportion = 2.2%	Asphaltic Surface Treatment	
Sand	Asphaltic Concrete	
Pine Grove Pit	(Friction Rating = III - Coarse Agg. Only)	
Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
Water Absportion = 0.5%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	
Updated = 8/24/2017	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	

APS00006490 (ABAP) JJ Ferguson Sand & Gravel-Cruger, MS

<u>Material</u>		Approved Uses	
Gravel		Base & Surface Course	
	Blackhawk Pit	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.54	Special Embankment (non-plastic)	
	Water Absportion = 1.7%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
	Blackhawk Pit	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
	Water Absportion = 0.5%	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	

Οu	ıt	Ωf	St	ate
\sim	IL.	VI.	$\mathbf{O}_{\mathbf{L}}$	alt

Out o	of State			
APSC	0006500	(A091)	Johnsville Sand & Gravel-Hermitage, AR	
Materia	1		Approved Uses	
Gravel	_		Granular Material for Subbase	
	Spec. Gravity-S	SSD = 2.55	Special Embankment (non-plastic)	
	Water Absporti	ion = 1.5%	Asphaltic Surface Treatment	
Sand			Asphaltic Concrete	
	Spec. Gravity-S	SSD = 2.62	(Friction Rating = III - Coarse Agg. Only)	
	Water Absporti	ion = 0.5%	Portland Cement Concrete	
Updated	d = 8/24/2017			
APSO	00006530	(ASAG)	King Sand & Gravel-Kerens, TX	
<u>Materia</u>	<u>.I</u>		Approved Uses	
Sand O	nly		Granular Material for Subbase	
	Spec. Gravity-S	SSD = 2.62	Special Embankment (non-plastic)	
	Water Absporti	ion = 0.5%	Asphaltic Concrete	
Updated	d = 8/24/2017		Portland Cement Concrete	
APSC	0006540	(AB91)	Krystal Gravel, IncCrystal Springs, MS	
<u>Materia</u>	<u>l</u>		Approved Uses	
Gravel			Base & Surface Course	
	Spec. Gravity-S	SSD = 2.53	Granular Material for Subbase	
	Water Absporti	ion = 2.2%	Special Embankment (non-plastic)	
Sand			Asphaltic Surface Treatment	
	Spec. Gravity-S	SSD = 2.62	Asphaltic Concrete	
	Water Absporti	ion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
Updated	Water Absporti d = 8/24/2017	ion = 0.5%	(Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete	
•	•	ion = 0.5% (ASAL)	, , , , , , , , , , , , , , , , , , , ,	
•	d = 8/24/2017 00006680		Portland Cement Concrete	
APSO	d = 8/24/2017 00006680	(ASAL)	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS	
APSC Materia	d = 8/24/2017 00006680 <u>I</u> Spec. Gravity-S	(ASAL) SSD = 2.48	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase	
APSO Materia Gravel	d = 8/24/2017 00006680	(ASAL) SSD = 2.48	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic)	
APSC Materia	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absporti	(ASAL) SSD = 2.48 ion = 3.5%	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment	
APSO Materia Gravel	d = 8/24/2017 00006680 d Spec. Gravity-S Water Absporti	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete	
APSO Materia Gravel	d = 8/24/2017 00006680 L Spec. Gravity-S Water Absporti Spec. Gravity-S Water Absporti	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)	
APSO Materia Gravel	d = 8/24/2017 00006680 d Spec. Gravity-S Water Absporti	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete	
APSO Materia Gravel Sand Updated	d = 8/24/2017 00006680 d Spec. Gravity-S Water Absporti Spec. Gravity-S Water Absporti d = 8/24/2017 00006700	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK	
Materia Gravel Sand Updated APSO Materia	d = 8/24/2017 00006680 d Spec. Gravity-S Water Absporti Spec. Gravity-S Water Absporti d = 8/24/2017 00006700	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5%	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses	
APSO Materia Gravel Sand Updated	d = 8/24/2017 00006680 d Spec. Gravity-S Water Absporti Spec. Gravity-S Water Absporti d = 8/24/2017 00006700	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS)	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course	
Materia Gravel Sand Updated APSO Materia	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absporti Spec. Gravity-S Water Absporti d = 8/24/2017 00006700 I Broken Bow Sa	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS)	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course Granular Material for Subbase	
Materia Gravel Sand Updated APSO Materia	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absporti Spec. Gravity-S Water Absporti d = 8/24/2017 00006700 I Broken Bow Sa Spec. Gravity-S	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS) and & Gravel SSD = 2.56	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course Granular Material for Subbase Asphaltic Surface Treatment	
Materia Gravel Sand Updated APSO Materia Gravel	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absporti Spec. Gravity-S Water Absporti d = 8/24/2017 00006700 I Broken Bow Sa	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS) and & Gravel SSD = 2.56	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course Granular Material for Subbase Asphaltic Surface Treatment Asphaltic Concrete	
Materia Gravel Sand Updated APSO Materia	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absporti d = 8/24/2017 00006700 I Broken Bow Sa Spec. Gravity-S Water Absporti	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS) and & Gravel SSD = 2.56 ion = 1.2%	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course Granular Material for Subbase Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)	
Materia Gravel Sand Updated APSO Materia Gravel	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absporti d = 8/24/2017 00006700 I Broken Bow Sa Spec. Gravity-S Water Absporti	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS) and & Gravel SSD = 2.56 ion = 1.2% and & Gravel	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course Granular Material for Subbase Asphaltic Surface Treatment Asphaltic Concrete	
Materia Gravel Sand Updated APSO Materia Gravel	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absporti d = 8/24/2017 00006700 Broken Bow Sa Spec. Gravity-S Water Absporti Broken Bow Sa Spec. Gravity-S Spec. Gravity-S Spec. Gravity-S	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS) and & Gravel SSD = 2.56 ion = 1.2% and & Gravel SSD = 2.74	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course Granular Material for Subbase Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)	
Materia Gravel Sand Updated APSO Materia Gravel	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absporti d = 8/24/2017 00006700 I Broken Bow Sa Spec. Gravity-S Water Absporti Broken Bow Sa Spec. Gravity-S Water Absporti	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS) and & Gravel SSD = 2.56 ion = 1.2% and & Gravel SSD = 2.74 ion = 0.4%	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course Granular Material for Subbase Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)	
Materia Gravel Sand Updated APSO Materia Gravel Sand	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absporti d = 8/24/2017 00006700 Broken Bow Sa Spec. Gravity-S Water Absporti Broken Bow Sa Spec. Gravity-S Spec. Gravity-S Spec. Gravity-S	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS) and & Gravel SSD = 2.56 ion = 1.2% and & Gravel SSD = 2.74 ion = 0.4%	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course Granular Material for Subbase Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)	

Page 33 of 59 - 12/26/2024 11:14:52 AM

Out of State

APS00006720 (AS	AX) Martin Marietta Aggregates-Garwood,TX	
<u>Material</u>	Approved Uses	
Gravel	Base & Surface Course	
Garwood Plant	Granular Material for Subbase	
Spec. Gravity-SSD = 2	2.57 Special Embankment (non-plastic)	
Water Absportion = 1.	0% Asphaltic Surface Treatment	
Sand	Asphaltic Concrete	
Garwood Plant	(Friction Rating = III - Coarse Agg. Only)	
Updated = 8/24/2017	Portland Cement Concrete	
APS00006780 (AB	AC) Memphis Stone & Gravel CoNesbit, MS	

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Anderson Plant	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete
11. 1.1. 1. 0/04/0047	

Updated = 8/24/2017

APS00006790 (ABAD) Memphis Stone & Gravel Co.-Senatobia, MS

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Perry Plant	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete

Updated = 8/24/2017

APS00006840 (ASAQ) ODDEE Smith Constr.Inc.-Brookhaven, MS

<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Oddee California Camp Pit	Granular Material for Subbase
Spec. Gravity-SSD = 2.56	Special Embankment (non-plastic)
Water Absportion = 1.2%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Oddee California Camp Pit	(Friction Rating = III - Coarse Agg. Only)
Updated = 8/24/2017	Portland Cement Concrete

APS00006860 (A018) Perkinston Sand & Gravel-Perkinston, MS

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
Water Absportion = 0.5%	Asphaltic Concrete
Updated = 8/24/2017	Portland Cement Concrete

APS00006910 (ASAF) R & R Logging & Gravel-Columbia, MS

<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.49	Granular Material for Subbase
Water Absportion = 3.5%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 8/24/2017	Portland Cement Concrete

Water Absportion = 0.5%

A-2. OUT-OF-STATE PRODUCERS/SUPPLIERS

Out of State

APS00006930	(ASAP)	Riverside Sand & Gravel-T	ylertown, MS
-------------	--------	---------------------------	--------------

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
NW St. Paul Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete

Updated = 8/24/2017

APS00006980 (ASAY) Simpson Materials Co.-Valley Park, MO

<u>Material</u>	Approved Uses	
Gravel	Base & Surface Course	
Ranken Site	Granular Material for Subbase	
Spec. Gravity-SSD = 2.51	Special Embankment (non-plastic)	
Water Absportion = 2.5%	Asphaltic Surface Treatment	
Sand	Asphaltic Concrete	
Ranken Site	(Friction Rating = III - Coarse Agg. Only)	
Updated = 8/28/2017	Portland Cement Concrete	

Portland Cement Concrete

APS00007170 (AB27) The Fordyce Co-Victoria, TX

<u>Material</u>	Approved Uses	
Gravel	Base & Surface Course	
Briggs Plant	Granular Material for Subbase	
Spec. Gravity-SSD = 2.74	Special Embankment (non-plastic)	
Water Absportion = 0.8%	Asphaltic Surface Treatment	
Sand	Asphaltic Concrete	
Briggs Plant	(Friction Rating = III - Coarse Agg. Only)	
Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
Water Absportion = 0.5%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	
11 1 4 1 0/00/0047		

Updated = 8/28/2017

APS00007210 (ASAH) Triangle Aggregates, LLC-Jackson, AL

<u>Material</u>		Approved Uses	
Gravel		Base & Surface Course	
	Couch - Triangle Pit	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.61	Special Embankment (non-plastic)	
	Water Absportion = 0.8%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
	Couch - Triangle Pit	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD = 2.63	Portland Cement Concrete	

Updated = 8/28/2017

APS00007250 (ASAE) Trinity Materials-West Lockesburg, AR

<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.56	Granular Material for Subbase
Water Absportion = 1.2%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 8/28/2017	Portland Cement Concrete

Out of State

APSO	00007510	(ASAA)	Wooten Sand & Gravel-Fouke,AR
<u>Material</u>			Approved Uses
Gravel			Base & Surface Course
	Spec. Gravity-	SSD = 2.60	Granular Material for Subbase
	Water Absport	ion = 1.0%	Special Embankment (non-plastic)
Sand			Asphaltic Surface Treatment
	Spec. Gravity-	SSD = 2.62	Asphaltic Concrete
	Water Absport	ion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated	d = 8/24/2017		Portland Cement Concrete

APS00011350 (ASAS) Eastern Oklahoma Quarries, LLC - Spiro, OK

<u>Material</u>	Approved Uses	
Sand Only	Granular Material for Subbase	
Spiro Pit	Special Embankment (non-plastic)	
Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
Water Absportion = 0.5%	Portland Cement Concrete	
Updated = 8/24/2017		

APS00011360 (ASAZ) Shale Support Holdings, LLC - Nicholson, MS

<u>Material</u>	Approved Uses
Gravel	Granular Material for Subbase
Nicholson Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.49	Asphaltic Surface Treatment
Water Absportion = 3.5%	Asphaltic Concrete
Sand	(Friction Rating = III - Coarse Agg. Only)
Nicholson Pit	Portland Cement Concrete
Spec. Gravity-SSD = 2.63	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
Updated = 8/28/2017	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)

APS00011380 (ASBA) South Gate Aggregates, LLC - Nicholson, MS

<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Burge Pit	Granular Material for Subbase
Spec. Gravity-SSD = 2.47	Special Embankment (non-plastic)
Water Absportion = 3.5%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Burge Pit	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.63	Portland Cement Concrete
Updated = 8/28/2017	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)

APS00011450 (ASBC) Huey P. Stockstill, LLC- Nicholson, MS

<u>Material</u>	Approved Uses	
Sand Only	Granular Material for Subbase	
Santa Rosa Pit	Special Embankment (non-plastic)	
Spec. Gravity-SSD = 2.63	Asphaltic Concrete	
Updated = 8/24/2017	Portland Cement Concrete	

(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)

A-2. OUT-OF-STATE PRODUCERS/SUPPLIERS

\bigcirc	ıŧ	Ωf	Sta	ıtα
\mathbf{v}	ıι	UI.	Olc	แธ

Out of State			
APS00011470	(ASBB)	Eastern Oklahoma Quarries - Garland, AR	
Material	,	Approved Uses	Ī
Sand Only		Granular Material for Subbase	
Chieftan Sand F	Pit	Special Embankment (non-plastic)	
Spec. Gravity-S	SSD = 2.63	Asphaltic Concrete	
Water Absportion	on = 0.8%	Portland Cement Concrete	
Updated = 8/24/2017		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	
APS00011630	(ASBE)	Heidelberg Materials - Bristol Plant	
<u>Material</u>		Approved Uses	
Sand Only		Granular Material for Subbase	
Bristol Plant F.k	K.A. Hanson	Special Embankment (non-plastic)	
Spec. Gravity-S	SSD = 2.63	Portland Cement Concrete	
Updated = 5/22/2023			
APS00011690	(ASBF)	Hammett & Green Aggregates - Vicksburg, MS	
<u>Material</u>		Approved Uses	
Gravel		Base & Surface Course	
Henry Mine Pit		Granular Material for Subbase	
Spec. Gravity-S		Special Embankment (non-plastic)	
Water Absportion	on = 1.2%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
Henry Mine Pit		(Friction Rating = III - Coarse Agg. Only)	
Spec. Gravity-S		Portland Cement Concrete	
Water Absportion	on = 0.5%		
Updated = 1/8/2019			
APS00012160		Dickerson & Bowen Co., Inc - Brookhaven, MS	
<u>Material</u>		Approved Uses	
Gravel Only		Base & Surface Course	
D & B Brookhav		Granular Material for Subbase	
Spec. Gravity-S		Asphaltic Surface Treatment	
Water Absportion	on = 2.2%	Asphaltic Concrete	
Updated = 8/28/2017		(Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete	
APS00012380			
		LeHigh Hanson - Garwood, TX	
Material		Approved Uses	
Sand Only		Granular Material for Subbase	
Arena Pit	200 000	Special Embankment (non-plastic)	
Spec. Gravity-S		Asphaltic Concrete Portland Cement Concrete	
Water Absportion Updated = 8/24/2017	JII = 0.5%	Portland Cement Concrete	
APS00012890		D & J Construction Company, LLC - West Monroe	
Material Sand Only		Approved Uses Granular Material for Subbase	
Spec. Gravity-S	SSD = 2.62	Special Embankment (non-plastic)	
Water Absportion		Asphaltic Concrete	
Updated = 1/16/2018	J.1 0.070	Portland Cement Concrete	

Water Absportion = 1.5%

Updated = 10/5/2021

A-2. OUT-OF-STATE PRODUCERS/SUPPLIERS

, , <u>_</u> , ,	
Out of State	
APS00012930	Regional Sand & Gravel, LLC #2 - Clinton
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.54	Granular Material for Subbase
Water Absportion = 1.5%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 7/26/2018	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
APS00012980	Gulf Coast Sand & Gravel - Jackson, AL
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.59	Granular Material for Subbase
Water Absportion = 1.2%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.63	Asphaltic Concrete
Updated = 1/16/2018	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete
APS00013340	Heritage Sand and Gravel - Columbia, MS
<u>Material</u>	Approved Uses
<u>Material</u> Gravel	Approved Uses Base & Surface Course
Material Gravel Spec. Gravity-SSD = 2.50	Approved Uses Base & Surface Course Granular Material for Subbase
Material Gravel Spec. Gravity-SSD = 2.50 Water Absportion = 3.0%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic)
Material Gravel Spec. Gravity-SSD = 2.50 Water Absportion = 3.0% Sand	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment
Material Gravel Spec. Gravity-SSD = 2.50 Water Absportion = 3.0% Sand Spec. Gravity-SSD = 2.62	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete
Material Gravel Spec. Gravity-SSD = 2.50 Water Absportion = 3.0% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)
Material Gravel Spec. Gravity-SSD = 2.50 Water Absportion = 3.0% Sand Spec. Gravity-SSD = 2.62	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete
Material Gravel Spec. Gravity-SSD = 2.50 Water Absportion = 3.0% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 4/7/2020	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
Material Gravel Spec. Gravity-SSD = 2.50 Water Absportion = 3.0% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 4/7/2020 APS00014030	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate) Sierra FRAC Sand - Plain Dealing
Material Gravel Spec. Gravity-SSD = 2.50 Water Absportion = 3.0% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 4/7/2020	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
Material Gravel Spec. Gravity-SSD = 2.50 Water Absportion = 3.0% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 4/7/2020 APS00014030 Material Sand Only	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate) Sierra FRAC Sand - Plain Dealing Approved Uses Granular Material for Subbase
Material Gravel Spec. Gravity-SSD = 2.50 Water Absportion = 3.0% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 4/7/2020 APS00014030 Material	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate) Sierra FRAC Sand - Plain Dealing Approved Uses Granular Material for Subbase
Material Gravel Spec. Gravity-SSD = 2.50 Water Absportion = 3.0% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 4/7/2020 APS00014030 Material Sand Only Spec. Gravity-SSD = 2.62	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate) Sierra FRAC Sand - Plain Dealing Approved Uses Granular Material for Subbase Special Embankment (non-plastic)
Material Gravel Spec. Gravity-SSD = 2.50 Water Absportion = 3.0% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 4/7/2020 APS00014030 Material Sand Only Spec. Gravity-SSD = 2.62 Water Absportion = 0.5%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate) Sierra FRAC Sand - Plain Dealing Approved Uses Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Concrete
Material Gravel Spec. Gravity-SSD = 2.50 Water Absportion = 3.0% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 4/7/2020 APS00014030 Material Sand Only Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 11/15/2018	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate) Sierra FRAC Sand - Plain Dealing Approved Uses Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Concrete Portland Cement Concrete
Material Gravel Spec. Gravity-SSD = 2.50 Water Absportion = 3.0% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 4/7/2020 APS00014030 Material Sand Only Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 11/15/2018 APS00014570	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate) Sierra FRAC Sand - Plain Dealing Approved Uses Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Concrete Portland Cement Concrete Arkansas Granufill Supply - Hot Springs, AR
Material Gravel Spec. Gravity-SSD = 2.50 Water Absportion = 3.0% Sand Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 4/7/2020 APS00014030 Material Sand Only Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% Updated = 11/15/2018 APS00014570 Material	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate) Sierra FRAC Sand - Plain Dealing Approved Uses Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Concrete Portland Cement Concrete Arkansas Granufill Supply - Hot Springs, AR Approved Uses

A-2. OUT-OF-STATE PRODUCERS/SUPPLIERS

Out	of	State

Out of State	
APS00014750	Rock Island Sand and Gravel - Harrell Pit-Hampton
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.58	Granular Material for Subbase
Water Absportion = 1.0%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 1.0%	(Friction Rating = III - Coarse Agg. Only)
Updated = 10/5/2021	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
APS00014970	Gulf Coast Sand - Nicholson, MS
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.48	Granular Material for Subbase
Water Absportion = 2.9%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.68	Asphaltic Concrete
Water Absportion = 0.1%	(Friction Rating = III - Coarse Agg. Only)
Updated = 1/27/2022	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
APS00015010	Island Sand & Gravel - Crossett, AR
<u>Material</u>	Approved Uses
Sand Only	Base & Surface Course
Spec. Gravity-SSD = 2.64	Granular Material for Subbase
Water Absportion = 0.2%	Special Embankment (non-plastic)
Updated = 3/28/2022	Asphaltic Surface Treatment
	Asphaltic Concrete
	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete - Gravel Only
APS00015130	Lafarge Aggs - Cave-In-Rock, IL - Transition Ledge
<u>Material</u>	Approved Uses
Sand	Base & Surface Course
Stone	Granular Material for Subbase
(Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.65	Asphaltic Surface Treatment
Water Absportion = 1.3%	Asphaltic Concrete
Updated = 6/20/2022	(Friction Rating = IV - Coarse Agg. Only)

Riprap & Stone Revetment

A-2. OUT-OF-STATE PRODUCERS/SUPPLIERS		
Out of State		
APS00015180	Arcosa Aggregates - Plant 1347 - Hattiesburg, MS	
<u>Material</u>	Approved Uses	
Gravel	Base & Surface Course	
Spec. Gravity-SSD = 2.53	Granular Material for Subbase	
Water Absportion = 2.2%	Special Embankment (non-plastic)	
Sand	Asphaltic Surface Treatment	
Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
Updated = 5/4/2022	Portland Cement Concrete	
APS00015190	Arcosa Aggregates - Plant 1348 - Columbia, MS	
<u>Material</u>	Approved Uses	
Gravel	Base & Surface Course	
Spec. Gravity-SSD = 2.53	Granular Material for Subbase	
Water Absportion = 2.2%	Special Embankment (non-plastic)	
Sand	Asphaltic Surface Treatment	
Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
Updated = $5/4/2022$	Portland Cement Concrete	
	(Sand from this source is potentially deleterious in Portland Cement Concrete	

APS00015310 Hastie Mining and Trucking #2 - Cave-In-Rock, IL

<u>Material</u>	Approved Uses
Sand	Base & Surface Course
Stone	Granular Material for Subbase
(Siliceous Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.69	Asphaltic Surface Treatment
Water Absportion = 1.0%	Asphaltic Concrete
Updated = 7/29/2022	(Friction Rating = IV - Coarse Agg. Only)
	Riprap & Stone Revetment

mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of

Class F fly ash and GGBFS with a minimum of 50% replacement)

Class F fly ash and GGBFS with a minimum of 50% replacement)

APS00015540 Hammett Gravel Company, Inc. - Red Mountain Plant

Mate	<u>erial</u>	Approved Uses
Sand	d Only	Base & Surface Course
	Spec. Gravity-SSD = 2.64	Granular Material for Subbase
	Water Absportion = 0.5%	Special Embankment (non-plastic)
Upda	ated = 3/28/2024	Asphaltic Surface Treatment
		Asphaltic Concrete
		(Friction Rating = III - Coarse Agg. Only)
		Portland Cement Concrete
		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of

A-2. OUT-OF-STATE PRODUCERS/SUPPLIERS

Out of State

APS00015780	RockCo Mining, LLC Courtland, MS
<u>Material</u>	Approved Uses
Sand Only	Base & Surface Course
Spec. Gravity-SSD = 2.65	Granular Material for Subbase
Water Absportion = 0.4%	Special Embankment (non-plastic)
Updated = 1/12/2024	Asphaltic Surface Treatment
	Asphaltic Concrete
	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete - Gravel Only

APS00015900	Huey P. Stockstill, LLC Boone Mine
<u>Material</u>	Approved Uses
Sand Only	Base & Surface Course
Spec. Gravity-SSD = 2.64	Granular Material for Subbase
Water Absportion = 0.1%	Special Embankment (non-plastic)
Updated = 3/14/2024	Asphaltic Surface Treatment
	Asphaltic Concrete
	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)

NOTES:

Note A-1:

Source approval samples of gravel and sand are obtained by personnel of the Materials and District Laboratories. The source is defined as the pit or quarry which produces the aggregate being evaluated. All aggregate which does not pass through the 4.75mm (No. 4) sieve shall be source approved prior to use. Certain aggregates may be approved for restricted use. A complete source approval analysis shall be run on each aggregate source.

Note A-2:

All material, regardless of prior approval, shall be sampled in accrodance with the Materials Sampling Manual and tested for conformance to the appropriate specifications. Any deviation in performance from the original sample submitted may result in removal of the material from the approved list.

Note A-3:

A specific gravity value of 2.62 (SSD) may be used for all in-state silica sands used for portland cement concrete.

Note A-4:

Because absorption has been found to correlate with the type and specific gravity of silica sands and chert gravels, the water absorption factors given in the following table may be used:

Out of State

APS00005710	(ABBC) Ag	recasa Del Caribe-San Pedro Sula, HON
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Limestone)		Granular Material for Subbase
Spec. Gravity-	SSD = 2.63	Special Embankment (non-plastic)

Water Absportion = 1.6% Asphaltic Surface Treatment
Updated = 6/24/2022 Asphaltic Concrete

(Friction Rating = IV - Coarse Agg. Only)

Portland Cement Concrete
(may be used on bridge decks)

Riprap & Stone Revetment

APS00005770 (ABBY) APAC - Brickey's Stone-Bloomsdale, MO - Burlington

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Burlington Formation	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.64	Asphaltic Surface Treatment
Water Absportion = 1.4%	Asphaltic Concrete
Updated = 6/24/2022	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete
	(may be used on bridge decks)
	Riprap & Stone Revetment

APS00005900 (AB25) Arcosa Lightweight - Erwinville, LA

<u>Material</u>	Approved Uses
Lightweight Aggregate	Special Embankment (non-plastic)
(Expanded Clay)	Asphaltic Surface Treatment
Spec. Gravity-SSD = 1.65	(Type B, C, & D applications only)
Water Absportion = 16.3%	Asphaltic Concrete
Updated = 12/8/2021	(excluding wearing surfaces)
	(Friction Rating = I - Coarse Agg. Only)
	Portland Cement Concrete

APS00005960 (ABBU) Winn Materials of Kentucky-Grand Rivers, KY-StLouis

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Siliceous Limestone)	Granular Material for Subbase
St. Louis Formation	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.69	Asphaltic Surface Treatment
Water Absportion = 0.5%	Asphaltic Concrete
Updated = 10/20/2021	(Friction Rating = IV - Coarse Agg. Only)
	Riprap & Stone Revetment

Out of State

Out of State			
APS00005970	(ABBK)	Texas Materials - Burnet.TX	
<u>Material</u>		Approved Uses	
Stone		Base & Surface Course	
(Limestone)		Granular Material for Subbase	
F.K.A OldCast	le Materials -	Special Embankment (non-plastic)	
Spec. Gravity-	SSD = 2.78	Asphaltic Surface Treatment	
Water Absport	ion = 0.7%	Asphaltic Concrete	
Updated = 1/12/2024		(Friction Rating = IV - Coarse Agg. Only)	
		Portland Cement Concrete	
		(excluding bridge decks)	
		Riprap & Stone Revetment	
APS00006080	(ABBN)	Crystal Hill Quarry-North Little Rock, AR	
<u>Material</u>		Approved Uses	
Stone		Base & Surface Course	
(Sandstone)		Granular Material for Subbase	
Granite Mount	ain Quarries	Special Embankment (non-plastic)	
Spec. Gravity-	SSD = 2.62	Asphaltic Surface Treatment	
Water Absport	ion = 0.9%	Asphaltic Concrete	
Updated = 9/24/2024		(Friction Rating = II - Coarse Agg. Only)	
		Riprap & Stone Revetment	
APS00006250	(A033)	Granite Mountain Quarries-Little Rock, AR	
<u>Material</u>		Approved Uses	
Stone		Base & Surface Course	
(Granite)		Granular Material for Subbase	
Syenite Granit	е	Special Embankment (non-plastic)	
Spec. Gravity-		Asphaltic Surface Treatment	
Water Absport	ion = 0.9%	Asphaltic Concrete	
Updated = $2/16/2024$		(Friction Rating = II - Coarse Agg. Only)	
		Portland Cement Concrete	
		Riprap & Stone Revetment	
APS00006340	(A077)	Hanson Aggregates-Perch Hill Plant-Chico,TX	
<u>Material</u>		Approved Uses	
Stone		Base & Surface Course	
(Limestone)		Granular Material for Subbase	
Perch Hill Plan	nt	Special Embankment (non-plastic)	
Spec. Gravity-	SSD = 2.68	Asphaltic Surface Treatment	
Water Absport	ion = 0.8%	Asphaltic Concrete	
Updated = 6/24/2022		(Friction Rating = IV - Coarse Agg. Only)	

Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment

	D.	ΟI	HER AGGREGATE WATERIALS	
APS00006370	(AA90)	На	stie Mining Company-Cave-in-Rock,IL	
<u>Material</u>			Approved Uses	
Stone			Base & Surface Course	
(Sandstone)			Granular Material for Subbase	
Hastie Mining (Company Qua	ırry	Special Embankment (non-plastic)	
Spec. Gravity-	SSD = 2.66		Asphaltic Surface Treatment	
Water Absport	ion = 0.8%		Asphaltic Concrete	
Updated = 8/24/2017			(Friction Rating = I - Coarse Agg. Only)	
			Portland Cement Concrete	
			Riprap & Stone Revetment	
APS00006440	(AA91)	Ide	al Domicana, SA-Santo Domingo, DR	
<u>Material</u>			Approved Uses	
Stone			Base & Surface Course	
(Limestone)			Granular Material for Subbase	
Spec. Gravity-	SSD = 2.61		Special Embankment (non-plastic)	
Water Absporti	ion = 1.3%		Asphaltic Surface Treatment	
Updated = 8/25/2017			Portland Cement Concrete	
APS00006480	(ABBO)	Jar	maica Aggregates Limited dba Lafarge	
<u>Material</u>			Approved Uses	
Stone			Base & Surface Course	
(Crushed Alluv	rial Stone)		Granular Material for Subbase	
Spec. Gravity-	SSD = 2.72		Special Embankment (non-plastic)	
Water Absporti	ion = 1.0%		Asphaltic Surface Treatment	
Updated = 8/25/2017			Asphaltic Concrete	
			(Friction Rating = III - Coarse Agg. Only)	
			Portland Cement Concrete	
			Riprap & Stone Revetment	
APS00006560	(ABAN)	Laf	arge Aggregates-Cave-In-Rock, IL - SandStone	
<u>Material</u>			Approved Uses	
Stone			Base & Surface Course	
(Sandstone)			Granular Material for Subbase	
Spec. Gravity-			Special Embankment (non-plastic)	
Water Absport	ion = 0.8%		Asphaltic Surface Treatment	
Updated = $6/3/2020$			Asphaltic Concrete	
			(Friction Rating = I - Coarse Agg. Only)	
			Portland Cement Concrete	
			(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	
			Riprap & Stone Revetment	

Out of State

APS00006570	(ABAM)	Lafarge Aggregates-Cave-In-Rock, IL - Sil. Limestn	
<u>Material</u>		Approved Uses	
Stone		Base & Surface Course	
(Siliceous Limes	stone)	Granular Material for Subbase	
Ledge 8 - 10		Special Embankment (non-plastic)	
Spec. Gravity-S	SSD = 2.68	Asphaltic Surface Treatment	
Water Absportion	on = 0.7%	Asphaltic Concrete	
Updated = $6/24/2022$		(Friction Rating = III - Coarse Agg. Only)	
		Portland Cement Concrete	
		(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)	
		(may be used on bridge decks)	
		Riprap & Stone Revetment	

APS00006580 (ABCA) Lafarge Aggregates-Fredonia, KY

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Siliceous Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.69	Special Embankment (non-plastic)
Water Absportion = 0.7%	Asphaltic Surface Treatment
Updated = 6/24/2022	Asphaltic Concrete
	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete
	(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
	(may be used on bridge decks)
	Riprap & Stone Revetment

APS00006690 (AA86) Martin Marietta Aggregates-Bahamas, BAH

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Porous Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.38	Special Embankment (non-plastic)
Water Absportion = 3.9%	Asphaltic Surface Treatment
Updated = 8/25/2017	Asphaltic Concrete
	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment

\cap	+	of.	Sta	+~
Ou	L	ΟI	Sia	ιe

APS0000	06/10	(AA92)	Martin Marietta Aggregates-Cove,AR
<u>Material</u>			Approved Uses
Stone			Base & Surface Course
(Rhy	olite)		Granular Material for Subbase
Trap	rock		Special Embankment (non-plastic)
Spe	c. Gravity-S	SSD = 2.66	Asphaltic Surface Treatment
Wat	er Absportio	on = 0.7%	Asphaltic Concrete
Updated = 7/	20/2022		(Friction Rating = II - Coarse Agg. Only)
			Riprap & Stone Revetment

APS00006730 (AE	BAW) Martin Marietta A	Aggregates-Malvern, AR - SandStone
-----------------	------------------------	------------------------------------

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Sandstone)	Granular Material for Subbase
Jones Mill Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.53	Asphaltic Surface Treatment
Water Absportion = 2.2%	Asphaltic Concrete
Updated = 8/25/2017	(Friction Rating = II - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment

Out of State

APS00006740 (ABAX) Martin Marietta Aggregates-Malvern, AR - Granite

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Granite)	Granular Material for Subbase
Jones Mill Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.58	Asphaltic Surface Treatment
Water Absportion = 0.9%	Asphaltic Concrete
Updated = 2/16/2024	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment

APS00006750 (AA39) Martin Marietta Aggregates-Mulgrave, NS

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Granite)	Granular Material for Subbase
Spec. Gravity-SSD = 2.70	Special Embankment (non-plastic)
Water Absportion = 0.9%	Asphaltic Surface Treatment
Updated = 2/16/2024	Asphaltic Concrete
	(excluding OGFC and coarse mix)
	(Friction Rating = I - Coarse Agg. Only)
	Portland Cement Concrete
	(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
	Riprap & Stone Revetment

APS00006760	(AA51)	Martin Marietta Aggregates-Sawyer,OK
<u>Material</u>	,	Approved Uses
Stone		Base & Surface Course
(Sandstone)		Granular Material for Subbase
Spec. Gravity-	SSD = 2.52	Special Embankment (non-plastic)
Water Abspor	tion = 2.3%	Asphaltic Surface Treatment
Updated = 6/3/2020		Asphaltic Concrete
		(Friction Rating = I - Coarse Agg. Only)
		Portland Cement Concrete
		(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
		Riprap & Stone Revetment
APS00006880	(AB13)	Pine Bluff Sand & Gravel-Deleware, AR
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Sandstone)		Granular Material for Subbase
River Mountai	n Quarry	Special Embankment (non-plastic)
Spec. Gravity-	-SSD = 2.63	Asphaltic Surface Treatment
Water Abspor	tion = 1.0%	Asphaltic Concrete
Updated = 11/10/2020		(Friction Rating = I - Coarse Agg. Only)
		Portland Cement Concrete
		(Stone from this source is potentially deleterious in Portland Cement Concret mixes, requires 30% Class F fly ash or 50% slag to mitigate)
4 DQ00000000	(4000)	Riprap & Stone Revetment
APS00006890	(ABBS)	Pine Bluff Sand & Gravel-Salem,KY
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Siliceous Lim		Granular Material for Subbase
Cumberland R		Special Embankment (non-plastic)
Spec. Gravity-		Asphaltic Surface Treatment
Water Abspor	tion = 0.8%	Asphaltic Concrete
Updated = 10/28/2021		(Friction Rating = III - Coarse Agg. Only)
		Riprap & Stone Revetment
APS00007160	(AB15)	Texas Crushed Stone Co., IncGeorgetown, TX
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Limestone)		Granular Material for Subbase
Spec. Gravity-		Special Embankment (non-plastic)
Water Abspor	tion = 3.6%	Asphaltic Surface Treatment
Updated = 6/3/2020		Asphaltic Concrete
		(Friction Rating = IV - Coarse Agg. Only)
		Portland Cement Concrete
		(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
		(excluding bridge decks) Riprap & Stone Revetment

	B. OTHER AGGREGATE MATERIALS
APS00007180 (A056)	Tower Rock Stone Co-St.Genevieve, MO- Limestn Zn8
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.64	Special Embankment (non-plastic)
Water Absportion = 1.6%	Asphaltic Surface Treatment
Updated = 5/21/2018	Asphaltic Concrete
	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment
APS00007190 (A079)	Tower Rock Stone Co-St.Genevieve, MO- Oolitic
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Oolitic Stone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.47	Special Embankment (non-plastic)
Water Absportion = 4.8%	Asphaltic Surface Treatment
Updated = 8/25/2017	Asphaltic Concrete
	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment
Out of State	
APS00007260 (AB61)	Martin Marietta - Bridgeport TX
APS00007260 (AB61) <u>Material</u>	Martin Marietta - Bridgeport TX Approved Uses
,	
<u>Material</u>	Approved Uses
Material Stone	Approved Uses Base & Surface Course
Material Stone (Limestone)	Approved Uses Base & Surface Course Granular Material for Subbase
Material Stone (Limestone) Bridgeport	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic)
Material Stone (Limestone) Bridgeport Spec. Gravity-SSD = 2.64	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment
Material Stone (Limestone) Bridgeport Spec. Gravity-SSD = 2.64 Water Absportion = 1.3%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete
Material Stone (Limestone) Bridgeport Spec. Gravity-SSD = 2.64 Water Absportion = 1.3%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks)
Material Stone (Limestone) Bridgeport Spec. Gravity-SSD = 2.64 Water Absportion = 1.3%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete
Material Stone (Limestone) Bridgeport Spec. Gravity-SSD = 2.64 Water Absportion = 1.3%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks)
Material Stone (Limestone) Bridgeport Spec. Gravity-SSD = 2.64 Water Absportion = 1.3% Updated = 6/24/2022	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment
Material Stone (Limestone) Bridgeport Spec. Gravity-SSD = 2.64 Water Absportion = 1.3% Updated = 6/24/2022 APS00007340 (A042) Material Stone	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses Base & Surface Course
Material Stone (Limestone) Bridgeport Spec. Gravity-SSD = 2.64 Water Absportion = 1.3% Updated = 6/24/2022 APS00007340 (A042) Material	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses
Material Stone (Limestone) Bridgeport Spec. Gravity-SSD = 2.64 Water Absportion = 1.3% Updated = 6/24/2022 APS00007340 (A042) Material Stone (Limestone) Calera Quarry	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic)
Material Stone (Limestone) Bridgeport Spec. Gravity-SSD = 2.64 Water Absportion = 1.3% Updated = 6/24/2022 APS00007340 (A042) Material Stone (Limestone) Calera Quarry Spec. Gravity-SSD = 2.71	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment
Material Stone (Limestone) Bridgeport Spec. Gravity-SSD = 2.64 Water Absportion = 1.3% Updated = 6/24/2022 APS00007340 (A042) Material Stone (Limestone) Calera Quarry Spec. Gravity-SSD = 2.71 Water Absportion = 0.7%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete
Material Stone (Limestone) Bridgeport Spec. Gravity-SSD = 2.64 Water Absportion = 1.3% Updated = 6/24/2022 APS00007340 (A042) Material Stone (Limestone) Calera Quarry Spec. Gravity-SSD = 2.71	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only)
Material Stone (Limestone) Bridgeport Spec. Gravity-SSD = 2.64 Water Absportion = 1.3% Updated = 6/24/2022 APS00007340 (A042) Material Stone (Limestone) Calera Quarry Spec. Gravity-SSD = 2.71 Water Absportion = 0.7%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete
Material Stone (Limestone) Bridgeport Spec. Gravity-SSD = 2.64 Water Absportion = 1.3% Updated = 6/24/2022 APS00007340 (A042) Material Stone (Limestone) Calera Quarry Spec. Gravity-SSD = 2.71 Water Absportion = 0.7%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only)

Οι	ıt	of	State
\sim	~ .	\sim	\mathbf{c}

APS00007350 (AA95)	Vulcan Materials Co-Cancun, MEX
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.38	Special Embankment (non-plastic)
Water Absportion = 3.7%	Asphaltic Surface Treatment
Updated = 6/24/2022	Asphaltic Concrete
	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete
	(may be used on bridge decks)
	Riprap & Stone Revetment

APS00007380 (ABBQ) Vulcan Materials Co-Grand Rivers, KY- Ft Payne

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Siliceous Limestone)	Granular Material for Subbase
Ft. Payne Formation	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.68	Asphaltic Surface Treatment
Water Absportion = 0.2%	Asphaltic Concrete
Updated = 10/29/2021	(Friction Rating = III - Coarse Agg. Only)
	(Friction Rating = II for ADT <= 20,000 - Coarse Agg. Only)

APS00007390 (ABBP) Vulcan Materials Co-Grand Rivers, KY- Warsaw

<u>Mat</u>	<u>terial</u>	Approved Uses	
Stor	ne	Base & Surface Course	
	(Limestone)	Granular Material for Subbase	
	Warsaw Formation	Special Embankment (non-plastic)	
	Spec. Gravity-SSD = 2.67	Asphaltic Surface Treatment	
	Water Absportion = 0.9%	Asphaltic Concrete	
Upd	dated = 10/29/2021	(Friction Rating = IV - Coarse Agg. Only)	
		Riprap & Stone Revetment	

Out of State

APS00007430 (ABBT) Vulcan Materials Co-Tuscumbia, AL- Pride Quarry

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.60	Special Embankment (non-plastic)
Water Absportion = 1.9%	Asphaltic Surface Treatment
Updated = 6/24/2022	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
	(may be used on bridge decks)
	Riprap & Stone Revetment

	B.	OTHER AGGREGATE MATERIALS
APS00007450	(AB19)	Vulcan Materials Co-Trinity, AL
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Limestone)		Granular Material for Subbase
Trinity Plant		Special Embankment (non-plastic)
Spec. Gravity-	SSD = 2.65	Asphaltic Surface Treatment
Water Absport	ion = 1.2%	Asphaltic Concrete
Updated = 10/25/2017		(Friction Rating = IV - Coarse Agg. Only)
		Portland Cement Concrete
		(excluding bridge decks)
		Riprap & Stone Revetment
APS00007480	(ABAY)	Warren Paving-Salem, KY - Upper Warsaw Formation
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Siliceous Lim	estone)	Granular Material for Subbase
Slats Lucas Q	uarry	Special Embankment (non-plastic)
Spec. Gravity-	SSD = 2.69	Asphaltic Surface Treatment
Water Absport	ion = 0.4%	Asphaltic Concrete
Updated = 10/20/2021		(Friction Rating = III - Coarse Agg. Only)
		(Friction Rating = II for ADT <10,000 - Coarse Agg. Only)
		Riprap & Stone Revetment
APS00007500	(AB78)	Winn Materials, IncClarksville, TN
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Siliceous Lim	estone)	Granular Material for Subbase
Spec. Gravity-	SSD = 2.70	Special Embankment (non-plastic)
Water Absport	ion = 0.6%	Asphaltic Surface Treatment
Updated = 10/28/2021		Asphaltic Concrete
		(Friction Rating = IV - Coarse Agg. Only)
		Riprap & Stone Revetment
APS00007520	(AB04)	Delta Materials - Marble Falls, TX
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Sandstone)		Granular Material for Subbase
Spec. Gravity-		Special Embankment (non-plastic)
Water Absport	ion = 2.1%	Asphaltic Surface Treatment
Updated = 8/25/2017		Asphaltic Concrete
		(Friction Rating = I - Coarse Agg. Only)
		Portland Cement Concrete Riprap & Stone Revetment

Updated = 11/9/2018

B.	OTHER AGGREGATE MATERIALS
APS00011430 (ABCD)	APAC - Brickey's Stone-Bloomsdale, MO - Plattin
Material	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Plattin Formation	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.60	Asphaltic Surface Treatment
Water Absportion = 2.0%	Asphaltic Concrete
Updated = 7/26/2018	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(excluding bridge decks)
	Riprap & Stone Revetment
Out of State	
APS00011620 (ABCI)	Central Stone Co - Farmington, MO
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Granite)	Granular Material for Subbase
Butler Hill Granite Quarry	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Surface Treatment
Water Absportion = 0.3%	Asphaltic Concrete
Updated = 2/16/2024	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(excluding bridge decks)
	Riprap & Stone Revetment
APS00011870	Lafarge Aggregates-Smithland, KY-Three Rivers-S1
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Siliceous Limestone)	Granular Material for Subbase
3RvrQry-Bench S1-Pit#1	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.67	Asphaltic Surface Treatment
Water Absportion = 1.0%	Asphaltic Concrete
Updated = $5/20/2020$	(Friction Rating = III - Coarse Agg. Only)
	Riprap & Stone Revetment
APS00012130	Tower Rock Stone Co-St.Genevieve, MO- Limestn Zn12
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Ledge 12	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.68	Asphaltic Surface Treatment
Water Absportion = 0.8%	Asphaltic Concrete

(Friction Rating = IV - Coarse Agg. Only)

Riprap & Stone Revetment

\cap	ııt	$\cap f$	State
\sim	uι	OI.	State

APS00012300	Vulcan Materials Co-West Loachapoka, AL
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Granite)	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
Water Absportion = 0.4%	Asphaltic Surface Treatment
Updated = 2/16/2024	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(excluding bridge decks)
	Riprap & Stone Revetment

APS00012320	Winn Materials of Kentucky-Grand Rivers, KY-Warsaw
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Siliceous Limestone)	Granular Material for Subbase
Warsaw Formation	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.65	Asphaltic Surface Treatment
Water Absportion = 1.1%	Asphaltic Concrete
Updated = 11/10/2020	(Friction Rating = IV - Coarse Agg. Only)
	Riprap & Stone Revetment

APS00012600	Martin Marietta	- MMR - Hondo	TX
AF 3000 12000	iviai iii iviai ietta	- IVIIVIIX - I IUI IUU,	, 1/

<u>Materi</u>	<u>al</u>	Approved Uses	
Stone		Base & Surface Course	
	(Limestone)	Granular Material for Subbase	
	Medina Rock & Rail Quarry	Special Embankment (non-plastic)	
	Spec. Gravity-SSD = 2.53	Asphaltic Surface Treatment	
	Water Absportion = 2.2%	Asphaltic Concrete	
Update	ed = 8/29/2017	(Friction Rating = IV - Coarse Agg. Only)	
		Riprap & Stone Revetment	

Out of State

APS00012680	warren Paving-Salem, KY-Lower High Calcium Ledge	
<u>Material</u>	Approved Uses	
Stone	Base & Surface Course	
(Limestone)	Granular Material for Subbase	
Lower Warsaw Formation	Special Embankment (non-plastic)	
Spec. Gravity-SSD = 2.67	Asphaltic Surface Treatment	
Water Absportion = 0.7%	Asphaltic Concrete	
Updated = 6/24/2022	(Friction Rating = IV - Coarse Agg. Only)	
	Portland Cement Concrete	
	(may be used on bridge decks)	
	Riprap & Stone Revetment	

APS00012880	Lafarge Aggregates-Smithland, KY-Three Rivers-S2	
<u>Material</u>	Approved Uses	
Stone	Base & Surface Course	
(Siliceous Limestone)	Granular Material for Subbase	
Spec. Gravity-SSD = 2.69	Special Embankment (non-plastic)	
Water Absportion = 0.8%	Asphaltic Surface Treatment	
Updated = 5/20/2020	Asphaltic Concrete	
	(excluding OGFC and coarse mix)	
	(Friction Rating = III - Coarse Agg. Only)	
	Riprap & Stone Revetment	

Out of State

APS00012960	APAC R4 ObrusS.A. D.C.V Boca Del Rio, Mexico
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Granite)	Granular Material for Subbase
Spec. Gravity-SSD = 2.89	Special Embankment (non-plastic)
Water Absportion = 1.5%	Asphaltic Surface Treatment
Updated = 2/16/2024	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment

APS00013370 Canteras LA Ponderosa S.A. - OoliticStnFormtn -5.1

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.71	Special Embankment (non-plastic)
Water Absportion = 1.2%	Asphaltic Surface Treatment
Updated = 2/21/2024	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment

APS00014110 Rogers Group - Lacey's Springs Quarry

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.70	Special Embankment (non-plastic)
Water Absportion = 0.7%	Asphaltic Surface Treatment
Updated = 2/14/2020	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment

APS00014340	Lafarge Aggregates-Smithland, KY-Upper Fredonia	
<u>Material</u>	Approved Uses	
Stone	Base & Surface Course	
(Siliceous Limestone)	Granular Material for Subbase	
Spec. Gravity-SSD = 2.70	Special Embankment (non-plastic)	
Water Absportion = 1.0%	Asphaltic Surface Treatment	
Updated = 10/21/2020	Asphaltic Concrete	
	(Friction Rating = IV - Coarse Agg. Only)	
	Riprap & Stone Revetment	

Out of State

APS00014530	Martin Marietta - Mill Creek - Granite
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Granite)	Granular Material for Subbase
Spec. Gravity-SSD = 2.74	Special Embankment (non-plastic)
Water Absportion = 1.0%	Asphaltic Surface Treatment
Updated = 2/16/2024	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment

APS00014540 Martin Marietta - Mill Creek - Limestone

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Dolomitic Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.81	Special Embankment (non-plastic)
Water Absportion = 0.4%	Asphaltic Surface Treatment
Updated = 5/31/2022	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	Rinran & Stone Revetment

APS00014560 Shorline Aggregates Inc. - South Brook Quarry

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Granite)	Granular Material for Subbase
Spec. Gravity-SSD = 2.71	Special Embankment (non-plastic)
Water Absportion = 0.5%	Asphaltic Surface Treatment
Updated = 2/16/2024	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment

\bigcirc	4	٦f	State
\mathbf{U}	ut	OI.	State

APS00014700	Heidelberg Materials-Servtex Quarry-New Braunfels
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
F.K.A. Hanson Aggregates	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.57	Asphaltic Surface Treatment
Water Absportion = 2.0%	Asphaltic Concrete
Updated = 5/22/2023	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
	(excluding bridge decks)
	Riprap & Stone Revetment

APS00014710	Arcosa Lightweight - Livingston, AL	
<u>Material</u>	Approved Uses	
Lightweight Aggregate	Special Embankment (non-plastic)	
(Expanded Clay)	Asphaltic Surface Treatment	
Spec. Gravity-SSD = 1.07	Asphaltic Concrete	
Water Absportion = 20.8%	(Friction Rating = I - Coarse Agg. Only)	
Updated = 12/8/2021	Portland Cement Concrete	

Out of State

APS00014740	Heidelberg Materials - Burnet Quarry
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Siliceous Limestone)	Granular Material for Subbase
F.K.A. Hanson Aggregates	- Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.78	Asphaltic Surface Treatment
Water Absportion = 0.6%	Asphaltic Concrete
Updated = 5/22/2023	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(excluding bridge decks)
	Riprap & Stone Revetment

APS00014900	Neely's Landing LLC Jackson, MO	
<u>Material</u>	Approved Uses	
Stone	Base & Surface Course	
(Siliceous Limestone)	Granular Material for Subbase	
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)	
Water Absportion = 1.0%	Asphaltic Surface Treatment	
Updated = 10/20/2021	Asphaltic Concrete	
	(Friction Rating = III - Coarse Agg. Only)	
	Portland Cement Concrete	
	Riprap & Stone Revetment	

\cap	ı ıt	$\cap f$	Sta	te
\sim	uι	OI.	Ota	ı

APS00014980	Arcosa Lightweight - Streetman Plant	
<u>Material</u>	Approved Uses	
Lightweight Aggregate	Asphaltic Surface Treatment	
(Expanded Shale)	Asphaltic Concrete	
Spec. Gravity-SSD = 1.65	(Friction Rating = I - Coarse Agg. Only)	
Water Absportion = 14.1%	Portland Cement Concrete	
Updated = 12/2/2022		

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.67	Special Embankment (non-plastic)
Water Absportion = 1.3%	Asphaltic Surface Treatment
Updated = 6/24/2022	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(may be used on bridge decks)
	Rinran & Stone Revetment

APS00015110 Lafarge Aggregates-Cave-In-Rock, IL-Dolomite Ledge

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Dolomitic Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.67	Special Embankment (non-plastic)
Water Absportion = 1.1%	Asphaltic Surface Treatment
Updated = 6/24/2022	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
	(may be used on bridge decks)
	Riprap & Stone Revetment

APS00015120 Lafarge Aggrs-Cave-In-Rock, IL-Upper St. Gen Ledge

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.67	Special Embankment (non-plastic)
Water Absportion = 0.9%	Asphaltic Surface Treatment
Updated = 6/24/2022	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(may be used on bridge decks)
	Riprap & Stone Revetment

ìG	GREGATES APPROVED MATERIALS LIST		
	В	. OTHER AGGREGATE MATERIALS	
	Out of State		
	APS00015130	Lafarge Aggs - Cave-In-Rock, IL - Transition Ledge	
	<u>Material</u>	Approved Uses	
	Sand	Base & Surface Course	
	Stone	Granular Material for Subbase	
	(Limestone)	Special Embankment (non-plastic)	
	Spec. Gravity-SSD = 2.65	Asphaltic Surface Treatment	
	Water Absportion = 1.3%	Asphaltic Concrete	
	Updated = 6/20/2022	(Friction Rating = IV - Coarse Agg. Only)	
		Riprap & Stone Revetment	
	APS00015230	Shoreline Agg., Inc Point Rousse Quarry	
	<u>Material</u>	Approved Uses	
	Stone	Base & Surface Course	
	(Granite)	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.79	Special Embankment (non-plastic)	
	Water Absportion = 0.4%	Asphaltic Surface Treatment	
	Updated = 2/16/2024	Asphaltic Concrete	
		(Friction Rating = III - Coarse Agg. Only)	
		Portland Cement Concrete	
		Riprap & Stone Revetment	
	APS00015310	Hastie Mining and Trucking #2 - Cave-In-Rock, IL	
	<u>Material</u>	Approved Uses	
	Sand	Base & Surface Course	
	Stone	Granular Material for Subbase	
	(Siliceous Limestone)	Special Embankment (non-plastic)	
	Spec. Gravity-SSD = 2.69	Asphaltic Surface Treatment	
	Water Absportion = 1.0%	Asphaltic Concrete	

<u>iviate</u> i	<u>riai</u>	Approved Uses
Sand		Base & Surface Course
Stone	9	Granular Material for Subbase
	(Siliceous Limestone)	Special Embankment (non-plastic)
	Spec. Gravity-SSD = 2.69	Asphaltic Surface Treatment
	Water Absportion = 1.0%	Asphaltic Concrete
Upda	ted = 7/29/2022	(Friction Rating = IV - Coarse Agg. Only)
		Riprap & Stone Revetment

Matco Aggregates LLC. - Actopan Quarry - Basalt APS00015390

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Granite)	Granular Material for Subbase
Spec. Gravity-SSD = 2.87	Special Embankment (non-plastic)
Water Absportion = 2.1%	Asphaltic Surface Treatment
Updated = 2/16/2024	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment

APS00015610 CEMEX 4200 Balcones Quarry - New Braunfels,TX

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.58	Asphaltic Surface Treatment
Water Absportion = 1.5%	Asphaltic Concrete
Updated = 8/16/2023	(Friction Rating = IV - Coarse Agg. Only)
	Riprap & Stone Revetment

В.	OTHER AGGREGATE MATERIALS
Out of State	
APS00015630	Lafarge Aggrs-Cave-In-Rock, IL - Downeys Bluff Led
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.67	Asphaltic Surface Treatment
Water Absportion = 1.1%	Asphaltic Concrete
Updated = 9/15/2023	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) Riprap & Stone Revetment
APS00015640	Coastal Industrial Resources, LLC-Gibralgar Quarry
Material	Approved Uses
Stone	Base & Surface Course
(Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.65	Asphaltic Surface Treatment
Water Absportion = 1.6%	Asphaltic Concrete
Updated = 9/15/2023	(Friction Rating = IV - Coarse Agg. Only)
Opuateu = 9/13/2023	Riprap & Stone Revetment
A DC0004E720	
APS00015720	GCA Materials - May Pen, Jamaica
Material Chara	Approved Uses
Stone	Base & Surface Course
(Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.65	Asphaltic Surface Treatment
Water Absportion = 2.0%	Asphaltic Concrete
Updated = 9/15/2023	(Friction Rating = IV - Coarse Agg. Only)
A DO0004 5700	Riprap & Stone Revetment
APS00015790	Cemex Materials Newfoundland, Inc Canada
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Dolomitic Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.75	Asphaltic Surface Treatment
Water Absportion = 0.4%	Asphaltic Concrete
Updated = 11/13/2023	(Friction Rating = IV - Coarse Agg. Only)
	Riprap & Stone Revetment
APS00015840	Souter Limestone and Minerals, LLC Gore, OK
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.67	Special Embankment (non-plastic)
Water Absportion = 0.7%	Asphaltic Surface Treatment
Updated = 1/12/2024	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete

(may be used on bridge decks) Riprap & Stone Revetment

Out of State

APS00015850	Holcim, Inc Three Rivers Quarry - Smithland, KY	
<u>Material</u>	Approved Uses	
Stone	Base & Surface Course	
(Limestone)	Special Embankment (non-plastic)	
Spec. Gravity-SSD = 2.66	Asphaltic Surface Treatment	
Water Absportion = 1.0%	Asphaltic Concrete	
Updated = 1/29/2024	(Friction Rating = IV - Coarse Agg. Only)	
	Riprap & Stone Revetment	

APS00015940 Two Countries Materials S.A. DE CV - Mexico

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.68	Asphaltic Surface Treatment
Water Absportion = 2.0%	Asphaltic Concrete
Updated = 3/14/2024	Riprap & Stone Revetment

APS00016010 Tajo Chirripo S.A. - Limon

<u>Material</u>	Approved Uses Base & Surface Course
Stone	
(Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.66	Asphaltic Surface Treatment
Water Absportion = 1.6%	Asphaltic Concrete
Updated = 6/20/2024	(Friction Rating = IV - Coarse Agg. Only)
	Riprap & Stone Revetment

APS00016120	Antoine Rock Quarry - Delight, AR	
<u>Material</u>	Approved Uses	
Stone	Riprap & Stone Revetment	
(Limestone)		

Updated = 9/10/2024

NOTES:

Note B-1:

Refer to Subsections 501.02 and 1003.06 for definition and application of Friction Ratings.

Note B-2:

All material, regardless of prior approval, shall be sampled in accrodance with the Materials Sampling Manual and tested for conformance to the appropriate specifications. Any deviation in performance from the original sample submitted may result in removal of the material from the approved list.

REFERENCE:

DOTD Standard Specifications and Special Provisions, Section 1003

DOTD Supplemental Specifications

DOTD Maintenance Specifications

No information contained in this list is to be used for promotional purposes.