

SPECIFICATIONS

TO BE A NEW 35 FT. TANDEM DUAL 15K AXLE, GOOSENECK TRAILER AND SHALL MEET OR EXCEED THE FOLLOWING SPECIFICATIONS:

GVWR: 30,000 LBS

GCWR: 24,000 LBS

Deck Length: 30 feet long

Deck Width: 8'6" Wide

Deck Height: Approximately 36" (Unloaded)

Dovetail Length: 5 feet long w/ dozer cleats

Frame: 14 inch 22lbs/ft. wide flange H-beam

Anti-Twist: 4.5" Sch. 40 Torque Tube runs length of trailer & 3"x4" tube frame truss

Floor braces: 4" channel cross members

Ramps: 5 foot fold over self-cleaning dozer ramps with spring assist (heavy duty)

Axles: Qty of 2, 15,000 lbs. electric brake Dexter Axles (or equal)

Brakes: Electric brakes on both axles

Jacks: Qty of 2, 2 speed, 25,000 lbs. drop leg

Steps: Qty of 2, one on each side in front

Plug: 7 way RV Style

Suspension: 60,000 LBS rated Hutchens H9700 or equal

Rubrail & Stakepockets: 2.5"x 3/8" rubrail full length of deck on each side w/ standard stake pockets spaced every 18"

Hitch: 2 5/16" adjustable gooseneck coupler

Safety Chains: 5/8" grade 80 heavy duty

Safety: Electric brake-away safety device

Floor: 2"x8" treated wood

Floor Over Axles: ¼" Diamond Plate steel runners over wheels only

Tires: 235/75R17.5, 16 ply

Wheels: 8 hole 17.5 dual rims

Spare: Full size spare included

Spare Mount: Storage mount in tongue

Toolbox: Mounted under tongue, Dimensions: 35.5"x12"x10.5"

Lights: Rubber mounted sealed beam LED lights

Conspicuity: 3M Reflective Tape DOT

Coating: Fully primed and painted black (No other color will be accepted)

Warranty: 1-year warranty on all welds and workmanship on the trailer. 5-year warranty on axles and axle components, 5-year warranty on suspension and suspension components.

REGISTRATION FEES SHOULD NOT BE INCLUDED IN PRICING AS LDWF WILL DO THIS PROCESS.