



STATE OF LOUISIANA
DEPARTMENT OF TRANSPORTATION AND DEVELOPMENT
TECHNICAL SPECIFICATIONS FOR

Bumper Pull 20 ft. Container Chassis/Trailer

SERIES NO. 505-000

REV. 11/25/2024

EQUIPMENT SPECIFICATION 505-000B

GENERAL

This specification sets forth the minimum requirements for a bumper pull 20 ft. Container Chassis/Trailer.

Equipment shall be new, a production model of current manufacture, and must meet all state and Federal safety and emission standards in effect at time of order.

REPRESENTATIVE SPECIFICATIONS

A Conexwest model CXW-20TRNBP, with appropriate options and standard features, was used to develop these specifications and establish equivalency evaluation criteria.

Equipment of similar style, type, character, quality, features, and purpose conforming to the following detailed requirements/specifications will be considered. For evaluation purposes, bidders proposing an exception/equivalent option/feature to those specified herein, may be required to provide manufacturer/product information (catalogue sheets, detailed specifications, pictures, etc.). This information will be evaluated against the minimum requirements of this specification. Proposed submittals that are determined not to be equivalent to the established criteria will be rejected.

LOUISIANA AUTHORIZED DEALER(S)

Proposed item(s) should be from a manufacturer who has at least one (1) authorized dealer **within the State of Louisiana** where parts and service can be obtained. Authorized dealer(s) must have properly trained technicians plus all other resources necessary to perform warranty and repair services in complete accordance with the manufacturer's requirements. A letter certifying the ability to meet this requirement, inclusive of the company name(s) and address(es) of the Louisiana authorized dealer(s), should be supplied with the bid submittal and may be required prior to award.

DELIVERY & ACCEPTANCE

Vendor shall perform a test run of each unit to verify that all features and capabilities are operating properly at time of delivery. Documentation of testing may be required prior to acceptance by the Department.

Unit(s) must be delivered completely assembled (including all components, accessories, etc.) and ready for operation without any additional preparation including, but not limited to, ensuring all fluid levels are at their full mark, fuel tank(s) is full, all necessary lubrication has been performed, etc. A Louisiana safety inspection shall be performed on each vehicle prior to delivery and a Louisiana safety inspection sticker properly affixed.

Any unit delivered under this specification is subject to rejection if there is evidence of poor workmanship, by either the vendor or the original manufacturer. Noted defects and/or nonconformance findings may

be corrected by the vendor. Corrections must be completed and approved by the Equipment Engineer or his representative prior to final acceptance.

Unit(s) shall be delivered "**on the ground**;" DOTD will not unload nor provide any unloading equipment to the vendor/delivery driver in order to offload the unit(s).

NOTE: The Department will have space available for equipment to be unloaded.

EACH UNIT MUST BE SUPPLIED WITH THE FOLLOWING DOCUMENTATION AT TIME OF DELIVERY:

1. Notarized Bill of Sale
2. Original Certificate of Origin (MSO), (no photocopy)
3. Dealer's Service Policy
4. Owner's/Operator's Manual(s)
 - a. One (1) Hardcopy
 - b. One (1) Digital Copy
 - i. Acceptable Formats: PDF delivered via USB "Flash Drive", or E-mail
5. Service Manual(s)
 - a. One (1) Hardcopy
 - b. One (1) Digital Copy
 - i. Acceptable Formats: PDF delivered via USB "Flash Drive", or E-mail
6. Build Sheet(s) – as applicable
 - a. One (1) Hardcopy
 - b. Build sheets should be written in plain language (not company specific codes) and include, at a minimum, all standard & optional features of the delivered unit.

NOTE: Invoices will not be processed for payment until the unit(s) have been inspected by the Equipment Engineer or their representative and deemed in compliance with the specifications.

BID SUBMITTALS

Any additions, deletions, or variations from the specifications should be noted in the "Bidder's Exceptions" page of this specification. Exceptions that are noted to be less than a minimum requirement will not be accepted.

Any additions, deletions or variations from the manufacturer's standard published specifications should be noted on the "Bidder's Exceptions" page of this specification. Unless otherwise noted, any items appearing in the manufacturer's standard published specifications furnished by the Bidder are assumed to be included in the Bidder's submittal.

Bidder should note on their submittal any installation(s) to the equipment that will be performed by the vendor instead of the manufacturer.

Failure to note any specification exceptions, manufacturer specification alterations, and/or vendor installations prior to award may result in rejection of the equipment at the time of delivery.

THE NUMBER OF DELIVERY DAYS AFTER RECEIPT OF ORDER (ARO) MAY BE USED AS A FACTOR IN THE AWARD.

EQUIPMENT SPECIFICATIONS

NOTICE TO BIDDERS

Bidder should review the detailed "Equipment Specification" completely and respond to the compliance question at the end of each section by marking "X", in the space provided, for "Yes" or "No". Mark "Yes" to indicate that the equipment bid meets the section exactly as specified. Mark "No" if there are exceptions to any part of that section. Exceptions/deviations to any part of the specification are to be detailed on the "Bidder's Exceptions" page of this specification.

IN ORDER TO BE CONSIDERED FOR AWARD, BIDDER SHOULD RETURN THIS SPECIFICATION, COMPLETED IN FULL, WITH THEIR BID SUBMITTAL.

Note: All values listed below are minimums unless noted otherwise.

1. Chassis/Trailer Design and Construction

1.1. Dimensions of Chassis/Trailer

1.1.1. 24' in length including trailer tongue

1.1.2. 8' 0" width

1.1.3. Deck Length 19' 10"

1.2. GVWR 14,000 lbs.

Comply: ____Yes ____No

1.3. Frame and Crossmembers

1.3.1. Chassis frame deck perimeter to be constructed of 6" I-beam

1.3.2. Chassis frame deck perimeter to be 19' 10" long

1.3.3. Chassis frame deck perimeter to be 8' 0" wide

1.3.4. Crossmembers to be a maximum of 5' apart

1.3.5. Crossmembers to be non-load bearing

1.3.6. Crossmembers to be 3" I-beam or Channel

1.3.7. Four container locks to accommodate 20ft container

1.3.8. Four leveling jacks rated at 12,500 pounds each

1.3.9. Trailer and container height not to exceed 13' 6" when container is mounted on trailer

Comply: ____Yes ____No

1.4. Trailer Tongue

1.4.1. 6" I-beam Construction

1.4.2. single 6" I-beam tongue crossmember

1.4.3. Pintle hitch coupler, adjustable height (rated capacity must meet or exceed GVWR of trailer)

1.4.4. 8,000 pound drop leg jack mounted to tongue cross member

1.4.5. Two (2) safety chains with safety latch hooks

Comply: ____Yes ____No

EQUIPMENT SPECIFICATIONS

1.5. Axles, Suspension and Brakes

1.5.1. Tandem Axles

1.5.2. Axles rated for 7,000 pounds each

1.5.3. Multi-leaf spring suspension, designed for use by the trailer industry

1.5.4. Electric brakes on both axles

1.5.5. Electric breakaway kit with battery & charger

Comply: ____ Yes ____ No

1.6. Wheels and Tires

1.6.1. 16 inch 8 lug wheels

1.6.2. Four first line, first quality ST235/80/16(E) tires on all wheels

1.6.3. Combined load rating must equal or exceed gross axle weight rating (GAWR)

1.6.4. Spare tire and wheel mounted on trailer

Comply: ____ Yes ____ No

1.7. Electrical & Lighting

1.7.1. Plug – 7-way RV-style

1.7.2. All lighting must be LED and must conform to latest Louisiana & Federal laws

1.7.3. Wiring harness to be sealed or ran in conduit for protection

1.7.3.1. Harness must be securely fastened to chassis and protected from damage by the use of non-metallic (rubber/plastic) grommets or bushings where it passes through holes in steel chassis.

1.7.3.2. Splices should be done with waterproof connectors plus sealed and covered with heat shrink tubing

1.7.3.3. "SCOTCH LOCK" OR SIMILAR INSULATION DISPLACEMENT CONTACT (IDC) QUICK SPLICE CONNECTORS ARE NOT ALLOWED

1.7.4. 2" high visibility conspicuity tape (red/white) on each side, full length

1.7.5. All lighting must be LED and must conform to the latest Louisiana & Federal laws

Comply: ____ Yes ____ No

1.8. Paint: Manufacturer's standard, black or gray

Comply: ____ Yes ____ No

