

Attachment B – Specifications

RFx. No.: 3000024489

Title: *Rebid*Boat Package - DEQ

Line 1: Boat & Motor

Specifications for Boat and Trailer: Note: **Engine was purchased already. Accurate boat specifications are needed due to the size and type of engine. Boat size outside these specifications can cause safety and operational issues.**

Boat: **Model is Gator Trax 14-16'x44" GT Model or Equal**

- Length – from bow to stern: 14-16'
- Bottom Hull Width 44"
- Top Hull Width 63"
- Transom Height: mandatory 19-22"
- Side Height: mandatory True 17-19 "
- Aluminum Hull thickness at least .125" (thickness of aluminum used to build the boat)
- Due to the size of the boat (<20'), floatation is required by USCG to be built within the vessel.
- Front deck with floatation - mandatory
- Welded Cleats - 1 on bow, 2 in rear port and starboard, 2 at midship – port and starboard - preferred
- 18" depth Center Bench seat with top storage hatch - mandatory
- Fuel Tank: Plastic 6 gallons
- Driver side ½ box for seat
- 1 - 12 Volt cranking battery
- 15" Huntdeck with floatation = Huntdeck is an industry term used for a covered void space behind the rear deck to keep the nose of the boat down when taking off from a stop. Shallow water feature. Safety aspect - in case there is a man overboard. Person can re-board the boat on the Huntdeck. - mandatory

Trailer: **Tennessee Trailers, Model is GT54 or Equal**

- Minimum 2650 lb axle
- 14" tires
- 4 adjustable bunks with Teflon coat
- Galvanized - mandatory
- Spare tire and mount
- No brakes on trailer
- Swivel jack – mandatory
- LED lights - preferred
- Step in front and in back of tires
- Boat tie down straps - mandatory
- Safety chains
- Side guides (adjustable)

Line 2: Whaler Boat

Boat/Trailer/Motor Package Specifications

- Make - 2025 Boston Whaler or Equal
- Model - 250 Outrage or Equal
- Overall Length (L.O.A) 25' 5" (7.75 m)
- Beam 9' (2.74 m)
- Draft 20" (.46 m)
- Weight (dry, no engine) 5,350 lbs (2,427 kg)
- Weight (with engine, fuel and water) 7,325 lbs (3,322 kg)
- Maximum Weight Capacity 3,642 lbs (1,652 kg)
- Swamped Capacity 2,980 lbs (1,352 kg)
- Persons Capacity 12
- Bridge Clearance with Hardtop 8'7"
- Maximum Horsepower 450 hp (336 kW)
- Minimum Horsepower 350 hp (261 kW)
- Transom Height 25" (.63 m) Dual engines
- Fuel Capacity 172 gallons (651 L)
- Water capacity 26 gallons (98.4 L)
- Automatic bilge pumps, 750 GPH fwd, 1100 GPH aft
- Electric horn
- Electrical distribution / breaker panel with key switches (inside console)
- Freshwater system with 26-gallon tank and transom shower
- LED navigation lights
- Raw water washdown
- Recessed electric trim tabs with indicators
- Propeller - stainless steel
- Tilt steering

Additional equipment requested:

- Hardtop with electronics box and windshield wiper – Product must include: bow area floodlight, cockpit floodlights (2), dome light (red and white), electronics box, lifejacket storage, outrigger ready, rod holders (5) tempered glass windshield with power actuated vent
- 12" Simrad NSX Navigation Package or equal - Simrad NSX 12" MFD or equal (GPS, Chart Plotter, Fishfinder) active Imaging 3 in 1 Transom Mount Transducer (CHIRP, SideScan, DownScan) Integrated Mercury SmartCraft Connect and C-Map Discover™ X Chart Card: NorthAmerica/Canada)
- VHF radio, Simrad RS40 VHF or equal radio with AIS and HS40 wireless handset
- Battery Package (for dual engines)Charging System
- Gel Coat Full Hull Color - White
- Black Graphics
- White hardtop frame with Electrical box
- Shore (Tan) Exterior Upholstery PackageStandard) or equal
- Bow tow eye

Motors: Two - 225 V6 DTS Black Mercury Four Stroke engines hydraulic power steering and fuel/water separators Merc or Equal

Trailer: Marine Trailer - McClain ATT 3010 10k GVWR Aluminum Trailer or Equal

- Tandem Axle Aluminurn Trailer
- Disc Brakes on both axles
- Fixed Bunks for Outrage 250
- Fits boat length 25.5"
- Spare Tire & Carrier