## Specifications

## To be a new 30ft Flat Bed Gooseneck Trailer with Hydraulic Dove Tail & Shall Meet or Exceed the Following Specifications

Length- 30 Foot total length including a minimum 10 foot hydraulic dove tail

**Hydraulic dove tail** – 10 foot minimum with steel sides  $\frac{1}{2}$ " inch by  $\frac{1}{2}$ " inch square bar cleats on outside of 10 foot of dove tail. Minimum 2 hydraulic cylinders 5" inch by 7  $\frac{1}{2}$ " inch, with a minimum 10,000 pound lift capacity.

Gross Vehicle Weight Rating – 30,000 pounds

Frame and Neck– 12" inch minimum neck and minimum 22lb I-beam minimum

Width – 102" inches

**Deck Height** – 33.5" inches (Unloaded)

Axles- 2 tandem 15,000 pound electric over hydraulic oil bath hubs

Wheels - Black or silver in color 17.5" inch 8 hole tandem dual

**Tires** – ST215/75 R17.5 LRH LRE 16 ply

Brakes – Electric over hydraulic brakes

Suspension - low profile heavy duty hutch suspension

Crossmembers – 3" inch I beam, 12" inch on center

Bridging- frame to be bridged

Deck – 2" inch treated lumber

**Coupler** – 2" 5/16" inch 30,000 pound capacity with 3/8" inch safety chains

Jacks- 2 hydraulic jacks with minimum 15,000 pound lift capacity

Battery charger- Minimum 110 volt 5 amp battery charger

**Hydraulics** – 48" inch square box mounted under belly with self-contained 1000 pound per square inch pump with 12 volt 27 series deep cycle battery. Hydraulic pump will be dual acting for dove tail and front jack operation. Hydraulics to be operated with hard wired remote wired into 12 volt electrical system.

**Toolbox** – Lockable toolbox with chain hanger located on the front under gooseneck. Dimensions - W 12 inches x D 19 inches x L 60 inches.

Lights- DOT approved flush mount lifetime LED lights.

Wiring – Minimum 16 gauge insulated and all weather sealed wiring with 7-way RV plug

Paint- Black powder coated with primer

**Rub rail** –  $2^{n}x 6^{n}x 1/8^{n}$  inch rectangular tubing with stake pockets with DOT approved reflective tape

**Spare tire and mount** – spare tire to match existing size tires and tire and wheel mount on top of gooseneck.

## Successful bidder shall deliver trailer to:

Bodcau WMA

168 Ben Durden Rd

Haughton, LA 71037