

Attachment B – Specifications

RFx No.: 3000024639

Title: *Rebid* Building Materials - DOC/DWCC

Successful vendor to provide building materials for David Wade Correctional Center Recreational Building to include all framing materials, windows, and doors.

Jobsite Address: David Wade Correctional Center
Recreation Building
670 Bell Hill Road
Homer, LA 71040

Scope of Work:

LINE

1. 8"X 48" Quickcrete Building Form Tube (Sonotube)	20 Each
2. 4"x4"x8' Grader #2 Treated Ground Contact	6 Each
3. 6"x6"x10' Grade #2 Treated Ground Contact	8 Each
4. 2"x12"x16' Grade #1 Treated Ground Contact	12 Each
5. 2"x4"x8' Grade #1 Treated Ground Contact	24 Each
6. 2"x4"x12' Grade #1 Treated Ground Contact	15 Each
7. 2"x8"x16' Grade #1 Treated Ground Contact	12 Each
8. 5/4"x6"x16' Decking Board Grade #1 Treated Ground Contact	40 Each
9. 2"x12"x16' Grade #2 Yellow Pine	6 Each
10. 2"x12"x14' Grade #2 Yellow Pine	50 Each
11. 1-1/8" Thick 4'x8' Oriented strand board, Tongue and Groove Warrantied	30 Each
12. 2"x4"x92- 5/8" Spruce Pine Fir	200 Each
13. 2"x4"x16' Grade #3 Yellow Pine	145 Each
14. 2"x6"x16' Grade #1 Yellow Pine	55 Each

Metal Quote

1. 20' 26GA Ram-Z Rib Charcoal Grey Metal	12 Each
2. 15' 26GA Ram-Z Rib Charcoal Grey Metal	12 Each
3. 9' 26GA Ram-Z Rib Charcoal Grey Metal	12 Each
4. 12'3" Perling Rib Ridge Charcoal Grey Metal	3 Each
5. 10'3" Residential Rake Trim Charcoal Grey Metal	9 Each
6. 10'3" Residential Eave Trim Charcoal Grey Metal	8 Each
7. 36" I/O Foam Closures	25 Each
8. 1-1/2" Wood Grip Lifetime Charcoal Grey Screws	750 Each
9. 1" Lap/Stitch Lifetime Charcoal Grey Screws	250 Each
10. 3/8" x 45' Seam/Butyl Tape	11 Each

Other Framing Material

- | | |
|--|---------|
| 1. 1"x6"x16' Grade #2 Treated Ground Contact | 25 Each |
| 2. 5/8" Thick 4'x8' T-1-11 8" On Center | 50 Each |
| 3. 3/8" Thick 4'x8' BC Sanded Pine | 17 Each |
| 4. Eave Vent 16"x8" White Aluminum Surface Corrosion Resistant | 16 Each |
| 5. 1/2" Thick 4'x12' Lite Sheetrock, HS Lite | 65 Each |
| 6. 1"x4"x14' Yellow Pine. Grade #2 | 75 Each |
| 7. Compound Joint Ready Mix 4.5GA | 4 Pail |

Windows

- | | |
|--|--------|
| 1. Raw Opening 36"x52" Actual Window Dimensions 35-1/2"X 51-1/2" Single Hung Cornerstone Cream White Vinyl Window Low E With Clear Screen and Double Locks | 4 Each |
| 2. Foil Flashing Tape 4"x75' BUTYL based adhesive layer | 1 Roll |

Exterior Doors

- | | |
|---|--------|
| 1. Raw Opening 38-1/4" x 82-5/16". Door Size 3' X 6' 8"x 1-3/4" Thick Smooth Fiber Glass Door with 9 Lite Glass Insert Low-E ,with two panel bottom. Right hand inswing. 2-3/8" backset double bore (2-1/8" diameter bore with standard 5-1/2" spacing) with recessed latch preps. Set of brushed nickel hinges, primed dura-frame 4-9/16" Jamb with no exterior trim. Brushed nickel adjustable security strike plate for lockset only, bronze compression weather-strip, and 5-3/4" composite adjustable Bronze with dark cap sill. | 1 Each |
|---|--------|

Interior Doors

- | | |
|--|--------|
| 1. Raw opening 38-1/2" x 82-1/2". Door Size 3" X 6'8" X 1-3/8" Thick. Textured 6 Panel Primed Hollow Core Single Door. Left hand swing, with 3-1/2" standard satin nickel hinges. Pre hung in FJ pine 4-5/8" Jamb, with FJ pine stops. 2-3/8" backset face bore, with recessed edge prep. Two sided 1"x 4" S4S (3-1/2" x 21/32") FJ pine butt joint casing (loose square cut) | 1 Each |
| 2. Raw opening 38-1/2" x 82-1/2". Door Size 3" X 6'8" X 1-3/8" Thick. Textured 6 Panel Primed Hollow Core Single Door. Right hand swing, with 3-1/2" standard satin nickel hinges. Pre hung in FJ pine 4-5/8" Jamb, with FJ pine stops. 2-3/8" backset face bore, with recessed edge prep. Two sided 1"x 4" S4S (3-1/2" x 21/32") FJ pine butt joint casing (loose square cut) | 1 Each |
| 3. Raw opening 34-1/4" x 82-1/2". Door Size 2'8" x 6'8"x 1-3/8" Thick Textured 6 panel primed molded hollow core single door. Left hand inswing, with 3-1/2" standard satin nickel hinges. Pre hung in Fj pine 4-5/8" jamb, with FJ pine stops. 2-3/8" backset face bore, with recessed edge prep. Two sides 1" x 4" S4S (3-1/2" x 21-32") FJ pine Butt Joint Casing (loose square cut) | 1 Each |
| 4. Raw opening 34-1/4" x 82-1/2". Door Size 2'8" x 6'8"x 1-3/8" Thick Textured 6 panel primed molded hollow core single door. Right hand inswing, with 3-1/2" standard satin nickel hinges. Pre hung in Fj pine 4-5/8" jamb, with FJ pine stops. 2-3/8" backset face bore, with recessed edge prep. Two sides 1" x 4" S4S (3-1/2" x 21-32") FJ pine Butt Joint Casing (loose square cut) | 1 Each |

Interior Trim/Insulation

- | | |
|--|----------|
| 1. R-13 Kraft Faced Fiberglass Batt 3-1/2" x 15" x 93" 116.25 SF Per Bag | 13 Each |
| 2. R-30 Kraft Faced Fiberglass Batt 10"x24" 88.00 SF Per Bag | 11 Rolls |
| 3. 16' Quarter Round Primed Molding | 13 Each |
| 4. 3-1/4" x 17' Primed Colonial Base Molding | 18 Each |
| 5. 16' Base Shoe Primed Molding | 18 Each |
| 6. 2-1/4"x14' Colonial Case Molding | 13 Each |
| 7. 3/4" Thick 4"x8" China Birch C-2 18MM | 21 Each |
| 8. 1"x12"x12' Eastern White Pine Shelving | 15 Each |