

0

# Bid Number <u>50–00148708</u>

Pre-Placed Emergency Contract for Point Repair, Lining and
Emergency Restoration of Existing Sewer Mainlines, Force Mains and
Televising, Cleaning and Rehabilitation of Sewer Lines the Jefferson
Parish Department of Public Works- Department of Sewerage

October 21, 2025 at 2:00 pm

## **ATTENTION VENDORS!!!**

Please review all pages and respond accordingly, complying with all provisions in the technical specifications and Jefferson Parish Instructions for Bidders and General Terms and Conditions. All bids must be received on the Purchasing Department's eProcurement site by the bid due date and time.

Jefferson Parish Purchasing Department 200 Derbigny Street General Government Building, Suite 4400 Gretna, LA 70053

**Buyer Name: Donna M Evans, Purchasing Specialist II** 

Buyer Email: <a href="mailto:DONNA.EVANS@jeffparish.gov">DONNA.EVANS@jeffparish.gov</a>

Buyer Phone: 504-364-2691

INVITATION TO BID THIS IS NOT AN ORDER

DATE: 9/24/2025

BID NO: 50-00148708

**JEFFERSON PARISH** 

PURCHASING DEPARTMENT P.O. BOX 9 GRETNA, LA. 70054-0009 504-364-2678 PURCHASING SPECIALIST: @jeffparish.gov

Page:

BIDS WILL BE RECEIVED ONLINE VIA WWW.JEFFPARISHBIDS.NET UNTIL 2:00 PM, 10/21/2025
AND PUBLICLY OPENED THEREAFTER IN THE WEST BANK PURCHASING DEPT, SUITE 4400, JEFFERSON PARISH
GENERAL GOVERNMENT BUILDING, 200 DERBIGNY STREET, GRETNA, LA 70053. At no charge, bidders are to submit
their bid via Jefferson Parish's electronic procurement page. Additional instructions are included in the text box
highlighting electronic procurement.

#### LATE BIDS WILL NOT BE ACCEPTED

NOTE: ONLY BIDS WRITTEN IN INK OR TYPEWRITTEN, AND PROPERLY SIGNED BY A MEMBER OF THE FIRM OR AUTHORIZED REPRESENTATIVE, WILL BE ACCEPTED. PENCIL AND/OR PHOTOSTATIC FIGURES FOR SIGNATURES SHALL RESULT IN BID REJECTION. HOWEVER, ELECTRONIC SIGNATURES AS DEFINED IN La. R.S. 9:2602(8) ARE ACCEPTABLE. IN ACCORDANCE WITH La. R.S. 9:2602(8, JEFFERSON PARISH REQUIRES A SECURED DIGITAL SIGNATURE AND BIDDERS MUST PROVIDE PROOF OF THE SECURED SIGNATURE WITH BID SUBMISSION.

#### INSTRUCTIONS FOR BIDDERS AND GENERAL CONDITIONS

- A. All bids submitted are subject to these instructions and general conditions and any special conditions and specifications contained herein, and in the terms and conditions of Resolution No. 136353 and/or Resolution No. 141125, all of which are made part of this bid proposal and ensuing contract by reference. By submitting a bid, vendor agrees to comply with all provisions of Louisiana Law as well be in compliance with the Jefferson Parish Code of Ordinances ("JPCO"), Louisiana Code of Ethics, and applicable Jefferson Parish ethical standards.
- B. The General Conditions for construction projects (141125) and the General Conditions for the purchase of materials, services and/or supplies (136353) are those adopted by the Jefferson Parish Council by Resolution No. 136353 and Resolution No. 141125, respectively. The General Conditions adopted by these resolutions shall be considered as much a part of this document and the ensuing contract or P.O. as if they were written wholly herein. A copy of each may be obtained from the Office of the Parish Clerk, Suite 6700, Jefferson Parish General Government Building, 200 Derbigny Street, Gretna, LA 70053. You may also obtain a copy of each by visiting the Purchasing Department webpage at http://www.jeffparish.gov/464/Purchasing and clicking on Online Forms.
- C. Jefferson Parish adheres to the Louisiana Code of Governmental Ethics, contained in La. R.S. 42:1101, et seq. Vendor/Proposer by this submission, warrants that there are no "conflicts of interest" related to this procurement that would violate applicable Louisiana Law. Violation of the Louisiana Code of Governmental Ethics may result in rescission of contract, permit or licenses, and the imposition of fines and/or penalties, without contractual liability to the public in accordance with applicable law.
- D. All vendors submitting bids should register as a Jefferson Parish vendor if not already yet registered. Registration forms may be downloaded from http://www.jeffparish.gov/464/Purchasing and by clicking on Vendor Information. Current W-9 forms with respective Tax Identification numbers and vendor applications may be submitted at any time; however, if your company is not registered and/or a current W-9 form is not on file, vendor registration is mandatory. Vendors may experience a delay in payment if your company is not a registered vendor with Jefferson Parish.
- E. All quotations shall be based on F.O.B. Agency warehouse or job site (see Additional Requirements section), anywhere within the Parish as designated by the Purchasing Department. This provision does not apply to Public Works projects.
- F. Jefferson Parish requires all products to be new (current) and all work must be performed according to standard practices for the project. Unless otherwise specified, no aftermarket parts will be accepted. Unless otherwise specified, all workmanship and materials must have at least one (1) year guaranty, in writing, from the date of delivery and/or acceptance of the project. Any deviations or alterations from the specifications must be indicated on the bid form with bid submission. Supporting documentation may be required upon request.

Page: 2

DATE: 9/24/2025

BID NO: 50-00148708

G. Bidders should submit all questions in writing via email to the Purchasing Specialist's email address as indicated above, no later than five (5) working days prior to the bid opening. Bid numbers must be mentioned in all requests. If submitting online, vendors may send questions via the E-Procurement site no later than five (5) working days prior to the bid opening. The Purchasing Department will issue a written response to bidders' questions in the form of an Addendum. Please note that all official communication will be expressed in the form of an addendum.

- H. All formal Addenda require written acknowledgement on the bid form by the bidder. Failure to acknowledge any Addendum on the bid form shall cause the bid to be rejected. Jefferson Parish reserves the right to award bid to next lowest responsive and responsible bidder in this event.
- If this bid requires a pre-bid conference (see Additional Requirements section), bidders are advised that such conference will be held to allow bidders the opportunity to identify any discrepancies in the bid specifications and seek further clarification regarding instructions.
- J. JEFFERSON PARISH WILL ACCEPT ONE BID ONLY FROM EACH VENDOR. Items bid must meet specifications. JEFFERSON PARISH WILL ACCEPT ONE PRICE FOR EACH ITEM UNLESS OTHERWISE INDICATED. Two or more prices for one item will result in bid rejection. Bidders are required to complete, sign and return the bid form and/or complete and return the associated line-item pricing forms as indicated. Vendors must not alter the bid forms. Doing so will cause the bid to be rejected.
- K. Written evidence of the authority of the individual signing the bid having such authority must be submitted with the bid. Failure to comply will cause bid to be rejected. Acceptable written evidence may be a printout of the Louisiana Secretary of State's website listing the signatory as an officer or a manager. Such printout shall be included with the bid submission. Bids submitted by Owners or Sole Proprietorships must include certification that he or she owns the entity for which the bid is signed. This documentation must be submitted with the bid. Failure to do so will result in bid rejection. A sample corporate resolution can be downloaded from our website http://www.jeffparish.gov/464/Purchasing or you may provide your own document. A sample certification of sole proprietorship can also be downloaded from our website http://www.jeffparish.gov/464/Purchasing or you may provide your own document.
- L. AWARD OF CONTRACT: Jefferson Parish reserves the right to award contracts or place orders on a lump sum or individual item basis, or such combination, as shall in its judgment be in the best interest of Jefferson Parish. Every contract or order shall be awarded to the LOWEST RESPONSIVE and RESPONSIBLE BIDDER, taking into consideration the CONFORMITY WITH THE SPECIFICATIONS and the DELIVERY AND/OR COMPLETION DATE. SPLIT AWARDS MADE TO SEVERAL VENDORS WILL ONLY BE GRANTED TO THOSE DEEMED RESPONSIVE AND RESPONSIBLE.
  - a. All bid prices shall remain valid for 45 days. Jefferson Parish and the lowest responsive and responsible bidder(s) by mutual written consent may mutually agree to extend the deadline for award by one (1) or more extensions of thirty (30) calendar day increments.
  - b. PROTESTS: Only those vendors that submit bids in response to this solicitation may protest any element of the procurement, in writing to the Director of the Purchasing Department. Written protest must be received within 48 hours of the release of the bid tabulation by the Purchasing Department. After consultation, the Parish Attorney's Office will then respond to protests in writing. (For more information, please see Chapter 2, Article VII, Division 2, Sec. 2-914.1 of the Jefferson Parish Code of Ordinances.)
  - c. PREFERENCE: Unless federal funding is directly spent by Jefferson Parish for this purchase, preference is hereby given to materials, supplies, and provisions produced, manufactured or grown in Louisiana, quality being equal to articles offered by competitors outside the state. "LSA R.S. 38:2251-2261"
- M. USE OF BRAND NAMES AND STOCK NUMBERS: Where brand names and stock numbers are specified, it is for the purpose of establishing certain minimum standards of quality. Bids may be submitted for products of equal quality, provided brand names and stock numbers are specified. Complete product data may be required prior to award.
- N. CANCELLATION OF CONTRACT: JEFFERSON PARISH reserves the right to cancel all or any part if not shipped promptly. No charges will be allowed for parking or cartage unless specified in quotation. The order must not be filled at a higher price than quoted. JEFFERSON PARISH reserves the right to cancel any contract at any time and for any reason by issuing a THIRTY (30) day written notice to the contractor.
  - a. For good cause and as consideration for executing a contract with Jefferson Parish, vendor conveys, sells, assigns and transfers to Jefferson Parish or its assigns all rights, title and interest in and to all causes of action it may now or hereafter acquire under the antitrust laws of the United States and the State of Louisiana, relating to the particular good or services purchased or acquired by Jefferson Parish.
- O. PRICES: Jefferson Parish is exempt from paying sales tax under La. R.S. 47:301 (8)(c). All prices for purchases by Jefferson Parish of supplies and materials shall be quoted in the unit of measure specified and, unless otherwise specified, shall be exclusive of state and local taxes. The price quoted for work shall be stated in figures no more than four (4) decimal points. In the event there is a difference in unit prices and totals, the unit price shall prevail.
  - a. Quantities listed are for bidding purposes only. Actual requirements may be more or less than quantities listed.

Page: 3

DATE: 9/24/2025

BID NO: 50-00148708

#### INSTRUCTIONS FOR BIDDERS AND GENERAL CONDITIONS

- P. ANTI- DISCRIMINATION: Bidders are not to exclude from participation in, deny the benefits of, or subject to discrimination under any program or activity, any person in the United States on the grounds of race, color, national origin, or sex; nor discriminate on the basis of age under the Age Discrimination Act of 1975, or with respect to an otherwise qualified handicapped individual as provided in Section 504 of the Rehabilitation Act of 1973, or on the basis of religion, except that any exemption from such prohibition against discrimination on the basis of religion as provided in the Civil Rights Act of 1964, or Title VI and VII of the Act of April 11, 1968, shall also apply. This assurance includes compliance with the administrative requirements of the Revenue Sharing final handicapped discrimination provisions contained in Section 51.55 (c), (d), (e), and (k)(5) of the Regulations. New construction or renovation projects must comply with Section 504 of the 1973 Rehabilitation Act, as amended, in accordance with the American National Standard Institute's specifications (ANSI A17.1-1961).
  - a. In accordance with La. R.S. 38:2216.1, Jefferson Parish is prohibited from entering into a contract with a value of \$100,000 or more with a company for the purchase of goods or services unless the contract contains a written verification from the company of both of the following: 1) The company does not have a practice, policy, guidance, or directive that discriminates against a firearm entity or firearm trade association based solely on the entity's or association's status as a firearm entity or firearm trade association. 2) The company will not discriminate against a firearm entity or firearm trade association during the term of the contract based solely on the entity's or association's status as a firearm entity or firearm trade association. As a result, the awarded bidder will be required to verify the above in the ensuing contract.
- Q. INSPECTOR GENERAL: It shall be the duty of every parish officer, employee, department, agency, special district, board, and commission: and the duty of every contractor, subcontractor, and licensee of the parish, and the duty of every applicant for certification of eligibility for a parish contract or program, to cooperate with the Inspector General in any investigation, audit, inspection, performance review, or hearing pursuant to JPCO 2-155.10(19). By signing this document, every corporation, partnership, or person contracting with PARISH, whether by cooperative endeavor, intergovernmental agreement, bid, proposal, application or solicitation for a parish contract, and every application for certification of eligibility for a parish contract or program, attests that it understands and will abide by all provisions of JPCO 2-155.10.
- R. Proof of Cyber Security Training may be required for the successful bidder. Pursuant to La. R.S. 42:1267, any contractor who has access to state or local government information technology assets is required to complete cybersecurity training during the term of the contract and during any renewal period. As a Parish contractor, you are responsible for taking the cyber training, whether from the State or another source. After completion of said training please forward proof to your contract monitor/Parish contact.

Jefferson Parish and its partners as the recipients of federal funds are fully committed to awarding a contract(s) to firm(s) that will provide high quality services and that are dedicated to diversity and to containing costs. Thus, Jefferson Parish strongly encourages the involvement of minority and/or woman-owned business enterprises (DBE's, including MBE's, WBE's and SBE's) to stimulate participation in procurement and assistance programs.

The purpose and intention of this invitation to bid is to afford all suppliers an equal opportunity to bid on all construction, maintenance, repair, operating supplies and/or equipment listed in this bid proposal.

Advertised bids will be tabulated and a copy of the tabulation will be forwarded to each responding bidder after nine (9) working days.

DATE: 9/24/2025

BID NO: 50-00148708

#### INSTRUCTIONS FOR BIDDERS AND GENERAL CONDITIONS

# IN ACCORDANCE WITH STATE REGULATIONS JEFFERSON PARISH OFFERS ELECTRONIC PROCUREMENT TO ALL VENDORS

This electronic procurement system allows vendors the convenience of reviewing and submitting bids online. This is a secure site and authorized personnel have limited read access only. Bidders are to submit electronically using this free service; while the website accepts various file types, one single PDF file containing all appropriate and required bid documents is preferred. Bidders submitting uploaded images of bid responses are solely responsible for clarity. If uploaded images/documents are not legible, then bidder's submission will be rejected. Please note all requirements contained in this bid package for electronic bid submission.

Please visit our E-Procurement Page at www.jeffparishbids.net to register and view Jefferson Parish solicitations. For more information, please visit the Purchasing Department page at http://www.jeffparish.gov/464/Purchasing.

### ADDITIONAL REQUIREMENTS FOR THIS BID

PLEASE MATCH THE NUMBERS PRINTED IN THIS BOX WITH THE CORRESPONDING INSTRUCTIONS BELOW. IF THE NUMBER IS NOT SPECIFIED IN THIS BOX, IT IS NOT APPLICABLE FOR THIS BID.

3, 4, 5, 6, 7, 10, 11, 12, 13, 14, 15, 16

- MANDATORY PRE-BID All bidders must attend the MANDATORY pre-bid conference and will be required to sign in and
  out as evidence of attendance. In accordance with LA.R.S. 38:2212(I), all prospective bidders shall be present at the
  beginning of the MANDATORY pre-bid conference and shall remain in attendance for the duration of the conference. Any
  prospective bidder who fails to attend the conference or remain for the duration shall be prohibited from submitting a bid for
  the project.
- 2. NON-MANDATORY PRE-BID Attendance to this pre-bid conference is optional. However, failure to attend the pre-bid conference shall not relieve the bidder of responsibility for information discussed at the conference. Furthermore, failure to attend the pre-bid conference and inspection does not relieve the successful bidder from the necessity of furnishing materials or performing any work that may be required to complete the work in accordance with the specification with no additional cost to the owner.
- 3. JP LICENSE Contractor must hold current applicable JEFFERSON PARISH licenses with the Department of Building Permits. Contractor shall obtain any and all permits required by the JEFFERSON PARISH Department of Building Permits. The contractor shall be responsible for the payment of these permits. All permits must be obtained prior to the start of the project. Contractor must also hold any and all applicable municipality, Federal and/or State licenses. Contractor shall be responsible for the payment of these permits and shall obtain them prior to the start of the project.
- 4. LSCB LICENSE A LA State Contractor's License will be required in accordance with LA.R.S. 37:2150 et. seq. and such license number must be entered in the appropriate field in the electronic procurement system. Failure to comply will cause the bid to be rejected.
- 5. SITE VISIT It is the bidder's responsibility to visit the job site and evaluate the job before submitting a bid.
- 6. JOB SITE CLEANLINESS Job site must be clean and free of all litter and debris daily and upon completion of the contract. Passageways must be kept clean and free of material, equipment, and debris at all times. Flammable material must be removed from the job site daily because storage will not be permitted on the premises. Precautions must be exercised at all times to safeguard the welfare of JEFFERSON PARISH and the general public.

Page: 5

DATE: 9/24/2025

BID NO: 50-00148708 INSTRUCTIONS FOR BIDDERS AND GENERAL CONDITIONS

7. PUBLIC WORKS BIDS - All awards for public works in excess of \$5,000.00 will be reduced to a formal contract which shall be recorded at the contractor's expense with the Clerk of Court and Ex-Officio Recorder of Mortgages for the Parish of Jefferson. A price list of recordation costs may be obtained from the Clerk of Court and Ex-Officio Recorder of Mortgages for the Parish of Jefferson. All awards in excess of \$25,000.00 will require both a performance and a payment bond. Unless otherwise stated in the bid specifications, the performance bond requirements shall be 100% of the contract price. Unless otherwise state in the bid specifications, the payment bond requirements shall be 100% of the contract price. Both bonds shall be supplied at the signing of the contract.

- NON-PUBLIC WORKS BIDS A performance bond will be required for this bid. The amount of the bond will be 100% of the
  contract price unless otherwise indicated in the specifications. The performance bond shall be supplied at the signing of the
  contract.
- 9.. NON-PUBLIC WORKS BIDS A payment bond will be required for this bid. The amount of the bond will be 100% of the contract price unless otherwise indicated in the specifications. The payment bond shall be supplied at the signing of the contract.
- 10. INSURANCE All bidders must comply with the requirements stated in the attached "Standard Insurance Requirements" sheet attached to this bid solicitation. Any deviation from the Standard Insurance Requirements must be requested in writing prior to bid opening. Proof of coverage will be required prior to award. Failure to comply with this instruction will result in bid rejection.
- 11. BID BOND A bid bond will be required with bid submission in the amount of 5% of the total bid, unless otherwise stated in the bid specifications. Vendors must submit an electronic bid bond through the respective online clearinghouse bond management system(s) as indicated in the electronic bid solicitation on Central Auction House. No scanned paper copies of any bid bond will be accepted as part of the electronic bid submission.
- 12. AS-NEEDED WORK This is a requirements-based contract to be provided on an as needed basis. JEFFERSON PARISH makes no representations on warranties with regard to minimum guaranteed quantities unless otherwise stated in the bid specifications.
- 13. FREIGHT Freight charges should be included in total cost when quoting. If not quoted FOB DELIVERED, freight must be quoted as a separate item. Bid may be rejected if not quoted FOB DELIVERED or if freight charges are not indicated on bid form.
- 14. AFFIDAVIT Completed, Signed and Properly Notarized Affidavits Required; This applies to all solicitations in conformity with the provisions contained in LA.R.S. 38:2212.9, LA.R.S. 38:2212.10, LA.R.S. 38:2224, and Sec 2-923.1 of the Jefferson Parish Code of Ordinances. For bidding purposes, all bidders must submit with bid submission COMPLETED, SIGNED and PROPERLY NOTARIZED Affidavits, including: Non-Conviction Affidavit, Non-Collusion Affidavit, Campaign Contribution Affidavit, Debt Disclosures Affidavit and E-Verify Affidavit. For the convenience of vendors, all affidavits have been combined into one form entitled GENERIC BID AFFIDAVIT. This affidavit must be submitted in its original format, and without material alteration, in order to be compliant and for the bid to be considered responsive. A scanned copy of the completed, signed and properly notarized affidavit may be submitted with the bid, however, the successful bidder must submit the original affidavit in its original format and without material alteration upon contract execution. Failure to comply will result in the bid submission being rejected as non-responsive. The Parish reserves the right to award bid to the next lowest responsive and responsible bidder in this event.
- 15. FEDERAL FUNDING The ensuing contract for this bid solicitation may be eligible for FEMA reimbursement and/or Federal funding/reimbursement. As such, the referenced appendix will be applicable accordingly and shall be considered a part of the bid documents and ensuing contract. All applicable certifications must be duly completed, signed and submitted as per the appendix instructions. Failure to submit applicable certifications per the appendix instruction will result in bid rejection.
- 16. TAX EXEMPT For this project, the Contractor shall not pay any state or local sales or use taxes on materials and equipment which are affixed and made part of the immovable property of the project or which is permanently incorporated in the project (hereinafter referred to as "applicable materials and equipment"). All purchases of applicable materials or equipment shall be made by the contractor on behalf of and as the agent of Jefferson Parish (Owner), a political subdivision of the State of Louisiana. No state and local sales and use taxes are owed on applicable materials and equipment under the provisions of Act 1029 of the 1991 Regular Session Louisiana Revised Statute 47:301(8)(c). Owner will furnish to contractor a certificate form which certifies that Owner is not required to pay such state or local sales and use taxes, and contractor shall furnish a copy of such certificate to all vendors or suppliers of the applicable materials and equipment, and report to Owner the amount of taxes not incurred.
- 17. TECH AFFIDAVIT The Technology Affidavit is required for this solicitation and shall be submitted with the bid submission. Failure to do so will result in your bid being rejected. Pursuant to La. R.S. 38:2237.1, prior to the procurement of telecommunications or video surveillance equipment or services, the vendor shall provide documentation by affidavit that the equipment or services to be procured are not prohibited telecommunications or video surveillance equipment or services as defined in R.S. 39:1753.1(A). This affidavit is supplied as a courtesy to Affiant. It is the responsibility of the affiant to insure the affidavit submitted to Jefferson Parish complies, in both form and content, with federal, state and parish laws. No procurement shall be made from a vendor or other entity who fails to provide the documentation; any procurement in contravention to this requirement shall be null and void by law.

BID FOR:

JEFFERSON PARISH

PURCHASING DEPT

TO:

Page: 6

PRE-PLACED EMERGENCY CONTRACT F

POINT REPAIR, LINING AND EMERGE

200 DERBIGNY ST. SUITE 4400	POINT REPAIR, LINING AND EMERGE
<u>GRETNA, LA 70053</u>	RESTORATION OF EXISTING SEWER M
(Owner to provide name and address of owner)	FORCE MAINS AND TELEVISING, CLEA (Owner to provide name of project and
	other identifying information)
The undersigned bidder hereby declares and represents that she/he; a) has can not received, relied on, or based his bid on any verbal instructions contrary to inspected and is familiar with the project site, and hereby proposes to provide to perform, in a workmanlike manner, all work and services for the construct accordance with the Bidding Documents prepared by:  (Owner to provide name of entity preparing bidding documents.)	the Bidding Documents or any addenda, c) has personally all labor, materials, tools, appliances and facilities as required in and completion of the referenced project, all in strict
(Owner to provide name of entity preparing hidding documents)	and dated:
Bidders must acknowledge all addenda. The Bidder acknowledges receipt of assigned to each of the addenda that the Bidder is acknowledging)	f the following <b>ADDENDA</b> : (Enter the number the Designer ha
<b>TOTAL BASE BID:</b> For all work required by the Bidding Documents (includernates) the sum of:	luding any and all unit prices designated "Base Bid" * but not
	Dollars (\$ )
<b>ALTERNATES:</b> For any and all work required by the Bidding Documents alternates in the unit price description.	for Alternates including any and all unit prices designated as
Alternate No. 1 (Owner to provide description of alternate and state whether	add or deduct) for the lump sum of:
	Dollars (\$ )
Alternative 2/0	
Alternate No. 2 (Owner to provide description of alternate and state whether	•
	Dollars (\$ )
Alternate No. 3 (Owner to provide description of alternate and state whether	r add or deduct) for the lump sum of:
NAME OF BIDDER:	
ADDRESS OF BIDDER:	
LOUISIANA CONTRACTOR'S LICENSE NUMBER:	
NAME OF AUTHORIZED SIGNATORY OF BIDDER:	
TITLE OF AUTHORIZED SIGNATORY OF BIDDER:	
SIGNATURE OF AUTHORIZED SIGNATORY OF BIDDER **:	
DATE:	

## \* The <u>Unit Price Form</u> shall be used if the contract includes unit prices. Otherwise it is not required and need not be included with the form. The number of unit prices that may be included is not limited and additional sheets may be included if needed.

THE FOLLOWING ITEMS ARE TO BE INCLUDED WITH THE SUBMISSION OF THIS LOUISIANA

UNIFORM PUBLIC WORK BID FORM:

BID SECURITY in the form of a bid bond, certified check or cashier's check as prescribed by LA-R.S. 38:2218.(A) is attached to and made a part of this bid.

<sup>\*\*</sup> A CORPORATE RESOLUTION OR WRITTEN EVIDENCE of the authority of the person signing the bid for the public work as prescribed by LA-R.S. 38:2218 (B)(5).

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid	0001 - Man hole,	catch basin and	wet well inspection
DESCRIPTION:	Alt.#	PRE-PLACED EMERGE	NCY CONTRACT FO	R POINT REPAIR, LINING, EMERGENCY RESTORATION
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0001	50.00	DA		
	X Base Bid	0002 - Smoke test:	ina	
DESCRIPTION:	Alt.#		5	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0002	5,000.00	LF		
			•	
	X Base Bid	0003 - Dye water :	flooding	
DESCRIPTION:	Alt.#	byc water .	110041119	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0003	10.00	HR		
			1	1
	X Base Bid	0004 - Clean 8 inc	ch or 10 inch s	ewer of debric
DESCRIPTION:	Alt.#	0004 - Clean o in	en or to men s	ewel of deblis
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0004	10,000.00	LF		
	X Base Bid	0005 - Clean 12 i		h
DESCRIPTION:	Alt.#	0005 - Clean 12 1	nch sewer of de	DIIS
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0005	2,000.00	LF		,
	,			
	X Base Bid	0006 01 15 4-		and the second of the second o
DESCRIPTION:	Alt.#	0006 - Clean 15 i	nen or 18 Inen	sewer of debris
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0006	1,000.00	LF	OMIT I MOE	OHIT THE EXTENSION (Quantity times offer 1905)
	.,555.00		l	1
	X Base Bid			6.11.1
DESCRIPTION:	Alt.#	0007 - Clean 21 i	ncn or 24 inch	sewer or debris
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0007	500.00	LF	ONTTRIOL	ONLY MODE EXTENSION (Quantity times office rice)
	300.00	<u> </u>		<u> </u>
	₩ p p: 1			
DESCRIPTION:	X Base Bid	0008 - Clean wet v	well	
DEE NO	QUANTITY	UNIT OF MEASURE	LIMIT PRICE	HANT DDICE EVTENCION (Occasión diseas Hais Polar)
0008	8,000.00	GA	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0000	0,000.00	<b>υ</b> Λ	I	I

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid	0000 - Barrana		
DESCRIPTION:	=	0009 - Remove sewa	age by vacuum or	pump trucks up to 16,000 gallons
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0009	16,000.00	GA		
	X Base Bid	0010 - Remove sewa	age by vacuum or	pump trucks up to 32,000 gallons
DESCRIPTION:	Alt.#	0010 Remove Bewe	ige by vacaam or	pump tracks up to 32,000 garrons
REF NO.	QUANTITY	UNIT OF MEASURE	LINIT PRICE	LIMIT PRICE EVENICION (Occasión diman Unit Price)
			UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0010	32,000.00	GA		
	X Base Bid	0011 - Remove sewa	age by vacuum or	pump trucks up to 90,000 gallons
DESCRIPTION:	Alt.#		5 1	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0011	90,000.00	GA		
	,	-	<u> </u>	
	FF			
DESCRIPTION:	X Base Bid	0012 - Video inspe	ection/radial vi	ew camera in 8 inch thru 12 inch pipe
DECOKII TION.	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0012	10,000.00	LF		
	X Base Bid	0013 - Wideo inche	action/radial wi	ew camera in 15 inch thru 24 inch pipe
DESCRIPTION:	Alt.#	VIGCO INSPE	ccion, radiar vi	the camera in 15 men enta 24 men pipe
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0013	1,000.00	LF	OMITIMOL	ONLY THOSE EXTENSION (Quantity times only Thos)
0013	1,000.00	Li		
DECODINE 1011	X Base Bid	0014 - TV/inspecti	lon/dye-flooding	g or exfiltration testing 6 inch - 12 inch
DESCRIPTION:	Alt.#	pipe		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0014	500.00	LF		
	'			
	X Base Bid	0015 777 1	' / '	517
DESCRIPTION:		<del>-</del>	ion/aye-flooding	g or exfiltration testing 15 inch - 21 inch
	Alt.#	pipe		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0015	500.00	LF		
	X Base Bid	0016 - Remote illu	ımination of 15	inch - 21 inch pipe
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0016	10.00	EA		

Bid# 50-00148708

TO: JEFFERSON PARISH PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

DESCRIPTION	X Base Bid	0017 - Additional	setup for TV in	nspection 6 inch thru 12 inch
DESCRIPTION:	Alt.#	pipe		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0017	10.00	EA		
	X Base Bid	0018 - Additional	set up for TV :	inspection 15 inch thru 24 inch pipe
DESCRIPTION:	Alt.#		-	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0018	10.00	EA		
	X Base Bid	0019 - Insertion	of 4.5 mm cured	in place pipe in 6 inch pipe
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0019	1,000.00	LF		
	X Base Bid	0020 - Insertion	of 4.5 mm cured	in place pipe in 8 inch pipe
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0020	2,000.00	LF		
	X Base Bid	0021 - Insertion	of 6.0 mm cured	in place pipe in 8 inch pipe
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0021	5,000.00	LF		
	X Base Bid	0022 - Insertion	of 6.0 mm cured	in place pipe in 10 inch pipe
DESCRIPTION:	Alt.#			F-10-1 F-F F-F-
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0022	1,000.00	LF		
	I.		1	
	X Base Bid	0023 - Insertion	of 6.0 mm cured	in place pipe in 12 inch pipe
DESCRIPTION:	Alt.#			- F-1000 F-F1 - 11 - 11 - 11 - 11 - 11 -
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0023	750.00	LF		
L			1	
	X Base Bid	0024 - Insertion	of 6.0 mm cured	in place pipe in 15 inch pipe
DESCRIPTION:	Alt.#			F F-F F-F0
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0024	750.00	LF		

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	TZ D D ' 1			
DESCRIPTION:	X Base Bid	0025 - Insertion o	of 6.0 mm cured	in place pipe in 18 inch pipe
DESCRIPTION.	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0025	300.00	LF		
	J.			
DESCRIPTION.	X Base Bid	0026 - Insertion o	of 7.5 mm cured	in place pipe 21 inch pipe
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0026	300.00	LF		
	J.			
DESCRIPTION:	X Base Bid	0027 - Insertion o	of 9.0 mm cured	in place pipe in 24 inch pipe
DESCRIPTION.	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0027	100.00	LF		
	X Base Bid	0000 73344	1 5	
DESCRIPTION:	H	0028 - Additional	1.5 mm thicknes	ss for 6 inch and 8 inch cured in place pipe
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0028	100.00	LF		
	X Base Bid	0029 - Additional	1 5 mm thicknes	ss for 10 inch and 12 inch cured in place
DESCRIPTION:	Alt.#	pipe	1.5 mm chicking	so for 10 men and 12 men eared in place
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
			UNIT PRICE	UNIT PRICE EXTENSION (Quantity times unit Price)
0029	100.00	LF		
	X Base Bid	0030 - Additional	1.5mm thickness	s for 15 inch and 18 inch cured in place pipe
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0030	50.00	LF		
0000	00.00			
				7
DESCRIPTION:	X Base Bid	0031 - Additional	1.5 mm thickness	ss for 21 inch and 24 inch cured in
DESCRIPTION.	Alt.#	place pipe		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0031	50.00	LF		
	<u> </u>			
	X Base Bid	0022 Intonal	ionatmiation for	m gleanout by gured in place pine
DESCRIPTION:	=	0032 - Lateral rec	CONSTRUCTION ITC	om cleanout by cured in place pipe
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0032	25.00	EA		

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid	0033 - Extension	of lateral recor	nstruction from cleanout by		
DESCRIPTION:	Alt.#	cured in place pip	pe			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0033	100.00	LF				
	X Base Bid	0024	3			
DESCRIPTION:		0034 - Set up for long segment lateral reconstruction from mainline cured				
REF NO.	QUANTITY	in place pipe UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0034	15.00	EA	UNIT PRICE	ONIT PRICE EXTENSION (Quantity times offit Price)		
0034	15.00	EA				
	_					
DECCRIPTION.	X Base Bid	0035 - Long segmen	nt lateral recor	nstruction from mainline		
DESCRIPTION:	Alt.#	cured in place pi	pe			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0035	30.00	EA				
	X Base Bid	0036 - Extension (	of long segment	lateral reconstruction from mainline by cured		
DESCRIPTION:	Alt.#	in place pipe	or rong beginene	raceful recombetacefon from maintine by carea		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0036	100.00	LF	OHITIMOL	SINI TRIOL EXTENSION (Quantity times Sini Trios)		
0000	100.00	<u> </u>				
DESCRIPTION:	X Base Bid	005, Boodp 101,		ateral cured in place pipe lateral		
	Alt.#	connection recons				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0037	20.00	DA				
	X Base Bid	0038 - Short segme	ent lateral con	nection reconstruction from mainline by cured		
DESCRIPTION:	Alt.#	in place pipe				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0038	100.00	EA				
	X Base Bid	0039 - Service re	construction/ re	eplacement by excavation 0 - 6		
DESCRIPTION:	Alt.#	feet deep	construction, i	splacement by excavation o		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0039	10.00	EA	0	Citi i i i i i i i i i i i i i i i i i i		
3000	10.00	L/(	<u> </u>			
	le					
DESCRIPTION:	X Base Bid		construction/ re	eplacement by excavation 6 - 10		
DECOMITION.	Alt.#	feet deep				
<b>REF NO.</b> 0040	QUANTITY 10.00	UNIT OF MEASURE EA	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid	0041 - Service red	construction/ re	eplacement by excavation 10
DESCRIPTION:	Alt.#	feet deep or great	er	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0041	10.00	EA		
	X Base Bid	0042 - Repair/adju	ıst cleanout	
DESCRIPTION:	Alt.#	1 , 3		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0042	20.00	EA		
	X Base Bid	0043 - Installatio	on of sewer clea	anout Type 1
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0043	20.00	EA		
	X Base Bid	0044 - Replace sec	ction of service	e line
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0044	20.00	EA		
	X Base Bid	0045 - Restore 6 i	nch to 10 inch	main by point repair (0 to 8 foot deep)
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0045	4.00	EA		
,	•			
	X Base Bid	0046 - Restore 6 i	nch to 10 inch	main by point repair (8 foot to 12 foot deep)
DESCRIPTION:	Alt.#			17 Forms Separation (6 2000 00 22 2000 000 17)
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0046	2.00	EA		
	I.			
	X Base Bid	0047 - Restore 6 :	inch to 10 inch	main by point repair (beyond 12 foot deep)
DESCRIPTION:	Alt.#			, , , , , , , , , , , , , , , , , , , ,
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0047	2.00	EA		
	· · · · · · · · · · · · · · · · · · ·			
	X Base Bid	0048 - Restore 6 i	inch to 10 inch	main beyond point repair (0 to 8 feet deep)
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0048	10.00	LF		

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	_			
	X Base Bid	0049 - Restore 6	inch to 10 inch	main beyond point repair (8 to 12 feet deep)
DESCRIPTION:	 			
DEENIO		LINIT OF MEASURE	LINIT PRIOF	LIMIT PRIOR EXTENSION (Occasion described Paiss)
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0049	10.00	LF		
	X Base Bid	OOFO Bogtoro	ingh 10 ingh m	main beyond point repair (beyond 12 feet
DESCRIPTION:	IH .		IIICII - IO IIICII II	main beyond point repair (beyond 12 reet
	Alt.#	deep)	1	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0050	10.00	LF		
	X Base Bid	0051 D		
DESCRIPTION:		0051 - Restore 12	inch to 24 inch	n main by point repair (0 to 8 feet deep)
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0051	16.00	EA		
	X Base Bid	0050 - Dantaga 10		
DESCRIPTION:		0052 - Restore 12	inch to 24 inch	n main by point repair (8 feet to 12 feet deep)
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0052	16.00	EA		
	X Base Bid	0052 - Dantaga 10		
DESCRIPTION:	<b> </b>	0053 - Restore 12	Inch to 24 Inch	n main by point repair (beyond 12 feet deep)
	Alt.#		1	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0053	16.00	EA		
	X Base Bid	0054 Doobooo 10	imah ta 04 imah	harrand maint manain (0 to 0 foot doon)
DESCRIPTION:		0054 - Restore 12	inch to 24 inch	n main beyond point repair (0 to 8 feet deep)
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0054	16.00	LF		
	X Base Bid	0055 - Postoro 12	inch to 24 inch	n main beyond point repair (8 to 12 foot deep)
DESCRIPTION:	I=	0033 - Restole 12	IIICII CO 24 IIICI	i main beyond point repair (8 to 12 root deep)
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0055	16.00	LF		
0055	16.00	LF		
0055			ingh to 24 inch	main boyond point ropair /boyond 12 foot
DESCRIPTION:	X Base Bid	0056 - Restore 12	inch to 24 inch	n main beyond point repair (beyond 12 feet
DESCRIPTION:	X Base Bid	0056 - Restore 12 deep)		
	X Base Bid	0056 - Restore 12	inch to 24 inch	n main beyond point repair (beyond 12 feet  UNIT PRICE EXTENSION (Quantity times Unit Price)

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	TZ D D' 1			
DESCRIPTION:	X Base Bid	0057 - Insertion o	of tee for servi	ce lateral in 8 inch - 12 inch mainline
D2001(III 1101(I	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0057	10.00	EA		
	X Base Bid	0058 - Insertion o	of tee for gervi	ce lateral above 12 inch mainline
DESCRIPTION:	Alt.#	0050 - 11156161011 (	or tee for servi	ice fateral above 12 filen maintine
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0058	10.00	EA	ONTIFRICE	ONIT FRICE EXTENSION (Quantity times offit Frice)
0000	10.00	LA		
DESCRIPTION:	X Base Bid	0059 - Restore 4 i	inch force main	
DESCRIPTION.	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0059	50.00	LF		
	X Base Bid	0060 - Restore 6 i	inch force main	
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0060	50.00	LF		
			l.	
	X Base Bid	0061 - Restore 8 i	ingh forgo main	
DESCRIPTION:	Alt.#	0001 - Restole 6 1	Inch force main	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0061	50.00	LF	SIAIT FRIOE	CHAT I MOL EXTENSION (Quality times only 1 hos)
0001	30.00	Li		
DESCRIPTION:	X Base Bid	0062 - Restore 10	inch force main	ı
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0062	50.00	LF		
	X Base Bid	0063 - Restore 12	inch force mair	1
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0063	50.00	LF		
	X Base Bid	0064 - Restore 14	inch force main	
DESCRIPTION:	Alt.#	TOOT RESCOILE IT	IIICII TOTCC IIICIII	`
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0064	50.00	L E	2	

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid			
DESCRIPTION:	X Base Bld	0065 - Restore 16	inch force main	
DESCRIPTION.	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0065	50.00	LF		
0000	00.00			
	X Base Bid	0066 - Restore 18	inch force mair	
DESCRIPTION:	Alt.#			
DEE NO	QUANTITY	UNIT OF MEASURE	UNIT DDICE	LINIT DDICE EVERNOON (Oversity times Unit Drice)
REF NO.			UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0066	50.00	LF		
	X Base Bid	0.065		
DESCRIPTION:		0067 - Restore 20	inch force mair	
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0067	50.00	LF		
			'	
DESCRIPTION:	X Base Bid	0068 - Restore 24	inch force main	
DESCRIPTION.	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0068	50.00	LF		
0000	00.00	·	<u> </u>	
	r			
	X Base Bid	0069 - Additional	sheeting, braci	na (as directed)
DESCRIPTION:				ing, (as directed)
	Alt.#			ng, (as directed)
REF NO.	Alt.#	UNIT OF MEASURE		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
<b>REF NO.</b> 0069		UNIT OF MEASURE BDFT		
	QUANTITY			
	1,000.00	BDFT	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
	QUANTITY 1,000.00		UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0069  DESCRIPTION:	QUANTITY 1,000.00  X Base Bid Alt.#	BDFT 0070 - Additional	UNIT PRICE granular materi	UNIT PRICE EXTENSION (Quantity times Unit Price) al
DESCRIPTION:	QUANTITY  1,000.00  X Base Bid Alt.# QUANTITY	BDFT  0070 - Additional  UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0069  DESCRIPTION:	QUANTITY 1,000.00  X Base Bid Alt.#	BDFT 0070 - Additional	UNIT PRICE granular materi	UNIT PRICE EXTENSION (Quantity times Unit Price) al
DESCRIPTION:	QUANTITY  1,000.00  X Base Bid Alt.# QUANTITY	BDFT  0070 - Additional  UNIT OF MEASURE	UNIT PRICE granular materi	UNIT PRICE EXTENSION (Quantity times Unit Price) al
DESCRIPTION:	QUANTITY  1,000.00  X Base Bid Alt.#  QUANTITY  500.00	BDFT  0070 - Additional  UNIT OF MEASURE  CUYD	UNIT PRICE  granular materi  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price) al
DESCRIPTION: REF NO. 0070	QUANTITY  1,000.00  X Base Bid Alt.#  QUANTITY  500.00  X Base Bid	BDFT  0070 - Additional  UNIT OF MEASURE	UNIT PRICE  granular materi  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price) al
DESCRIPTION: REF NO. 0070  DESCRIPTION:	QUANTITY  1,000.00  X Base Bid Alt.# QUANTITY  500.00  X Base Bid Alt.#	BDFT  0070 - Additional  UNIT OF MEASURE  CUYD  0071 - Additional	UNIT PRICE  granular materi  UNIT PRICE  limestone	UNIT PRICE EXTENSION (Quantity times Unit Price)  al  UNIT PRICE EXTENSION (Quantity times Unit Price)
DESCRIPTION: REF NO. 0070	QUANTITY  1,000.00  X Base Bid Alt.#  QUANTITY  500.00  X Base Bid	BDFT  0070 - Additional  UNIT OF MEASURE  CUYD	UNIT PRICE  granular materi  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price) al
DESCRIPTION: REF NO. 0070  DESCRIPTION:	QUANTITY  1,000.00  X Base Bid Alt.# QUANTITY  500.00  X Base Bid Alt.#	BDFT  0070 - Additional  UNIT OF MEASURE  CUYD  0071 - Additional	UNIT PRICE  granular materi  UNIT PRICE  limestone	UNIT PRICE EXTENSION (Quantity times Unit Price)  al  UNIT PRICE EXTENSION (Quantity times Unit Price)
DESCRIPTION: REF NO. 0070  DESCRIPTION: REF NO.	QUANTITY  1,000.00  X Base Bid Alt.#  QUANTITY  500.00  X Base Bid Alt.#  QUANTITY	BDFT  0070 - Additional  UNIT OF MEASURE  CUYD  0071 - Additional  UNIT OF MEASURE	UNIT PRICE  granular materi  UNIT PRICE  limestone	UNIT PRICE EXTENSION (Quantity times Unit Price)  al  UNIT PRICE EXTENSION (Quantity times Unit Price)
DESCRIPTION: REF NO. 0070  DESCRIPTION: REF NO.	QUANTITY  1,000.00  X Base Bid Alt.# QUANTITY  500.00  X Base Bid Alt.# QUANTITY  500.00	BDFT  0070 - Additional  UNIT OF MEASURE  CUYD  0071 - Additional  UNIT OF MEASURE  CUYD	UNIT PRICE  granular materi  UNIT PRICE  limestone  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)  al  UNIT PRICE EXTENSION (Quantity times Unit Price)
DESCRIPTION: REF NO. 0070  DESCRIPTION: REF NO. 0071	QUANTITY  1,000.00  X Base Bid Alt.# QUANTITY 500.00  X Base Bid Alt.# QUANTITY 500.00	BDFT  0070 - Additional  UNIT OF MEASURE  CUYD  0071 - Additional  UNIT OF MEASURE	UNIT PRICE  granular materi  UNIT PRICE  limestone  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)  al  UNIT PRICE EXTENSION (Quantity times Unit Price)
DESCRIPTION: REF NO. 0070  DESCRIPTION: REF NO.	QUANTITY  1,000.00  X Base Bid Alt.# QUANTITY  500.00  X Base Bid Alt.# QUANTITY  500.00	BDFT  0070 - Additional  UNIT OF MEASURE  CUYD  0071 - Additional  UNIT OF MEASURE  CUYD	UNIT PRICE  granular materi  UNIT PRICE  limestone  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)  al  UNIT PRICE EXTENSION (Quantity times Unit Price)
DESCRIPTION: REF NO. 0070  DESCRIPTION: REF NO. 0071	QUANTITY  1,000.00  X Base Bid Alt.# QUANTITY 500.00  X Base Bid Alt.# QUANTITY 500.00	BDFT  0070 - Additional  UNIT OF MEASURE  CUYD  0071 - Additional  UNIT OF MEASURE  CUYD	UNIT PRICE  granular materi  UNIT PRICE  limestone  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)  al  UNIT PRICE EXTENSION (Quantity times Unit Price)

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

DESCRIPTION:	X Base Bid	0073 - Repoint exi	sting sewer mar	nhole or wetwell
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0073	2,000.00	SQFT		
DESCRIPTION:	X Base Bid Alt.#	0074 - Sewer Manho	ole or wetwell :	cehab by cementitous lining method
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0074	1,000.00	SQFT		
DESCRIPTION:	X Base Bid Alt.#	0075 - Manhole cov	ver adjustments	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0075	20.00	EA		
DESCRIPTION:	X Base Bid	0076 - Rehabilitat	ce manhole bench	n/trough
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0076	20.00	EA		
DESCRIPTION:	X Base Bid Alt.#	0077 - Remove and	replace manhole	e cone
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0077	5.00	EA		
DESCRIPTION:	X Base Bid	0078 - Remove and	replace manhole	e wall
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0078	100.00	VF		
	X Base Bid	0079 - Repair manl	nole line conne	ction
DESCRIPTION:	Alt.#	-		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0079	20.00	EA		
DESCRIPTION:	X Base Bid	0080 - Replace mar	nhole cover and	casting
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0800	10.00	EA		

Bid# 50-00148708

TO: JEFFERSON PARISH PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

DESCRIPTION:	X Base Bid	0081 - Remote cut	and brush serv	ices
DEENO	Alt.#	LINUT OF MEACURE	LINET DDIOF	UNIT PRIOF EXTENDION (Oversities three Half Prior)
REF NO. 0081	QUANTITY	UNIT OF MEASURE EA	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0061	250.00	EA		
DESCRIPTION:	X Base Bid	0082 - Internally	trim protruding	g service connection
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0082	25.00	EA	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Onit Price)
0002	25.00	LA		
	₩ D D. 1			
DESCRIPTION:	X Base Bid	0083 - Set up 3 i	nch bypass pump	
DEE NO	Alt.#	LINIT OF MEACURE	LINET DDIOF	LINET PRIOR EXTENSION (Occasion describedos a Hair Palas)
0083	QUANTITY 20.00	UNIT OF MEASURE EA	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0003	20.00	LA		
	<b></b>			
DESCRIPTION:	X Base Bid	0084 - Set up 4 i	nch bypass pump	
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0084	20.00	EA		
DESCRIPTION:	X Base Bid	0085 - Set up 6 in	nch bypass pump	
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0085	10.00	EA		
DESCRIPTION:	X Base Bid	0086 - Set up 8 i	nch bypass pump	
	Alt.#		,	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0086	5.00	EA		
DECODISTION	X Base Bid	0087 - Set up 10	inch bypass pum	р
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0087	2.00	EA		
DECODINE	X Base Bid	0088 - Set up 12 :	inch bypass pump	9
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0088	1.00	EA		

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT SUITE 4400 200 DERBIGNY ST. GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid	0089 - Operation o	of 3 inch hymaes	משוות
DESCRIPTION:	I <b>=</b>	operation o	or a rineir bypasi	o pamp
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0089	75.00	HR		
	J.			
	X Base Bid	0090 - Operation o	of 4 inch bypass	s pump
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0090		HR	511152	01111 1 1102 211 2110 1011 (Qualitati, anno 01111 1100)
0090	75.00	ПК		
	X Base Bid	0091 - Operation o	of 6 inch hypass	משוות :
DESCRIPTION:	Alt.#	operación (	or o men bypasi	, pamp
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0091	50.00	HR		
	X Base Bid	0000 0 11	5 0 1 3 3	
DESCRIPTION:		0092 - Operation o	of 8 inch bypass	s pump
<b>2200</b> 1411 110141	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0092	20.00	HR		
	I —			
	X Base Bid	0093 - Operation o	of 10 inch bypas	ss pump
DESCRIPTION:	X Base Bid	0093 - Operation o	of 10 inch bypas	ss pump
	Alt.#			
REF NO.	Alt.# QUANTITY	UNIT OF MEASURE	of 10 inch bypas	UNIT PRICE EXTENSION (Quantity times Unit Price)
	Alt.#			
REF NO.	Alt.# QUANTITY	UNIT OF MEASURE		
REF NO.	Alt.# QUANTITY	UNIT OF MEASURE HR	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
REF NO.	Alt.#QUANTITY 10.00	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
REF NO. 0093  DESCRIPTION:	Alt.#	UNIT OF MEASURE HR  0094 - Operation (	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price) ss pump
REF NO. 0093  DESCRIPTION: REF NO.	Alt.#	UNIT OF MEASURE  HR  0094 - Operation of MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
REF NO. 0093  DESCRIPTION:	Alt.#	UNIT OF MEASURE HR  0094 - Operation (	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price) ss pump
REF NO. 0093  DESCRIPTION: REF NO.	Alt.#	UNIT OF MEASURE  HR  0094 - Operation of MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price) ss pump
REF NO. 0093  DESCRIPTION: REF NO.	Alt.#	UNIT OF MEASURE  HR  0094 - Operation of UNIT OF MEASURE  HR	UNIT PRICE  Df 12 inch bypas  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)  SS pump  UNIT PRICE EXTENSION (Quantity times Unit Price)
REF NO. 0093  DESCRIPTION: REF NO.	Alt.#	UNIT OF MEASURE  HR  0094 - Operation of UNIT OF MEASURE  HR	UNIT PRICE  Df 12 inch bypas  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price) ss pump
REF NO. 0093  DESCRIPTION: REF NO. 0094  DESCRIPTION:	Alt.#	UNIT OF MEASURE HR  0094 - Operation of UNIT OF MEASURE HR  0095 - Extension of	UNIT PRICE  of 12 inch bypas  UNIT PRICE  of 6 inch bypass	UNIT PRICE EXTENSION (Quantity times Unit Price)  SS pump  UNIT PRICE EXTENSION (Quantity times Unit Price)  S discharge force main piping
REF NO. 0093  DESCRIPTION: REF NO. 0094	Alt.#	UNIT OF MEASURE  HR  0094 - Operation of UNIT OF MEASURE  HR	UNIT PRICE  Df 12 inch bypas  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)  SS pump  UNIT PRICE EXTENSION (Quantity times Unit Price)
REF NO. 0093  DESCRIPTION: REF NO. 0094  DESCRIPTION:	Alt.#	UNIT OF MEASURE HR  0094 - Operation of UNIT OF MEASURE HR  0095 - Extension of	UNIT PRICE  of 12 inch bypas  UNIT PRICE  of 6 inch bypass	UNIT PRICE EXTENSION (Quantity times Unit Price)  SS pump  UNIT PRICE EXTENSION (Quantity times Unit Price)  S discharge force main piping
REF NO. 0093  DESCRIPTION: REF NO. 0094  DESCRIPTION: REF NO.	Alt.#	UNIT OF MEASURE HR  0094 - Operation of UNIT OF MEASURE HR  0095 - Extension of UNIT OF MEASURE	UNIT PRICE  of 12 inch bypas  UNIT PRICE  of 6 inch bypass	UNIT PRICE EXTENSION (Quantity times Unit Price)  SS pump  UNIT PRICE EXTENSION (Quantity times Unit Price)  S discharge force main piping
REF NO. 0093  DESCRIPTION: REF NO. 0094  DESCRIPTION: REF NO.	Alt.#	UNIT OF MEASURE HR  0094 - Operation of UNIT OF MEASURE HR  0095 - Extension of UNIT OF MEASURE LF	UNIT PRICE  UNIT PRICE  Of 6 inch bypas:  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)  UNIT PRICE EXTENSION (Quantity times Unit Price)  discharge force main piping  UNIT PRICE EXTENSION (Quantity times Unit Price)
REF NO. 0093  DESCRIPTION: REF NO. 0094  DESCRIPTION: REF NO. 0095	Alt.#	UNIT OF MEASURE HR  0094 - Operation of UNIT OF MEASURE HR  0095 - Extension of UNIT OF MEASURE LF	UNIT PRICE  UNIT PRICE  Of 6 inch bypas:  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)  SS pump  UNIT PRICE EXTENSION (Quantity times Unit Price)  S discharge force main piping
REF NO. 0093  DESCRIPTION: REF NO. 0094  DESCRIPTION: REF NO.	Alt.#	UNIT OF MEASURE HR  0094 - Operation of UNIT OF MEASURE HR  0095 - Extension of UNIT OF MEASURE LF	UNIT PRICE  UNIT PRICE  Of 6 inch bypas:  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)  UNIT PRICE EXTENSION (Quantity times Unit Price)  discharge force main piping  UNIT PRICE EXTENSION (Quantity times Unit Price)
REF NO. 0093  DESCRIPTION: REF NO. 0094  DESCRIPTION: REF NO. 0095	Alt.#	UNIT OF MEASURE HR  0094 - Operation of UNIT OF MEASURE HR  0095 - Extension of UNIT OF MEASURE LF	UNIT PRICE  UNIT PRICE  Of 6 inch bypas:  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)  UNIT PRICE EXTENSION (Quantity times Unit Price)  discharge force main piping  UNIT PRICE EXTENSION (Quantity times Unit Price)

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid	0007 - Extension o	of 10 inch hymae	ss discharge force main piping
DESCRIPTION:	Alt.#	0097 Excells foli c	or to their bypar	so discharge force main piping
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0097	200.00	LF	51111711152	
	V D D: 4			
DESCRIPTION:	X Base Bid	0098 - Extension o	of 12 inch bypas	ss discharge force main piping
REF NO.	QUANTITY	UNIT OF MEASURE	LINIT DDICE	LIMIT PRICE EXTENSION (Oversity times Unit Price)
0098	200.00	LF	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0098	200.00	LI		
DESCRIPTION:	X Base Bid	0099 - Remove and	replace PCC roa	adway (9 inch thick)
	Alt.#	,		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0099	300.00	SY		
DECODIDE	X Base Bid	0100 - Place and r	remove temporary	y asphaltic concrete roadway
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0100	100.00	SY		
	X Base Bid	0101 - Remove and	replace concret	te driveways (6 inch thick)
DESCRIPTION:	Alt.#		-	•
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0101	250.00	SY		
	X Base Bid	0102 - Remove and	replace concret	te sidewalks (4 inch thick)
DESCRIPTION:	Alt.#	0102 Remove and	replace concret	SE SIGEWALKS (4 INCH CHICK)
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0102	500.00	SY		
	ı	l		
	X Base Bid	0102 01	ia troffic z	twol dowing nlan
DESCRIPTION:	Alt.#	0103 - Site specif	ic traille con	troi device pian
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0103	5.00	EA	ONIT I RIOL	CHAIT HOLE EXTENSION (Qualitary almost office 1 floor)
3100	0.00	L/ \	<u> </u>	
	<b>T</b>			
DESCRIPTION:	X Base Bid	0104 - Traffic cor	ntrol device set	t-up
	Alt.#		LINUT PRIOR	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0104	5.00	EA		

Bid# 50-00148708

TO: JEFFERSON PARISH PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

DESCRIPTION:	X Base Bid	0105 - Traffic control device operation			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0105	5.00	EA			
	X Base Bid	0106 - Traffic fla	acman		
DESCRIPTION:		0100 Hallic H	agmaii		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0106	100.00	HR	0	Similar England (Quantity amos similars)	
0100	100.00	1111			
DESCRIPTION:	X Base Bid	0107 - Insertion	5.5 MM RCPP in	10 inch force main	
	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0107	1,000.00	LF			
	X Base Bid	0108 - Insertion	5.5 MM RCPP in	12 inch force main	
DESCRIPTION:	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0108	1,000.00	LF			
	,				
	X Base Bid	0100 - Incertion	5 5 MM DCDD in	14 inch force main	
DESCRIPTION:	Alt.#	oloj inscicion .	J. J. Phr. Rell III	14 Inon Torce main	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0109	1,000.00	LF			
0100	,,,,,,,,,				
	TZ D D ! 1				
DESCRIPTION:	X Base Bid	0110 - Insertion	of 8.5 MM RCPP	in 18 inch force main	
	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0110	1,000.00	LF			
				7	
DESCRIPTION:	X Base Bid	0111 - Additional	1.5 mm thickne	ss for 10 inch to 12 inch RCPP	
DESCRIPTION.	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0111	500.00	LF			
	X Base Bid	0112 - Additional	1.5 mm thickne	ss for 14 inch to 18 inch RCPP	
DESCRIPTION:					
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0112	500.00	LF			

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid		7 7 /2 22	
DESCRIPTION:	I <b>=</b>	0113 - Rubber Tir	e loader/backhoe	
DEENO	Alt.#	LINUT OF MEASURE	LIMIT PRIOF	HART PRIOR EXTENDION (Occasios deservibres)
REF NO.	QUANTITY	UNIT OF MEASURE  DA	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0113	10.00	DA		
				,
DESCRIPTION:	X Base Bid	0114 - 5/8 cubic	yard track backhoe	
DESCRIPTION.	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0114	10.00	DA		
	X Base Bid	0115 - 1 cubic ya:	rd track backhoe	
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0115	10.00	DA		
	X Base Bid	0116 - 2 cubic va	rd rubber tire loader	
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0116	10.00	DA		
	,			
	X Base Bid	0117 - 2 cubic ya:	rd track backboe	
DESCRIPTION:	Alt.#_	oli / Z cabic ya	ra crack backnee	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0117	10.00	DA		, , ,
	V Pago Pid	2112 2 1		
DESCRIPTION:	X Base Bid	0118 - D-4 dozer		
	Alt.#		IINIT PRICE	IINIT PRICE EXTENSION (Quantity times linit Price)
REF NO.	Alt.# QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
	Alt.#		UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
REF NO.	Alt.#	UNIT OF MEASURE  DA		UNIT PRICE EXTENSION (Quantity times Unit Price)
REF NO.	Alt.#	UNIT OF MEASURE		UNIT PRICE EXTENSION (Quantity times Unit Price)
REF NO. 0118  DESCRIPTION:	Alt.#	UNIT OF MEASURE  DA  0119 - 35 Ton Mob	ile Crane	
REF NO. 0118  DESCRIPTION: REF NO.	Alt.#	UNIT OF MEASURE  DA  0119 - 35 Ton Mob  UNIT OF MEASURE		UNIT PRICE EXTENSION (Quantity times Unit Price)  UNIT PRICE EXTENSION (Quantity times Unit Price)
REF NO. 0118  DESCRIPTION:	Alt.#	UNIT OF MEASURE  DA  0119 - 35 Ton Mob	ile Crane	
REF NO. 0118  DESCRIPTION: REF NO.	Alt.#	UNIT OF MEASURE  DA  0119 - 35 Ton Mob  UNIT OF MEASURE  DA	ile Crane	
REF NO. 0118  DESCRIPTION: REF NO. 0119	Alt.#	UNIT OF MEASURE  DA  0119 - 35 Ton Mob  UNIT OF MEASURE	ile Crane	
REF NO. 0118  DESCRIPTION: REF NO. 0119  DESCRIPTION:	Alt.#	UNIT OF MEASURE  DA  0119 - 35 Ton Mob  UNIT OF MEASURE  DA  0120 - Chain saw	ile Crane  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
REF NO. 0118  DESCRIPTION: REF NO. 0119	Alt.#	UNIT OF MEASURE  DA  0119 - 35 Ton Mob  UNIT OF MEASURE  DA	ile Crane	

Bid# 50-00148708

TO: JEFFERSON PARISH PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

DESCRIPTION:	X Base Bid	0121 - Multi-purpo	ose saw	
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0121	10.00	DA		
	X Base Bid	0122 - Small tools	5	
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0122	10.00	DA		
	X Base Bid	0123 - Pick-up tr	ıck	
DESCRIPTION:	Alt.#	0125 TICK up cit	ack	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0123	10.00	DA		
			I	
	X Base Bid	0.004 1.7.1.		
DESCRIPTION:		0124 - Utility tr	ıck	
DEENO	Alt.#	LINUT OF MEACURE	LINET PRIOR	HART PRIOR EXTENSION (Oversity three Half Prior)
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0124	10.00	DA		
	I—			
DESCRIPTION:	X Base Bid	0125 - Single axle	e truck	
DESCRIPTION.	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0125	10.00	DA		
	X Base Bid	0126 - Tandem axle	e dump truck	
DESCRIPTION:	Alt.#		-	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0126	10.00	DA		
			•	
	X Base Bid	0127 - Wolding to	uak complete wi	th 200A welder and torch set
DESCRIPTION:	Alt.#	0127 - Welding ti	uck complete wi	th 200A werder and torch set
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0127	10.00	DA	OMITIMOL	ONT I MOL EXTENSION (Quantity times only ince)
V121	10.00	DA	l	
DESCRIPTION:	X Base Bid	0128 - Small gaso	line wacker pla	te approximately 24 inch x 24 inch
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0128	10.00	DA		

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid	0129 - Constructio	on water meter a	and 100 feet of 1-1/2 inch hose
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0129	10.00	DA		
	•			
	X Base Bid	0130 - Low boy		
DESCRIPTION:	Alt.#	orso hem bey		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0130	80.00	HR		
	Į.			
	X Base Bid	0131 - Foreman for	r Doint Penair/	Lining jobs
DESCRIPTION:	Alt.#	0131 - Poleman 101	roine kepair,	ining jobs
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0131	80.00	HR		
	X Base Bid	0132 - Operator		
DESCRIPTION:	Alt.#	-		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0132	80.00	HR		
	X Base Bid	0133 - Pipe Layer		
DESCRIPTION:	Alt.#	0133 - Fipe Dayer		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0133	80.00	HR	0	our rise and a second contribution
0100	00.00			
	TZ D D' 1			
DESCRIPTION:	X Base Bid	0134 - Laborer		
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0134	80.00	HR		
DESCRIPTION:	X Base Bid	0135 - Pipe fitte	r	
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0135	80.00	HR		
DESCRIPTION:	X Base Bid	0136 - Pipe Fitter	r's Helper	
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0136	80.00	HR		

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid	0137 - Carpenter		
DESCRIPTION:	Alt.#	-		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0137	80.00	HR		
	,			
	X Base Bid	0138 - Truck Drive	ar	
DESCRIPTION:	Alt.#	0150 IIdon BIIV		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0138	80.00	HR		
	J.			
	X Base Bid	0139 - Journeyman	Flectrician	
DESCRIPTION:	Alt.#	0133 - Oddineyman	Electician	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0139	80.00	HR		
	<u> </u>			
	X Base Bid	0140 - Slab Soddir	na	
DESCRIPTION:	Alt.#	0140 - Stab Soddii	19	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0140	1,500.00	SY		
	, ,			
	X Base Bid	0141 - Pehuild 1 I	JD +0 7 5 HD C11	bmersible Non-Cloq Pump
DESCRIPTION:	Alt.#	VIII REDUITU I I	11 00 7.5 111 50.	omerbible non crog ramp
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0141	4.00	EA		
	X Base Bid	0142 Poplago Imr	oollor 1 UD to '	7.5 HP Submersible Non-Clog Pump
DESCRIPTION:	Alt.#	0142 - Kepiace imp	pellel I Hr CO	7.5 HF Submersible Non-Clog Fump
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0142	1.00	EA		
L	<u>.                                    </u>			
	X Base Bid	0143 - Rebuild 10	HP to 25 HP Sui	bmersible Non-Clog Pump
DESCRIPTION:	Alt.#	orio negaria ro	111 00 23 111 54.	Difference from cross rump
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0143	4.00	EA		
,			•	
	X Base Bid	0144 - Replace Imr	neller 10 HP to	25 HP Submersible Non-Clog Pump
DESCRIPTION:	Alt.#	offi Reprace Imp	,01101 10 111 00	25 Saxmorbixio non croy rump
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0144	1.00	EA		

Bid# 50-00148708

TO: JEFFERSON PARISH PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid	0145 - Rebuild 30	HP to 100 HP St	ubmersible Non-Clog Pump
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0145	4.00	EA		
	X Base Bid	0146 - Replace Im	peller 30 HP to	100 HP Submersible Non-Clog Pump
DESCRIPTION:	Alt.#	1		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0146	1.00	EA		
	X Base Bid	0147 - Rebuild 125	5 HP to 250 HP \$	Submersible Non-Cloq Pump
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0147	4.00	EA		
	X Base Bid	0148 - Replace Imp	peller 125 HP to	250 HP Submersible Non-Clog Pump
DESCRIPTION:	Alt.#		•	3 1
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0148	1.00	EA		
	X Base Bid	0149 - Rebuild 300	) HP to 400 HP 5	Submersible Non-Clog Pump
DESCRIPTION:	Alt.#	0113 11024114 50		342
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0149	1.00	EA		
	'			
	X Base Bid	0150 - Replace Im	neller 300 HD to	0 400 HP Submersible Non-Clog Pump
DESCRIPTION:	Alt.#	0130 Repidee imp	Jerrer 500 m e	5 400 III BubiiicIBIBIC Noil Clog Tump
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0150	1.00	EA		
	J.			
	X Base Bid	0151 - Rebuild 1	HP to 5 HP Self	-Primer Pump
DESCRIPTION:	Alt.#	0101 110001110 1	00 0 111 0011	22102 24
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0151	4.00	EA		
			-	
	X Base Bid	0152 - Replace Imm	peller 1 HP to 1	5 HP Self-Primer Pump
DESCRIPTION:	Alt.#	111 1021000 1111		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0152	1.00	EA		

Bid# 50-00148708

TO: JEFFERSON PARISH PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

DESCRIPTION:	X Base Bid	0153 - Rebuild 7.5	5 HP to 25 HP Se	elf-Primer Pump
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0153	4.00	EA		
DESCRIPTION:	X Base Bid	0154 - Replace Imp	peller 7.5 HP to	o 25 HP Self-Primer Pump
DEENIG	Alt.#	LINET OF MEASURE	INUT PRIOR	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0154	1.00	EA		
DECODIDE	X Base Bid	0155 - Rebuild 30	HP to 75 HP Se	lf-Primer Pump
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0155	4.00	EA		
	X Base Bid	0156 - Replace Imp	peller 30 HP to	75 HP Self-Primer Pump
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0156	1.00	EA		
	J.			
	X Base Bid	0157 Debuild 1	ID to F IID Monte	isal Duilt Manathan Dun Dit Dunn
DESCRIPTION:	Alt.#	0157 - REDUITO I I	ip to 5 HP vert.	ical Built Together Dry-Pit Pump
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0157	5.00	EA	ONTTRICE	ONIT PRIOR EXTENSION (Quantity times office rice)
0137	0.00	LA		
DESCRIPTION:	X Base Bid	0158 - Replace Imp	peller 1 HP to !	5 HP Vertical Built Together Dry-Pit Pump
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0158	1.00	EA		
DESCRIPTION:	X Base Bid	0159 - Rebuild 7.	5 HP to 25 HP V	ertical Built Together Dry-Pit Pump
DESCRIPTION.	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0159	4.00	EA		
	X Base Bid	0160 - Replace Imp	peller 7.5 HP to	25 HP Vertical Built Together Dry-Pit Pump
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0160	1.00	EA		

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	V D D: 3			
DESCRIPTION:	X Base Bid	0161 - Rebuild 30	HP to 75 HP Ver	rtical Built Together Dry-Pit Pump
DESCRIPTION.	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0161	4.00	EA		
		l		
DE00010T1011	X Base Bid	0162 - Replace Imp	eller 30 HP to	75 HP Vertical Built Together Dry-Pit Pump
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0162	1.00	EA		,
0102	1.00	271		
	X Base Bid	0163 - Rebuild 100	) HP to 200 HP V	Vertical Built Together Dry-Pit Pump
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0163	4.00	EA	0	Citi i i i i i i i i i i i i i i i i i i
0103	4.00	LA		
	X Base Bid	0164 - Replace Imp	eller 100 HP to	200 HP Vertical Built Together Dry-Pit pump
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
			OMITIMOL	OHIT THOSE EXTENSION (Quantity times office 100)
0164	1.00	EA		
	X Base Bid	0165 - Rebuild 1 H	IP to 5 HP Verti	Ical Close-Coupled Dry-Pit Pump
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
	4.00	EA	0	Complete Extended (Quality alloce Complete)
0165	4.00	LA		
	X Base Bid	0166 - Replace Imp	eller 1 HP to 5	5 HP Vertical Closed-Coupled Dry-Pit Pump
DESCRIPTION:	Alt.#	1		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
		EA	ONIT FRICE	ONLY PRIOR EXTENSION (Quantity times office)
0166	1.00	EA		
	X Base Bid	0167 - Rebuild 7.5	5 HP to 25 HP Ve	ertical Close-Coupled Dry-Pit Pump
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
-		EA	OIIII I RIOL	CHAIT I MODE EXTENSION (Qualitary almost office 1 most)
0167	4.00	EA		
	X Base Bid	0168 - Replace Imr	beller 7.5 HP to	25 HP Vertical Close-Coupled Dry-Pit Pump
DESCRIPTION:				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
			ONIT FRICE	ONTI PRIOE EXTENSION (Quantity times offit Price)
0168	1.00	EA		

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	TZ D D ! 1			
DESCRIPTION:	X Base Bid	0169 - Rebuild 30	HP to 75 HP Ver	rtical Close-Coupled Dry-Pit Pump
DESCRIPTION.	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0169	4.00	EA		
		l		
	_			
DECODINE	X Base Bid	0170 - Replace Imp	eller 30 HP to	75 HP Vertical Close-Coupled Dry-Pit Pump
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0170	1.00	EA		· · ·
0110	1.00	271		
	X Base Bid	0171 - Rebuild 100	) HP to 200 HP V	Vertical Close-Coupled Dry-Pit Pump
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0171			OMIT I MOL	Chair Fillot Extendion (Quality almos office floor)
0171	4.00	EA		
	X Base Bid	0172 - Replace Imp	eller 100 HP to	200 HP Vertical Close-Coupled Dry-Pit Pump
DESCRIPTION:	Alt.#	1		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
			UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0172	1.00	EA		
	X Base Bid	0173 - Rebuild 250	) HP +0 400 HP 1	Vertical Close-Coupled Dry-Pit Pump
DESCRIPTION:	Alt.#	01/5 11020110 250	00 100 111 .	oronour cross coupred br <sub>1</sub> rro ramp
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
			UNIT PRICE	UNIT PRICE EXTENSION (Quantity times unit Price)
0173	1.00	EA		
	X Base Bid	0174 - Penlace Imr	paller 250 UD to	0 400 HP Vertical Close-Coupled Dry-Pit Pump
DESCRIPTION:	H	01/4 - Kepiace imp	Deller 250 Hr CC	7 400 Hr Vertical Close-Coupled Dry-Fit Fump
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0174	1.00	EA		
	X Base Bid	0175 - Rebuild 1 F	ID TO 5 UD Motor	r
DESCRIPTION:	<b> </b>	01/5 - Rebullu I i	ir io 5 hr Mocoi	<u>-</u>
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0175	4.00	EA		
	X Base Bid	0176 Davida 1 117	) +o E IID Mat	II + 000 DDM
DESCRIPTION:		0176 - Rewind 1 HF	CO 5 HP MOTOR	OD TO SOO KEM
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0176	1.00	EA		

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid	0177 - Rewind 1 H	to 5 HP Motor	Up to 1150 RPM
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0177	1.00	EA	0.111.0.111.0.2	(,,,,,
0177	1.00	LA		
	X Base Bid	0178 - Rewind 1 HE	to 5 HP Motor	Up to 1750 RPM
DESCRIPTION:	Alt.#			
DEENO	QUANTITY	LINIT OF MEASURE	LINIT DDIOF	LIMIT PRIOR EXTENSION (Occasion descended Paise)
REF NO.		UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0178	1.00	EA		
	X Base Bid	0179 - Rebuild 7.5	TID to DE IID Me	at an
DESCRIPTION:	<u> </u>	0179 - Rebuild 7.5	HP CO 25 HP MC	5001
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0179	4.00	EA		
	X Base Bid	0100 - Desired F. F.	IID +- OF IID M	The bar 000 DDM
DESCRIPTION:	=	0180 - Rewind 7.5	HP to 25 HP MOT	tor up to 900 RPM
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0180	1.00	EA		
	,			
	X Base Bid			
DESCRIPTION:		0181 - Rewind 7.5	HP to 25 HP Mot	tor Up to 1150 RPM
	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0181	1.00	EA		
,				
	TT 1			
DESCRIPTION:	X Base Bid	0182 - Rewind 7.5	HP to 25 HP Mot	tor Up to 1750 RPM
DECOKII TION.	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0182	1.00	EA		
	,			
	FT			
DESCRIPTION:	X Base Bid	0183 - Rebuild 30	HP to 75 HP Mo	tor
DESCRIPTION.	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0183	4.00	EA		
DESCRIPTION:	X Base Bid	0184 - Rewind 30 F	HP to 75 HP Moto	or Up to 900 RPM
DESCRIPTION:	Alt.#			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0184	1.00	EA		

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid				
DESCRIPTION:	ON: 🗮				
DEGOTAL TION.	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0185	1.00	EA			
		-			
	TT				
DESCRIPTION:	X Base Bid	0186 - Rewind 30 H	HP to 75 HP Moto	or Up to 1750 RPM	
DEGOTAL TION.	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0186	1.00	EA			
	<u>.</u>				
	V Dogo Did				
DESCRIPTION:	X Base Bid	0187 - Rebuild 100	) HP to 200 HP I	Motor	
	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0187	4.00	EA			
	X Base Bid	0100 Powind 100	UD +0 200 UD M	otor IIn to 900 PDM	
DESCRIPTION:		0188 - Rewind 100	HP CO 200 HP M	ocor op co 900 kPM	
	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0188	1.00	EA			
	X Base Bid	0188 Powind 100	UD +0 200 UD M	ptor Up to 1150 RPM	
DESCRIPTION:	믐	0109 - Rewind 100	HP CO 200 HP MC	ocol op co 1150 kFM	
	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0189	1.00	EA			
	X Base Bid	0190 - Rewind 100	HP to 200 HP M	ptor Up to 1750 RPM	
DESCRIPTION:	Alt.#	orgo newina roo	111 00 200 111 11	Sect of to 1750 km	
DEENO		LINIT OF MEACURE	LIMIT DDICE	LIMIT DDICE EVTENCION (Quantity times limit Drice)	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0190	1.00	EA			
	X Base Bid	0191 - Rebuild 250	) HP to 350 HP I	Motor	
DESCRIPTION:	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0191	4.00	EA		,	
3.01	4.00				
DESCRIPTION	X Base Bid	0192 - Rewind 250	HP to 350 HP M	otor Up to 900 RPM	
DESCRIPTION:	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0192	1.00	EA			

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid	0102 Powind 250	UD +0 3E0 UD M	otor Un to 1150 PDM	
DESCRIPTION:					
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0193	1.00	EA	UNIT FRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0193	1.00	EA			
	TION: Alt.#_				
DESCRIPTION:					
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0194	1.00	EA			
	,				
	V Dogo Did				
DESCRIPTION:	X Base Bid	0195 - Rebuild 400	) HP Motor		
	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0195	1.00	EA			
	X Base Bid	0196 - Rewind 400	HP Motor-725RPI	M	
DESCRIPTION:	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0196	1.00	EA			
	<b>T</b> Z D = = = D : 4				
DESCRIPTION:	Base Bid 0197 - Replace any size unrepairable TESCO controller with TESCO Liq 5				
	Alt.#	controller			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0197	5.00	EA			
	X Base Bid	0198 - Repair TESC	CO Lig 3 Contro	ller	
DESCRIPTION:	Alt.#	-	-		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0198	5.00	EA			
J	I				
	₩ D D' 1				
DESCRIPTION:	X Base Bid	0199 - Repair TESC	CO Liq 4 Contro	ller	
	L_ALT.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0199	5.00	EA			
	X Base Bid	0200 - Repair TESC	CO Lig 5 Contro	ller	
DESCRIPTION:	Alt.#	_	•		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0200	5.00	EA			

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid	0201 - Small Lathe	e Work		
DESCRIPTION:	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0201	78.00	HR			
	X Base Bid	0202 - Small Vert	ical Axis Boring	Mill Work	
DESCRIPTION:	Alt.#		3		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0202	40.00	HR			
	J.				
	X Base Bid	0203 - Keyway Cut	tina		
DESCRIPTION:	Alt.#	0200 Reyway cae	21119		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0203	40.00	HR			
	<u>'</u>				
	X Base Bid	0204 - Small Mill:	ing Machine Work		
DESCRIPTION:	∏alt.#		5		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0204	40.00	HR			
	J				
	X Base Bid	0205 - Key Cutting	~		
DESCRIPTION:	Alt.#	0205 Rey eaceing	3		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0205	40.00	HR		( 100 )	
0200					
	X Base Bid				
DESCRIPTION:		0206 - Saw Work			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
	40.00	HR	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times unit Price)	
0206	40.00	LIIX			
	X Base Bid				
DESCRIPTION:	X Base Bid 0207 - Lapping Machine Work Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0207	40.00	HR	OHITTHOL	ONIT I THOSE EXTENSION (Quantity times office ince)	
0201	40.00	TIIX	<u> </u>		
	V Bago Did	0000 5 1 - 1	1		
DESCRIPTION:	I <u></u>	X Base Bid 0208 - Dynamic Balancing			
REF NO.	Alt.#	UNIT OF MEASURE	UNIT PRICE	HAIT DDICE EVENCION (Occasión diseas Hait Baire)	
0208	40.00	HR	ONIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0200	1 40.00	LIIX	1		

Bid# 50-00148708

TO: JEFFERSON PARISH PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

DESCRIPTION:	X Base Bid 0209 - Miscellaneous Assembly Work				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0209	40.00	HR	UNITPRICE	UNIT PRICE EXTENSION (Quantity times unit Price)	
0209	40.00	TIIN			
DESCRIPTION:	X Base Bid Alt.#	0210 - Miscellaneo	ous Measurement	Work	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0210	40.00	HR			
DESCRIPTION:	ON: Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0211	40.00	HR			
	I.				
	X Base Bid	0212 - Superintend			
DESCRIPTION:	Alt.#	0212 - Superincent	delic		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0212	40.00	HR			
	X Base Bid	0010	. Tife Openium	Daniel and Alba	
DESCRIPTION:	Alt.#	0213 - Foreman for	r Lill Station	Repair Jobs	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0213	80.00	HR	0	Chill I Mod 2012 2010 Children was a series of the children was a series o	
0210					
	X Base Bid				
DESCRIPTION:		0214 - Mechanic			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0214	40.00	HR	ONTTRICE	ONIT PRIOR EXTENSION (Quantity times office thes)	
0214	40.00	TIIX			
	T 1				
DESCRIPTION:	X Base Bid	0215 - Electricia	n		
DEE NO	L ALT.#				
REF NO.		HR	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0215	417.00	ПК			
	- · ·				
DESCRIPTION:	X Base Bid	0216 - Welder with	n Welding Truck	and Fuel	
	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0216	80.00	HR			

Bid# 50-00148708

TO: JEFFERSON PARISH PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

DESCRIPTION:	X Base Bid				
	Alt.#	LINUT OF MEASURE	1007 PD107		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0217	80.00	HR			
DESCRIPTION:	Base Bid 0218 - Trades Helper				
	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0218	198.00	HR			
DESCRIPTION:	X Base Bid	0219 - Mechanic T	ruck/Hoist-2000	Pound Capacity with Operator and Fuel	
DESCRIPTION:	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0219	5.00	DA			
	X Base Bid	0220 - Boom Truck	-5000 Pound Cap	acity with Operator and Fuel	
DESCRIPTION:	Alt.#				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
0220	5.00	DA			
	X Base Bid	0221 - Flatbed Tr	ruck-1 1/2 Ton w	ith Operator and Fuel	
DESCRIPTION:	Alt.#				
REF NO.	QUANTITY	LINIT OF MEACURE			
0221		UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
	5.00	DA	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
	5.00		UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
	5.00 X Base Bid	DA			
DESCRIPTION:					
	X Base Bid	DA			
DESCRIPTION:	X Base Bid	DA 0222 - Electricia	n Truck with Fu	el	
REF NO.	X Base Bid Alt.# QUANTITY	DA  0222 - Electricia  UNIT OF MEASURE	n Truck with Fu	el	
REF NO.	X Base Bid Alt.#_ QUANTITY 18.00	DA  0222 - Electricia  UNIT OF MEASURE  DA	n Truck with Fu	e1  UNIT PRICE EXTENSION (Quantity times Unit Price)	
REF NO.	X Base Bid Alt.# QUANTITY 18.00  X Base Bid	DA  0222 - Electricia  UNIT OF MEASURE	n Truck with Fu	e1  UNIT PRICE EXTENSION (Quantity times Unit Price)	
REF NO. 0222	X Base Bid Alt.#_ QUANTITY 18.00	DA  0222 - Electricia  UNIT OF MEASURE  DA	n Truck with Fu	e1  UNIT PRICE EXTENSION (Quantity times Unit Price)	
DESCRIPTION: REF NO. 0222  DESCRIPTION:	X Base Bid Alt.# QUANTITY 18.00  X Base Bid Alt.#	DA  0222 - Electricia  UNIT OF MEASURE  DA  0223 - Bucket Tru	n Truck with Fu  UNIT PRICE	el  UNIT PRICE EXTENSION (Quantity times Unit Price)  r and Fuel	
DESCRIPTION: REF NO. 0222  DESCRIPTION: REF NO.	X Base Bid Alt.# QUANTITY 18.00  X Base Bid Alt.# QUANTITY	DA  0222 - Electricia  UNIT OF MEASURE  DA  0223 - Bucket Tru  UNIT OF MEASURE	n Truck with Fu  UNIT PRICE	el  UNIT PRICE EXTENSION (Quantity times Unit Price)  r and Fuel	
DESCRIPTION: REF NO. 0222  DESCRIPTION: REF NO. 0223	X Base Bid Alt.# QUANTITY 18.00  X Base Bid Alt.# QUANTITY 5.00	DA  0222 - Electricia  UNIT OF MEASURE  DA  0223 - Bucket Tru  UNIT OF MEASURE  DA	n Truck with Fu  UNIT PRICE  ack with Operato  UNIT PRICE	el  UNIT PRICE EXTENSION (Quantity times Unit Price)  r and Fuel	
DESCRIPTION: REF NO. 0222  DESCRIPTION: REF NO. 0223	X Base Bid Alt.# QUANTITY 18.00  X Base Bid Alt.# QUANTITY 5.00	DA  0222 - Electricia  UNIT OF MEASURE  DA  0223 - Bucket Tru  UNIT OF MEASURE	n Truck with Fu  UNIT PRICE  ack with Operato  UNIT PRICE	el  UNIT PRICE EXTENSION (Quantity times Unit Price)  r and Fuel	
DESCRIPTION: REF NO. 0222  DESCRIPTION: REF NO. 0223	X Base Bid Alt.# QUANTITY 18.00  X Base Bid Alt.# QUANTITY 5.00	DA  0222 - Electricia  UNIT OF MEASURE  DA  0223 - Bucket Tru  UNIT OF MEASURE  DA	n Truck with Fu  UNIT PRICE  ack with Operato  UNIT PRICE	el  UNIT PRICE EXTENSION (Quantity times Unit Price)  r and Fuel	

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid	0225 - Operation	of 50 KW Generator	
DESCRIPTION:	Alt.#	-		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0225	5.00	DA		
	X Base Bid	0226 - Operation	of 50 KW Generator	
DESCRIPTION:	Alt.#	•		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0226	40.00	HR		
	X Base Bid	0227 - Set Up 100	KW Generator	
DESCRIPTION:	Alt.#	022, 200 op 100	1 0011010001	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0227	5.00	EA		
	<u>'</u>			
	X Base Bid	0228 - Operation	of 100 KW Generato	r
DESCRIPTION:	Alt.#	· · · · · ·		
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0228	40.00	HR		
	X Base Bid	0229 - Operation	of 100 KW Generato	r
DESCRIPTION:	Alt.#	0225 Operation	or row am denerate	_
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0229	5.00	DA		
3223			<u> </u>	
	X Base Bid			
DESCRIPTION:	<u> </u>	0230 - Set Up 200	KW Generator	
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0230	5.00	EA	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times offic Price)
0200	3.00	LA		
	X Base Bid	0001 0 11	5 000 THY G	
DESCRIPTION:	Alt.#	0231 - Operation	of 200 KW Generato	r
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)
0231	40.00	HR	ONTTRICE	ONIT TRIOL EXTENSION (Quantity times office rice)
0201	40.00	TIIX		
	X Base Bid	0020 00000	- F 000 IVI G :	
DESCRIPTION:	I <u>—</u>	0232 - Operation	of 200 KW Generato	r
REF NO.	Alt.#	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)

#### LOUISIANA UNIFORM PUBLIC WORK BID FORM UNIT PRICE FORM

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT SUITE 4400 200 DERBIGNY ST. GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

DESCRIPTION: X Base Bid 0233 - Set Up 300 KW Generator Alt.#						
0233	5.00	EA	0			
0233	3.00	LA				
	X Base Bid	0234 - Operation	of 300 KW Generator			
DESCRIPTION:	Alt.#					
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0234	40.00	HR		,		
	10.00					
DECODIDE	X Base Bid	0235 - Operation	of 300 KW Generator			
DESCRIPTION:	Alt.#					
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0235	5.00	DA				
	₩ p p					
DESCRIPTION:	X Base Bid	0236 - Set Up 500	KW Generator			
DECOKII TION:	Alt.#					
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0236	5.00	EA				
	1					
	X Base Bid	0227 Operation	of EOO VW Conorator			
DESCRIPTION:	X Base Bid	0237 - Operation	of 500 KW Generator			
	Alt.#					
REF NO.	Alt.#	UNIT OF MEASURE	of 500 KW Generator	UNIT PRICE EXTENSION (Quantity times Unit Price)		
	Alt.#			UNIT PRICE EXTENSION (Quantity times Unit Price)		
REF NO.	Alt.#	UNIT OF MEASURE		UNIT PRICE EXTENSION (Quantity times Unit Price)		
REF NO.	Alt.#	UNIT OF MEASURE HR	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
REF NO.	Alt.#QUANTITY 40.00	UNIT OF MEASURE HR		UNIT PRICE EXTENSION (Quantity times Unit Price)		
REF NO. 0237  DESCRIPTION:	Alt.#	UNIT OF MEASURE HR  0238 - Operation	UNIT PRICE			
REF NO. 0237  DESCRIPTION: REF NO.	Alt.#QUANTITY 40.00  X Base Bid Alt.#QUANTITY	UNIT OF MEASURE HR  0238 - Operation UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)  UNIT PRICE EXTENSION (Quantity times Unit Price)		
REF NO. 0237  DESCRIPTION:	Alt.#	UNIT OF MEASURE HR  0238 - Operation	UNIT PRICE			
REF NO. 0237  DESCRIPTION: REF NO.	Alt.#	UNIT OF MEASURE HR  0238 - Operation UNIT OF MEASURE	UNIT PRICE			
REF NO. 0237  DESCRIPTION: REF NO. 0238	Alt.#QUANTITY 40.00  X Base Bid Alt.#QUANTITY	UNIT OF MEASURE HR  0238 - Operation UNIT OF MEASURE	UNIT PRICE  of 500 KW Generator  UNIT PRICE			
REF NO. 0237  DESCRIPTION: REF NO.	Alt.#	UNIT OF MEASURE HR  0238 - Operation  UNIT OF MEASURE DA	UNIT PRICE  of 500 KW Generator  UNIT PRICE			
REF NO. 0237  DESCRIPTION: REF NO. 0238	Alt.#	UNIT OF MEASURE HR  0238 - Operation  UNIT OF MEASURE DA	UNIT PRICE  of 500 KW Generator  UNIT PRICE			
REF NO. 0237  DESCRIPTION: REF NO. 0238  DESCRIPTION:	Alt.#QUANTITY 40.00  X Base Bid Alt.#QUANTITY 5.00  X Base Bid Alt.#_Alt.#Alt.#Alt.#Alt.#Alt.#Alt.#Alt.#Alt.#_Alt.#Alt.#_Alt.#Alt.#_Alt.#Alt.#_Al	UNIT OF MEASURE HR  0238 - Operation  UNIT OF MEASURE DA  0239 - Set Up 800	UNIT PRICE  of 500 KW Generator  UNIT PRICE  KW Generator	UNIT PRICE EXTENSION (Quantity times Unit Price)		
REF NO. 0237  DESCRIPTION: REF NO. 0238  DESCRIPTION: REF NO.	Alt.#	UNIT OF MEASURE HR  0238 - Operation  UNIT OF MEASURE DA  0239 - Set Up 800  UNIT OF MEASURE	UNIT PRICE  of 500 KW Generator  UNIT PRICE  KW Generator	UNIT PRICE EXTENSION (Quantity times Unit Price)		
REF NO. 0237  DESCRIPTION: REF NO. 0238  DESCRIPTION: REF NO.	Alt.#	UNIT OF MEASURE HR  0238 - Operation  UNIT OF MEASURE DA  0239 - Set Up 800  UNIT OF MEASURE EA	UNIT PRICE  of 500 KW Generator  UNIT PRICE  KW Generator  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
REF NO. 0237  DESCRIPTION: REF NO. 0238  DESCRIPTION: REF NO. 0239	Alt.#	UNIT OF MEASURE HR  0238 - Operation  UNIT OF MEASURE DA  0239 - Set Up 800  UNIT OF MEASURE EA	UNIT PRICE  of 500 KW Generator  UNIT PRICE  KW Generator	UNIT PRICE EXTENSION (Quantity times Unit Price)		
REF NO. 0237  DESCRIPTION: REF NO. 0238  DESCRIPTION: REF NO.	Alt.#	UNIT OF MEASURE HR  0238 - Operation  UNIT OF MEASURE DA  0239 - Set Up 800  UNIT OF MEASURE EA	UNIT PRICE  of 500 KW Generator  UNIT PRICE  KW Generator  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
REF NO. 0237  DESCRIPTION: REF NO. 0238  DESCRIPTION: REF NO. 0239	Alt.#	UNIT OF MEASURE HR  0238 - Operation  UNIT OF MEASURE DA  0239 - Set Up 800  UNIT OF MEASURE EA	UNIT PRICE  of 500 KW Generator  UNIT PRICE  KW Generator  UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		

Wording for "DESCRIPTION" is to be provided by the Owner. All quantities are estimated. The contractor will be paid based upon actual quantities as verified by the Owner.

#### LOUISIANA UNIFORM PUBLIC WORK BID FORM UNIT PRICE FORM

Bid# 50-00148708

JEFFERSON PARISH TO: PURCHASING DEPT 200 DERBIGNY ST. SUITE 4400 GRETNA, LA 70053

(Owner to provide name and address of owner)

PRE-PLACED EMERGENCY CONTRACT FOR POINT REPAIR, LINING AND EMERGENCY **RESTORATION OF EXISTING SEWER MAINLINES** FORCE MAINS AND TELEVISING, CLEANING AND

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

	X Base Bid 0241 - Operation of 800 KW Generator					
DESCRIPTION:	Alt.#					
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0241	5.00	DA				
	X Base Bid	0242 - Set Up 100	N KW Generator			
DESCRIPTION:	Alt.#	0212 BCC 0P 100	o im deliciacoi			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0242	5.00	EA	0.0	Cim Fine Enterior (Quality units office ince)		
02.2	0.00					
	X Base Bid					
DESCRIPTION:		0243 - Operation o	of 1000 KW Gene:	rator		
	Alt.#					
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0243	40.00	HR				
	ı					
DECODINE	X Base Bid	0244 - Operator o	f 1000 KW Gener	ator		
DESCRIPTION:	Alt.#					
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0244	5.00	DA				
	X Base Bid	0245 - Set Up 200	N KW Generator			
DESCRIPTION:	Alt.#	0213 BCC 0P 2000	o im deliciacoi			
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0245	5.00	EA				
02.10		<del></del>				
	<b>.</b>					
DESCRIPTION:	X Base Bid	0246 - Operation	of 2000 KW Gene	rator		
	Alt.#					
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0246	40.00	HR				
DE000:00:00:00	X Base Bid	0247 - Operation	of 2000 KW Gene	rator		
DESCRIPTION:	Alt.#					
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0247	5.00	DA				
	X Base Bid	0248 - Unforeseen	Work			
DESCRIPTION:	Alt.#	0210 UNIOTOBEEN				
REF NO.	QUANTITY	UNIT OF MEASURE	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)		
0248	1.00	JOB				

Wording for "DESCRIPTION" is to be provided by the Owner. All quantities are estimated. The contractor will be paid based upon actual quantities as verified by the Owner.

#### **PUBLIC WORKS BID INSTRUCTIONS**

## A. LOUISIANA CONTRACTOR'S LICENSE FOR THIS PROJECT

Must be in the following category:
Municipal & Public Construction
Each bidder shall comply with all rules and regulations of the Louisiana State Licensing Board for Contractors in accordance with existing state laws, and shall comply with the Licensing Requirements of LRS 37:2150 et. seq.
B. PROBABLE CONSTRUCTION RANGES AND PRICES
Range of the Probable Construction Cost for Base Bid:
Range of the Probable Construction Cost for Alternate No. 1:
Range of the Probable Construction Cost for Alternate No. 2:
Range of the Probable Construction Cost for Alternate No. 3:
Range of the Previous Contract Cap (Public Work Maintenance Contract): \$10,000,000 – 15,000,000

The estimated cost range is for informational purposes only and may be subject to change. The bid prices received from bidders will be evaluated based on the actual estimate value, which will be read aloud at the time of bid opening, for award determination.

The purpose and intention of this invitation to bid is to afford all suppliers/contractors an equal opportunity to bid on construction, maintenance, repair, operating, services, supplies and/or equipment listed in this bid proposal. Jefferson Parish will accept one bid only from each vendor. Items bid on must meet or exceed specifications. Where brand names, make, manufacturer or stock numbers are specified, it is for the purpose of establishing certain minimum standards of quality. Bidders may submit for products of equal quality, style, type and character, provided brand names and stock numbers are specified. Complete product data may be required prior to award.

The price quoted for the work shall be stated in figures no more than four (4) decimal points. In the event there is a difference in unit prices and totals, the unit prices shall prevail. In the event there is a difference in unit prices, written unit prices shall prevail over numerical unit prices.

The quantities listed on the bid form are prepared for comparison of bids and may be approximate. Bid item quantities may be increased, decreased, or omitted as provided in the specifications. Payment to the contractor will be made in accordance with measurement and payment requirements for bid items and other requirements of the project specifications.

Jefferson Parish requires all products to be new (current), and all work must be performed according to standard practices for the project. Unless otherwise specified, no after market parts will be accepted. Unless otherwise specified, all workmanship and materials must have at least a one (1) year warranty, in writing, from the date of delivery/acceptance of the project.

#### C. METHODS OF BID SUBMISSION

All bids shall be submitted electronically through Jefferson Parish's eProcurement System online at <a href="https://www.jeffparishbids.net">www.jeffparishbids.net</a>. Registration and use of this site are free to Jefferson Parish vendors.

Only bids properly signed (see more below) will be accepted. NO LATE BIDS WILL BE ACCEPTED. The name of the bidder must be legibly shown. If the bidder is an individual, their name and address should be shown. If the bidder is an entity, the name of the person given the requisite authority to submit the bid on behalf of the entity shall be shown and the address of the entity's place of business should be shown.

Evidence of agency, corporate, limited liability or partnership authority of the person submitting and signing the bid is required for submission of bid. A copy of a corporate resolution or other signature authorization shall be required for submission of the bid. Failure to include a copy of the appropriate signature authorization will result in the rejection of the bid unless bidder has complied with L.R.S. 38:2212(B)(5). A sample corporate resolution and sample certification of sole proprietorship can be downloaded from the Jefferson Parish Purchasing Department's website <a href="Document Library Jefferson Parish">Document Library Jefferson Parish, LA (jeffparish.gov)</a>, or you may provide your own document. Photostatic or font signatures shall result in the bid being rejected. However, an electronic signature as defined in L.R.S. 9:2602(8) is acceptable. Signature must be a secured digital signature.

#### D. TIMELINES

#### 1. Prior to the closing time for receipt of scheduled bids

A bid may be withdrawn at any time prior to the scheduled closing time for receipt of bids, by withdrawing via the eProcurement System online or providing a request in writing, executed by the bidder or his duly authorized representative, to the Purchasing Department prior to that time. When such a request is received, the bid will be returned to the bidder unopened. However, no bid can be modified, corrected or withdrawn after the time set for closing such bid, except as provided by L.R.S. 38:2214(C) & (D).

The Parish, its engineers, architects or anyone distributing plans and specifications for Parish public work projects, equal to or over the contract limit as defined in L.R.S. 38:2212, shall furnish all prime bidders who request bid documents and who are properly licensed by the Louisiana State Licensing Board for Contractors with at least one set of complete bid documents. A deposit or fee may be charged on the documents as authorized by L.R.S. 38:2212.

Addenda may be issued, as authorized by L.R.S. 38:2212 (O). All formal Addenda require written acknowledgment on the bid form by the bidder. Failure to acknowledge an Addendum on the bid form shall cause the bid to be rejected. Jefferson Parish reserves the right to award the bid to the next lowest responsive and responsible bidder in this event.

Prior to submitting a bid each bidder shall visit the site of the proposed work and fully acquaint himself with all surface and subsurface conditions as they may exist so that he may fully understand the facilities, difficulties, and restrictions attending the execution of the work under this Contract. Bidders shall also thoroughly examine and be familiar with Drawings, Specifications, and Contract Documents. The failure or omission of any bidder to receive or examine any form, instrument, drawing, or document or to visit the site and acquaint himself with conditions there existing, shall in no way relieve any bidder from any obligation with respect to his bid and the responsibility in the premises rests with him. Submission of a bid shall be considered prima facie evidence that the bidder has made such examination and is satisfied as

to the conditions to be encountered in performing the work and as to requirements of the plans, project specifications, Resolution No. 141125, as amended, and contract forms.

Any pre-bid test and boring data in connection with subsurface conditions which have been completed by the Parish or its engineers and furnished to the bidder shall not be considered as fully representative of subsurface conditions existing throughout the area tested nor shall they in any way be binding upon the Parish, it being understood that said data is furnished the bidder for his convenience only and the bidder shall be solely responsible for conducting his own boring explorations he deems necessary in preparing his bid. Any prospective bidder wishing to conduct boring explorations on Parish property must obtain written permission from Jefferson Parish prior to such explorations.

No claims shall be made against the Parish for additional compensation due to unforeseen subsurface conditions arising during progress of the work and which might be in variance with the Parish's pre-bid boring data.

#### 2. Post-closing time for receipt of scheduled bids

Except as where provided by law, bidder agrees that this bid shall be legally binding and may not be withdrawn for a period of forty-five (45) calendar days after the scheduled closing time for receiving bids. In the event the Parish issues the Letter of Award (copy of adopted resolution awarding bid by Jefferson Parish Council) during this period, the bid accepted shall continue to remain binding pending execution of the Contract.

Bidder agrees to execute the ensuing Contract and will deliver applicable Bonds to secure the faithful performance thereof.

The Parish of Jefferson reserves the right to cancel this contract for convenience by issuing a thirty (30) day written notice to contractor.

#### E. BID REVIEW AND AWARD

#### 1. Rejection of Bids

- a. Jefferson Parish may reject any and all bids for just cause in accordance with L.R.S. 38:2214(B). Just cause, for the purpose of the construction of public works, is defined, but is not limited to, the following circumstances:
  - The public entity's unavailability of funds sufficient for the construction of the proposed public work.
  - (2) The failure of any bidder to submit a bid within an established threshold of the preconstruction estimates for that public work, as part of the bid specifications.
  - (3) A substantial change by the public entity prior to the award in the scope or design of the proposed public work.
  - (4) A determination by the public entity not to build the proposed public work within twelve months of the date for the public opening and reading of bids.
  - (5) The disqualification by the public entity of all bidders.

- b. Additionally, bids may be considered irregular and be rejected for any of the following, but is not limited to the following circumstances:
  - (1) If the bid form is on a form other than that furnished by the Parish or if the form is altered or any part thereof is detached.
  - (2) If affidavits included in bid form and/or required by law are not returned with the bid or are not properly executed and notarized.
  - (3) If there are unauthorized additions, conditional or alternate bids or irregularities which alter the general terms and conditions, the plans or specifications, or make the bid incomplete, indefinite, or ambiguous as to its meaning.
  - (4) If the bidder adds provisions reserving the right to accept or reject the award or to enter into the contract pursuant to the award.
  - (5) If an owner or a principal officer of the bidding firm is an owner or a principal officer of a firm which has been declared by the Parish to be ineligible to bid.
  - (6) If the proposed bid security does not meet the requirements of Section J.
  - (7) If more than one proposal for the same work, services, materials or supplies is received from an individual, partner, firm, corporation, joint venture, other legal entity, or combination thereof under the same or a different name.
  - (8) The bid is not properly signed or the authority of the signature person submitting the bid is deemed insufficient or unacceptable.
  - (9) If the bidder does not possess the proper license(s) required as noted in the specifications.
  - (10) Any other reasons for rejection set forth by State or Parish laws, Ordinances or Resolutions.
- c. In awarding contracts for materials and supplies, Jefferson Parish shall reject the lowest bid if received from a bidder domiciled in a Communist country, or if the materials or supplies are manufactured in a Communist country, including but not limited to Soviet Union, China, North Korea and Vietnam, and to award the contract to the next lowest bidder. This Section shall not apply to any country having established trade relations agreements or approvals from the government of the United States. (L.R.S. 38:2212.3)
- d. In accordance with L.R.S. 38:2216.1, Jefferson Parish is prohibited from entering into a contract with a value of \$100,000 or more with a company for the purchase of goods or services unless the contract contains a written verification from the company of both of the following: 1) The company does not have a practice, policy, guidance, or directive that discriminates against a firearm entity or firearm trade association based solely on the entity's or association's status as a firearm entity or firearm trade association. 2) The company will not discriminate against a firearm entity or firearm trade association during the term of the contract based solely on the entity's or association's status as a firearm entity or firearm trade association. As a result, the awarded bidder will be required to verify the above in the ensuing contract.

#### 2. Disqualification of Bids

- a. The causes for disqualification from consideration for award of a contract with Jefferson Parish are as follows (Jefferson Parish Code of Ordinances, Section 2-912):
  - Conviction for commission of a criminal offense as an incident to obtaining or attempting to obtain a public or private contract or subcontract, or in the performance of such contract or subcontract;

- (2) Conviction under state or federal statutes of embezzlement, theft, forgery, bribery, falsification or destruction of records, receiving stolen property, or any other offense indicating a lack of business integrity or business honesty which currently, seriously, and directly affects responsibility as a Parish contractor;
- Conviction under state or federal antitrust statutes arising out of the submission of bids or proposals;
- (4) Violation of contract provisions, as set forth below, of a character which is regarded by the Purchasing Director or his designee for Jefferson Parish to be serious as to justify disqualification:
  - Deliberate failure without good cause to perform in accordance with the specifications or within the time limit provided in the contract; or
  - ii. A recent record of failure to perform or of unsatisfactory performance in accordance with the terms of one or more contracts; provided that failure to perform or unsatisfactory performance caused by acts beyond the control of the contractor shall not be considered to be a basis for disqualification; or
  - iii. Failure to timely pay, without cause, a subcontractor for work performed under a construction contract as required under Section 2-976 in Chapter 2, Article VII, of the Jefferson Parish Code of Ordinances, provided disqualification on such basis shall not exceed a period of one (1) year from the deadline to pay the subcontractor.
- (5) Any other cause the Purchasing Director determines to be so serious and compelling as to affect responsibility as a Parish contractor, including debarment by another governmental entity for any cause;
- (6) Violation of the State Code of Ethics or the ethical standards set forth in the Jefferson Parish Code of Ordinances;
- (7) Failure to secure, provide, and/or maintain necessary licenses and/or permits during the term of the contract;
- (8) Failure to comply with the Jefferson Parish Code of Ordinances and/or the Jefferson Parish Comprehensive Zoning Ordinance;
- (9) For any other reason in which the Paishdeems you to not be a responsible bidder.
- The procedures for disqualification from consideration for award of a contract with Jefferson Parish are set forth in Sec. 2- 912 (b).

#### Note:

A bid which is not responsive to, or does not meet bid specifications, will be rejected as being non-responsive, but that bidder will not be disqualified from future Parish bids, nor will that bidder be given a hearing pursuant to procedure listed below.

#### 3. Award of Contract

The award of the contract, if it be awarded, will be by the Parish to the lowest responsive and responsible bidder whose proposal shall have complied with all the bid requirements. The successful bidder will be notified via the e-Procurement site that his bid has been accepted. No contract shall be executed with any contractor until their certificates of insurance, performance bonds, labor and materials payment bonds, or any other bonds required are made satisfactory to the Parish.

Jefferson Parish reserves the right to award contracts or place orders on a lump sum or individual item basis, or such combination as shall, in its judgment, be in the best interest of Jefferson Parish. Every contract or order shall be awarded to the lowest responsible bidder, taking into consideration the conformity with the specifications, and the delivery and/or completion date.

Preference will be given to bidders requesting a preference in their bid in accordance with L.R.S. 38:2251-2261 for materials, supplies, and provisions, produced, manufactured or grown in Louisiana, quality being equal to articles offered by competitors outside the State of Louisiana, unless federal funding is directly spent by Jefferson Parish on this project.

The successful bidder shall execute the contract with the Parish in the form of the contract set forth in Resolution No. 141125 Standard General Conditions of the Construction Contract. One copy of the executed contract with all documents forming a part thereof shall be filed at the expense of the contractor, with the Recorder of Mortgages in Jefferson Parish.

<u>PROTESTS</u>: Only those vendors that submit bids in response to this solicitation may protest any element of the procurement, in writing to the Director of the Purchasing Department. Written protest must be received within 48 hours of the release of the bid tabulation by the Purchasing Department. After consultation, the Parish Attorney's Office will then respond to protests in writing. (For more information, please see Chapter 2, Article VII, Division 2, Sec. 2-913 of the Jefferson Parish Code of Ordinances.)

Upon full execution of the contract and receiving a written notice to proceed, the bidder agrees that all work shall be completed as follows:

The work shall be substantially complete within \_\_\_\_ calendar days of the written notice to proceed and completed and shall be ready for final acceptance no more than 30 calendar days after substantial completion.

#### F. SALES TAX EXEMPTION

For this project, the contractor shall not pay any state or local sales or use taxes on materials and equipment which are affixed and made part of the immovable property of the project or which is permanently incorporated in the project (hereinafter referred to as "applicable materials and equipment"). All purchases of applicable materials or equipment shall be made by the contractor on behalf of and as the agent of Jefferson Parish (Parish), a political subdivision of the State of Louisiana. No state and local sales and use taxes are owed on applicable materials and equipment under the provisions of Act 1029 of the 1991 Regular Session – Louisiana Revised Statute 47:301(8)(c). Parish will furnish to contractor a certificate form which certifies that Parish is not required to pay such state or local sales and use taxes, and contractor shall furnish a copy of such certificate to all vendors or suppliers of the applicable materials and equipment, and report to Parish the amount of taxes not incurred.

#### G. LIQUIDATED DAMAGES

In accordance with Resolution No. 141125, as amended, Bidder agrees to pay, as liquidated damages, the sum of  $\frac{N/A}{}$  for: (1) each consecutive calendar day after the agreed date of substantial completion that the work remains substantially incomplete, and (2) each consecutive calendar day after the 30th day following the actual date of substantial completion that the work has not been finally completed.

In addition to, but not in lieu of the per diem liquidated damages, Parish shall also be entitled to recover from the contractor or the contractor's surety additional liquidated damages as detailed in Resolution No. 141125, as amended. These additional liquidated damages may include, but are not limited to the following, in the amounts and for each of the items identified in the Supplementary Conditions:

(1)	Extended Architectural and/or Engineering Fees	\$ N/A	/hour
(2)	Extended Resident Project Representative Fee	\$ N/A	/hour
(3)	Extended Construction Management Fees	\$ N/A	/day
(4)	Extended Parish's Overhead and Personnel Expenses	\$ N/A	/hour

(5) Parish's Other Costs Directly Related to the Delay in Completion Beyond the Contract Times

Whenever contractor's work requires inspections in excess of the budgeted amount for inspection, the contractor shall reimburse the Parish for the additional costs incurred by the Parish attributable to inspection of the contracted project in excess of the budgeted amount for inspections.

The reasonable budget for such inspections is \$\_N/A\_\_\_\_. Resident Project Representative overtime rates shall be calculated at 1.2 times the hourly rate. The cost of inspection in excess of this budgeted amount shall be assessed against Contractor's progress payments, all in accordance with Louisiana Public Bid Law.

## H. ETHICAL STANDARDS AND COOPERATION WITH THE OFFICE OF THE INSPECTOR GENERAL, INCLUDING CONFLICTS OF INTEREST

Vendor agrees by bid submission to comply with all provisions of Louisiana Law as well as compliance with the Jefferson Parish Code of Ordinances, Louisiana Code of Ethics, as published on <a href="http://ethics.la.gov">http://ethics.la.gov</a> and applicable Jefferson Parish ethical standards and Jefferson Parish Terms and Conditions.

Inspector General: It shall be the duty of every Parish officer, employee, department, agency, special district, board, and commission; and the duty of every contractor, subcontractor, and licensee of the Parish, and the duty of every applicant for certification of eligibility for a Parish contract or program, to cooperate with the Inspector General in any investigation, audit, inspection, performance review, or hearing pursuant to JPCO 2-155.10(19). Every Parish contract and every bid, proposal, application or solicitation for a Parish contract, and every application for certification of eligibility for a Parish contract or program shall contain a statement that the corporation, partnership, or person understands and will abide by all provisions of JPCO 2-155.10. By submitting a bid, Bidder acknowledges this and will abide by all provisions of the referenced JPCO.

<u>Conflicts of Interest</u>: Jefferson Parish adheres to the Louisiana Code of Governmental Ethics, contained in Louisiana Revised Statutes Annotated, R.S. 42:1101, et seq. Vendor/Proposer by this submission warrants that there are no "conflicts of interest" related to this procurement that would violate applicable Louisiana Law. Violation of the Louisiana Code of Governmental Ethics may result in rescission of contract, permit or licenses, and the imposition of fines and/or penalties, without contractual liability to the public in accordance with applicable law.

#### I. REQUIRED AFFIDAVITS

For convenience, all legally mandated affidavits have been combined into one form, entitled **Generic Bid Affidavit**. All bidders must submit with their bid submission, a completed, signed and properly notarized affidavit in its original format and without alteration in order to be compliant and for the bid to be considered responsive. A scanned copy of the completed, signed and properly notarized affidavit may be submitted with the bid; however, the successful bidder must submit the original affidavit in its original format and without material alteration prior to, or at contract execution. Failure to comply will result in the bid submission being rejected as non-responsive. The Parish reserves the right to award bid to the next lowest responsive and responsible bidder in this event.

The person submitting the bid, and whose authority to submit has been evidenced on the Designation of Authority is the proper party to execute the **Generic Bid Affidavit.** 

☐ If this box is checked, then the **Technology Affidavit** is required for this solicitation and shall be submitted with the bid submission. Failure to do so will result in your bid being rejected. Pursuant to La. R.S. 38:2237.1, prior to the procurement of telecommunications or video surveillance equipment or services, the vendor shall provide documentation by affidavit that the equipment or services to be procured are not prohibited telecommunications or video surveillance equipment or services as defined in R.S. 39:1753.1(A). This affidavit is supplied as a courtesy to Affiant. It is the responsibility of the affiant to insure the affidavit submitted to Jefferson Parish complies, in both form and content, with federal, state and parish laws. No procurement shall be made from a vendor or other entity who fails to provide the documentation; any procurement in contravention to this requirement shall be null and void by law.

## J. BID REQUIREMENTS (BID DOCUMENTS, SPECIFICATIONS, BONDS, W-9 AND PAYMENT INFO)

Bidders must review the bid specifications and include any required documentation including but not limited to the LA Public Works Uniform Bid Form; Bid Security or Bid Bond; Acknowledgment of Addenda; Base Bid; Alternates; Signature of Bidder; Name, Title, and Address of Bidder; Name of Firm or Joint Venture; Corporate Resolution or written evidence of the authority of the person signing the bid; Louisiana Contractors License Number; Generic Bid Affidavit. Pursuant to L.R.S. 38:2212(B)(3)(b), bidders shall also be responsible for providing any other documentation as required. Please note that the payment and performance bonds must be supplied by the successful bidder at contract signing.

No oral interpretation will be made to any bidder as to the meaning of the drawings, specifications, or contract documents. Every request for such interpretation shall be made in writing and addressed and forwarded to the Engineer, Architect or person distributing plans and specifications. No inquiry received within five (5) days prior to the day fixed for opening of the bids will be given consideration. Every interpretation made to the bidder shall be in the form of an addendum to the specifications and shall be issued as authorized by L.R.S. 38:2212(O).

All such addenda shall become a part of the contract documents. Failure of any bidder to receive any such interpretation shall not relieve any bidder from any obligation under his bid as submitted without modification.

The specifications and plans are complementary of each other and all work called for or reasonably implied by either shall be performed as if called for by both. In case of conflict between the requirements of the specifications and plans, the specifications shall take precedence. Figured dimensions shall take precedence over scale dimensions, and larger scale details shall take precedence over smaller scale details in the general work drawings.

All vendors submitting bids shall register as a Jefferson Parish vendor, if not already registered. Registration forms may be downloaded from <a href="Vendor Information">Vendor Information</a> | Jefferson Parish, LA (jeffparish.gov) and click on Vendor Information. Current W-9 forms with respective Tax Identification numbers and vendor applications may be submitted at any time; however, if your company is not registered and/or a current W-9 form is not on file, vendor registration is mandatory. Vendors may experience a delay in payment if your company is not a registered vendor with Jefferson Parish.

Bidders must comply with all provisions of this Notice, the Standard General Conditions of the Construction Contract and any special conditions and specifications contained herein, all of which are made part of this bid proposal. Resolution No. 141125, as amended, will be considered a part of the bid whether attached or not. A copy of these terms and resolutions may be obtained from the Office of the Parish Clerk, Suite 6700, Jefferson Parish General Government Building, 200 Derbigny Street, Gretna, Louisiana 70053. Bidders may also obtain a copy by visiting the Purchasing Department's webpage at Document Library | Jefferson Parish, LA (jeffparish.gov) and clicking on online forms.

Bid Security: Bidders shall provide bid security in the form of an electronic bid bond in the amount of five percent (5%) of the total bid price (Base Bid and any Alternates) (as per R.S. 38:2218). The Bid Security shall remain valid until the contract is executed or until final disposition is made of the bids submitted. Such security will become the property of the Parish in the event the successful bidder fails or refuses to execute the contract or fails to produce performance and payment bonds upon contract signing. Bids shall remain binding for at least forty-five (45) days after the date set for the Bid Opening. In the event the Parish issues the Letter of Award during this period, the bid accepted shall continue to remain binding until the execution of contract. Jefferson Parish and the lowest responsible bidder, by mutual written consent, may agree to extend the deadline for award by one or more extensions of thirty (30) calendar days.

Bidders must submit an electronic bid bond through the respective online clearinghouse bond management system(s) as indicated in the electronic bid solicitation on Central Auction House. No scanned paper copies of any bid bond will be accepted as part of the electronic bid submission.

<u>Performance Bond:</u> A performance bond is required in 100% of the contract amount and is due at the signing of the formal contract, unless another percentage is required in the bid specifications. In the event of a conflict between these instructions and the bid specifications, the bid specifications shall control.

<u>Payment Bond</u>: A payment bond is required in 100% of the contract amount and is due at the signing of the formal contract, unless another percentage is required in the bid specifications. In the event of a conflict between these instructions and the bid specifications, the bid specifications shall control

#### K. INSURANCE REQUIREMENTS

All required insurance under this bid shall conform to Jefferson Parish Resolution No. 141125, as applicable. Contractors may not commence any work under any ensuing contract unless and until all required insurance and associated evidentiary requirements thereto have been met, along with any additional specifications contained in the Invitation to Bid. Except as where otherwise precluded by law, the Parish Attorney or her designee, with the concurrence of the Director of Risk Management or her designee, may agree on a case-by- case basis, to deviate from Jefferson Parish's standard insurance requirements, as provided in this Section. Vendors requesting deviation therefrom shall submit such requests in writing, along with compelling substantiation, to the Purchasing Department prior to the bid's due date. Any changes to the insurance requirements will be reflected in the bid specifications and addenda. Prior to contract execution and at all times thereafter during the term of such contract, contractors must provide and continuously maintain all coverages as required by the foregoing Resolutions, and the contract documents. Failure to do so shall be grounds for suspension, discontinuation or termination of the contract.

Within ten (10) days of bid opening, the apparent low bidder will be required to provide final insurance certificates to the Parish which shall name the Parish of Jefferson, its Districts Departments and Agencies under the direction of the Parish President and the Parish Council as additional insureds regarding negligence by the contractor for the Commercial General Liability and the Comprehensive Automobile Liability policies. Failure to provide your certificate of insurance within the ten (10) days, shall result in the Parish rejecting your bid and moving on to the next lowest bidder. Additionally, said certificates should reflect the name of the Parish Department receiving goods and services and reference the respective Jefferson Parish bid number.

#### JEFFERSON PARISH REQUIRED STANDARD INSURANCE

#### **WORKER'S COMPENSATION INSURANCE**

As required by Worker's Compensation Law of the State of the Contractor's headquarters. Employer's Liability is included, with minimum limits of \$500,000 per occurrence, except it shall be \$1,000,000 per occurrence when Work is to be over water and involves maritime exposures to cover all employees not covered under the State Worker's Compensation Act.

Note: If your company is not required by law to carry workmen's compensation insurance, i.e. sole employee of the company, then bidders must request a workmen's compensation insurance declaration affidavit prior to the bid opening date. This insurance declaration affidavit must be fully completed, signed, properly notarized and submitted within ten (10) days of the bid opening. A scanned copy may be submitted initially; however, the successful bidder must submit the original affidavit in its original format and without material alteration upon contract execution. Failure to comply will result in the bid submission being rejected as non-responsive. The Parish reserves the right to award bid to the next lowest responsive and responsible bidder in this event.

#### 

Shall provide limits not less than the following: \$1,000,000.00 Combined Single Limit Per Occurrence; 2 million General Aggregate for bodily injury and property damage

#### **BUSINESS AUTOMOBILE LIABILITY**

Bodily injury liability \$1,000,000.00 each person; \$1,000,000.00 each occurrence. Property Damage Liability \$1,000,000.00 each occurrence. Liability coverage to be provided for Any Auto or for ALL Owned Autos and Hired and Non-owned Autos

Note: This category may be omitted if bidders do not/will not utilize vehicles for the project AS DETERMINED BY Risk Management and Parish Attorney's Office after properly requesting a deviation as discussed above. Bidder must request a deviation prior to bid opening and may be given an automobile insurance declaration affidavit to execute. This insurance declaration affidavit must be fully completed, signed, properly notarized and submitted within ten (10) days of the bid opening. A scanned copy of the completed, signed and properly notarized affidavit may be submitted initially; however, the successful bidder must submit the original affidavit in its original format and without material alteration upon contract execution. Failure to comply will result in the bid submission being rejected as non-responsive. The Parish reserves the right to award bid to the next lowest responsive and responsible bidder in this event.

<u>DEDUCTIBLES</u> - The Parish Attorney with concurrence of the Director of Risk Management have waived the deductible section of the Terms and Conditions for all Invitations to Bid, until further notice.

<u>UMBRELLA LIABILITY COVERAGE</u> - An umbrella policy or excess may be used to meet minimum requirements. Certificate of Insurance must state which coverage the Umbrella sits over.

#### **FOR CONSTRUCTION AND RENOVATION PROJECTS:**

The following are required if selected below. Such insurance is due upon contract execution.

#### **OWNER'S PROTECTIVE LIABILITY**

To be for the same limits of liability for bodily injury and property damage liability established for commercial general liability.

#### <u>BUILDER'S RISK INSURANCE</u>

The contractor shall maintain Builder's Risk Insurance at his own expense to insure both the owner (Parish of Jefferson) and contractor as their interest may appear.

#### L. INDEMNIFICATION

Bidder acknowledges that bidder recovered the cost of any required insurance in the contract price as required by L.R.S. 9:2780.1(I) and that bidder recovered any such cost for the purposes of insuring an obligation to indemnify Jefferson Parish, defend Jefferson Parish, or hold Jefferson Parish harmless and that bidder's indemnity liability is limited to the amount of the proceeds that are payable under the insurance policy or policies that bidder has obtained.

#### M. FAMILIARITY WITH LAWS AND ORDINANCES

Bidders shall familiarize themselves with and shall comply with all applicable Federal and State Laws, Parish/Municipal Ordinances, Resolutions, and the rules and regulations of all authorities having jurisdiction over construction of the project, which may directly or indirectly affect the work or its prosecution.

These laws and/or ordinances will be deemed to be included in the contract, the same as though herein written in full.

In case of conflict between the requirements of these specifications and any State and/or Federal Regulations or Laws, the State and/or Federal Regulations or Laws shall take precedence in all cases in which State and/or Federal Funding of the contract, in whole or in part, depends upon compliance with said State and/or Federal Regulations or Laws.

#### N. MISCELLANEOUS

The successful bidder may be required to furnish a statement of the origin, composition, and manufacture of materials to be used in construction of the work together with samples, which samples may be subjected to testing to determine their quality and fitness for the work, as specified.

Bidders are not to exclude from participation in, deny the benefits of, or subject to discrimination under any program or activity, any person in the United States on the grounds of race, color, national origin, sex or religion except that any exemption from such prohibition against discrimination on the basis of religion as provided in the Civil Rights Acts of 1964, or Title VI and VII of the Act of April 11, 1968 shall also apply, as amended; nor discriminate on the basis of age under the Age Discrimination Act of 1975, as amended; nor with respect to an otherwise qualified handicapped individual as provided in Section 504 of the Rehabilitation Act of 1973, as amended. This assurance includes compliance with the administrative requirements of the Revenue Sharing final handicapped discrimination provisions contained in Section 51.55 (c), (d), (e), and (k) (5) of the Regulations.

Non-negotiable contract terms include but are not limited to taxes, assignment of contract, audit of records, EEOC and ADA compliance, record retention, content of contract/order of precedence, contract changes, force majeure, governing law, including ethics statements, claims or controversies, and termination based on contingency of appropriation of funds, as applicable.

CYNTHIA LEE SHENG

RENNY SIMNO



#### May 2025

## **Changes to Jefferson Parish Bidding Information**

The Jefferson Parish Purchasing Department would like to make vendors aware of the following changes that are now effective:

## > Additional Requirements for Bid Instructions:

The Additional Requirements for Bid Instructions have been revised. The numbers correlating with the instructions may not be the same number as past bids. **Please read ALL instructions and bid documents carefully and thoroughly prior to bid submission.** 

#### > Affidavits:

There is a new affidavit for all bids named "Generic Bid Affidavit". The Public Works Bid Affidavit and Non-Public Works Bid Affidavit are no longer valid. **The "Generic Bid Affidavit" must be submitted with ALL bid submissions.** 

## > <u>Insurance Requirements</u>:

Within ten (10) days of bid opening, the apparent low bidder will be required to provide <u>FINAL</u> insurance certificates evidencing the insurance coverages of the subject bid (please refer to each individual bid specifications requirements) to Jefferson Parish which shall name "the Parish of Jefferson, its Districts, Departments, and Agencies under the direction of the Parish President and the Parish Council" as additional insured on the Commercial General Liability and the Comprehensive Automobile Liability policies to protect against negligence by the contractor, as provided by contract.

Failure to provide your certificate of insurance within the ten (10) days of bid opening shall result in the Parish rejecting your bid as non-responsive and moving on to the next apparent lowest bidder.

You may still opt to send in your insurance certificates with your bid submission, however, if the provided certificates are not in FINAL form, if you are the apparent low bidder, then you will still be required to send in a FINAL certificate within 10 days of bid opening.

## Generic Bid Affidavit Instructions

This affidavit is supplied as a courtesy to Affiant. It is the responsibility of the affiant to insure the affidavit submitted to Jefferson Parish complies, in both form and content, with federal, state and parish laws. It is the responsibility of the Affiant to submit a new affidavit if any additional campaign contributions are made after the affidavit is executed but prior to the time the council acts on the matter.

#### The Affidavit MUST comply with the following requirements to be accepted.

- Must be signed by an authorized representative of the entity.
- Must be notarized by a notary with proper jurisdiction who must sign and print name, and include bar/notary number.
- Location where the notarization is taking place should be filled in at the top of the affidavit not the location of the contract services.
- MUST select either Choice A or B when required.
- If choice A is selected, it must include an attachment.

#### Affidavits with the following WILL NOT be accepted.

- If both choice A and B are selected, the affidavit will not be accepted.
- An affidavit marked N/A will not be accepted.
- An affidavit missing attachment(s) when required will not be accepted.
- An affidavit that is notarized by a notary who does not have jurisdiction in the place where notarized or is not active will not be accepted.
- Affidavits that are older than six (6) months will not be accepted.

Instruction sheet may be omitted when submitting the affidavit.

#### Generic Bid

### **AFFIDAVIT**

STATE OF				
PARISH/COUNTY OF				
BEFORE ME, the ur	ndersigned authority,	personally car	ne and appeared:	
	(Affiant) who af	ter being duly	sworn by me, deposed and	
said that he/she is the fully a	uthorized		of	
	(Entity), who su	bmitted a bid	to the Parish of Jefferson.	
Affiant further said:				
Campaign Contribution Dis (Choose A or B, if option A		include the r	equired attachment):	
Choice A	date and amount of elected officials of a officers, directors a more of the Entity of the date of this affice. Owners have not mor former members	the Parish of J nd owners, inc during the two- davit. Further, ade any contri of the Jefferso ough or in the	paign contributions, including the tion, made to current or former efferson by Entity, Affiant, and/or cluding employees, owning 25% or year period immediately preceding Entity, Affiant, and/or Entity butions to or in support of current on Parish Council or the Jefferson name of another person or legal.	r ng
Choice B	There are <b>NO</b> camp disclosure under Ch		ions made which would require section.	
Affiant further said:				
Debt Disclosures (Choose A or B, if option A	A is indicated please	include the r	equired attachment):	
Choice A	elected or appointed	d official of the	ots owed by the affiant to any e Parish of Jefferson, and any and appointed official of the Parish of	
Choice B	There are <b>NO</b> debts of this section.	which would	require disclosure under Choice A	L

#### Affiant further said:

That Affiant has employed no person, corporation, firm, association, or other organization, either directly or indirectly, to secure the public contract under which he received payment, other than persons regularly employed by the Affiant whose services in connection with the construction, alteration or demolition of the public building or project or in securing the public contract were in the regular course of their duties for Affiant; and

That no part of the contract price received by Affiant was paid or will be paid to any person, corporation, firm, association, or other organization for soliciting the contract, other than the payment of their normal compensation to persons regularly employed by the Affiant whose services in connection with the construction, alteration or demolition of the public building or project were in the regular course of their duties for Affiant.

#### Affiant further said:

Affiant personally has not been convicted of, nor has he/she entered into a plea of guilty or nolo contendere to any of the crimes or equivalent federal crimes listed below. No individual partner, incorporator, director, manager, officer, organizer, or member, who has a minimum of a ten percent ownership in the Bidding Entity, has been convicted of or has entered a plea of guilty or nolo contendere to any of the crimes or equivalent federal crimes listed below. A conviction of or plea of guilty or nolo contendere to the following state crimes or equivalent federal crimes shall permanently bar any person or the bidding entity from bidding on public projects:

- (a) Public bribery (R.S. 14:118)
- (b) Corrupt influencing (R.S. 14:120)
- (c) Extortion (R.S. 14:66)
- (d) Money laundering (R.S. 14:230)

A conviction of or plea of guilty or nolo contendere to the following state crimes or equivalent federal crimes shall bar any person or the bidding entity from bidding on public projects for a period of five years from the date of conviction or from the date of the entrance of the plea of guilty or nolo contendere:

- (a) Theft (R.S. 14:67)
- (b) Identity Theft (R.S. 14:67.16)
- (c) False accounting (R.S. 14:70)
- (d) Issuing worthless checks (R.S. 14:71)
- (e) Bank fraud (R.S. 14:71.1)
- (f) Forgery (R.S. 14:72)
- (g) Contractors; misapplication of payments prohibited (R.S. 14:202)
- (h) Malfeasance in office (R.S. 14:134)

The five-year prohibition provided for in this section shall apply only if the crime was committed during the solicitation or execution of a contract or bid awarded pursuant to these provisions. If evidence is submitted substantiating that a false attestation has been made and the project must be readvertised or the contract canceled, the awarded entity

making the false attestation shall be responsible to the public entity for the costs of rebidding, additional costs due to increased costs of bids and any and all delay costs due to the rebid or cancellation of this project.

#### Affiant further said:

- (1) Entity is registered and participates in a status verification system to verify that all employees in the State of Louisiana are legal citizens of the United States or are legal aliens.
- (2) Entity shall continue, during the term of the contract, to utilize a status verification system to verify the legal status of all new employees in the State of Louisiana.
- fidavit

(3) Entity shall require all subcorverifying compliance with state	ntractors to submit to the Entity a sworn afferments (1) and (2) above.
	Signature of Affiant
	Printed Name of Affiant
SWORN AND SUBSCRIBED TO BEFORM NOTARY PUBLIC ON THEOF, 20	DAY
Notary Public	
Printed Name of Notary	
Notary/Bar Roll Number	
My commission expires	•

## **Evidence of Authority Instructions**

Only an authorized Agent shall sign this proposal. Each Proposer is required to provide satisfactory evidence of the authority of the person signing for the agency, corporation, partnership or other legal entity, which shall be attached to the proposal.

The following page is a sample Corporate Resolution. This sample is supplied as a courtesy to Proposers, but it is the responsibility of the Proposer to ensure the evidence of authority they submit to Jefferson Parish complies, in both form and content, with federal, state and Parish laws. Additionally. sample Sole **Proprietorship** a Certification found be may https://www.jeffparish.gov/466/Document-Library.

Instruction sheet may be omitted when submitting.

## **CORPORATE RESOLUTION**

_	Date
	Sociotal y-11 casuloi
_	Secretary-Treasurer
c m c	hereby certify the foregoing to be a true and correct opy of an excerpt of the minutes of the above dated neeting of the Board of Directors of said orporation, and the same has not been revoked or escinded.
Resolved that constituted and designated as agent and authority to act on behalf of this contransactions with the Parish of Jefferson including but not limited to, the executive sureties, contracts and acts and to receive provisions of any such bid or contract, the executive sureties in the provisions of any such bid or contract, the executive sureties is the provisions of any such bid or contract, the executive sureties is the provisions of any such bid or contract, the executive such as the provision of the provision in the p	
At the meeting of Directors of	
Incorporated.	
Excerpt from minutes of meeting of the	Board of Directors of



# Designation of Construction Contractor as Agent of a Governmental Entity Sales Tax Exemption Certificate

		, an agency of the officed
Legal Name of Governmental Entity	of the Otata of I	
States government, or an agency, board, commission, or instrumentality	of the State of L	ouisiana or its political subdivisions, including
parishes, municipalities and school boards, does hereby designate the fo	ollowing contracto	or as its agent for the purpose of making sales
tax exempt purchases on behalf of the governmental body:		
Name of Contractor		
Address		
City	State	ZIP
This designation of agency shall be effective for purchases of component of tangible personal property for the following named construction projec		erials, taxable services and leases and rentals
Construction Project		Contract Number
This designation and acceptance of agency is effective for the period		
Beginning Date (mm/dd/yyyy) End	Date (mm/dd/yyyy)	
Purchases for the named project during this period by the designated con	tractor shall be co	onsidered as the legal equivalent of purchases

directly by the governmental body. Any materials purchased by this agent shall immediately, upon the vendor's delivery to the agent, become the property of this government entity. This government entity, as principal, assumes direct liability to the vendor for the payment of any property, services, leases, or rentals made by this designated agent. This agreement does not void or supersede the obligations of any party created under any construction contract related to this project, including specifically any contractual obligation of the construction contractor to submit payment to the vendors of materials or services for the project.

This contractor-agent is not authorized to delegate this purchasing agency to others; separate designations of agency by this governmental entity are required for each contractor or sub-contractor who is to purchase on behalf of this governmental entity. The undersigned hereby certify that this designation is the entirety of the agency designation agreement between them. In order for a purchase for an eligible governmental entity through a designated agent to be eligible for sales tax exemption, the designation of agency must be made, accepted, and disclosed to the vendor before or at the time of the purchase transaction.

Designation of Agency			Acceptance of Agency			
Signature of Authorized Designator		Date (mm/dd/yyyy)	Signature of Contractor or Subcontractor Authorized	Acceptor	Date (mm/dd/yyyy)	
Name of Authorized Designator			Name of Contractor's or Subcontractor's Acceptor			
Name of Governmental Entity		Name of Contractor				
Address		Address				
City	State	ZIP	City	State	ZIP	

This designation of agency form, when properly executed by both the contractor and the governmental entity, shall serve as evidence of the sales tax exempt status that has been conferred onto the contractor. No other exemption certificate form is necessary to claim exemption from sales taxes. The agency agreement evidenced by this sales tax exemption certificate must be implemented at the time of contract execution with the governmental entity. The contract between the governmental entity and his agent must contain provisions to authenticate the conferment of agency.

#### **SPECIFICATIONS FOR**

EMERGENCY POINT REPAIR, LINING, EMERGENCY SEWER RECONSTRUCTION, AND CLEANING OF EXISTING SANITARY SEWERS, INCLUDING SERVICE LATERALS AND MANHOLES AT SCATTERED LOCATIONS IN JEFFERSON PARISH

#### AND

## EMERGENCY LIFT STATION REPAIR/RESTORATION OF EXISTING LIFT STATION DAMAGES

## DAMAGED AS A RESULT OF A NATURAL DISASTER OR OTHER STATE OF EMERGENCY FOR THE JEFFERSON PARISH DEPARTMENT OF SEWERAGE

#### 1.0 GENERAL CONDITIONS:

#### 1.1 SCOPE OF WORK:

These specifications are for Emergency replacement, repair, cleaning, and lining of existing sewer lines; and, Emergency lift station repair including but not limited to pumps, motors, air compressors, control panels, and other work incidental thereto to assist the Department of Sewerage work crews only during Natural Disasters or Other State of Emergencies. No work is guaranteed under this contract and actual quantities used may fall below or exceed the estimated quantities listed on the bid form. All work covered under this contract must conform to Jefferson Parish Engineering Department standard detail sheets, available in the Jefferson Parish Engineering Department.

The Contractor is made aware that, because of the nature of this contract, it will be necessary to make repairs on an Emergency 24 hour, seven (7) days a week, nights, week-ends, and holiday basis. There will be no extra compensation for repairs during these events. The Contractor must have two (2) contact employees; one primary and one back-up, on a 24 hour basis available to coordinate work initiation.

The contract will be awarded to the lowest responsible bidder complying with all provisions of this invitation, providing the bid is reasonable and that it is in the best interest of Jefferson Parish to accept. The Parish of Jefferson reserves the right to accept or reject the bid in whole or part.

Purchases for this project shall be exempt from state sales and use tax according to La. R.S. 47:301(8)(c)(i). The successful bidder shall be granted the tax-exempt status of Jefferson Parish via Form R-1020, Designation of Construction

Contractor as Agent of a Governmental Entity Sales Tax Exemption Certificate. Form R-1020 is distributed by the Louisiana Department of Revenue.

The Department of Sewerage's Director shall assign a person and/or persons to be the Project Manager.

The Contractor's State License shall be in the category of **Municipal and Public Works Construction.** 

#### **1.2 BONDS:**

Contractor will be required to furnish a 5% surety with bid submission. This shall be 5% of the total of the bid submission.

Contractor will furnish a performance bond in an amount of 50% of the contract price, for any and all Notices to Proceed, within 24 hours of the Contractor's receipt of the Notice to Proceed. In addition, contractor will furnish a labor, material, and payment bond in an amount of 50% of the contract price, for any and all Notices to Proceed, within 24 hours of the Contractor's receipt of the Notice to Proceed. If, due to emergency conditions, the Contractor cannot obtain and furnish the bonds within 24 hours, the Contractor shall provide written justification for the delay and obtain the bonds as soon as possible. In no case will any payment be issued for work performed by the Contractor until both bonds have been furnished. The cost of the bond premiums will be the responsibility of the Contractor.

#### 1.3 FAMILIARIZATION WITH THE WORK:

The contractor may contact the Department of Sewerage Lift Station Section for documents that will provide the pumping capacities, hierarchy of both the East and West Bank Sewerage Systems, the generator requirements of each lift station, the availability of emergency pump out connections and a proposed emergency situation plan. While the information contained in this document is not warranted to be exact, it is imperative that the prospective bidders familiarize themselves with this document in order to fully understand and price his bid.

Before submitting bid, each prospective bidder shall familiarize themselves with the work, local labor conditions and all laws, regulations, Jefferson Parish Engineering Department standard detail sheets, and other factors affecting performance of the work. Contractor shall carefully correlate his observations with the requirements of the contract documents and otherwise satisfy themselves of the expense and difficulties for performance of the work. The submission of a bid will constitute a

representation of compliance by the bidder. There will be no subsequent financial adjustment for lack of such familiarization.

#### 1.4 CONTRACT TIME:

The contract time is for two (2) years. Should Jefferson Parish have not entered into a new contract for the same Scope of Work as this contract prior to May 1<sup>st</sup> of the year in which the contract is set to expire, then the contract shall be automatically extended until the end of the calendar year of the same year the contract is set to expire.

#### 1.5 SUB-CONTRACTORS:

All bidders wishing to use the services of sub-contractors must submit a complete list of all sub- contractors with their bid. If no subcontractors will be used, a statement to that effect must be submitted with the bid.

#### 1.6 WORK SCHEDULING:

Contractor must be prepared to begin construction within two (2) days after a Natural Disaster or Other State of Emergency. Because of the nature of this contract, it may be necessary for the contractor to respond to emergencies (set up personnel, equipment, contacts, etc.) immediately upon notification, within twenty-four (24) hours of call out. In the event of a hurricane/tropical storm, it is the responsibility of the contractor to contact appropriate Parish personnel at the Emergency Operations Center (EOC), either by phone at (504) 349-5360, or in person at 910 3<sup>rd</sup> Street, Gretna, Louisiana, within 24 hours of landfall to determine if services will be required. In the event of a sudden natural disaster or other State of Emergency, appropriate Parish personnel will contact the contractor if services are required.

Failure of the Contractor to meet the above time constraints may result in the following:

- a. Have the work performed by others and back charged to the Contractor
- b. Contract termination

The failure of Jefferson Parish to assert a breach for the failure of the Contractor to perform at anytime shall not be construed to be a waiver of Jefferson Parish's rights hereunder. Each work order or request by the Director, Assistant Director, or Project Manager will designate a job number. All correspondence, billing, etc. pertaining to the work shall reference this job number designation. If the Contractor does not diligently proceed with the work, then the issuance of additional work will

be withheld. All locations of work shall have a GPS assigned by the contractor and submitted with invoices

#### 1.7 JEFFERSON PARISH GENERAL SPECIFICATIONS:

The general specifications for these contract documents are set forth in Jefferson Parish Council Resolution No. 141125. The resolution is not reproduced herein. However, bidders shall be presumed to have full knowledge of these general conditions. Copies are, at all times, available with the Clerk of Jefferson Parish Council, General Government Building, 200 Derbigny Street, Suite 6600, (504) 364-2626.

#### 1.8 LIQUIDATED DAMAGES:

Because of the nature of this emergency basis contract, liquidated damages will not be assessed. If the Contractor should fail to complete issued work orders in a timely manner and to the satisfaction of the Parish, the issuance of additional work orders will be withheld, and may result in contract termination.

#### 1.09 RETAINAGE:

There will be no retainage with held on this contract.

#### 1.10 EMERGENCY PERSONNEL REQUIREMENTS:

The work demands of this contract will require the Contractor to be able to respond to emergencies within one hour of notification. The Contractor is responsible for insuring that all personnel are self-sufficient, that is, provides for all equipment, materials, and services necessary to sustain its employees at all times. This includes, but is not limited to, the provision of adequate housing, food, transportation, sanitary facilities, and fuel.

#### 1.11 SCHEDULING WORK:

Work under this contract will be released by Work Orders or under the direction of the Director, Assistant Director, or the Project Manager. Work Orders will include available maps and instructions for the exact work to de done, provided the computer systems (work order programs) are up and running. The maps will reflect the approximate location and existing conditions of utilities, if available.

The Contractor performing work under this contract shall be required to coordinate his operations with the designated Project Manager. If possible, the Contractor shall notify residents by (fliers, door hangers, etc.) a minimum of 24 hours prior to commencing work on any work issued work by the Parish. Additional notification periods for various items of work can be found in the specifications.

Once work has begun at a specific location, the Contractor must diligently pursue the work to be done until the work is completed. The Parish reserves the right to order the Contractor to dispatch additional men and equipment to the job site if, in the opinion of the Project Manager, work is not proceeding in an orderly manner. The Parish may order the Contractor to employ additional crews in order to complete the work.

The Director and/or Project Manager has the right to require the Contractor to remove incompetent employees from the jobsite.

Some manholes may have been paved over or otherwise covered up, may exist, may not be correctly shown in the Parish plans, or may be shown as a clean-out, or vice versa. The Contractor shall make a reasonable, good faith effort to locate the manholes. The uncovering and raising of manholes may be performed by the Parish or the Parish's designated Contractor. The Contractor shall complete an "Unable to Complete Assignment" form and turn it in to the inspector.

#### 1.12 WORK BY OTHERS:

The Contractor performing work under this contract shall be required to coordinate his operations with all Parish Public Works Departments, as may be required. The Parish is not restricted from utilizing its own personnel and equipment; the personnel or equipment of other governmental entities; or, of any other entities or contractors, when the services performed by those entities can be performed with greater speed or less cost to the Parish.

The parties are entering into a non-exclusive contract and the Parish retains the right to obtain similar services from additional providers, if necessary. The parties intend the Parish to procure other services from contractors when to do so would result in services being obtained in a more prompt and economic manner, due to the emergency nature of the work.

#### 1.13 NOTIFICATION OF RESIDENTS:

The following steps for notification of the citizenry and involvement of local officials shall be required. If possible, twenty-four to forty-eight hours prior to starting work, a hand-bill, announcing and describing the work will be distributed to each household or commercial establishment located in the area. Close communications between the Contractor, Parish and local officials, the Sheriff's Office, and Fire Department shall be maintained to ensure that no major problems arise.

Any fire stations located in the area of testing should also be notified daily by the Contractor, prior to smoke testing. The scheduled work for the day and the general area of testing should be indicated 24-hours in advance. Hospitals, nursing homes, and schools must be notified, by the Contractor, the day of testing no less than one (1) hour prior to the actual test.

# TECHNICAL SPECIFICATIONS SECTION 1 SCOPE OF WORK

#### 1.01 GENERAL:

The work to be performed on this contract shall consist of replacement or restoration of existing sewer mains (gravity or force) by Point Repair; the restoration of roadways, driveways, sidewalks, and ground cover (sod) associated with the work; cleaning, television inspection, root removal, and dye-water flooding; smoke testing of gravity sanitary sewer; cleaning and physical inspection, rehab of mainline and laterals; rehabilitation of sewer manholes and wet-wells; and reconstruction of sanitary sewers by installing a cured-in-place (CIPP) using one of two approved processes, Insituform or National Liner, or approved alternate; AND, emergency lift station repair, electrical and mechanical including pumps, motors, air compressors, control panels, and all miscellaneous components required to complete emergency repairs as a result of damage by an event or natural disaster designated as a State of Emergency.

Contractor shall provide the locations of each portable pump and/or vacuum trucks, and all repairs with GPS used for the project, describe what the pumps were used for, describe how and where the pumped fluid was dispose of, and what type of fuel each pump used. Contractor shall provide the locations with GPS or all lift stations the pumped fluid was removed from and location of where the fluid was delivered. Contractor shall provide pump run times for all pumps used to remove sewer as per FEMA's requirements.

# TECHNICAL SPECIFICATIONS SECTION 2 MEASUREMENT AND PAYMENT

2.01 GENERAL:

Payment for the various items of the Bid Schedule shall include all compensation to be received by the Contractor for furnishing all tools, equipment, supplies, and manufactured articles, and for all labor, operations, and incidentals related to the items of work being described. No separate payment will be made for any item that is not specifically set forth in the Bid Schedule and all costs therefore shall be included in the prices named in the Bid Schedule for the various items of work.

#### 2.02 ESTIMATED QUANTITIES:

This is a unit price emergency contract and the quantities shown on the "Bid Form" are for comparison of bids only. Items of work performed under this contract will be on an as needed basis and actual quantities installed may vary significantly from the quantities stated in the Bid Form (Quantities shown may be increased, decreased, or not used at all.)

#### 2.03 PHYSICAL INSPECTION OF MANHOLES, CATCH BASIN & WET WELLS:

- A. Measurement: Measurement for payment of physical inspection of manholes, catch basins, and wet wells will be per each structure inspected.
- B. Payment: Payment for this item will be made at the contract unit bid price per each and shall constitute full compensation for all labor, materials, and equipment required to complete this item as specified in Section 3.

#### 2.04 SMOKE TESTING:

- A. Measurement: Measurement for payment of smoke testing shall be made per linear foot, with measurement being made between centerlines of consecutive manholes for the line segment tested.
- B. Payment: Payment for smoke testing will be made at the unit bid price per linear foot of pipe tested, in accordance with these specifications and shall constitute full compensation for supplying all necessary labor, materials, equipment, and incidentals.

#### 2.05 DYE-WATER FLOODING:

A. Measurement: Measurement for payment of dye-water flooding will be made per hour required to complete the task specified for each individual work order. A two-hour minimum will be allowed for each work order.

B. Payment: Payment for dye-water flooding will be made at the unit bid price per hour and shall constitute complete compensation for all labor, materials, and equipment required to complete this testing, as specified herein.

#### 2.06 CLEANING SANITARY SEWER LINES:

- A. Measurement: Measurement for payment of cleaning sanitary sewer pipe and associated manholes shall be per linear foot, with measurement being made between centerlines of consecutive manholes for the line segments and manholes cleaned.
- B. Payment: Payment for cleaning sanitary sewer lines and associated manholes shall be made at the unit bid price per linear foot for various pipe sizes and debris level, without regard to pipe type. Payment shall constitute full compensation for all labor, materials, and equipment necessary to complete this item of work, as specified herein and shall include all costs associated with debris removal and disposal.

#### 2.07 CLEANING WET WELLS:

- A. Measurement: Measurement for payment of cleaning wet wells will be per gallon required to complete the task specified for each individual work order. This task is for cleaning the wet wells of all sewage and debris in the wet well. This method will only be used in cases where no other method of emergency sewer service is available.
  - B. Payment: Payment for cleaning wet wells shall be made at the unit bid price per gallon and shall constitute complete compensation for all labor, materials, and equipment necessary to complete this item of work as specified herein, including the disposal of the sewage and debris removed plus GPS locations.

#### 2.08 SEWAGE REMOVAL FROM SEWERAGE SYSTEM:

- A. Measurement: Measurement for payment of sewage removal from sewerage system, including wet wells, will be per gallon required to complete the task, by vacuum truck or large pumping truck, as specified in the work order, or as directed by the Director, Assistant Director, or Project Manager.
- B. Payment: Payment for removal of sewage from the sewerage system, mainlines, manholes, and wet wells, shall be made at the unit bid price per gallon and shall constitute complete compensation for all labor, materials, and equipment necessary to complete the item of work, as specified herein, including the disposal of the sewage and debris removed plus GPS location of work.

#### 2.09 RADIAL VIEW COLOR CAMERA EVALUATION VIDEO:

- A. Measurement: Measurement for payment of radial view color camera evaluation video will be made per linear foot, with measurement being made between centerlines of consecutive structures for the line segments televised. The use of a radial view color camera will be specifically directed by the Project Manager.
- B. Payment: Payment for radial view color camera evaluation video will be made at the unit bid price per linear foot and shall constitute full compensation for all labor, materials, and equipment necessary to complete the item specified.

#### 2.10 TELEVISION INSPECTION WITH DYE-FLOODING OR EXFILTRATION:

- A. Measurement: Measurement for payment of television inspection with either dye-flooding or exfiltration testing shall be per linear foot, with measurement being made between centerlines of consecutive manholes for the line segments televised.
- B. Payment: Payment for television inspections with either dye-flooding or exfiltration testing shall be made at the unit bid price per linear foot for the various sizes of sanitary sewer lines televised. It shall include complete compensation for all labor, materials, and equipment necessary to complete this item of work, as specified herein.

#### 2.11 REMOTE ILLUMINATION OF 15 INCH THRU 24 INCH PIPE:

- A. Measurement: Measurement for payment of remote illumination pipe inspection will be made per each pipe section inspected. This item will typically be performed on pipe sections of less than fifty (50) feet in length.
- B. Payment: Payment for remote illumination pipe inspection will be made at the unit bid price for each pipe section inspected.

#### 2.12 ADDITIONAL SET UP FOR TELEVISION INSPECTION:

A. Measurement: Measurement for this item will be made per each additional setup required, due to an obstruction in the line being televised. Initial setup

for inspection required for normal operation will not be measured separately nor included in this item

B. Payment: Payment will be made at the unit bid price per each additional setup required. Separate payment will be made for the actual linear footage of line televised due to a "reverse Setup".

#### 2.13 INSTALLATION OF CURED IN PLACE PIPE (CIPP) FOR MAIN LINES:

- A. Measurement: Measurement for payment of installation of CIPP will be made per linear foot, as measured between centerlines of consecutive structures for the line segment replaced.
- B. Payment: Payment for CIPP insertion will be made at the unit bid price per linear foot for the sizes and thickness of CIPP installed, in accordance with these specifications. Payment for installation of CIPP shall be for pre-inversion cleaning, pre and post inversion television inspection, wet out of liner, curing of liner, cutting ends, sealing CIPP in manholes, testing and cleanup, and in accordance with the bid unit prices for the various pipe sizes. Additional compensation will be made for initial cleaning and pipe inspection, in accordance with the bid unit prices for these items.

Item No. 20 will be used for 8 inch vitrified clay pipe only. Item No. 21 will be used for all other types of 8 inch pipe.

There will be no direct payment for sewer bypass up to, and including the first 4 inch pump. If more than one 4 inch pump or a larger pump is required to adequately handle the flow, the Contractor will be paid at the bid unit prices for each size pump setup and at the appropriate hourly operating rate as approved by the Project Manager.

There will be no direct payment for pre-television inspection of sewer mainline prior to lining. Cost shall be incidental to work.

#### 2.14 ADDITIONAL THICKNESS FOR CURED IN PLACE PIPE (CIPP):

A. Measurement: Measurement for payment of installation of additional thickness of CIPP will be made per linear foot, as measured between

centerlines of consecutive structures for the line segment lined with additional thickness.

B. Payment: Payment for additional thickness of CIPP will be made at the unit bid price per linear foot for the sizes and additional thicknesses of CIPP installed, in accordance with these specifications. Payment for pre-inversion cleaning, pre and post inversion television inspection, wet out of liner, insertion of liner, curing manholes or wet-well, testing, cleanup, and bypass pumping, will be paid for under separate bid items. Payment for this item will only be made if the additional thickness is approved by the Project Manager, prior to insertion.

#### 2.15 CURED IN PLACE PIPE (CIPP) RE-CONSTRUCTION OF SERVICE LATERALS:

- A. Measurement: Measurement for payment of CIPP Re-construction of service laterals will be on a per each basis for each performed, up to 35 feet in length and on a linear foot basis for lengths which exceed the initial 35 feet, with the exception of a "short segment" reconstruction from mainline, which will be defined as the installation of a "top hat" seal, and lateral lining up to 5 feet in length. The "short segment" re-construction will include a standard cut of the lateral at the mainline.
- B. Payment: Payment for CIPP Re-construction will be made at the unit bid price, either on a per each basis for the range specified, or a linear foot basis for lengths in excess for the range specified, for CIPP installed in accordance with these specifications. Payment for CIPP Re-construction will be for pre-inversion cleaning, pre-inversion inspection, wet out of CIPP, insertion of CIPP, curing of CIPP, cutting ends, sealing CIPP in cleanouts and mainline, testing, and cleanup; and, in accordance with the unit bid prices for the various pipe lengths. Additional payment for "Setup for Lateral Re-construction from Mainline by CIPP" will be made for each "Setup" of equipment. The actual number of laterals reconstructed from this "Setup" may vary from 1 to 20.

## 2.16 SEWER FORCE MAIN REHABILITATION BY REINFORCED CURED-IN-PLACE PIPE (CIPP):

A. Measurement: Measurement for payment of installation of Sewer Force Main Rehabilitation by Reinforced CIPP will be made per linear foot, as measured between centerlines of consecutive structures or access points for the line segment repaired. End seals will be on a per each basis.

B. Payment: Payment for Sewer Force Main Rehabilitation by Reinforced CIPP insertion will be at the unit bid price per linear foot for the sizes and thickness of the RCPP installed, in accordance with these specifications. Payment will include the pre-inversion cleaning, pre and post inversion video inspection, wet-out, insertion, curing and end cut of the RCPP; testing, cleanup, and all required end seals. Initial cleaning will be compensated in accordance with the unit bid price for the closest diameter sewer cleaning pay items.

#### 2.17 SERVICE RECONSTRUCTION/REPLACEMENT STACK BY EXCAVATION:

A. Measurement: The unit bid price for Service Reconstruction/Replacement by excavation will be measured per each. Reconnection by excavation method will include the stack and up to eight (8) feet of service line, as necessary. Measurement will also be based on the various depths in increments of zero (0) up to six feet (6'), over 6 feet (6') to ten feet (10'), and over ten feet (10') deep, for all types and sizes of sewers, as shown.

Depth of Bury is to measure from Natural Ground Level to the Flow Line of the Sanitary Sewer Main at the Point of Reconnection. The minimum trench width shall be three feet (3') – zero inches (0").

One or more connections discharging into a common point will be considered as one house/building service connection. The Contractor will not be allowed to increase the number of service reconnections. This item also includes, as incidental to the work, field locating all live service connections from the ground in portions of the sanitary sewer that cannot be negotiated with the TV camera or where the camera was submerged.

B. Payment: Payment for service reconnection excavation shall be made at the contract unit bid price per each, based on various depth increments. Payment shall be full compensation for locating service connections, material, sheeting and bracing, dewatering, labor, equipment, and incidentals necessary to provide a complete service reconnection.

#### 2.18 SERVICE LINE REPAIR:

A. Measurement: Measurement for the work items listed below will be per each work item completed, or on a linear foot basis for lengths which exceed those indicated. The measured quantity shall include, but not be limited to, sheeting and shoring, repair of service line, removal and replacement of drainage features, and any other incidentals necessary to complete the various work items. Pavement replacement will be paid under separate pay items.

- 42. Repair/adjust cleanout Per Each
- 43. Installation of Sewer Cleanout Type 1 Per Each
- 44. Replace Section of Service Line Per Each
- 45-56. Restore 6"–24" Main by Point Repair, Per Each and Beyond– Per Linear Foot
- 59-68. Restore 4" 24" Sewer Force Main by Point Repair Per Linear Foot
- B. Payment: Payment for service line repair will be made by the unit bid price per each repair made for all sizes of service lines, for all depths. The minimum length of service line point repair shall be eight (8') feet. The minimum trench width shall be 3'-0". No separate pay will be made if the work is done within the limits of service line reconnection.

Payment for main line point repair shall be made by the unit bid price per each repair for varying depths. Depth of repair is determined by averaging the invert elevation of the sewer line at the upstream and downstream manholes of the repair. The pay length of each repair shall be eight (8') feet. Beyond Point Repair will be paid per linear feet for each repair which exceeds eight (8') feet in length.

All pipe fittings, adapters, concrete collar, bedding, and removal and replacement of grass sodding required shall be considered incidental to service line repair.

If no pay item is included for any work required to properly complete a service line repair as specified, the cost to perform said work, including any required removal and replacement of materials, shall be considered incidental to the service line repair.

Payment will be made under:

- 42. Repair/Adjust Cleanout Per Each
- 43. Installation of Sewer Cleanout Type 1 Per Each
- 44. Replace Section of Service Line Per Each

- 45-56. Restore 6" 24" Main by Point Repair Per Each, and Beyond Per Linear Foot
- 59-68. Restore 4" 24" Sewer Force Main by Point Repair Per Linear Foot

### 2.19 RE-POINT EXISTING SEWER MANHOLES OR WET WELL:

- A. Measurement: The measurement for Re-pointing Existing Sewer Manholes or Wet Wells will be by the square foot manhole surface re-pointed.
- B. Payment: The actual quantity of manhole grouted, as measured above, will be paid for the unit bid price. This price and payment will constitute full compensation for furnishing all labor, equipment, material, and incidentals necessary to complete this item of work.

### 2.20 SEWER MANHOLE/WET WELL REHABILITATION BY CEMENTITIOUS LINING:

- A. Measurement: Measurement for rehabilitation of sewer manholes or wet-wells by cementitious lining will be by the square foot.
- B. Payment: Payment will be made per square foot of the manhole or wet-well from the bench (manholes) or invert (wet-wells) to the bottom of the manhole cover. Payment will include all materials, labor, grout, equipment, and related work items to rehabilitate the manhole or wet-well. Locating, uncovering, and cleaning the manholes, photographic documentation, preparation of forms and benches, and patching or plugging leaking joints and voids will be considered incidental to manhole or wet-well wall rehabilitation. Photographic documentation must be submitted prior to payment. No separate payment will be made for re-pointing of manholes or wet-wells, which are then lined under this item.

### 2.21 MANHOLE REHABILITATION:

A. Measurement: Measurement for rehabilitation of sewer manholes or wet-wells by cementitious lining will be by the square foot.

Other items associated with manhole rehabilitation:

- 75 Manhole Cover Adjustments (Street or Easement) Per Each
- 76 Rehabilitate Manhole Bench/Trough Per Each

- 77 Remove and Replace Manhole Cone Per Each
- 78 Remove and Replace Manhole Wall Per Vertical Foot
- 79 Repair Manhole/Line Connection Per Each
- 80 Replace manhole cover and casting Per Each

### B. Payment:

- 1. Manhole Cover Adjustments: Elevation adjustment to the top of the existing manholes will be paid per each manhole cover raised/lowered. This item will include labor, material, etc. required to locate, excavate, and adjust the manhole and/or reset the frame to the desired level, utilizing riser rings and/or grout.
- 2. Rehabilitate Manhole Bench/Trough: Separate payment will be made for manhole benches in manholes that will be rehabilitated. Benches to be constructed in manholes that will not be rehabilitated, as directed by the Project Manager, shall be done so in accordance with these specifications. Payment will be made at the contract unit price per each, which will include all materials, labor, incidentals, and equipment needed to construct manhole benches.
- 3. Removal and Replacement of Manhole Cones will be paid for at the unit bid price per each, which will include grouting/sealing and any other materials, labor, equipment, and incidentals necessary to complete this item.
- 4. Removal and Replacement of Manhole Walls will be paid for at the unit bid price per vertical foot, which will include grouting/sealing and any other material, labor, equipment, and incidentals necessary to complete this item.
- 5. Repair Manhole/Line Connections will be paid for at the unit bid price per each, which will include testing and sealing with grout, and any other material, labor, equipment, and incidentals necessary to complete this item.

### 2.22 RE-OPENING SERVICE CONNECTIONS:

A. Measurement: Measurement for payment of reopening the existing service

- connections from the interior of the pipe will be per each internal service re-connection of the type indicated.
- B. Payment: Payment will be made at the unit bid price per each for remote cutting with brush to re-open service connections and will constitute complete compensation for all labor, equipment, and materials required to satisfactorily complete this item of work, as specified herein.

### 2.23 INTERNALLY TRIM PROTRUDING HOUSE CONNECTIONS:

- A. Measurement: Measurement for internally trimming protruding house connections shall be per each connection trimmed. This item shall include all costs associated with set-up and trimming of the connections. This work will only be done with prior approval of the Project Manager
- B. Payment: Payment will be made for each connection trimmed at the unit bid price.

### 2.24 SET-UP AND OPERATION OF BY-PASS PUMPS:

- A. Measurement: Separate measurement will be made for set-up and operation of by-pass pumps. These items are in addition to the minimum by-pass pumping requirements of other bid items and will only be allowed with prior approval of the Project Manager. This item will be used for emergency pumping of upstream sewer areas to down stream manholes or wet wells. Each set-up will be measured separately with operation of the pumps being measured on the actual hourly time used. Each "Set-Up" pay item shall include all costs associated with providing of the pumping equipment and up to 350 feet of discharge force main. If additional force main is required to reach the designated discharge point, this additional force main will be measured by the linear foot and be paid for at the appropriate "Extension of Force Main" pay item for the pump size.
- B. Payment: Payment for set-up of the by-pass pumps will be at the unit bid price per each for each size required. The item will be used for pumping beyond the minimum requirements of other bid items and for emergency pumping from upstream sewer areas to down stream manholes or wet wells. Payment for operation of each size pump shall be at the hourly unit bid prices. Payment for extension of force main shall be per linear foot, as measured above.

### 2.25 REMOVE AND REPLACE PORTLAND CEMENT CONCRETE:

A. Measurement: The measurement for Removal and Replacement of Portland Cement

Concrete Roadway will be by the square yard.

B. Payment: The actual quantity of applicable roadway removed and replaced will be paid for at the unit bid price. This price and payment will constitute full compensation for furnishing all labor, equipment, materials, wire mesh, if required, replacement of signing, striping, and any other incidentals necessary to complete the work.

## 2.26 REMOVE AND REPLACE ASPHALTIC CONCRETE ROADWAY & PLACE AND REMOVE TEMPORARY ASPHALTIC CONCRETE ROADWAY:

- A. Measurement: The measurement for Removal and Replacement of Asphaltic Concrete Roadway; and the Placement and Removal of Temporary Asphaltic Concrete Roadway will be by the square yard.
- B. Payment: The actual quantity of asphaltic roadway removed and replaced within the authorized pay limit, as shown on the drawings and indicated in the specifications, will be paid for at the unit bid price. This price and payment will constitute full compensation for furnishing all labor, equipment, materials, and incidentals necessary to complete the work. Should the thickness of the existing asphalt pavement exceed the six-inch (6") asphalt concrete minimum thickness required by the standard detail, the Contractor shall match the existing pavement. Payment for the additional thickness will be pro-rated, based upon the unit bid price of this item. For each additional inch of thickness, the Contractor will be paid an additional one-sixth (1/6) of the unit price of the pay item. Temporary Asphaltic Roadway will be 2" thick. Payment for any additional thickness of temporary asphalt will be pro-rated, based upon the unit bid price for this item.

### 2.27 REMOVE AND REPLACE CONCRETE DRIVEWAY:

- A. Measurement: The measurement for Removal and Replacement of Concrete Driveways will be by the square yard.
- B. Payment: The actual quantity of applicable driveway removed and replaced will be paid for at the unit bid price. This price and payment will constitute full compensation for furnishing all labor, equipment, materials, wire mesh, saw-cutting, excavation, back-fill, expansion joint material, removal of the existing drive-way, and any other related items, necessary to complete the work.

### 2.28 REMOVE AND REPLACE SIDEWALKS:

A. Measurement: The measurement for Removal and Replacement of Sidewalks will be by the square yard.

B. Payment: The actual quantity of applicable sidewalk removed and replaced will be paid for at the unit bid price. This price and payment will constitute full compensation for furnishing all labor, equipment, materials, reinforcement (if required), and will include excavation, backfill, temporary asphaltic materials where removal occurred, expansion joint materials, and incidentals (i.e. saw-cutting and other related items) necessary to complete the work.

### 2.29 SITE SPECIFIC TRAFFIC CONTROL DEVICE PLAN:

- A. Measurement: Measurement for payment of development of each plan will be made on a per each basis for each location directed by the Owner or Project Manager.
- B. Payment: Payment for developing Site Specific Traffic Control Device Plans in accordance with the requirements of the specifications will be made at the unit bid price per each. The unit price shall be considered full compensation for this item and will include all labor, materials, Engineering Services, and any other services required for development of the Plan.

### 2.30 TRAFFIC CONTROL DEVICE SET-UP:

- A. Measurement: Measurement for payment of each set-up shall be made on a per each basis for each location directed by the Owner or Project Manager.
- B. Payment: Payment for completing each Traffic Control Device Set-up will be made at the unit bid price per each. This set-up will be in accordance with the Site Specific Traffic Control Device Plan, previously approved by the Owner/Project Manager.

### 2.31 TRAFFIC CONTROL DEVICE OPERATION:

- A. Measurement: Measurement for payment shall be made on a "per day" basis. A day shall be considered 24 continuous hours of operation. This shall be used only as directed by the Owner or Project Manager.
- B. Payment: Payment for each "day" of operation shall be considered full compensation for maintaining the approved traffic control device plan. Maintenance will include all necessary labor, equipment, materials, traffic engineering services, and other incidentals as required. Payment for each fraction of a day will be made as follows: Payment for operation of over 12 to 24 hours will be considered a full day. Payment for 1 to 12 hours will be considered a half day.

### 2.32 TRAFFIC FLAGMAN:

- A. Measurement: Measurement for payment shall be made on a unit price basis per hour required to fulfill the requirements of the Traffic Control Device Plan.
- B. Payment: Payment for providing a traffic control flagman will be made at the unit bid price per hour, as authorized by the Owner or Project Manager. Payment will constitute full compensation for all labor, materials, travel expenses, supervision, and related items necessary to complete each day of implementation or training, as dictated by the Owner or Project Manager.

### 2.33 JOURNEYMAN ELECTRICIAN

- A. Measurement: Measurement for payment for each journeyman electrician shall be made on a per hour basis. Number of journeyman electricians shall be directed by the Owner or Project Manager.
- B. Payment: Payment for each journeyman electrician shall be made at the unit price per hour.

This unit price shall be considered full compensation for this item, and will include all labor, materials, and services required to furnish journeyman electricians.

### 2.34 SLAB SODDING

- A. Measurement: Measurement for Slab Sodding will be by the square yard of finished surface, alter all conditions of the Technical Specifications have been met.
- B. Payment: Payment for Slab Sodding satisfactorily placed, as measured above, will be paid at the unit bid price. This price and payment will constitute full compensation for furnishing all labor, equipment, and materials necessary to complete this item of work.

### 2.35 UNFORESEEN EMERGENCIES:

A. Measurement: Measurement for unforeseen emergency work will be made on an as incurred basis. Parts and supplies incidental to the scope of services to be provided under this bid which are not listed as separate line items in the bid shall be billed and paid at dealer/wholesale invoice without increase or mark-up. Notwithstanding the foregoing, Contractor must receive prior

approval by the Department Director prior to purchasing these parts for repairs. Additionally, these third party invoices shall be included in the contractor's billing invoice for payment. The cost of any incidental drayage between the local supplier and the job site will not be considered for pay.

B. Payment: Payment will be made only when the Contractor is directed by the Parish to make repairs within the scope of work of this proposal but not specifically covered by items contained elsewhere in this proposal. Payment will include furnishing all labor, equipment, and materials needed to accomplish the directed emergency work. Payment will be made in accordance with the hourly or daily rate bid for labor and equipment items. Equipment rates for bid (equipment only) for unforeseen emergency work cannot exceed the AED green book rates. As follow: Day Rate = AED weekly rate. The hourly rate will be determined by dividing the daily rate by 8.

## TECHNICAL SPECIFICATIONS SECTION 3

### MANHOLE AND WET WELL INSPECTIONS

### 3.01 SCOPE OF WORK:

Manholes and wet wells will be inspected to locate defects, which are causing or could cause soil erosion and degradation to the sanitary sewer system, and/or other underground utilities, or surface structures, and which are allowing leaks into, or out of the sewer system.

### 3.02 DOCUMENTATION OF INSPECTION:

Observations shall be recorded on a manhole and wet well physical inspection report form. The information recorded on this form shall include location of the structure; relationship of a structure's incoming and outgoing lines; size of lines; depth of lines; condition of cover, ring, wall, bench and invert; type of material; and any other pertinent information which would affect a rehabilitation decision. The "Manhole Inspection Report", which may be obtained from the Project Manager, will be used to record the inspection results. All information and manhole numbers will be obtained from the Project Manager.

### 3.03 COMPILATION OF DATA:

All the data gathered in the field investigation shall be input into a sewer system management program, if required, by the Contractor to generate reports detailing the leaks identified and any further evaluation work to be done. These reports shall be delivered to the Project Manager daily to document completion of field work.

# TECHNICAL SPECIFICATIONS SECTION 4 SMOKE TESTING

### 4.01 GENERAL:

Smoke testing is to be accomplished on a limited basis. It will be, at the discretion of the Project Manager, to determine which lines will be smoke tested.

### 4.02 EXECUTION:

The smoke shall be blown by a specially designed gasoline powered blower, located on top of a central manhole. Blower pressure must be adequate to force smoke throughout the isolated sanitary sewer and to the ground surface through cracks, channels, etc., through which rain-water inadvertently enters the sanitary system defects, resulting in soil erosion and undermining of streets and sidewalks. The blower shall deliver no less that 4000 cfm. Only one line segment on each side of the blower shall be tested on a set-up. Where practical, inlets to the sanitary system shall be sandbagged or plugged during smoke testing so that sufficient blower pressure can be developed.

If manholes are located in the street or in a driveway, adequate safety precautions must be taken, as specified in these Procedures. Plugs or sandbags shall be placed in the lines entering the far upstream manhole of the test line segments, and the line exiting the far downstream manhole of the test line segments. Care must be taken to ensure that sufficient water head in the sewers is not developed to interrupt service to any citizen, or to create hazardous conditions. When all plugs or sandbags are secure, blowers are placed on top of the open manholes and started. When the blower is running, a smoke bomb or liquid smoke is simultaneously induced and placed so that smoke is forced into the sewer segment being tested. Smoke shall be blown for a minimum of five (5) minutes and until all leaks are identified. Color flags shall be placed at each smoke leak (except those on building roofs) to indicate intensity of smoke:

- heavy intensity red
- medium intensity yellow
- light intensity blue

The front, back, and side of buildings; sewer rooftop vents, roof drains, storm manholes, inlets, ditches, and the surface along the main sewer line shall be checked for the presence of smoke. During the testing, a field inspection test report and service line field inspection test report shall be completed by the Contractor.

### 4.03 DOCUMENTATION OF TESTS:

Observations of leaks at the manhole and along the sanitary system or drainpipe shall be recorded on a field inspection report form. The information recorded on this form shall include line number, description, and location of any leaks observed. Also included shall be a sketch on the line layout. Digital color photos shall be taken of all manhole leaks, lateral leaks, service line leaks, and mainline leaks. The main purpose of the photograph is to locate the leak for future testing or rehabilitation purposes. The digital color photos should show smoke emitting from the located leak. The "Smoke Test Report" form shall be used to record the inspection results. Forms will be obtained from the Project Manager.

### 4.04 NOTIFICATION OF RESIDENTS: AS REQUESTED BY THE PROJECT MANAGER

The following steps will be taken for notifying the citizenry local officials of smoke testing. If possible, twenty-four to forty-eight hours prior to starting work a hand-bill, announcing and describing the smoke testing program will be distributed to each household or commercial establishment located in the area to be smoke tested. Close communications between the Contractor, local officials, the police department, and fire department will be maintained to avoid major problems. Minimum footage issued in a work order for smoke testing will be 3,000 feet within a limited geographical area. The Contractor must notify the Project Manager no less than 48 hours in advance of smoke testing.

The Contractor must notify the fire department before testing begins, on each day of smoke testing. Any fire stations located in the area of testing should also be notified daily by the Contractor prior to testing. The scheduled work for the day and the general area of testing should be indicated 24-hours in advance. Hospitals, nursing homes, and schools must be notified, by the Contractor, the day of testing no less than one (1) hour prior to the actual test.

### 4.05 COMPILATION OF DATA:

All data gathered by the Contractor in the field investigation shall be input into a program compatible with a departmental program, if available, and/or as approved by the Project Manager, software program, to generate reports detailing the leaks identified and any further evaluation work to be done. These reports and field module CD's or other methods, shall be delivered to the Project Manager daily to document field work completion. The information recorded on the "Smoke Test Form" will include, but not be limited to, manhole-to-manhole segment number, street address, description, and accurate location of any leaks observed. A sketch of the main line layout and sketches of service/lateral lines, which have leaks, must also be included. The location, with measurements of all leaks shall be shown on the sketches. Digital color photos must be taken of all leaks. The main purpose for taking a digital color photo is to locate the leak for future testing or rehabilitation. The digital photo must always show the colored flag, and normally should show smoke emitting from the located leak. Should power sources be down during an emergency, and cause the Contractor to not be able to provide data to the Parish, Contractor shall save information and submit when power is restored.

# TECHNICAL SPECIFICATIONS SECTION 5 DYE-WATER FLOODING

### 5.01 GENERAL:

Dye water flooding will be used to trace and identify specific defects, which are causing or could cause soil erosion and degradation to the sanitary system. Dye-water flooding will also be used to located cross connections between sanitary and storm sewers. Dye-water flooding may also be used on other inflow services, such as leaks within five (5') feet of a manhole. Dye used in this operation shall be non-toxic and shall conform to all local, state, and federal guidelines.

### 5.02 EXECUTION:

Dye-water flooding will be accomplished by flooding the ground surface, or a line segment, with color-dyed water to simulate a storm water runoff condition. Dye-water flooding may be accomplished in conjunction with television inspection. It will be at the discretion of the Project Manager to determine which lines will be dye-water flooded. A minimum waiting period of 30 minutes for dye-water flooding will be required when no resulting leaks are observed. Water for use in dye-water flooding may be obtained from the Jefferson Parish Water System, provided the Contractor obtains and uses a water meter from the Department of Water. The Contractor will be responsible for the payment of all costs for water used.

### 5.03 DOCUMENTATION OF TEST:

The results of the dye-water flooding and testing must be recorded on a report form. The information recorded on this form must include: location of manhole or line flooded, lines plugged, location(s) flooded along line, locations of leaks observed in sanitary or drain systems. Digital color photos must be taken of the dye-flooding in progress and when possible, digital color photos should be made of the leaks located. The "Dye-Water Test Form", must be used to record the results. A sketch of the line layout with locations plugged and flooded must be included on the Form.

## TECHNICAL SPECIFICATIONS SECTION 6

#### **CLEANING**

### 6.01 GENERAL:

The intent of sewer line cleaning is to remove foreign materials from the lines and restore the sewer to a minimum of 95% of the original carrying capacity, or as required for proper seating of internal pipe joint sealing packers. Since the success of the other phases of work depends a great deal on the cleanliness of the lines, the importance of this phase of the operation is emphasized. It is recognized that there are some conditions, such as broken pipe and major blockages that prevent cleaning from being accomplished, or where additional damage would result if cleaning were attempted or continued. Should such conditions be encountered, the Contractor will not be required to clean those specific manhole sections. A daily log must be maintained to record the location of the manholes, catch basins, wet wells sanitary, and drain lines cleaned; lengths of the lines cleaned; method of cleaning; line sizes; and, volume and type of debris removed.

### 6.02 EQUIPMENT:

The equipment, which is expected to be used for the cleaning work on this project, is a high velocity combination sewer cleaner and vacuum truck supplying water at a minimum of 80 gpm at a minimum of 2000 psi.

### 6.03 EXECUTION:

If the cleaning of an entire section cannot be successfully performed from one manhole, the equipment shall be re-setup on the other manhole and cleaning attempted again. If successful cleaning cannot then be performed, it will be assumed that a major blockage exists. The cleaning efforts will then be abandoned until an excavation and "point repair" can be made by Parish supplied forces. The cleaning operation can then be resumed. The Contractor will be paid for the initial cleaning attempt. After removal of the blockage the Contractor will again clean the line section. The Contractor will be paid for the second cleaning at the same rate as the initial cleaning. All sludge, dirt, sand, grease, rocks, and other solid or semi-solid materials resulting from the cleaning operation shall be removed from the downstream manhole of the section being cleaned. Passing material from manhole section, which could cause line stoppages, accumulations of sand in wet wells or damage pumping equipment, will not be permitted. The Contractor will not be responsible for removing mortar or other material, which is securely attached to pipe walls or joints.

Cleaning will be complete when video inspection of the pipe indicates that all loose debris has been removed, so that the entire pipe wall is visible.

#### 6.04 DISPOSAL OF MATERIALS:

Materials shall be disposed of from the work site at the end of each work-day. The Contractor will provide satisfactory evidence daily to the Parish of the amount of material removed from the pipes. These quantities will be subjected to certification, as deemed necessary by the Project Manager. The Contractor will be responsible for the disposal of materials removed during the cleaning process. The Contractor must adhere to all local, state, and federal guidelines in disposal of this material.

### 6.05 CLEANING OF WET WELLS:

The Contractor will be required to clean sewer system wet wells in conjunction with sewer pipeline cleaning. Removal of all loose debris from wet wells will be required when cleaned.

### 6.06 REMOVAL OF SEWAGE FROM SYSTEM:

The Contractor will be required to pump sewage out of wet wells and manholes, and transfer it to areas as designated by the Director, Assistant Director, or the Project Manager. This is an emergency operation that will allow the residents the use of their sanitary facilities. Contractor may use vacuum trucks or large pump out trucks to remove the sewage from the wet wells and/or manholes.

**A.** The contractor shall provide all information requested in this section, as listed below if needed:

- 1. Hauling to Approved Landfill (River Birch Landfill)
  - a. A Copy of the sludge hauling permit from LDEQ.
  - b. Copies of all truck scale tickets.
  - c. Description of proposed haul route to be used for transportation to

site.

- d. All required approvals from local, state, and federal regulators including EPA and LDEQ.
- e. Contractor shall obtain and submit to River Birch Landfill the Generator Waste Profile form, as required, which will be obtained from River Birch Landfill.

# TECHNICAL SPECIFICATIONS SECTION 7 ROOT REMOVAL

PAGE INTENTIONALLY LEFT BLANK

# TECHNICAL SPECIFICATIONS SECTION 8 VIDEO INSPECTION

### 8.01 GENERAL:

When cleaning is completed, the Contractor will proceed with the video inspection.

It is the intent of the Parish to determine applicable cost effective rehabilitation and repair techniques based on video inspection performed on this contract.

### 8.02 EXECUTION:

Pipe inspection shall be accomplished by one of the following methods:

- A. Television Inspection of 6" thru 24" Mainline Pipe
  - 1. The contractor shall use a pan and tilt articulating lens closed circuit color video system to remotely inspect the pipe. The television camera used for the inspection shall be one specifically designed and constructed for such inspection. Lighting for the camera shall be suitable to allow a clear picture of the entire periphery of the pipe. The camera shall be operative in 100% humidity conditions. The camera, television monitor, the video recorder, and other components of the video system shall be capable of producing the picture quality required to properly evaluate the condition of the pipe being inspected.
  - 2. Depth of flow shall not exceed that shown below for the respective pipe sizes measured in the manhole.
    - Maximum Depth of Flow for Television Inspection:
    - 6" 10" pipe . . . . . . . . . 20 % of pipe diameter
    - o 12" 24" pipe . . . . . . . . 25% of pipe diameter

The Contractor will be required to dewater pipe depths as necessary to allow the required visibility. This dewatering will be considered incidental to the video inspection. Picture quality and definition shall be to the satisfaction of the Project Manager.

3. Plugging: A sewer line plug shall be installed upstream of the section being worked. The plug shall permit a portion of the sewerage to be released. After the work has been completed, sewage flow should be restored to normal.

Sewer plugs shall be installed in the influent pipe of a manhole. The plug shall be equipped with an air hose to permit deflation from above ground. A strong rope should be attached to enable the plug to be quickly pulled out of the manhole. The Contractor will be responsible for preventing a plug from being pushed into the outgoing pipe when stored sewage is released.

- 4. The camera shall be moved through the line in either direction at a moderate rate, stopping when necessary to permit proper documentation of the pipe's condition. In no case will the television camera be moved at a speed greater than 30 feet per minute. Manual winches, power winches, TV cable, and powered rewinds or other devices that do not obstruct the camera view or interfere with proper documentation of the pipe conditions shall be used to move the camera through the line. If, during the inspection operation, the television camera will not pass through the entire section, due to an obstruction such as a dropped joint, crushed pipe, etc., the Contractor shall set up his equipment so that the inspection can be performed from the opposite end. If, again, the camera fails to pass through the entire section because of an obstruction, the inspection shall be considered complete at that time. When manually operated winches are used to pull the television camera through the line, radios, or other suitable means of communication must be set up between the two ends of the section being inspected to insure good communication between crew members.
- 5. The importance of accurate distance measurements is emphasized. Measurement for location of defects and service connections must be done with a metering device located in the video inspection van. The footage reading of the counter must be displayed at all times on the monitor and on videotape. Marking on the cable, or the like, which would require interpolation for manhole depth, will not be allowed. Accuracy of the distance meter shall be checked by use of a tape, and the accuracy shall be within 1%.
- 6. The location of all significant pipe defects must be recorded on the inspection log including, but not limited to, cracked and missing pipe, degree of pipe deterioration, open or shifted joints, leaking joints, leak estimates, crushed pipe, and obstruction. The log must also show pipe type, size, depth, manhole locations, and location of all service connections. In addition, as part of the mainline video inspection, the

Contractor must determine and record the street number addresses of all observations

- 7. The Contractor performing the videoing shall be responsible for the accuracy of addresses and assessed point repair footages provided under this contract.
- 8. After issuance of a video inspection work order, but prior to initiation of field inspection work, the Contractor will field survey the work order area to determine of this manhole addresses qualifiers. Upon completion of this manhole survey, the Contractor will submit a complete mainline inventory of all manholes in the work order scope to the Project Manager for approval. The Contractor must use the Parish addressing standard for this inventory.
- 9. A digital MPEG recording, using software compatible with the Department of Sewerage or PWIRS software, should be made, by the Contractor, of all pipe sections video inspected. The recording will include a complete "Color" video of the entire inspection. The video inspection must have the capability of permanently displaying on the video tape, information concerning the pipe inspected, including: project number, data, street name, manhole designations, size of pipe, and the footage counter. On at least a bi-weekly basis (emergency permitting), the contractor will deliver, to the Parish, a computer media containing all field investigation data collected during the week, and television inspection data, as provided in Sections 24 & 25, which shall be completed during each video inspection. For the duration, the contractor will maintain a local library containing a copy of all video recording generated on this Contract. All the data gathered in the field investigation shall be uploaded into a system compatible with the Department of Sewerage program. All codes must follow the Jefferson Parish Standards.
- 10. Video inspection activities may be coordinated with dye-flooding when directed by the Project Manager.
- 11. Since Jefferson Parish is in a high rainfall area and all original sanitary and drain pipe capacities are needed, no reconstruction method will be considered that does not provide at least 100% flow capacity of the original sanitary and storm sewer pipes.
- 12. The Contractor will be paid for the actual linear feet of pipe inspected at the unit bid prices for the various sizes of sanitary or storm sewer

pipes. The Contractor will be paid additional compensation for television inspection when a reverse setup is required because of an obstruction in the pipe by which the camera cannot pass. A "reverse setup" occurs when a line section must be television inspected from both directions because an obstruction halted camera progress from the initial setup. The Contractor will be paid for the initial inspection attempt as though it was satisfactorily completed. Whenever a reinspection is performed after removal of the obstruction, the Contractor shall be paid again at the same rate as for the first video inspection.

- 13. All the data gathered in the field investigation shall be input into a system compatible with the sewer system management program by the Contractor, to generate reports detailing the leaks identified and any further evaluation or repair work to be done.
- 14. All digital videos gathered in the television inspection shall be digitized using a system compatible with Jefferson Parish and/or PWIRS software.

## TECHNICAL SPECIFICATIONS SECTION 9

### PIPE REHABILITATION BY INSTALLATION OF CURED-IN-PLACE PIPE

### 9.01 GENERAL:

It is the intent of this specification to provide for the reconstruction of existing sanitary and storm sewer pipes by forming a new pipe within an existing structurally deteriorated pipe, which has generally maintained its original shape. The cured-in-place- pipe (CIPP) shall provide flow capacity equal to or greater than "100% of the original pipe's flow capacity when new." The installation of the CIPP shall be accomplished by the use of the Insituform Process, LMK, or National Liner Process. The process is defined as the reconstruction of sanitary sewer pipe by installation of a thermosetting, resin impregnated, flexible felt, fiber tube (coated on one side with polyethylene) into the existing sanitary sewer pipe, utilizing a water column. Curing is accomplished by circulating hot water (or other approved fluid) throughout the length of the tube to cure the thermosetting resin into a hard impermeable pipe. The pipe shall extend the full length of the original pipe and shall provide a structurally sound, joint less, closed-fitting, cured-in-place-pipe.

### 9.02 REFERENCED SPECIFICATIONS:

This specification references ASTM F 1216 (Rehabilitation of pipelines by the inversion and curing of a resin-impregnated tube) and ASTM F1743 (Rehabilitation of pipelines by pulled-in-place installation of a cured-in-place thermosetting resin pipe). ASTM D790, (Test Methods for flexural properties of non-reinforced plastics) which are made a part hereof by such reference and shall be the latest edition and revision thereof. In case of conflicting requirements between this specification and these referenced documents, this specification will govern.

### 9.03 GENERAL CORROSION REQUIREMENTS:

The CIPP shall be fabricated from materials which, when cured, will be chemically resistant to withstand internal exposure to permitted storm-water and sanitary sewerage.

### 9.04 MATERIALS:

A. The flexible felt fiber tube shall be fabricated to a size that when installed, will neatly fit the internal circumference of the conduit specified by the Parish. An allowance shall be made for some circumferential stretching during inversion.

Minimum tube thickness must be as indicated on the bid form. Additional thickness will be used if required by site conditions.

- B. The minimum length will be that deemed necessary by the Contractor to effectively span the distance from the inlet to the outlet of the respective manholes or other termination points, unless otherwise specified. The Contractor must verify the lengths in the field before impregnation of the tube with resin. Individual insertion runs can be made over one or more manhole sections, as determined in the field by the Contractor.
- C. Unless otherwise specified, the Contractor must furnish either a polyester or vinyl ester resin and a compatible catalyst system that provides cured physical strengths, as specified herein. Epoxy vinyl ester resins shall be Derakene 411 series, or approved equal. Polyester resins shall be manufactured by Alpha Owens Corning, or approved equal.
- D. The materials used must result in an installed CIPP flow capacity which will be equal to, or greater than, 100% of the original pipe's flow capacity when new.
- E. Physical Strength: The CIPP shall conform to the minimum structural standards, listed below, or to the then current standards approved by Insituform of North America or Inliner USA.

Physical <u>Test Method</u>

Minimum Values

Characteristic

Flexural Stress #101 (Modified ASTM D-790)

4,500 psi

Flexural Modules #101 Modified ASTM D-790 250,000 psi

Of Elasticity

### 9.05 PRE-INSTALLATION PROCEDURES:

The following installation procedures must be adhered to, unless otherwise approved by the Project Manager.

- A. Safety The Contractor must carry out his operations in strict accordance with all applicable OSHA standards. Particular attention is drawn to those safety requirements involving work on an elevated platform and entry into a confined space.
- B. *Pre-inversion Cleaning* It will be the responsibility of the Contractor to remove all loose debris, which is located within the sanitary pipe.
- C. Pre-inversion Inspection Inspection of sanitary sewer pipe must be performed by experienced personnel trained in locating breaks, obstacles, and connections by closed circuit television inspection. The interior of the pipe must be carefully inspected to determine the location of any condition, which may prevent proper installation of the CIPP, and it must be noted so that these conditions can be corrected. A videotape and suitable log must be kept for later reference by the Parish and/or Contractor.
- D. Line Obstructions If inspection reveals an obstruction, (such as attached mortar, dropped joints, protruding taps, or collapsed pipe), that cannot be removed by conventional pipe cleaning equipment, that will prevent completion of the inversion process, then a point repair excavation will be made to uncover and remove or repair the obstruction. Such work will be performed by the Parish, the Parish's designated Contractor, or will be authorized under this contract.
- E. *Protruding Tap Removal* A robotic machine capable of grinding off clay and concrete lateral protrusions and reinstatement cutting will be used. The machine will work inside the parent and relined pipe without damaging parent or relined pipe walls.

Protruding laterals will be ground back to a ¼" protrusion or less. Grinding will be done using a slow speed (1,000 to 1,500 rpm) diamond chip covered ball grinder of nominal 1.50" to 2.00" diameter. Segmented, notched, or chipping type cutters, which crack and chip the lateral pipe resulting in broken or cracked laterals, will not be accepted.

F. By-passing – When required for acceptable completion of an inversion process task and/or to avoid damage due to sewer spills or overflows, the Contractor must provide for sanitary water flow maintenance around the section or sections of pipe designated for the inversion process. The bypass will typically be made by plugging the line at an existing upstream manhole and pumping the flow into a downstream manhole or adjacent system. The pump and by-pass of sanitary sewerage into the storm-water system will not be allowed.

The Contractor will notify all parties whose service laterals will be out of service, and advise against water usage until the mainline is back in service. Notification will be at least 24 hours prior to CIPP installation, and no more that 72 hours prior to lining. Notification will be done with a "door hanger" approved by the Director, Assistant Director, or Project Manager.

### 9.06 INSTALLATION PROCEDURES:

- A. Wet-Out The Contractor will designate a location where the tube will be impregnated ("wet out") with resin using distribution rollers and vacuum to thoroughly saturate the felt fiber tube, prior to installation. The Contractor must allow the Project Manager to inspect the materials and wet out procedure. A catalyst system compatible with the resin and tube must be used.
- B. Insertion The wet out tube must be inserted through an existing manhole or other approved access, and the application of a fluid column sufficient to fully extend it to the next designated manhole or termination point. The fluid column will be adjusted to be of sufficient height to cause the impregnated tube to hold tight against the existing pipe wall, produce dimples at side connections, and flared ends at the manholes.
- C. Curing After the insertion is completed, the Contractor must supply a suitable heat source and fluid re-circulation system capable of delivering hot fluid uniformly throughout the section to effect a consistent cure of the resin. The curing temperature will be that recommended by the resin/catalyst system manufacturer.

The heat source must be fitted with suitable monitors to gauge the temperature of the incoming and outgoing fluid supply. Another such gauge must be placed between the impregnated tube and the invert of the original pipe at the manholes(s) or other termination points, to determine the temperatures during the resin curing process. Initial cure will be considered completed when the exposed portions of the CIPP appear to be hard and the remote temperature sensing device indicates the cure period to be of adequate duration, as recommended by the resin/catalyst system manufacturer and modified for the inversion process.

D. Cool-down – The Contractor must cool the hardened CIPP to a temperature below 100 degrees Fahrenheit before relieving the fluid column. Cool fluid may be added to the fluid column while draining hot fluid from a small hole at the opposite end of the CIPP, so that a constant fluid column height is maintained until cool-down is completed. Care must be taken in the release of the fluid column so that a vacuum will not be developed that could damage the newly installed CIPP.

E. Warranty – The finished CIPP must be continuous over the entire length of an inversion run and be as free as commercially practical from visual defects, such as foreign inclusions, dry spots, pinholes, and delamination. It must also meet the water-tightness test requirement specified below. During the warranty period any defects, which will affect the integrity or strength of the CIPP, must be repaired at the Contractor's expense, in a manner mutually agreed to by the Parish and the Contractor. The warranty period is for one year after acceptance by the Parish.

### 9.07 SEALING AT MANHOLES:

If the CIPP fails to make a tight seal at a manhole or other termination point, the Contractor must apply a seal at that point. The seal must be of a material compatible with the CIPP material.

### 9.08 RESTORATION OF SANITARY SEWER SERVICE CONNECTIONS:

After the CIPP has been cured in place, the Contractor must re-open the existing active sanitary sewer connections, as designated by the Project Manager. This will usually be done without excavation, and in the case of non-man-entry pipe, (i.e. pipe less than 24" in diameter) from the interior of the pipeline by means of a television camera and a cutting device that re-establishes the sanitary sewer connections to not less than 90% of their original size (when new) and must be fully functional. Restored openings should be neatly and smoothly cut and without rough edges. Care must be exercised not to damage the CIPP or the existing main or lateral pipes. Cutting devices that use high pressure water must not be used, since they may cause damage to the lateral. All liner materials must be removed from the internal wall of lateral connection. When fiberglass or other reinforcing fibers, that may cause wicking at lateral openings, are used, the lateral opening edges must be sealed with a resin mixture compatible with the tube resin. Connections should not be over cut, as this could damage the pipe, break the CIPP seal, and/or interfere with future lining of the lateral.

Lateral reinstatement must be done using either a wire steel brush cutter or a coarse carbide crystal surface type cutter. This method of cutting must not damage the lateral pipe material and must result in a smoothed even surface, which is flush with and follows the lateral pipe internal wall contour regardless of penetration geometry. The use of drill or router bits will not be allowed. Holes cut outside the lateral opening or oversized cutting (more than 105%) must be corrected to the Owner's satisfaction.

If under normal circumstances the CIPP interior method of tap cutting does not prove satisfactory, an external tie-in of the house connection will be required. This external tie-in must be made by the Contractor, at Contractor's expense.

### **9.09 TESTING:**

The water-tightness of the CIPP must be gauged by monitoring the water level in the inversion tube while curing. The water testing must be done directly on the finished product and not on an intermediary hose, which is not part of the final product.

For each installation, the Contractor must perform tests on a sample of the cured installed liner. Tests conducted shall include the following:

- a. Thickness of sample
- b. Flexural strength
- c. Flexural modules of elasticity

The method for taking the sample must be as follows: Place a short section of pipe in the manhole aligned with and the same size as the existing sewer. Run the impregnated tube through the pipe and cure the CIPP under restrained conditions. Label samples with the project number, date of installation, location, manhole number, and specified thickness.

These tests will be conducted in accordance with Modified A.S.T.M. D-790. The testing will be accomplished by an independent, certified testing laboratory, provided, and paid for by the Parish.

### 9.10 **CLEAN-UP**:

Upon acceptance of the installation work and testing, the Contractor must restore the area affected by his operations to its original state.

### 9.11 POST VIDEOS:

At the completion of the rehabilitation of a pipe-line, a digital inspection CD of the completed line segment will be given to the Project Manager by the Contractor. The Project Manager will use this inspection to determine if this line has been restored in a satisfactory fashion.

This inspection shall be performed, one section at a time, by closed circuit color television, using a radial view camera. The flow entering the section being inspected shall be plugged, as required and previously described. The television camera used for this inspection must be one that is specifically designed and constructed for such conditions. The camera shall be pulled through the pipe slowly in order to fully inspect for any defects. Location records shall be kept by the Contractor, which will clearly show the exact location, in relation to adjacent manholes, of all house connections. A computer-generated copy of this log and data disc shall be supplied to the Project Manager.

### 9.12 SERVICE RECONSTRUCTION/REPLACEMENT PRIOR TO CIPP:

For deteriorated or damaged connections, or ones, which are protruding and cannot be cut internally, the Contractor will excavate and make the repair prior to installation of the CIPP.

After the liner has been put into place and allowed to normalize to ambient temperature, and recover from any imposed stretch, each existing service connection shall be reconnected to the new liner. A portion of the existing sanitary sewer main, or "Carrier pipe", around each service connection must be removed to expose the liner pipe and to provide sufficient working space for installing a pre-fabricated polyethylene saddle or an approved alternate. The polyethylene saddle must be a one-piece saddle equipped with a neoprene gasket, so that a complete seal is accomplished when the strap-on saddle is tightened with two (2) stainless steel bands; one on each side. The stub-out attached to the saddle must protrude into the liner a distance equal to the wall thickness of the liner in place. The new 4", 6", or 8" stub-out, or lateral, must be connected to the existing service line with a flexible PVC coupling, with stainless steel shear rings and hardware. Couplings must be "Fernco" 5000 Series or "Mission Rubber" Arc. A service reconnection shall consist of the removal and replacement of any cracked, offset, or leaking existing service, up to a distance of eight feet (8') from the center of the new liners, measured horizontally.

The new flexible coupling must be secured to the existing service lateral, and new stub and/or stack, with stainless steel bands.

### **9.13 PATENTS:**

The Contractor shall warrant to the Parish that the methods, materials, and equipment used herein, where covered by license are furnished in accordance with such license and the prices included in this proposal include applicable royalties and fees in accordance with such licenses. The Contractor shall warrant and hold harmless the Parish against all claims for patent infringement and any loss thereof.

### TECHNICAL SPECIFICATIONS

### **SECTION 10**

### SERVICE LINE OR MAINLINE POINT REPAIR

### 10.01 SCOPE OF WORK:

The work covered by this item consists of furnishing all labor, material, equipment, supervision, etc. necessary to perform emergency repairs on the portion of a service line located within the utility easement, street right-of-way, or mainline sewer. Such emergency repairs will only be addressed if located in an easement or right-of-way (no repair to service lines will be made on private property). The location of the repair will be determined by smoke testing the manhole section in which the repair is located. The Project Manager will direct the Contractor to make the line repair. It will be the Contractor's responsibility to accurately field locate the exact point of emergency repair. Service line emergency repairs are required to repair a variety of defects, including: cleanout repair, removing from service disconnected services, repairing storm sewer cross connections, disconnecting surface drains, and repairing faulty service taps.

### 10.02 MATERIALS:

Materials for line repair must be of the same types as specified in the "Replacement Pipe and Fittings" section and "Sewer Clean-outs" section.

### 10.03 SMOKE TESTING TO DETERMINE SERVICE LINE POINT REPAIR LOCATION(S):

The Contractor shall perform smoke tests in accordance with Section 4 "Smoke Testing".

### 10.04 CONTRACTOR SUBMITTALS:

The Contractor must submit digital color photographs to the Project Manager. Said digital color photographs must be recorded to a CD, or other acceptable devices, clearly indicating the location of all smoke leaks from service and main lines with a designated manhole section. The location of all line leaks, including locations outside of right-of-way and easements, shall be referenced to a permanent structure.

### 10.05 METHOD OF POINT REPAIR:

After the location of the point repair is determined, the Contractor will excavate and remove the damaged pipe and replace with new pipe. The minimum length of pipe replaced will be three (3) feet.

The Contractor will excavate, shape the bottom of the trench, and place the required pipe bedding, so that the grade of the replaced pipe matches the existing line grade.

The pipe replacement material must be gasket joint, gravity PVC sewer pipe (ASTM D-3034, SDR 26), and have a minimum cell classification of 12454 A or B, as defined in ASTM C-1784. Installation must be in strict compliance with the manufacturer's recommendations. The method of joining the ends of the replaced pipe with the existing pipe must be water-tight. The existing and new pipe must be joined with shielded repair couplings, stainless steel shear rings, and hardware ("Fernco" 5000 series or "Mission Rubber "Arc).

NOTE: Numerous service line point repairs along with lateral line point repairs and obstruction removals are located in areas, which in many instances will require the removal of existing landscaping, structures, etc. Items removed or disturbed must be replaced to a condition equal to, or better than the original condition. All necessary labor, equipment, materials, and other items necessary to complete this work in accordance with the plans and specifications are incidental.

### 10.06 GENERAL DESCRIPTION OF WORK ITEMS:

- A. REPAIR/ADJUST CLEANOUT: Cement, plaster, or replace the broken cleanout.
- B. INSTALLATION OF SEWER CLEANOUT TYPE 1: As detailed on Jefferson Parish Standard drawings.
- C. REPLACE SECTION OF SERVICE LINE: Replace length of service line as specified.
- D. RESTORE 6" 24" MAIN BY EMERGENCY REPAIR: Replace 6" to 24" main line at various depths, up to eight (8') feet in depth.
- E. RESTORE 6" 24" MAIN BEYOND EMERGENCY REPAIR: Replace 6" to 24" main line at various depths, beyond eight (8') feet in depth.

- F. RESTORE 4" 24" SEWER FORCE MAIN REPAIRS: Remove and replace a section of 4" to 24" force main less than eight (8') feet in depth.
- G. RESTORE 4" 24" SEWER FORCE MAIN BEYOND EMERGENCY REPAIR: Replace a 4" to 24" force main at various depths, beyond eight (8') feet in depth.

### 10.07 REMOVAL OF DEBRIS:

Excess excavated material and debris are to be removed from the work site daily. The cost of hauling excess excavation and debris will be included in the bid price for "Service Line Repair".

### **10.08 TESTING:**

Upon completion of the point repairs on a designated line segment, the Contractor must perform a smoke test, as previously described, to check the integrity of the repairs made. This smoke test must be done upon completion of all repairs in a manhole section, and prior to backfilling. The Project Manager and Contractor must check each repair. If any smoke is detected at the repair location, the Contractor must redo the repair and repeat the smoke test, at no additional cost to the Owner. All smoke testing and re-testing shall be considered incidental to the point repair.

### TECHNICAL SPECIFICATIONS

### **SECTION 11**

### REPLACEMENT PIPE, FITTINGS, AND MISCELLANEOUS ITEMS

### 11.01 SCOPE OF WORK:

The Contractor shall furnish all labor, materials, equipment, and incidentals to complete an "Emergency Repair" using materials described herein, compatible to the removed materials.

### 11.02 SUBMITTALS:

- A. If requested, Contractor shall submit to the Parish, a list of materials to be furnished and the names of his suppliers.
- B. All submittals shall comply with Jefferson Parish Department of Engineering Standard Specifications and Details.

### 11.03 MATERIALS:

### **11.03.01** Poly-vinyl Chloride (PVC) Pipe used for Gravity Sewer:

- A. Poly-vinyl Chloride (PVC) gravity sewer pipe and fittings, 4" through 16" diameter, shall conform to ASTM D-3034, "Type PSM Poly-vinyl Chloride (PVC) Sewer Pipe and Fittings", SDR—26.
- B. Poly-vinyl Chloride (PVC) gravity sewer pipe and fittings, 18" through 24" diameter, shall conform to ASTM F-679, "Poly-vinyl Chloride (PVC) Large-Diameter Plastic Pipe and Fitting", T-2 wall thickness
- C. All gravity sewer lines with more than ten feet (10') of cover and any pipe under roadways with less than four feet (4') of cover shall conform to the specifications "Poly-vinyl Chloride (PVC) Pipe C-900"
- D. The supplier will be responsible for the performance of all inspection and testing requirements specified in ASTM D-3034 or ASTM F-679, as applicable. Complete

records of inspections, examinations, and tests must be kept and submitted to the Project Manager. The Project Manager reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary, to ensure that materials and services conform to the prescribed requirements.

- E. The pipe must be joined with an integral bell and spigot type rubber gasket joints. Each integral bell joint must consist of a formed bell with a rubber gasket. Gaskets must conform to ASTM F-477. Joints should permit contraction, expansion, and settlement; and yet maintain a water-tight connection.
- F. Pipe must be furnished in standard laying lengths not exceeding 20 feet (20').
- G. All fittings and accessories must be furnished by the pipe supplier, and must have bell and/or spigot configurations compatible with the pipe.

### **11.03.02** Ductile Iron Pipe and Fittings

- A. All ductile iron pipe must be ductile iron manufactured, in accordance with the requirements of the latest revision of AWWA C 150 and C 151, must conform to ANSI specifications A21.51, and thickness design A21.50-76. Pipe supplied must be Class 51 for pipe eight inches (8") and smaller, Class 52 for pipe ten inches (10") and larger, and must meet all requirements for push-on rubber gasket joints, in accordance with AWWA C111.
- B. Unrestrained joint pipe must be supplied in lengths not in excess of 21 feet. Pipe must be either the rubber-ring type, push-on joint, or standard mechanical joint pipe, as manufactured by the American Cast Iron Pipe Company, U.S., Pipe and Foundry Company, Clow Corporation, or approved equal.
- C. Fittings must meet the requirements of ANSI/AWWA C110. Rubber gaskets must conform to ANSI A21.11 mechanical and push-on type joints.
- D. All ductile iron pipe and fittings less than twelve inches (12") in diameter and larger must have cement mortar lining and bituminous seal coat on the inside, in accordance with AWWA C104, and coal tar enamel coat on the outside, in accordance with ANSI A 21.4.

All ductile iron pipe and fittings less than twelve inches (12") in diameter and larger must have a polyethylene lining on the inside and a coal tar enamel coating on the

outside. Polyethylene must comply with ASTM S1248, compounded with carbon black to provide resistance to ultra violet rays during ground storage. The polyethylene must be 40 mills thick and must be bonded to the interior of the pipe and fittings by a heat process. The coal tar enamel outside coating must be in accordance with ANSI A21.4.

E. Restrained joints must be provided at locations shown on the drawings. Restrained joint pipe and fittings for twelve inches (12") and smaller diameter pipe must be "Mechanical Joint with Retainer Gland", as manufactured by American Cast Iron Pipe Company; "Lok-Tyton", as manufactured by U.S. Pipe Company; "Super-Lock", as manufactured by Clow Corporation, or equal.

### 11.04 IDENTIFICATION:

Each length of pipe and each fitting must be marked with the name of manufacturer, size, and class. All gaskets must be marked with the name of manufacturer, size, and proper insertion direction.

### 11.05 MANHOLE CONNECTIONS:

Pipe stubs for all manhole connections should not exceed two feet (2') in length. Caps must be furnished where required.

### 11.06 LAYING POLY-VINYL CHLORIDE (PVC) PIPE AND FITTINGS:

- A. Poly-vinyl Chloride (PVC) pipe must be laid in accordance with the Jefferson Parish Department of Engineering Green Sheets and Standard Details. All work must be in accordance with industry standards. Embedment of pipe must conform to ASTM D2321, "Recommended Practice for Underground Installation of Flexible Thermoplastic Sewer Pipe". Bell holes must be excavated so that after installation, only the pipe barrel will bear upon the trench bottom. Proper selection/placement of bedding and backfill materials are necessary to minimize deflection of the pipe diameter. No blocking under the pipe will be permitted, except as allowed in these specifications.
- B. The Contractor must use care in handling/installing pipe and fittings. Storage of pipe on the job site must be done in accordance with the pipe manufacturer's recommendation, and with approval of the Project Manager. Under no circumstances will pipe or fittings be dropped either into the trench or during unloading. The interior of the pipe must be kept clean of oil, dirt, and foreign

matter, and the machined ends and couplings must be wiped clean immediately prior to joining.

- C. The Contractor must use a PVC pipe cutter where necessary to cut and machine all PVC pipe in the field. A "full insertion mark" must be provided on each field-cut pipe end. Field-cut pipe must be beveled with a beveling tool made especially for plastic pipe. Bevels must be in accordance with the manufacturer's requirements.
- D. Each length of pipe and each fitting must be marked with the normal size, the SDR designation, the name of the manufacturer or his trademark, and the date of manufacture.
- E. Rubber gaskets must be marked with manufacturer's identification, sizes, and proper insertion direction.
- F. The interior of the pipe and the jointing seal must be free from sand, dirt, and trash before installing in the line. Extreme care must be taken to keep the bells of the pipe free from dirt and rocks, so joints may be properly assembled, without over stressing the bells. The jointing of the pipe must be done in strict accordance with the pipe manufacturer's instructions and must be done entirely in the trench.
- G. Each time the work is halted for more than one (1) hour, the ends of the pipe should be closed to prevent foreign material from entering the pipe.
- H. In all cases where this type of pipe is installed, a metallic tape must be affixed to the top of the pipe. The tape shall be Type A-1 Alertine Detectable Marking Tape, or approved equal.

### 11.07 LAYING DUCTILE IRON PIPE AND FITTINGS:

- A. All buried piping must be installed in accordance with recommendations of the pipe manufacturer, and as specified herein.
- B. Care should be taken in handling, storage, and installation of pipe and fittings to prevent damage to the pipe or coating. All pipe and fittings must be examined before lying, and no piece should be installed which is found to be defective. All damage to the pipe coating must be repaired according to the manufacturer's recommendations.

- C. Rubber gaskets must be marked with manufacturer's identification, sizes, and proper insertion direction.
- D. The interior of the pipe and the jointing seal must be free from sand, dirt, and trash before installing in the line. Extreme care must be taken to keep the bells of the pipe free from dirt and rocks, so joints may be properly assembled, without over stressing the bells. The jointing of the pipe must be done in strict accordance with the pipe manufacturer's instructions and must be done entirely in the trench.
- E. Each time the work on the sewer is halted more than one (1) hour, the ends of the pipe should be closed to prevent foreign material from entering the pipe.

#### 11.08 MARKER TAPE:

Marker tape must be installed on all lines. The color should be yellow with "CAUTION – SEWER LINE BURIED BELOW" written on it. The tape must be two inches (2") wide, and located between the bedding and the backfill, along the centerline of the pipe.

#### 11.09 PIPE COUPLINGS:

Repairs made to similar pipe must be accomplished with the use of similar repair couplings or spool pieces. Repairs made to dissimilar gravity sewer line pipe (i.e., PVC to clay, transit or other) must be accomplished with the use of shielded repair couplings with stainless steel shear rings and hardware. Shielded repair couplings must be Fernco's 5000 series or Mission Rubber's Arc. All pipe couplings must attach to the existing and replacement pipes by means of stainless steel bands with screw and housing to assure a positive seal around the pipe.

# **TECHNICAL SPECIFICATIONS**

# SECTION 12 SEWER CLEAN-OUTS AND MANHOLES

# 12.01 SCOPE OF WORK:

When ordered, the Contractor will be required to install service lateral clean-outs. A sewer clean-out installation will consist of all pipe, fittings, adapters, castings, and/or cover boxes. Sewer clean-out must be Type 1 installation as shown of the Standard Details. Materials for manhole rehabilitation are also covered herein.

# 12.02 MATERIALS:

- A. Approved pipe and fittings, (See "Replacement Pipe and Fittings")
- B. Clean-out Frame & Cover: Vulcan V-8504, or approved equal.
- C. Manhole Walls and Cones: Manufactured in accordance with ASTM C478.

# 12.03 EXECUTION:

A. Sewer clean-outs are to be installed as indicated on the Standard Detail sheet. Sewer clean-out piping will be installed from the depth of the service lateral to the existing grade line, so that the sewer clean-out plug fitting and cover are flush with the grade line.

Sewer clean-out frame and cover are to be installed flush with grade line. The frame will be encased in a 4-inch thick square concrete footing, extending 3-inches around the clean-out frame.

B. Each manhole or cone section must be installed as indicated on the drawings, and as specified herein. Wall sections must be furnished in lengths required to match the existing lengths as closely as possible.

Joints between the sections must comply with ASTM C443 and be sealed with neoprene gaskets, minimum thickness 3/16 inch or ram neck joint material.

# TECHNICAL SPECIFICATIONS

# **SECTION 13**

# CURED-IN-PLACE-LATERAL RECONSTRUCTION FROM CLEAN-OUT

# 13.01 DESCRIPTION:

Work under this item will provide for the reconstruction of lateral sanitary sewer pipelines with the installation of resin impregnated, flexible felt tubes. The resin impregnated flexible felt tube must be installed into the existing service using a pull rope or a push rod. Curing must be accomplished with hot water or other methods approved by the Project Manager. The curing method must be suitable for the selected resin, such that the resin produces a hard, impermeable pipe wall. The cured-in-place pipe (CIPP) should extend throughout the initially defined and agreed upon length, in a joint less, continuous, tight fitting, watertight pipe-within-a-pipe, to effect a seal with the mainline reconstructed pipe. Approved products are those provided by LMK Enterprises, Insituform Technologies and National Liner Process.

Materials will be governed by the requirements of Technical Specification Section 9 – "Pipe Rehabilitation by installation of Cured-in-Place Pipe".

# 13.02 REFERENCE SPECIFICATIONS:

This specification references ASTM test methods, which are made a part thereof by such reference, and must be the latest edition and revision thereof.

# 13.03 GENERAL CORROSION REQUIREMENTS:

The finished cured-in-place product must be fabricated from materials which, when cured, will be chemically resistant to withstand exposure to domestic sewage.

All constituent materials will be suitable for service in the environment intended. The final product will not deteriorate, corrode, or lose structural strength that will reduce the projected product life.

#### 13.04 CIPP MATERIALS:

A flexible felt tube must be fabricated to a size that, when installed, will neatly fit the internal circumference of the conduit specified by the Owner. Allowance must be made for circumferential stretching during insertion.

The minimum length will be that deemed necessary by the Installer, as approved by the Owner, to effectively span the distance from the lateral connection at the main to the desired termination location in the service lateral pipe. The Installer must verify the lengths in the field before impregnation.

Unless otherwise specified, the Installer must furnish a specially designed, unsaturated, polyester resin and catalyst system compatible with the CIPP process that provides cured physical strengths specified herein.

#### 13.05 PHYSICAL STRENGTH:

The structural performance of the finished pipe must be adequate to accommodate all anticipated loads throughout its design life. No cured-in-place pipe reconstruction technology will be allowed that requires bonding to the existing pipe for any part of its structural strength. Only resin vacuum impregnation will be allowed. If reinforcing materials (fiberglass, etc.) are used, the reinforcing materials must be fully encapsulated within the resin to assure that the reinforcement is not exposed, either to the inside of the pipe, or at the interface of the CIPP and the existing pipe.

Design methods are to be derived from traditionally accepted pipe formulae for various loading parameters and modes of failure. All equations will be modified to include totality as a design parameter. The design method must be submitted to the Project Manager for approval.

The cured CIPP shall conform to the minimum structural standards listed below.

CURED CIPP

ASTM Standards
Results

Flexural stress

ASTM D 790

4,500 psi

Flexural Module of Elasticity

ASTM D 790

250,000 psi

#### 13.06 INSTALLATION PREPARATION:

The following installation procedures must be adhered to, unless otherwise approved by the Owner's representative.

Safety – The Installer must carry out his operations in strict accordance with all applicable OSHA standards. Particular attention is drawn to those safety requirements involving entering confined spaces.

Cleaning of Sewer Line – It will be the responsibility of the Installer to remove all internal debris out of the sewer line (refer to standard sewer cleaning specification, contained in Technical Specification Section 6 – Cleaning)

Inspection of Pipelines – Inspection of pipelines must be performed by experienced personnel, trained in locating breaks and obstacles by closed circuit television. The interior of the pipeline must be carefully inspected to determine the location of any conditions, which may prevent proper installation of CIPP into the pipelines, and it must be noted so that these conditions can be corrected. A videotape and suitable log must be kept for later reference by the Owner.

Bypassing Sewage – The Installer, when required, must provide for the flow of sewage around the section or sections of mainline pipe where the service lateral designated for CIPP is located. The bypass must be made by plugging the line at an existing upstream manhole and pumping the flow into a downstream manhole, or adjacent system. The pump and bypass lines must be of adequate capacity and size to handle the flow.

The service lateral must be inactive during the time of installation. This is normally accomplished by turning off the homeowner's services, or requesting that the homeowner refrain from using his services during the required period of installation.

Line Obstruction – It will be the responsibility of the Installer to clear the line of obstructions such as solids, dropped joints, roots, or collapsed pipe that will prevent the insertion of the CIPP material. If inspection reveals an obstruction that cannot be removed by conventional sewer cleaning equipment, then the Installer must make a point repair excavation to uncover and remove, or repair the obstruction. Such excavation must be approved in writing by the Owner's representative prior to the commencement of the work, and will be considered as a separate pay item.

#### 13.07 INSTALLATION OF CIPP:

The Installer must designate a location where the felt tube will be vacuum impregnated prior to installation. The Installer will allow the Project Manager to inspect the materials and "Wet-out" Procedure. A catalyst system compatible with the resin and felt tube must be used.

The wet-out tube must be attached to a pull cable strung from the lateral and main to the downstream manhole. The tube will be pulled through the lateral so that the end ring projects into the main. The tube will be firmly seated against the mainline wall by pulling back on the end of the tube. The tube must be inflated with water or other appropriate medium to fully expand the tube and press it firmly against the walls of the existing lateral.

Curing – After inversion is completed, the Installer must supply suitable heat source and water recirculation equipment. The equipment must be capable of delivering hot water or other approved heat source throughout the section by means of a pre-strung hose, to uniformly raise the water temperature above the temperature required to affect a cure of the resin. This temperature will be determined by the resin/catalyst system employed.

The heat source must be fitted with suitable monitors to gauge the temperature of the incoming and outgoing water supply. Water temperature in the line during the cure period shall be recommended by the resin manufacturer.

Initial cure will be deemed complete, when inspection of the exposed portions of the CIPP appears to be hard and sound; and the temperature gauge indicates that the temperature is of a magnitude to realize an exothermic. The cure period shall be of a duration recommended by the resin manufacturer, as modified for the CIPP process, during which time the recirculation of the water and cycling of the heat exchanger to maintain the temperature continues.

Cool-down – the Installer shall cool the hardened CIPP to a temperature below 100 degree F before relieving the pressure in the pressure apparatus. Cool-down may be accomplished by the introduction of cool air into the pressure apparatus to replace water being forced out of the pressure apparatus. Care must be taken to maintain proper pressure throughout the cure and cool-down period.

Finish – The finished CIPP must be continuous over the entire length of an inversion run and be as free as commercially practical of dry spots, lifts, and delamination. The lateral CIPP must not inhibit the closed circuit television post video inspection of the mainline or service lateral pipes.

During the warranty period, any defects which will affect the integrity of strength of the CIPP must be repaired at the Installer's expense, in a manner mutually agreed upon by the Owner and the Installer.

After the work is completed, the Installer will provide the Owner with a videotape showing the completed work, including the restored conditions.

#### 13.08 CLEAN-UP:

Upon acceptance of the installation work, the Installer must restore the project area affected by his operations.

#### **13.09 POST VIDEO:**

At the completion of the rehabilitation of a pipe-line a video inspection CD, or other means, of the completed line segment will be given to the Project Manager by the Contractor. The Project Manager will use this inspection to determine if this line has been restored in a satisfactory fashion.

This inspection must be performed, one section at a time, by closed circuit color television. The flow entering the section being inspected should be plugged. The television camera used for this inspection must be one that is specifically designed and constructed for such conditions. Picture quality and definition must be to the complete satisfaction of the Project Manager. If necessary, equipment will be removed and no payment made until satisfactory inspection is made. The camera must be pushed through the pipe slowly in order to fully inspect for any defects. Location records must be kept by the Contractor which will clearly show the exact location, in relation to adjacent manholes. A computer-generated copy of this log and data disk must be supplied to the Project Manager.

# TECHNICAL SPECIFICATIONS SECTION 14

# CIPP SERVICE LATERAL RECONSTRUCTION FROM MAINLINE PIPE (LONG SEGMENT)

# 14.01 DESCRIPTION:

Work under this item will provide for the rehabilitation of service lateral sanitary sewer lines (normally without excavation), by the installation of a resinimpregnated, flexible, felt tube, inverted into the existing service lateral utilizing a pressure apparatus positioned in the mainline pipe. Curing must be accomplished by circulating hot water or other approved method to cure the resin into a hard impermeable pipe within-a-pipe. When cured, the cured-in-place pipe (CIPP) should extend over the length of the inversion in a continuous tight fitting, watertight pipe-within-a-pipe, to effect a water seal with the rehabilitated mainline pipe.

Materials will be governed by the requirements of Technical Specifications Section 9 - "Pipe Rehabilitation by installation of Cured-in-Place Pipe".

# 14.02 REFERENCE SPECIFICATIONS:

This specification references ASTM test methods, which are made a part hereof by such reference and must be the latest edition and revision thereof.

#### 14.03 GENERAL CORROSION REQUIREMENTS:

The finished cured-in-place product must be fabricated from materials which, when cured, will be chemically resistant to withstand internal exposure to domestic sewage.

All constituent materials must be suitable for service in the environment intended. The final product should not deteriorate, corrode, or lose structural strength that will reduce the projected product life.

#### 14.04 CIPP MATERIALS:

A flexible, felt tube shall be fabricated to a size that, when installed, will neatly fit the internal circumference of the conduit specified by the Owner. Allowance should be made for circumferential stretching during insertion.

The minimum length will be that deemed necessary by the Installer, as approved by the Owner, to effectively span the distance from the lateral connection at the main to the desired termination location in the service lateral pipe. The installer must verify the lengths in the field before the tube resin impregnation begins.

One end of the tube must include a flexible felt brim similar to the edge of a top hat. This must be a minimum of 2 inches wide, and should be of the general size and angle of the service connection.

Unless otherwise specified, the Installer shall furnish a specially designed unsaturated, polyester resin and catalyst system compatible with the CIPP process, that provides cured physical strengths specified herein.

### 14.05 PHYSICAL STRENGTH:

The structural performance of the finished pipe must be adequate to accommodate all anticipated loads throughout its design life. No cured-in-place pipe rehabilitation technology will be allowed that requires bonding to the existing pipe for any part of its structural strength. Only resin vacuum impregnation will be allowed. If reinforcing materials (fiberglass, etc.) are used, the reinforcing materials must be fully encapsulated within the resin or at the interface of the CIPP and the existing pipe.

Design methods are to be derived from traditionally accepted pipe formulae for various loading parameters and modes of failure. All equations will be modified to include totality as a design parameter. The design method must be submitted to the Project Manager for approval.

The final CIPP shall conform to the minimum structural standards listed below:

<u>Final CIPP</u> <u>ASTM Standard</u> <u>Results</u>

Flexible Stress ASTM D790 4,500 psi

Flexural Modulus of Elasticity ASTM D790 250,000 psi

The effectiveness of the seal between the installed service lateral CIPP and the mainline pipe must be documented by third-party testing. A written report, including the test procedures and results must be submitted to the Project Manager for approval.

#### 14.06 INSTALLATION PREPARATION:

The following installation procedures must be adhered to, unless otherwise approved by the Owner's representative.

Safety – The Installer must carry out his operations in strict accordance with all applicable OSHA standards. Particular attention is drawn to those safety requirements involving entering confined spaces.

Cleaning of Sewer Line – It will be the responsibility of the Installer to remove internal debris from the sewer line (refer to standard sewer cleaning specification contained in Technical Specification Section 6 – Cleaning).

Inspection of pipelines - Inspection of pipelines should be performed by experienced personnel, trained in locating breaks and obstacles by closed circuit television. The interior of the pipeline must be carefully inspected to determine the location of any conditions which may prevent proper installation of CIPP into the pipelines. It should be noted so that these conditions can be corrected. A video CD and suitable log should be kept for later reference by the Owner.

Bypassing Sewage - The Installer, when required, shall provide for the flow of sewage around the section or sections of mainline pipe where the service lateral designated for CIPP is located. The bypass shall be made by plugging the line at an existing upstream manhole and pumping the flow into a downstream manhole or adjacent system. The pump and bypass lines shall be of adequate capacity and size to handle the flow.

It is required that the service lateral be inactive during the time of installation. This is normally accomplished by turning off the homeowner's services or requesting that the homeowner relinquish using his services during the required period of installation.

Line Obstruction – It shall be the responsibility of the Installer to clear the line of obstructions such as solids, dropped joints, roots or collapsed pipe that will prevent the insertion of the CIPP material. If inspection reveals an obstruction that cannot be removed by conventional sewer cleaning equipment, then the Installer shall make a point repair excavation to uncover and remove or repair the obstruction. Such excavation shall be approved in writing by the Owner's representative prior to the commencement of the work and shall be considered as a separate pay item.

# 14.07 CIPP INSTALLATION:

The Installer will designate a location where the felt tube will be resin vacuum impregnated prior to installation. The Installer must allow the Owner to inspect the material and resin impregnation procedure. A catalyst system compatible with the resin and felt tube must be used.

The resin impregnated tube must be loaded inside pressure apparatus above ground. The pressure apparatus, with an end attached to a robotic device must be winched through the mainline pipe to the service connection. The robotic device, together with a television camera will be used to position the pressure apparatus' inversion elbow at the service connection opening. Air pressure, supplied to the pressure apparatus through an air hose, must be used to invert the resin impregnated tube though the lateral pipe. The inversion head will be adjusted to be of sufficient pressure to cause the impregnated tube to invert completely in the lateral pipe and hold the tube tight to the pipe wall. Care should be taken timing the elevated curing temperatures so as not to over-stress the tube.

The pressure apparatus should include a bladder, which inflates in the mainline pipe, effectively seating the brim portion of the tube tightly against the service connection.

Curing — After inversion is completed, the Installer must supply a suitable heat source and water recirculation equipment. The equipment must be capable of delivering hot water, or other approved heat source, throughout the section by means of a pre-strung hose, to uniformly raise the water temperature above the temperature required to affect a cure of the resin. This temperature should be

determined by the resin/catalyst system employed. The heat source should be fitted with suitable monitors to gauge the temperature of the incoming and outgoing water supply. Water temperature in the line during the cure period must be recommended by the resin manufacturer.

Initial cure will be deemed to be complete when inspection of the exposed portions of the CIPP appear to be hard, sound, and the temperature gauge indicates that the temperature is of a magnitude to realize an exothermic. The cure period must be of a duration recommended by the resin manufacturer, as modified for the CIPP process, during which time the recirculation of the water and cycling of the heat exchanger to maintain the temperature continues.

Cool-down —The Installer should cool the hardened CIPP to a temperature below 100 degrees F before relieving the pressure in the pressure apparatus. Care should be taken to maintain proper pressure throughout the cure and cool-down period. Cool-down may be accomplished by the introduction of cool air into the pressure apparatus to replace water being forced out of the pressure apparatus.

*Finish* - The finished CIPP must be continuous over the entire length of an inversion run, and be as free as commercially practical of dry spots, lifts, and delamination. The lateral CIPP should not inhibit the closed circuit television post video inspection of the mainline or service lateral pipes.

During the warranty period, any defects which will affect the integrity of strength of the CIPP will be repaired at the Installer's expense, in a manner mutually agreed upon by the Owner and the Installer.

After the work is completed, the Installer will provide the Owner with a digital CD showing the completed work, including the restored conditions.

#### 14.08 CLEAN-UP:

Upon acceptance of the installation work, the Installer must restore the project area affected by his operations.

#### 14.09 POST VIDEOS:

At the completion of rehabilitation of a pipe-line, a video CD inspection of the completed line segment will be given to the Project Manager by the Contractor. The Project Manager will use this inspection to determine if this line has been restored satisfactorily. This inspection must be performed, one section at a time, by closed circuit color television. The flow entering the section being inspected should be plugged. The television camera used for this inspection must be one that is specifically designed and constructed for such conditions. Picture quality and definition must be to the complete satisfaction of the Project Manager. If necessary, equipment will be removed and no payment made until satisfactory inspection is made. The camera must be pulled through the pipe slowly, in order to fully inspect for any defects. Location records should be kept by the Contractor, which will clearly show the exact location of all house connections, in relation to adjacent manholes.

# TECHNICAL SPECIFICATIONS SECTION 15

# LATERAL CONNECTION RECONSTRUCTION FROM MAINLINE BY CIPP METHODS (SHORT SEGMENT)

# 15.01 DESCRIPTION:

Work under this item will consist of the reconstruction of service lateral connection (normally without excavation), by the installation of resin impregnated flexible felt tube inverted into the existing service lateral, utilizing a apparatus positioned in the mainline pipe. Curing should be accomplished by circulating hot water, or other approved method, to cure the resin into a hard impermeable pipe. When cured, the pipe should extend over the length of the inversion in a continuous tight fitting, watertight, pipe-within-a-pipe, to affect a seal with the reconstructed pipe. This method will be used in locations where no clean out exists, and installation of one to five foot lengths of lining material would repair/reinforce the lateral to mainline connection.

Materials will be governed by the requirements of Technical Specification Section 9 – "Pipe Rehabilitation by Installation of Cured-in-Place-Pipe".

#### 15.02 **METHOD**:

A resin impregnated tube is loaded inside a pressure apparatus above ground. In the case of a non-man entry pipe, the pressure apparatus is attached to a robotic placement device and winched through the main pipe to the service connection. Air supplied to the pressure apparatus is used to invert the tube and hold it tightly against the lateral pipe wall. Pressure is maintained throughout a heat induced cure by either air/stream pressure, hot water pressure, or a combination of both. Upon completion of cure, the pressure apparatus is removed, leaving the newly formed CIPP.

This method involves the use of standard and non-standard felt tubes and inversion techniques, and a "Top Hat" seal at the mainline, in order to produce a CIPP in the lateral with one end remotely accessible, and the other end not accessible. When utilizing this method there is no subsequent cutting or trimming, nor a remote end to be stripped out.

# TECHNICAL SPECIFICATIONS SECTION 16

# PRESSURIZED FORCE MAIN PIPE REHABILITATION BY REINFORCED CURED-IN-PLACE PIPE

#### 16.01 GENERAL:

It is the intent of this specification to provide for the reconstruction of existing pressurized sewer force main by installing a Reinforced Cured-In-Place Pressure Pipe (RCPP) within an existing structurally deteriorated pipe, which has maintained its original shape. The rehabilitation will be accomplished by the use of the Insituform® RPP Process, or Project Manager approved equal. The process is defined as the reconstruction of a deteriorated sanitary pressure pipe by installation of a thermosetting, resin impregnated, reinforced flexible felt/fiber tube (coated on one side with polyethylene), utilizing a water column. Curing is accomplished by circulating hot water (or other approved fluid) throughout the length of the tube to cure the thermosetting resin into a hard impermeable pipe. The pipe will extend the full length of the original pipe and will provide a structurally sound, joint less, close-fitting, cured-in-place pressure pipe.

# 16.02 REFERENCED SPECIFICATIONS:

This specification references ASTM F1216 (Rehabilitation of pipelines by inversion and curing a resin impregnated tube), and ASTM D5813 (Cured-In-Place, Thermosetting Resin Sewer Pipe). In case of conflicting requirements between this specification and these referenced documents, this specification will govern.

#### 16.03 GENERAL CORROSION REQUIREMENTS:

The RCPP shall be fabricated from materials which, when cured, will be chemically resistant to withstand internal exposure to permitted storm water and sanitary sewerage.

# 16.04 MATERIALS:

- A. The reinforced flexible felt/fiber tube shall be fabricated to a size that, when installed, will neatly fit the internal circumference of the conduit. Nominal tube thickness will be per design guidelines specified herein, and indicated on the bid form. Additional thickness will be used as required by design requirements.
- B. The minimum length shall be that deemed necessary by the Contractor to effectively span the distance from the inlet to the outlet of the respective termination points, unless otherwise specified. The Contractor will verify the lengths in the field before impregnation of the tube with resin.
- C. Unless otherwise specified, the Contractor will furnish a flexible vinyl ester resin and catalyst system such as Dow Derekane 411 or Interplastic 8319, that provides the cured physical strengths specified herein.

- D. The materials used will result in an installed CIPP flow capacity, which will be equal to, or greater than, 100% of the original pipe's flow capacity when new.
- E. Internal mechanical compression fit end seals will be required to seal the ends of the RCPP within the existing force main. Victaulic Depend-O-Lock (BRICO) end seals, or approved equal, are required.

# 16.05 DESIGN REQUIREMENTS:

A. Physical Strength: The RCPP must conform to the minimum standards listed below, or to the current standards approved by ASTM. Pipe thickness must be designed per ASTM F1216-X1.

Physical Property	Test Method	Minimum Value	
Flexural Stress	#101 (Modified ASTM D-790)	4,500 psi	
Flexural	#101 (Modified ASTM D-790)	250,000 psi	
Modulus of			
Elasticity			

B. The RCPP must be designed to withstand internal pressures of up to 40 PSI as a standalone pipe (fully deteriorated host pipe). Design calculations will be submitted to the owner for review, prior to commencement of work. Burial depths of most mains are approximately 7 feet deep.

#### 16.06 PRE-INSTALLATION PROCEDURES:

The following pre-installation procedures must be adhered to, unless otherwise approved by the Project Manager.

- A. Safety The Contractor must carry out his operations in strict accordance with all applicable OSHA standards. Particular attention is drawn to those safety requirements involving work on an elevated platform and entry into a confined space.
- B. *Pre-inversion Cleaning* It shall be the responsibility of the Contractor to remove all loose debris located in the sanitary sewer pipe.
- C. Pre-inversion Inspection Inspection of sanitary sewer pipe must be performed by experienced personnel. Said personnel should be trained in the location of breaks, obstacles, and connections by closed circuit television inspection. The interior of the pipe must be carefully inspected to determine the location of any conditions which may prevent the proper installation of the RCPP, and it must be noted so that these conditions can be corrected. A videotape and suitable log should be kept for later reference by the Owner and/or Contractor.
- D. Line Obstructions If inspection reveals an Obstruction or Protrusion (such as attached mortar, dropped joints, protruding taps, or collapsed pipe) that cannot be removed by conventional pipe cleaning equipment, and will prevent completion of the inversion process, a point repair will be made by the Owner, or the Owner's designated Contractor.
- E. By-passing When required for acceptable completion of an inversion process task, and/or to avoid damage due to sewer spills or overflows, the Contractor will provide for sanitary water flow maintenance around the section or sections of pipe designated for the inversion process. The bypass will typically be made by plugging the line at an existing upstream manhole and pumping the flow into a downstream manhole, or adjacent system. The pump and bypass lines shall be of adequate capacity and size to handle the anticipated flow. Bypassing of sanitary sewerage into the storm water system will not be allowed.

# 16.07 INSTALLATION PROCEDURES:

- A. Wet Out The Contractor must wet-out the RCPP tube, using distribution rollers, and vacuum to thoroughly saturate the felt fiber tube, prior to installation. The Contractor will allow the Project Manager to inspect the materials and wet out procedure. A catalyst system compatible with the resin and tube must be used.
- B. Insertion The wet out tube must be inserted through an approved access, and the application of a fluid column sufficient to fully extend it to the next designated termination point. The fluid column will be adjusted to be of sufficient height to cause the impregnated tube to hold tight against the existing pipe wall.
- C. Curing After the insertion is completed, the Contractor should supply a suitable heat source and circulation system capable of delivering hot fluid uniformly throughout the section, to effect a consistent cure of the resin. The curing schedule must be that recommended by the resin/catalyst system manufacturer for pipeline rehabilitation.
- D. Cool-down The Contractor shall cool the hardened RCPP to a temperature below 100 degrees Fahrenheit before relieving the fluid column. A constant fluid column height is to be maintained until cool-down is completed. Care should be taken in the release of the fluid column, so that a vacuum will not be developed that could damage the newly installed CIPP.
- E. Warranty The finished CIPP must be continuous over the entire length of an inversion run, and be as free as commercially practicable from visual defects. It must also meet the water tightness test requirements specified below. During the warranty period, any defects that will affect the integrity or strength of the CIPP will be repaired at the Contractor's expense, in a manner mutually agreed to by the Owner and the Contractor. The warranty period is for one year after acceptance by the Parish.

#### 16.08 SEALING AT TERMINATIONS:

The Contractor must install an internal compression fit mechanical seal at the ends of the newly installed RCPP to prevent any leakage. Victaulic Depend-O-Lock (BRICO) end seals, or approved equal, are required.

#### 16.09 TESTING:

The water tightness of the CIPP will be gauged by monitoring the water level in the inversion tube while curing. The water testing must be done directly on the finished product.

A service test will be performed after the installation is complete, with the termination points exposed for inspection. The force main will be placed in service and observed for a 24 hour period. Any leaks of the rehabilitated pipe will be corrected by the contractor, at no cost to the Parish.

The Contractor will perform a test on a sample of the cured installed liner for each work order requested by the Owner. These tests will be conducted in accordance with Modified ASTM D-790 and will include the following:

- a. Thickness of sample
- b. Flexural strength

#### c. Flexural modulus of elasticity

The final installed RCPP thickness must meet or exceed the minimum design thickness calculated for the installation to be deemed acceptable by the owner.

#### 16.10 CLEAN-UP:

Upon acceptance of the installation work and testing, the Contractor will restore the project area affected by his operations.

#### 16.11 POST REHABILITATION VIDEOS:

At the completion of the rehabilitation of a pipe-line, a video inspection CD of the completed line segment will be given to the Project Manager by the Contractor. The Project Manager will use this inspection to determine if this line has been restored satisfactorily.

This inspection must be performed, one section at a time, by closed circuit color television, using a radial view camera. The flow entering the section being inspected should be plugged, as previously described. The television camera used for this inspection must be one that is specifically designed and constructed for such conditions. Picture quality and definition must be to the complete satisfaction of the Project Manager. If necessary, equipment will be removed, and no payment made until satisfactory inspection is made. The camera must be pulled through the pipe slowly, in order to fully inspect for any defects. Location records should be kept by the Contractor, which clearly show the exact location of all house connections, in relation to adjacent manholes. A computer-generated copy of this log and data disk must be supplied to the Project Manager, per Sections 24 and 25.

# 16.12 PATENTS:

The Contractor must warrant to the Owner that the methods, materials, and equipment used herein, where covered by licenses, are furnished in accordance with such licenses. The bid prices must include any applicable royalties and fees in accordance with such licenses. The Contractor shall warrant and hold harmless the Owner against all claims for patent infringement and any loss thereof.

#### **TECHNICAL SPECIFICATIONS**

#### **SECTION 17**

# SEWER MANHOLE/WET WELL REHABILITATION BY A CEMENTITIOUS LINING METHOD

#### 17.01 SCOPE OF WORK:

This item will provide for manhole reconstruction to stop inflow, infiltration, and exfiltration; restore structural integrity; and provide protection against corrosion.

These specifications will govern all work, materials, and equipment required for manhole rehabilitation. This method will eliminate infiltration, provide corrosion protection, repair voids, and restore the structural integrity of the manhole. This will be done by applying a monolithic fiber-reinforced structural/structurally enhanced cementitious liner to the wall and bench surfaces of brick, concrete, or any other masonry construction materials.

Described herein are procedures for manhole preparation, cleaning, application, and testing. The applicator, shall furnish all labor, equipment, and materials for applying a cementitious mix to form a monolithic liner of a minimum  $\frac{1}{2}$  inch thickness with machinery specially designed for application. All aspects of the installation must be in accordance with the manufacturer's recommendations.

Lining materials must be those manufactured by AP/M Permaform – Johnston, IA, or Project Manager approved equal.

# 17.02 PATCHING MIX:

A quick setting cementitious material must be used as a patching mix, and must be mixed and applied according to manufacturer's recommendations. Said patching mix must meet the following minimum requirements:

A. Compressive Strength (ASTM C-109) 6 Hrs. 1400 psi

B. Shrinkage (ASTM C-596) 0% at 90% R.H.

C. Bond (ASTM C-321) 28 days, 150 psi

D. Density, when applied 105+ (-) pcf

# 17.03 INFILTRATION CONTROL MIX:

A rapid setting cementitious product, specifically formulated for leak control, shall be used to stop minor water infiltration. The product must be mixed and supplied according to manufacturer's recommendations, and must have the following minimum requirements:

A. Compressive Strength (ASTM C109)

600 psi 1 hour

1000 psi 24 Hrs.

B. Bond (ASTM C-32)

30 psi 1 hour

80 psi 24 Hrs.

#### 17.04 GROUTING MIX:

- A. Cementitious grout must be used for stopping very active infiltration and filling voids. It must be mixed and applied according to manufacturer's recommendations. The cementitious grout must be volume stable, have a minimum 28 day compressive strength of 250 psi, and a one (1) day strength of 50 psi.
- B. Chemical grouts may be used for stopping very active infiltration. It must be mixed and applied per manufacturer's recommendations.

# 17.05 **LINER MIX**:

A cementitious liner must be used to form a structurally enhanced monolithic liner covering all interior manhole surfaces. It must have the following minimum requirements at 28 days:

A. Compressive Strength (ASTM C-190)	10,000 psi
--------------------------------------	------------

B. Tensile Strength (ASTM C-496) 600 psi

C. Flexural Strength (ASTM C-293) 600 psi

D. Shrinkage (ASTM C-596) @ 90 degrees relative humidity 0% psi

E. Bond (ASTM C-321) 130 psi

F. Density, when applied 105+ (-) pcf

The cementitious liner must be made with Calcium Aluminate Cement, and must be used according to manufacturer's recommendations in applications where there is evidence of sever sulfide conditions (pH less than 3.0).

# 17.06 WATER:

Water must be clean and potable. Questionable water will be tested by a testing laboratory in, accordance with ASTM C-04. Potable water need not be tested.

# 17.07 OTHER MATERIALS:

No other material will be used with the mixes described in 17.02, 17.03, 17.04, and 17.05 without prior approval, or recommendations from the manufacturer.

#### 17.08 EQUIPMENT:

- A. Specially designed machines consisting of: an optimized progressive cavity pump, capable of producing a minimum of 250 psi pumping pressure; a contra-blend mixer with twin ribbon paddle and end discharge; and an air system for spray application of product, must be used for applying the cementitious lining.
- B. The Contractor will be responsible for ensuring that application and installation of the cementitious liner is made in accordance with, and approved by the manufacturer.

#### 17.09 PREPARATION:

- A. Covers must be placed over invert to prevent extraneous materials from entering the sewer lines.
- B. All foreign material must be removed from the manhole wall and bench, using a high pressure water spray (minimum 1200 psi). Loose and protruding brick, mortar, and concrete should be removed using a mason's hammer and chisel and/or scraper. Any large voids must be filled with quick setting patching mix.
- C. Active leaks must be stopped using quick setting, specially formulated mixes, according to manufacturer's recommendations. Some leaks may require weep holes to localize the infiltration during the application. When complete, the weep holes must be plugged with the quick setting mix, prior to the final liner application. When severe infiltration is present, drilling may be required in order to pressure grout, using a cementitious grout. Manufacturer's recommendation must be followed when pressure grouting is required.

#### 17.10 INVERT REPAIR:

- A. After all preparation has been completed, all loose materials must be removed, and the wall must be washed again.
- B. Any bench, invert, or service line repair must be made at this time, using the quick setting patching mix, and shall be used according to manufacturer's recommendations.
- C. Invert repair must be performed on all inverts with visible damage or infiltration. After blocking flow through the manhole, and thoroughly cleaning invert, the quick setting patch mix should be applied to the invert in an expeditious manner. The mix must be troweled uniformly onto the damaged invert, extending out to the base of the manhole, to sufficiently tie into the structural/structurally enhanced monolithic liner to be applied. The finished invert surfaces must be smooth and free of ridges. The flow may be reestablished in the manhole within 30 minutes after placement of the mix.

#### 17.11 MIXING:

- A. For each bag of product, use the amount of water specified by the manufacturer and mix using the approved equipment, in accordance with the manufacturer's equipment.
- B. Place the mix into the holding hopper and prepare another batch, with timing such that the nozzle man can spray in a continuous manner, without interruption, until each application is complete.

# 17.12 SPRAYING:

# 1st Application

A. Prior to spraying, the surface must be clean, and free of all foreign material. The surface should be damp, without noticeable water droplets or running water, but totally saturated, just prior to application. Materials must be spray applied from the bottom of the wall to the top, to a minimum uniform thickness to insure that all cracks, crevices, and voids are filled; and a relatively smooth surface remains right after troweling. The light troweling is performed to compact the material into voids and to set the bond.

2<sup>nd</sup> Application

B. A second application is applied after the 1<sup>st</sup> application has begun to take an initial set (disappearance of surface sheen which could take 15 minutes to 1 hour, depending on ambient conditions) to assure a minimum total finished thickness of ½ inch. Again, application shall be from the bottom up. The surface must then be troweled to a smooth finish, taking care not to over trowel, which could bring additional water to the surface and weaken it. Manufacturer's recommendations must be followed whenever more than 24 hours have elapsed between applications. A brush finish is acceptable, and is applicator's option.

# 3<sup>rd</sup> Application

C. The wooden covers must be removed at this time, and the bench sprayed so that a gradual slope is produced from the walls to the invert, with the thickness at the edge of the invert being no less than ½ inch. The wall/bench intersection shall be rounded to a uniform radius the full circumference of the intersection.

Mortar shall be installed when ambient temperatures are above 40 degrees F. Applying at temperatures below 40 degrees F is not recommended.

### 17.13 CURING:

Caution should be taken to minimize exposure of applied product to sunlight and air movement. If application of 2nd coat is to be longer than 15 minutes after completion of application of 1<sup>st</sup> coat, the manhole cover shall be set back in place. At no time should the finished product be exposed to sunlight or air movement for longer than 15 minutes before replacing the manhole cover. In extremely hot and arid climates, manhole should be shaded while reconstruction is in process.

The final application shall have a minimum of four (4) hours cure time before being subjected to active flow.

Traffic shall not be allowed over manholes for 24 hours after reconstruction is complete.

# 17.14 **WEATHER**:

The Contractor will apply cementitious lining in accordance with manufacturer's requirements concerning weather conditions.

#### 17.15 PRODUCT TESTING:

Four – 2 inch cubes must be cast each day, or from every 50 bags of product used, and shall be properly labeled and sent in for testing, in accordance with the Owner's or Manufacturer's directions, for compression strength testing, as described in ASTM C-109.

#### 17.16 FINAL ACCEPTANCE TESTING:

At the direction of the Project Manager, the rehabilitated manholes must be tested as follows:

Visually verify the absence of leaks.

Perform an exfiltration test as follows:

- A. For manholes 0 6 foot deep If water loss is one (1) inch or less in five minutes manhole is acceptable.
- B. For manholes over 6 feet deep If water loss is one (1) inch or less plus 1/8 inch per additional foot of depth in five minutes, manhole is acceptable.

# 17.17 VACUUM TEST:

Vacuum Test Timetable Manhole Diameter

<u>Depth – feet</u>	48 inches	60 inches	72 inches	96 inches
4	10 sec.	13 sec.	16 sec.	19 sec.
8	20 sec.	26 sec.	32 sec.	38 sec.

12	30 sec.	39 sec.	48 sec.	57 sec.
16	40 sec.	52 sec.	64 sec.	76 sec.
20	50 sec.	65 sec.	80 sec.	95 sec.
24	60 sec.	78 sec.	96 sec.	114 sec.
+ Each 2'	+5 sec.	+6.5 sec.	+8.0 sec.	+9.5 sec.

- A. Manhole depths must be rounded to the nearest foot. Testing times for intermediate values of manhole depth must be interpolated. For manhole depths greater than 24 feet, the values shown in the last line of the table should be added to the 24-foot value for each additional 2 feet of depth.
- B. If the manhole or structure fails the vacuum test, the Contractor must perform additional repairs and repeat the test procedures until satisfactory results are obtained.
- C. After the manhole rehabilitation work has been completed, the Contractor will allow the Project Manager to visually inspect manhole. The finished surface must be free of blisters, "runs", "sags", or other indications of uneven lining thickness. There must be no evidence of visible leaks,

# 17.18 WARRANTY:

Contractor will warrant that installation of the cementitious liner was performed in accordance with manufacturer's recommendation and will remain free from defects, failure of the liner due to defective material, installation, or workmanship for a period of five years from the Date of Completion.

# TECHNICAL SPECIFICATIONS SECTION 18

# REMOVAL AND RESTORATION OF ROADWAYS, CONCRETE CURB AND GUTTERS, SIDEWALKS AND DRIVEWAYS

#### 18.01 DESCRIPTION:

All work performed under this Section must be in accordance with the appropriate section of the LOUISIANA STANDARD SPECIFICATIONS FOR ROADS AND BRIDGES (2016 edition and/or latest revisions), and/or Jefferson Parish Standard Details, unless modified herein or directed in the field. American Disability Act (ADA) requirements, as well as other Federal, State, or local code requirements will apply.

This section will include the removal and restoration of all paved and unpaved roadway and walkway areas encountered on the project. This work will include replacement of pavements, shell or stone surfaces, base courses, curbs, gutters, and other improvements removed or damaged by the Contractor during the course of this Contract.

The unit bid price for a removal and replacement item must include:

- Cost of removal
- Saw-cutting (as required)
- Transportation and proper disposal of the removed material
- Placement AND REMOVAL of temporary walking/parking surface in sidewalk and driveway area (temporary asphalt)
- Actual permanent replacement cost

Under no circumstances, will removed concrete or asphalt material be allowed to be stockpiled at the site. All debris is to be removed from the site at the end of the work day. The Contractor is not allowed to stockpile any new roadway bedding material in roadways overnight.

Temporary asphalt surfacing will be used in roadway/parking locations, as directed by the Engineer. This asphalt will be placed upon completion of work, with permanent repair being made in approximately 30 days. Payment for placement of temporary asphalt will be made under the applicable bid item.

Unless otherwise approved by the Project Manager, the kind of pavement to be constructed in replacement work shall correspond with the kind removed from the area, or as shown on the detail sheet. The respective kind of concrete (asphalt or Portland cement) must be placed, shaped, and finished to establish grade and cross section, by practicable means, which will result in a dense, uniform-textured pavement. Abutting edges of old pavement must be trimmed of all loose fragments, painted with asphalt, or thoroughly moistened with water, as appropriate, to provide good bond between the old and new pavement.

All manholes in the pavement area shall be isolated (boxed out), by means of placing an approved circular ring (joint) around them, square or rectangular sections, using flexible joint material. Manholes in sidewalk areas will be formed so that an expansion joint is on both sides of the manhole.

All backfilled trenches must be properly maintained by the Contractor, at no direct pay, until such time as reconstruction is begun.

The Contractor is responsible for notifying the Owner, testing lab, and Jefferson Parish representative, at least 24 hours in advance of any placement of concrete or asphalt.

In addition, the Contractor is responsible for the proper and safe protection of the work area.

# 18.02 REMOVAL OF SURFACING:

All surfaces will initially be removed to a distance of one foot (1') outside the limits of the trench. Upon completion of all work, all concrete must be removed and replaced to the nearest joint, unless otherwise directed by the Project Manager or Owner. Final removal of asphalted concrete roadways will be to a minimum distance of three feet (3') from the edge of the trench and neat lined at this point. For driveway and sidewalk removal, if a joint does not exist at the property line or in close proximity to it, then the Contractor will make a saw-cut along this property line. There will be no direct payment for saw-cutting. Material removed will be

properly disposed of at no direct pay. There will be no direct payment for the removal of curbing, which is attached to, and removed with the roadway surface.

#### 18.03 BASE COURSE:

This work consists of furnishing and placing granular material for the roadway base, as per plan details, and in accordance with Section 501 and 1002 of the LOUISIANA STANDARD SPECIFICATIONS FOR ROADS AND BRIDGES (2016 and/or latest edition), unless otherwise specified.

The placement of the road base material will be confined to the limits of the trench line. If, due to the construction operation, the adjacent base material is disturbed adversely, the Contractor must remove and replace the material, as directed by the Project Manager. This work will be done at the Contractor's, cost unless the disturbance is beyond the Contractor's control. Density tests will be taken on the roadway base materials, as directed by the plans. The Contractor shall not be allowed to restore the roadway until the road base material in the trench area meet or exceed the following:

Density Requirements (Standard Proctor)

- A. Base Course (sand) -97%
- B. Base Course (Shell or sand/shell)-97%
- C. Base Course (stone) -95%
- D. Sub-base (sand) -97%

# 18.04 BASE MATERIAL:

Soil for base material must be pumped sand, obtained from the Mississippi River. It shall be an AASHTO Classification A-4, or better, having a Plasticity Index not to exceed "4", and a liquid not to exceed "25", and shall be free from trash, weeds, large lumps, humus, or any other deleterious matter.

#### 18.05 ASPHALT CONCRETE PAVING:

A. Permanent re-surfacing

All materials and construction under this section shall conform to Section 501 of the LOUISIANA STANDARD SPECIFICATIONS FOR ROADS AND BRIDGES (2016 Edition and/or latest revision), unless otherwise specified. The gradation of the mix shall be Type 3, AC-30 for any temporary repairs, as well as the permanent Wearing Course and Binder Course specified in Table 1 of the referenced section. The thickness of each course is as shown on the standard details.

Saw-cutting will be required along the entire limits of the removed asphalt area; if in contact with existing asphalt.

Job Mix Formula (per latest DOTD Standards)

1. Wearing Course (Type 3, AC-30)

2. Binder Course (Type 3, AC-30)

3. Base Course (Type 5A, AC-30)

# B. Temporary Re-surfacing

Until permanent roadway pavement surfacing is placed, temporary asphalt re-surfacing, a minimum of 2 inches thick shall be placed and maintained at locations determined by the Owner's Representative. At major intersections and critical locations, a greater thickness may be ordered. Temporary resurfacing must be placed as soon as the condition of the backfill is suitable to receive it, and must remain in place until the condition of the backfill is suitable for permanent re-surfacing.

The temporary asphaltic concrete any be any type mixture listed in Section 501, except Type 5B, of the LOUISIANA STANDARD SPECIFICATIONS FOR ROADS AND BRIDGES (2016 Edition and/or latest revision).

Prior to placing temporary re-surfacing, the Contractor must level and compact the backfill on which the surfacing is to be placed. The grade of the backfill on which the re-surfacing is to be placed must be such as to

provide the full thickness of temporary re-surfacing specified. The temporary resurfacing must be placed, rolled, maintained, removed, and disposed of by the Contractor.

# 18.06 CONCRETE PAVEMENT:

All materials and construction under this section shall conform to Section 601 of the LOUISIANA STANDARD SPECIFICATIONS FOR ROADS AND BRIDGES (2016 Edition and/or latest revision), unless otherwise specified.

All existing concrete pavement, curbs, walks, and driveways must be replaced to the line, grade, and thickness that existed prior to construction, or as directed by the Project Manager. Details of existing joints will be supplied at the time of construction. Prior to construction in an area, the Contractor must adequately reference the existing curb and other pavement elevations, to establish the preconstruction conditions.

The restored paving elevations must correspond to the elevations established prior to construction in the area, or as modified by the Project Manager, to allow for drainage of the area.

Curbs and sidewalks will be removed to the nearest joint scorings. Concrete street panels will be removed from joint to joint, unless otherwise directed by the Owner or Project Manager. Should a field condition require saw-cutting the existing pavement, there will be no direct payment. All such expenses should be included in the applicable bid item for removal and replacement of paving.

Portland Cement Concrete Requirements for roadway pavement and curbs:

- a. Seven (7) sacks of cement per cubic yard
- b. 2" to 4" slump
- c. The use of Fly Ash in the mix will not be permissible

The pavement will not be opened to traffic until a compressive strength of 4,000 psi is attained. In no case will the pavement be opened to traffic within a three (3) day period after the concrete has been placed.

The final roadway surface finish must be a "Drag Finish" as defined in the LOUISIANA STANDARD SPECIFICATIONS FOR ROADS AND BRIDGES (2016 Edition and/or latest revision), or as otherwise directed by the Department of Public Works.

# 18.07 CURBS, GUTTERS, AND MISCELLANEOUS:

Replacement of curbs, gutters, walks, dikes, and other like structures will consist of similar and matching construction to that of adjoining undisturbed structures. Such construction must be at least equal in respects to that of the structures removed in the work, and as shown on the standard details. The replacement of items not covered in the bid form shall be handled by the Owner, or through a separate contract.

#### 18.08 TESTING REQUIREMENTS:

All material and construction testing will be done as directed by the Project Manager, or, as follows:

#### Asphalt Roadways:

- a. One base thickness verification per 600 square yards or fraction thereof.
- b. One density test on the sub-base (if applicable) and base material per 600 square yards or fraction thereof.
- c. One pavement core for the thickness verification per 600 square yards of pavement or fraction thereof.

#### Concrete Roadways:

a. One slump test minimum per 100 cubic yards (accumulated volume) of

concrete or fraction thereof.

- b. Four (4) cylinders minimum per 100 cubic yards (accumulated volume) of concrete or fraction thereof.
- c. Independent densities, slumps, cylinders, cores, etc. will be required for isolated areas.

An initial testing will be performed by the Parish's testing laboratory, at the Parish's expense. All costs for testing to determine compliance after the initial test shall be borne by the Contractor, and will be deducted from payments due to the Contractor. The total deductions for testing costs to be paid for by the Contractor will be included in the reconciliation of final quantities. The Contractor is also responsible for the cost of all canceled or re-scheduled tests.

There shall be no adjustment in bid prices for pavement thickness deficiencies. If the concrete core is less than specified, two additional cores on the same slab within a five- foot (5') radius must be taken. If one of these cores is less than specified, then the entire panel (joint to joint) must be removed and additional cores on other adjacent panels within the core range (600 square yards) must be taken and the same procedure followed.

Joint Sealers: All joints in roadway surface shall be cleaned and sealed with approved joint sealant.

#### 18.09 USE OF WIRE MESH:

Wire mesh or rebar must be used in the replacement of sidewalks, driveways, and roadways, if it existed in the removed sections. The size and type used shall, at a minimum, be equal to, or better than that removed. There shall be no additional payment for the use of wire mesh.

#### 18.10 CLEANING FOR ACCEPTANCE OF STREET:

Prior to acceptance, the Contractor will be required to clean up any street as a result of construction activity, as directed by the Project Engineer/Owner's Representative.

### TECHNICIAL SPECIFICATIONS SECTION 19

#### TRAFFIC REGULATIONS

#### 19.01 REQUIREMENTS:

A. The Contractor will be responsible for the development and implementation of a traffic control device plan (TCDP), which will provide for the safe and expeditious movement of traffic through construction zones. A construction zone is defined as the immediate area of actual construction, which interferes with the driving or walking public. The TCDP must comply with the requirements set forth in the Manual on Uniform Traffic Control Devices (MUTCD), as revised, and with the general requirement stipulated below.

The TCDP for the site shall address the conditions for providing traffic flow within the zone during the influence of construction. The TCDP shall be schematically drawn of sheet(s) large enough to show adequate details and be easily readable and reproducible. If larger than eleven inches by seventeen inches (11" x 17"), the sheet(s) shall be submitted with a reproducible transparency so the Owner and Engineer can produce additional copies, as needed.

The TCDP must be designed and stamped by a Professional Engineer registered in the State of Louisiana, who is qualified by education and experience. Said Engineer must perform this work to the standards of practice established by the Louisiana State Licensing Board for Professional Engineers and Land Surveyors. This project will involve the following:

- Traffic Control through Construction Zones
- Urban experience in MUTCD applications, plan preparations, studies in volume, speed, pedestrians, and tort liability

The Contractor must submit copies of the TCDP to the Engineer for the Owner's and Jefferson Parish Traffic Engineering Division's review and approval. Such approval is required prior to the start of any work, which might affect the traffic pattern in the area.

#### B. Traffic Control

The necessary precautions shall include, but not be limited to: proper construction warning signs, signals, lighting devices, markings, barricades, channelization, and hand signaling devices (flagging operation). The Contractor will be responsible for installation and maintenance of all devices and requirements, for the duration of the construction period.

All work shall be performed in accordance with LDOTD standard specification, 2006 edition, except as noted. In addition to items shown on the plans, traffic control devices shall be in accordance with the MUTC.

The Contractor will be responsible for removal, relocation, or replacement of any traffic control device in the construction area, which exists as part of the normal pre-construction traffic control scheme. Any such actions will be performed by the Contractor under the supervision of the Department of Engineering, Traffic Engineering Division, and in accordance with the Specifications, unless otherwise specified.

The Contractor will consult with the Project Engineer and the Jefferson Parish Traffic Engineering Division immediately, on any vehicular/pedestrian safety or efficiency problem incurred as a result of construction of the project. If warranted, the Contractor's Engineer must make adjustments to the TCDP, and the Contractor must immediately implement the revised TCDP.

The Contractor is responsible for daily monitoring of traffic control devices, and must make appropriate changes to correspond to conditions.

A qualified Engineer must be provided by the Contractor to inspect the job site at the beginning of the project, after significant changes, and at 30-day intervals or more frequently, depending on the duration of the construction activity. A written report submitted to the Contractor, Project Engineer/Owner, and the Jefferson Parish Traffic Engineering Division, verifying compliance with the plan, adequacy of traffic control devices, and operating conditions will be required for each inspection. All deficiencies noted by the report must be corrected by Contractor.

As stated above, the Contractor will be responsible for development of a TCDP whenever normal traffic patterns are altered. Development of a "general" TCDP,

which may be used in most residential areas on low volume streets (pending approval of the Owner) shall be considered a subsidiary obligation of the Contractor. Traffic Control Device Set Up, and Traffic Control Device Operation for implementation of this TCDP will also be considered a subsidiary obligation of the Contractor.

#### **GENERAL NOTES**

In these notes, the term "ENGINEER" shall mean "QUALIFIED TRAFFIC ENGINEER".

- The design and application of all signals, pavement markings, channelizing devices, and warning signs must conform to the "Louisiana Manual on Uniform Traffic Control Devices", newest Edition as Revised, and the "Work Area Traffic Control Handbook" of Jefferson Parish.
- 2. Channelizing and delineation devices must be used to mark all construction areas. These must be Type II and/or Type III barricades, and/or barrels, all fully reflectorized with lights.
- 3. Traffic control devices must be used to mark all construction areas. These must be Type II and/or Type III barricades, and/or barrels, all fully reflectorized with lights.
- 4. Any temporary devices not applying to an appropriate situation, or that are no longer required, must be covered, removed, or obliterated by the Contractor.
- 5. The roadway and all traffic control devices must be restored to original conditions by the Contractor.
- 6. All excavation must be covered, backfilled, or protected, as directed by the Project Engineer, fully delineated (See Note 2) at night, and when work is not in progress. Excavated pits, etc. must be fully fenced or barricaded (See Note 2), to prevent access by pedestrians.
- 7. All materials and machinery must be stored outside of the road surface; creating no sight problems, and fully delineated, as in Note 2.

- 8. If sections of roadway are totally closed, the Contractor must notify the Sheriff's Traffic Division, 911 Operations, the Fire Department, and any major traffic generators (i.e. schools, etc.). A three working day, minimum, advance notice will be required.
- 9. On totally closed sections of the roadway, the Contractor must provide access for local traffic only.
- 10. Barrels used for channelizing and delineation devices as part of this traffic control device plan must be weighted with sandbags, and fully reflectorized, with lights.
- 11. The Contractor must check traffic control devices on a daily basis. At a minimum, these devices must be checked when beginning and ending the work day, to insure adherence to the plans, and proper adequacy of devices for day and night visibility. On weekends, devices must be checked a minimum once per day.
- 12. The Engineer must inspect the job site at beginning and end, after significant changes, and at 30-day intervals. A written report must be submitted to the Contractor, and to Jefferson Parish Department of Public Works; verifying compliance with the plan, adequacy of traffic control devices, and operating conditions. All deficiencies noted by the report must be corrected by the Contractor. The Contractor must notify the Engineer immediately of any significant changes to the traffic control devices and operating conditions.
- 13. Flagman and/or Sheriff's control must be provided, as needed, and specified by the Engineer.
- 14. At the time of construction, any additional traffic control devices which may be required by the Engineer, the Jefferson Parish Department of Public Works, or the Contractor must be provided by the Contractor.
- 15. Yellow, high visibility, pennant barrier flagging (nylon rope with plastic pennants) must be strung between Type II barricades and barrels/drums, only as directed by the Engineer.
- 16. This traffic control device plan indicates general traffic control devices to be used on this project. It is anticipated that conditions will vary, depending on the phase under construction. The arrangement of those devices will be reviewed on a day-to-day

basis. Should the Contractor have any question as to the arrangement of the devices, the Engineer shall be notified to make an inspection of the site.

- 17. The Contractor must provide for the movement of pedestrians at all times during construction. Care should be taken to keep existing sidewalks free of obstructions that may hinder pedestrian movements. If existing sidewalks must be obstructed, the Contractor must provide for the movement of pedestrians by posting appropriate signing, such as, "Sidewalk Closed Use other Side of Street". Signing shall be reflectorized, and lighted at night. Also, where trenches are excavated outside of the roadway surface, the Contractor must provide at least one accessible crossing of the backfilled trench area for each dwelling, for use by pedestrians.
- 18. The Contractor shall provide as much access as possible to area businesses.

#### **TECHNICAL SPECIFICATIONS**

#### **SECTION 20**

#### BY-PASS/EMERGENCY PUMPING

#### 20.01 SCOPE OF WORK:

This section provides for furnishing all equipment, fuel, labor, and materials necessary to set-up, operate, and maintain by-pass/emergency pumping. The Project Manager will assist with the quantities and disposition of water to be pumped. The Contractor will provide the necessary equipment to meet these minimum requirements. Contractor shall provide the locations, with GPS, of each portable pump on this emergency contract.

#### 20.02 PLUGGING OR BLOCKING:

It will be the responsibility of the Contractor to provide and install the required plug and blocking in the line for repair work, and as required for emergency pumping. This plug must be inserted into the line at a manhole immediately upstream from the section of line being repaired or inspected. The plug must be designed so that any portion of sewer flow can be released through the line. After all work has been completed, the plug and all blocking must be removed from the manhole.

#### 20.03 BY-PASS/EMERGENCY PUMPING:

When by-pass or emergency pumping is required, the Contractor must supply the necessary pumps, conduits, fuel, and other equipment to divert the flow of wastewater around the work site, or emergency pumped sewer areas. By-passed and/or emergency pumping of sewerage must be diverted to the system below the work site, or as designated by the Director, Assistant Director, or the Project Manager. Said sewage cannot be diverted into the storm drainage system. The by-pass system or emergency pumping must be of sufficient capacity to handle existing flows, plus additional flow that may occur during periods of rain.

For projects expected to last longer than one normal work day, only submersible or above ground pumps with electric motors will be acceptable, without prior approval of the Project Manager. During an emergency normal diesel pumps will be acceptable. The Contractor will be responsible for supplying the required electrical

feeds, electrical power, labor, fuel, and supervision to set up and operate the emergency pumping and by-pass system.

The Contractor must take every precaution to ensure that the plugging and bypassing of sewer flow does not cause flooding or damage to the public or private property being served by the sewers involved.

#### **TECHNICAL SPECIFICATIONS**

## SECTION 21 REQUEST FOR PAYMENT

#### **SECTION I & II**

#### 21.01 REQUIREMENTS INCLUDED:

Submit applications for payment to the Project Manager or designated Department of Sewerage representative in accordance with the schedule established by Conditions of the Contract. Payments may be submitted electronically.

#### 21.02 FORMAT AND DATA REQUIRED:

- A. Submit payment requests in the form required by Owner with itemized data typed on 8½" x 11" white paper continuation sheets.
- B. Provide itemized data on continuation sheet: Format, schedules, line items, and values.

#### 21.03 SUBSTANTIATING DATA FOR PROGRESS PAYMENTS:

- A. All payment requests must be accompanied by a Certificate of Payment, a signed affidavit regarding previous payment received, and a short progress narrative describing work performed since previous payment submittal.
- B. When the Owner or the Project Manager requires additional substantiating data, the Contractor must submit suitable information, with a cover letter.
- C. Submit two (2) copies of all data required with a cover letter for each monthly pay request. Any additional substantiating data requested must also be submitted as required in Part B above.

#### 21.04 PREPARATION OF APPLICATION FOR FINAL PAYMENT:

- A. Fill in application form as specified for progress payments.
- B. Use continuation sheet for presenting the final statement of accounting.

#### 21.05 SUBMITTAL PROCEDURE:

- A. Submit applications for payment to the Project Manager at the times stipulated in the Agreement.
- B. Number: Two (2) copies of each application unless submitted electronically.

#### **TECHNICAL SPECIFICATIONS**

#### **SECTION 22**

#### FIELD INSPECTION REPORTS

#### 22.01 DESCRIPTION:

This work will consist of the preparation of Field Inspection Report(s) required during various stages of the Service Agreement work progression. This work will be considered incidental to the cost of the associated fieldwork to create and acquire all pertinent data.

#### 22.02 PRE-REHABILITATION SUB-SYSTEM EVALUATION:

A. The Contractor must submit a pre-rehabilitation sub-system evaluation to the Owner, within 6 Weeks from completion of the field inspection work (including pipe inventory, physical inspection of manholes, smoke testing, dye-water flooding, and television inspection work).

For field inspection work:

- 1. An updated pipe inventory obtained from field survey.
- 2. One bound computer generated hard copy report per sub-system evaluated for each type inspection performed (pipe inventory, manhole physical inspection, smoke testing, and/or Condition Assessment CCTV inspection).
- 3. Media containing appropriate data and visual inspection results:
  - Manhole Inspection Digital JPEG images.
  - Smoke Testing Digital JPEG images of leaks.
  - CCTV Inspection Digital MPEG video as specified in Section 23.
- B. The Contractor must submit to the Owner a complete evaluation report of CCTV television inspection. This report must be produced using a system compatible with GBA Master Series TV Inspection Report and data

processing equipment specifically designed to record and transfer all information gathered during the CCTV inspection, as noted in Section 23.

- C. There will be no additional compensation paid to the Contractor for the first set of inspection reports, images, and videos provided to the Owner.
- D. All evaluation reports must also include the following:

Map Changes – Forms noting any field variances from Owner provided work orders and/or maps.

Critical Damage Reports – Forms noting any defects or observations encountered in field inspection — activities, which may indicate immediate failure, interruption of service, or sewer overflow may occur.

Cover Letter – A brief narrative describing any major issues identified during field inspection activities.

Glossary – A listing of any Contractor, software, or inspection report specific abbreviations and terminology, which may need to be clarified.

Appendix – Any original field forms used to collect data should be included as appendices.

### 22.03 POST REHABILITATIN REPORT UTILIZING A SYSTEM COMPATIBLE TO GBA MASTER SERIES:

The following must be submitted to the Owner, as noted in Section 23:

A. A CD, or other acceptable methods, with pre-rehabilitation and postrehabilitation video inspections for any CIPP rehabilitated line segments.

- B. A computer-generated report detailing each line segment rehabilitated with any restored or CIPP rehabilitated service connection locations noted. The report should be provided using a system compatible with the Parish program.
- C. A printed pipe inventory of all line segments included in the post-rehabilitation report.
- D. An upload disk including all pertinent data modified by rehabilitation activities, including but not limited to: television inspection, manhole inventory, etc.; in compatible Format.

#### 22.04 **HISTORY**:

The Contractor will be required to prepare an electronic digital version of "activity history records" for all inspection, repair, and rehabilitation efforts performed on this contract. This data upload must be prepared and transferred using a compatible program.

# TECHNICAL SPECIFICATIONS SECTION 23 NEW DATA MANAGEMENT SYSTEM

PAGE INTENTIONALLY LEFT BLANK

## TECHNICAL SPECIFICATIONS SECTION 24 CONTRACT CLOSEOUT

#### 24.01 REQUIREMENTS INCLUDED:

The Contractor must comply with the requirements stated in the Conditions of the Contract, and in specification for administrative procedures in closing out the work.

#### 24.02 FINAL ADJUSTMENT OF ACCOUNTS:

- A. Submit a final statement of accounting to the Project Manager
- B. Statement shall reflect all adjustments to the Contract Sum:
  - 1. The original Contract Sum
  - 2. Additions and deductions resulting from:
    - a. Cap Increase
  - 3. Total Contract Sum, as adjusted.
  - 4. Previous payments
  - 5. Sum remaining due

#### 24.03 FINAL APPLICATION FOR PAYMENT:

The Contractor must submit the final application for payment, in accordance with the procedures and requirements stated in the conditions of the contract.

#### 24.04 CONTRACTOR'S CLOSEOUT SUBMITTALS TO PROJECT MANAGER:

- A. Project Record Documents
- B. Warranties and Bonds
- C. Evidence of Payment and Release of liens: Requirement of General and

	Supplementary Conditions					
D.	Certificate of Insurance for Products and Completed Operations					
	SECTION II – EMERGENCY LIFT STATION REPAIR					

1.0 QUALIFICATIONS:

- 1.1 Before submitting bid, each prospective bidder shall familiarize themselves with the work, local labor conditions and all laws, regulations, Jefferson Parish Engineering Department standard detail sheets, and other factors affecting performance of the work. Contractor shall carefully correlate his observations with the requirements of the contract documents and otherwise satisfy themselves of the expense and difficulties for performance of the work. The submission of a bid will constitute a representation of compliance by the bidder. There will be no subsequent financial adjustment for lack of such familiarization.
- 1.2 The contractor must have complete repair facilities for off-site repair work as called for herein. The successful contractor must be able to troubleshoot all pump, motor and control panel problems that may arise.
- 1.3 The contractor's pump mechanic must be 1<sup>st</sup> class certified and experienced in the diagnoses and repair of wastewater pumps up to 400 horsepower. Pump mechanic must be a factory trained, authorized representative for a major pump manufacturer such as Hydromatic, Gorman Rupp, Clow, Yoeman, Fairbanks Morse, Flygt, Smith & Loveless, etc. Pump mechanic shall have the skill, knowledge, and necessary qualifications to inspect, troubleshoot, disassemble, repair, rebuild, and reassemble any of the wastewater pumps and related components.
- 1.4 The contractor's electrician must be 1<sup>st</sup> class certified and experienced in the diagnoses and repair of motors and control panels. Electrician must be a factory trained, authorized representative for a major control panel manufacturer, such as TESCO, Smith & Loveless, Allen Bradley, Gorman Rupp, Heally Ruff, etc. Electrician shall have the skill, knowledge and necessary qualifications to inspect, troubleshoot, disassemble, repair, rebuild, and reassemble any of the motors, control panels and related components.
- 1.5 The contractor shall possess or supply the appropriate machine tools, shop facilities, equipment, parts, materials, and labor to complete the work in a timely, cost efficient manner.
- 1.6 The contractor must have the necessary following equipment:
  - a. Mechanics truck with hoist capable of lifting 2000 lbs.
  - b. Boom truck capable of lifting 5000 lbs.
  - c. 1 ½ ton flatbed vehicle or equal to haul equipment to and from jobsites.
    - d. Electrician truck

- 1.7 The contractor or subcontractors must stock and maintain a sufficient inventory of factory recommended replacement parts and components for all pumps and controls to expedite repair/replacement.
- 1.8 The contractor must have an in-house motor shop or an established relationship with a motor shop.

#### **GENERAL SPECIFICATIONS:**

#### 2.0 PUMPS

- 2.1 Contractor will furnish all equipment, labor and materials to accomplish all the work specified in accordance with the contract documents. Unit price bid for each of the various pump categories of work shall include all direct and indirect costs attributable to that category of work including (but not limited to) labor, machine, tool cost, consumables, welding rods, lubricants, associative tools and equipment, supervision, insurance, and payroll.
- 2.2 Pump repair shall consist of replacing bearings, oil seals, mechanical seals, and any other component to complete the pump for use.
- 2.3 Contractor shall warrant that all pump work performed under this contract shall be performed in a good and workmanlike manner, that all materials furnished shall be of good merchantable quality and that the contractor's performance shall be free of defects. All pump repair work shall be guaranteed for a period of six (6) months from date of completion of repair. Any failure during the warranty period resulting from defective material and/or poor workmanship shall be repaired at the expense of the contractor, FOB Jefferson Parish Sewerage facilities.

#### 3.0 MOTORS

3.1 Contractor will furnish all equipment, labor, and materials to accomplish all the work specified in accordance with the contract documents. Unit price bid for each of the various motor categories of work shall include all direct and indirect costs attributable to that category of work including (but not limited to) labor, machine, tool cost,

consumables, welding rods, lubricants, associative tools and equipment, supervision, insurance, and payroll.

- 3.2 Work shall consist of inspection, testing, reconditioning, rewinding and related repair work of and for electric motors.
- 3.3 Bids are requested for qualified electric motor repair service contractors Underwriters Laboratories (UL) listed and who are familiar with the electrical, mechanical and physical make up and operation of electric motors as may be required by the Department of Sewerage.
- 3.4 Bidders should familiarize themselves with the work and any condition or conditions that could affect the bidders quote. There will be no subsequent financial adjustment for the lack of such familiarization. Under no circumstances should contractors assume that there will be the opportunity for multiple motor repairs in a given HP/RPM range based on the Lift Station Section inventory.
- 3.5 Contractor shall warrant that all work performed under this contract shall be performed in a good and workmanlike manner, that all materials furnished shall be of good merchantable quality and that the contractor's performance shall be free of defects. All motor repair work shall be guaranteed for a period of one (1) year from date of completion of repair. Any failure during the warranty period resulting from defective material and/or poor workmanship shall be repaired at the expense of the contractor, FOB Jefferson Parish Sewerage facilities.
- 3.6 The Department of Sewerage reserves the right to appoint an independent motor repair shop to disassemble and verify that repairs performed by the contractor were done in proper fashion. At such time, the contractor, or his representative, shall have the opportunity to be present for such verification.

#### 3.7 Facilities:

- A) Test Facilities.
- B) Two tank VPI system for varnish resin systems only. Contractors utilizing dip tank impregnating resin systems as manufactured by Epoxylite (Esterlite #605), technical service bulletin #605 shall be followed. Other manufacturer's products and procedures shall be on an approved equal basis.
- C) Electronic static and dynamic balancing equipment.
- D) Machinery for rehabbing bearings.

- E) Burning oven capable of maintaining constant burning temperature up to 800 degrees Fahrenheit max. Oven shall be equipped with water quenching device to prevent temperature runaway.
- F) Baking Oven.
- G) Adequate hi-pot facility, surge tester, and core loss tester.
- H) An FFT (Fast Fournier Transform) type vibration analyzer with 400 lines of resolution or greater and frequency range of 0.4 X running speed to 2,000HZ. The transducer shall be either the velocity type of the accelerometer type with a magnetic mount (Hand-held pickups are not acceptable).
- 3.8 Materials: All repair materials used to replace worn or damaged parts shall be new (I.E. not used) and be of equal or better quality as original parts. All Jefferson Parish standard specifications shall be adhered to. All worn and damaged parts (including bearings) which are replaced shall be tagged and returned with the repaired motor and also be listed on the billing invoice as having been returned.
- 3.9 Motor Rebuild/Reconditioning: Motor reconditioning shall be performed in accordance with the relevant manufacturer's specifications and procedures for each and every motor unless otherwise specified. Reconditioning shall include but not necessarily be limited to disassembly, cleaning, mechanical and electrical inspection, varnish treating windings, baking, replace bearings, check balancing, check coupling, greasing, assembly, testing and painting.
- 3.10 Rotor Reconditioning: Steam clean and dry by heating in oven. If the rotor core laminations are found damaged, loose and/or shorted they shall be repaired. Visually inspect for damage to air fans. If any exists, repair prior to varnishing the rotor. Check rotor bars and resistance rings (for cage rotors) for open circuit by either a growler or a sonic test. Rotor bar movement, if minimal, shall be corrected by giving the rotor a bonding resin treatment and curing.
- 3.11 Stator Reconditioning: Steam clean to remove oil, grease, salt and other unwanted deposits from windings. Do not pressure wash. Dry the windings by heating it in an oven for 4-6 hours at about 200 degrees Fahrenheit. Visually inspect for signs of physical damage and/or deterioration to the winding, core lamination and other abnormalities. Inspect all machine and mating surfaces to make sure they are free of nicks, burrs and all other foreign material. All broken ties, blocks and wedges shall be replaced. The loose blocks and wedges shall be tightened using an approved adhesive with a filler material or replaced in kind. Inspect and clean ventilation passages, and terminal leads for damage. Connectors shall be inspected for damage and/or burning signs. The damaged and/or burnt connectors shall be replaced. After work has been completed, treat the motor with a coat of baking type "H" varnish or

class "H" impregnating resin as manufactured by Expoylite (Esterlite #605) as outlined in Expoylite's technical bulletin #605 or approved equal.

3.12 Motor Rewinding: Motor rewinding shall be performed in accordance with the relevant manufacturer's specifications and procedures for each and every motor unless otherwise specified. Rewinding shall include but not necessarily be limited to disassembly, cleaning, removal of old winding, mechanical and electrical inspection, rewinding with class "H" insulation, one (1) dip and bake for 75 H.P. and smaller V.P.I. Dip and bake for 100 H.P. and larger followed by a second dip and bake (including all form coil wound motors), machine work (if necessary) and other parts, greasing, new leads (including in rewinding price), assembly, testing and painting.

#### 4.0 TESCO Liq Controllers:

During flood events or hurricanes, controllers could be flooded or moisture could have entered into controller units. Bidder shall quote on repairing or replacing the controller. The repairing phase shall consist of replacing all components that have received any moisture damage. Since these units vary in size, there is a good case that the complete unit will be inundated with water and the complete unit will have to be changed out. All TESCO Liq controllers that are replaced, shall be replaced with Liq 5's and include a five (5) year warranty.

#### 5.0 Machine Shop Services:

- The unit price bid for each of the various categories of work shall include all direct and indirect costs attributable to the category of work including (but not limited to) labor, machine tool cost, consumables, welding rods, lubricants, associative tools and equipment, supervision, insurance, and payroll.
- 5.2 Each of the bid item categories contemplates the usage of a particular fixed machine tool. The unit price bid for each category shall be for each hour of active work for the particular machine described, including on principal skilled craftsman to operate said machine, with all other incidental labor and supervision absorbed within the unit price bid for each hour of such usage.
- 5.3 Certain other bid item categories do not contemplate the usage of any specific machine, but rather contemplate the usage of a variety of hand tools, and measurement devices. For these categories, the bid price shall be for each man-hour performing the work so described.

- Another bid item category contemplates the usage of a welding machine and/or burning torch apparatus, along with all associative appurtenances to perform burn cutting and welding operations. For this category the bid price shall be for each hour of usage of said apparatus including one principal skilled welder/burner, with all other incidental labor and supervision absorbed within the unit price bid.
- 5.5 All drayage of work pieces (I.E., one delivery and one pick-up per piece) will be by others, generally upon parish vehicles, but occasionally upon vehicles of other contractors with parish approval. In each case, the work of this contract shall include the necessary hoisting and help to secure the load, however, there shall be no direct compensation for all such coordination in loading as this will be considered as part of the contractor's overhead and thus absorbed in the unit price bid.
- 5.6 Set-up time: The time required to set up a work piece for machine work will be allowed as work time, providing that such work is done in an effective manner.
- 5.7 The following is a list of the various categories of work contemplated:
  - Item 1: Small lathe work: General purpose turning, facing, boring and threading, on work pieces up to 16" in diameter and up to 60" in length, includes bar stock treading up to 2".
  - Item 2: Small vertical axis boring mill work: General purpose turning, facing and boring on work pieces up to 24" in height and up to 48" in diameter.
  - Item 3: Medium drill press work: General purpose drilling of holes up to 1" in diameter, threading, reaming and spot facing on work pieces up to 15" in height and of weight generally less than 200 pounds.
  - Item 4: Small milling machine work: General purpose milling, drilling, facing, spot facing and keyseating to be done on a bridgeport of small work pieces generally less than 200 pounds in weight.
  - Item 5: Keyway cutting: Keyseating of the bore of couplings, impellers and similar pieces with hub length up to 18", diameter up to 66" and keyways up to 1 ½" in width.

Item 6: Saw work: Transverse cutting of round bars, beams and other long shapes up to 12" in size (diameter or depth).

Item 7: Lapping machine work: Facing mechanical seals on work pieces up to 12" in diameter.

Item 8: Dynamic balancing: Balancing rotating elements up to 96" in length, 36" in diameter and 2500# weight at rotative speeds 900 RPM maximum.

Item 9: Miscellaneous assembly work: This item does not involve any of the machining operations but may be necessary prior to or after said operations. The workmen would not necessarily be skilled craftsmen as required for machining operations, but skilled in the handling of work pieces, wrench operations, and so forth.

Item 10: Miscellaneous measurement work: This item does not involve any of the machining operations but may be necessary prior to or after said operations. The measurement work would consist of taking precise measurements with inside or outside devices such as micrometers, depth gauges, etc. The price bid shall be per man hour of such effort.

Item 11: 440A welding machine/burning apparatus work: This item is for the making of weldments to be subsequently machined (Under other categories) using either raw stock materials and/or partially machined components. Included herein would be any welding associative with propeller reconditioning.

#### 6.0 Generators:

- The Department of Sewerage maintains approximately 507+ sewer lift stations. In preparation for emergencies and disasters, there will be a need for generators to power lift stations as requested. No disaster action will be taken until an official state of emergency or disaster is declared, or the appointed authority (Director of Public Works or Director of Sewerage) requests preparation up to 72 hours prior to disaster landfall.
- 6.2 Contractor shall provide on-site and/or on-call assistance 24 hours a day during and after a disaster and when necessary up to 72 hours prior to disaster landfall through the recovery period. Contractor shall be responsible for fuel costs, maintenance and repair costs, etc. associated with any vehicles and equipment that are used by

contractor for the delivery or staging of diesel generators during any declared State of Emergency.

- Diesel generators will be used to provide emergency electrical back-up power for lift stations as needed and as otherwise required. The generators need to be set up as hourly and daily rates. Contractor must guarantee availability 72 hours prior to an impending storm, or as soon as possible after a catastrophic event that would require its use.
- 6.4 Contractor shall provide Emergency Diesel Generator rental and include sufficient fuel, oil, and other commodities needed to run equipment as requested by Jefferson Parish in a work order or as directed by the Director or Public Works Manager. Provide and pay for all labor, tools, equipment, transportation, supervision, and all other services and facilities of any nature whatsoever necessary for safe delivery and staging.
- 6.5 Contractor will ensure that all drivers and equipment have proper identification and insurance and all generators be located by GPS.
- 6.6 Contractor will maintain records documenting orders placed, receipt, storage, and delivery of orders/services for ten (10) years after a declared disaster.
- 6.7 Pricing: Bid pricing to provide for a set-up charge for each type of generator. Set-up price shall include loading, transportation, and unloading at site as designated, pickup, delivery to origination and off-loading. Hourly and daily prices shall include all equipment, labor, fuel, oil, and other commodities needed to run equipment.
- The locations of lift stations that have existing generator hook ups and recommended generator sizes can be obtained from the Lift Station Section. Due to the type of emergency, the Parish could require one (1) or numerous generators to assist the Sewerage Department work crews during Natural Disasters or Other State of Emergencies. Any and all information may be obtained from Shane Dickerson, General Superintendent Lift Stations (504-437-4818).

#### 7.0 UNFORESEEN EMERGENCIES:

7.1 Measurement: Measurement for unforeseen emergency work will be made on an as incurred basis. Parts and supplies incidental to the scope of services to be provided under this bid which are not listed as separate line items in the bid shall be billed and paid at dealer/wholesale invoice without increase or mark-up. Notwithstanding the foregoing, Contractor must receive prior approval by the Department Director or Project Manager prior to purchasing these parts for repairs. Additionally, these third party invoices shall be

included in the contractor's billing invoice for payment. The cost of any incidental drayage between the local supplier and the job site will not be considered for pay.

7.2 Payment: Payment will be made only when the Contractor is directed by the Parish to make repairs within the scope of work of this proposal but not specifically covered by items contained elsewhere in this proposal. Payment will include furnishing all labor, equipment, and materials needed to accomplish the directed emergency work. Payment will be made in accordance with the hourly or daily rate bid for labor and equipment items. Equipment rates for bid (equipment only) for unforeseen emergency work cannot exceed the AED green book rates. As follow: Day Rate = AED weekly rate. The hourly rate will be determined by dividing the daily rate by 8.

#### **TELEVISION INSPECTION FORM**

UPSTREAM MANHOLE:				ADDRESS:					BANK:		
	QUALIFIER	₹:							· · · · · · · · · · · · · · · · · · ·		
DOWNS	DOWNSTREAM MANHOLE: ADDRESS:										
QUALIFIER:											
DATE:_	/	_/	_	TOTAL M/L LENGTH:(FT) UPS M/H DEPTH:							
	TV DIRECTION    1-US → DS 2-DS → US NSPECTION CREW										
WEATHER									LOT TREC A EASEMENT RR ACCESS		
LOOKIN	5-EASEMENT GD ACCESS 6-PRKG LOT GD ACCESS 7-PRKG LOT GD ACCESS 8-ALLEY PR ACCESS										
DYED TE	9-ALLEY GD ACCESS 10-OPEN AREA PR ACCESS 11-OPEN AREA GD ACCESS YED TEST										
	/ DEPTH										
	SE							ITATED L	INE 4-TV PRE-REHABILITATAED LINE		
				RMAL FLC	W 2-ADDE	D FLOW 3-NO	FLOW				
	D R START			STOB	[						
						•					
						DEGREASER	_  ROOT T	REAT.	_  POINT REP.    MH REP.		
	APE ER/HEIGHT(		1-RO		LIPTICAL )						
	PE				. ,	_	PLSTC M	ORTAR 5-	ASBESTOS CEMENT 6-CIP 7-RCP		
			8-AB	9-DIP 10-	POLYETHY	LENE 11-STEE	L 12-TRUS	S			
						3-SLIPLINED 4-					
SURFAC	E COVER	I	1-ASI	PHALT ST	2-CONC ST	3-SHELL ST 4-	SIDEWALK	5-TREES	/SHRBS 6-CLS TO FNCE 7-OPEN ARE	Α	
COMME					GRVL DR	V 16-SHELL DRY	V 17-CONC	PEA GR	/L DRV 18-GRASS		
	VTR INDEX	FOOT.	CLOCK POS	CODE	RATING	INFLT (GPM)**	LAT. MAT.	LAT. DIA.	ADDRESS		
1	<u> </u>										
	MENT:										
2											
COV	MENT:										
3											
CON	MENT:										
4											
CON	MENT:				L						
5					1						
CON	MENT:				<u> </u>			<u> </u>			
6			Γ		ı						
CON	II MENT:		<u> </u>	· · · · · · · · · · · · · · · · · · ·						{	
7			r								
										_	
L	MENT:									_	
8											
CON	MENT:										
9											
CON	MENT:								· · · · · · · · · · · · · · · · · · ·		
** ENTE	** ENTER INFILTRATION RATE ONLY IF ACTUAL LEAKAGE IS OBSERVED										
						AIR 3-POOR 4-	VERY POO	)R			
E						PAGE O				<del></del>	

113

#### **TELEVISION INSPECTION FORM**

INSPEC	NSPECTION CREW: DATE: // JOB NO:							JOB NO:	
UPSTRE	PSTREAM MANHOLE: ADDRESS: BANK:							BANK:	
c	QUALIFIER: _								
DOWNS	TREAM MAN	HOI E			ADDRE	:ee.			
					ADDAL	.33.			
	QUALIFIER: _								
ADDITIONAL OBSERVATIONS									
OB#	VTR INDEX	FOOT.	CLOCK POS	CODE	RATING	INFLT (GPM)**	LAT. MAT.	LAT. DIA.	ADDRESS
10									
	MMENT:								
11							<u> </u>		
12	MMENT:	r		,	ı	· · · · · · · · · · · · · · · · · · ·	r		r
<u> </u>	MMENT:				<u></u>			L	L
13		·	1		I		I		T
	MMENT:	l			l	l	l		L
14	1	l	1			ĺ	I	<u> </u>	T
СО	I MMENT:		1		<u> </u>	<u> </u>	<u> </u>	<u> </u>	L
15		I							
со	MMENT:	l	<u> </u>		1	l	l	l	<del></del>
16									
co	MMENT:	1				l			
17									
co	MMENT:		<del></del>						
18									
СО	MMENT:								
19									
СО	MMENT:								
20									
СО	MMENT:								
21		L							
	MMENT:		,						
22									
l	MMENT:					· · · · · · · · · · · · · · · · · · ·			
23	1								
	MMENT:		ı				г		
24	MMENT:								
25	WINTER I								
	MMENT:								
26	******* .		1						
	MMENT:								
Additional observations attached									
<u>  </u>	radiuonai 0080	., TauUIIS è							

PAGE \_\_\_\_ OF \_\_\_\_

## SEWER REHAB SECTION CRITICAL DAMAGE REPORT

DATE:			LIFT	STATION AREA:
M/H FROM:	M/H TO:	M/H LOCATO	DN:	
PIPE SIZE:	TOTAL LENGTH:	PIPE TYPE:	DEPTH:	OPERATOR:
CRITICAL DAMAG	GE LOCATION:			
CRITICAL DAMAG	GE FOOTAGE:	FROM UPS	DWN	CLOCK POSITION:
SURFACE COVER	OVER PROBLEM:		SURFACE COVER	MARKED: YES NO
ROUGH SKETCH:				
UPS M/H:	<b>—</b>		,	DWN M/H:
PROBLEMS/COM	MMENTS:			
RECEIVED BY:			DATE REPAI	R COMPLETED:

## FEMA CONTRACT PROVISIONS FOR NON-FEDERAL ENTITY UNDER FEDERAL AWARDS REQUIRED BY 2 C.F.R. §200.327 APPENDIX II TO 2 C.F.R. § 200

#### **REMEDIES**

(For all awarded contracts with a value greater than Simplified Acquisition Threshold as defined in 2CFR200 (\$250,000.00))

Any violation or breach of terms of this contract on the part of the Contractor or the Contractor's subcontractors may result in the suspension or termination of this contract or such other action that may be necessary to enforce the rights of the parties of this contract. The duties and obligations imposed by the contract documents and the rights and remedies available thereunder shall be in addition to and not a limitation of any duties, obligations, rights and remedies otherwise imposed or available by law.

Any violation or breach of terms of this contract of the Contractor or the Contractor's subcontractors will be subject to the remedies, including liquidated damages, described in the bid specifications or Request for Proposal and the Jefferson Parish General Terms and Conditions which are incorporated herein by reference in their entirety.

#### TERMINATION FOR CAUSE AND CONVENIENCE

(For all awarded contracts with a value greater than \$10,000.00)

Jefferson Parish reserves the right to terminate this contract for cause or convenience pursuant to the General Terms and Conditions which are incorporated herein by reference in their entirety.

#### **EQUAL EMPLOYMENT OPPORTUNITY**

(For all awarded contracts that meet the definition of "federally assisted construction contract" provided in 41 CFR Part 60)

Page **1** of **34** Revised: 2/18/2025

During the performance of this contract, the contractor agrees as follows:

(1) The contractor will not discriminate against any employee or applicant for employment because of race, color, religion, sex, sexual orientation, gender identity, or national origin. The contractor will take affirmative action to ensure that applicants are employed, and that employees are treated during employment without regard to their race, color, religion, sex, sexual orientation, gender identity, or national origin. Such action shall include, but not be limited to the following:

Employment, upgrading, demotion, or transfer; recruitment or recruitment advertising; layoff or termination; rates of pay or other forms of compensation; and selection for training, including apprenticeship. The contractor agrees to post in conspicuous places, available to employees and applicants for employment, notices to be provided setting forth the provisions of this nondiscrimination clause.

- (2) The contractor will, in all solicitations or advertisements for employees placed by or on behalf of the contractor, state that all qualified applicants will receive consideration for employment without regard to race, color, religion, sex, sexual orientation, gender identity, or national origin.
- (3) The contractor will not discharge or in any other manner discriminate against any employee or applicant for employment because such employee or applicant has inquired about, discussed, or disclosed the compensation of the employee or applicant or another employee or applicant. This provision shall not apply to instances in which an employee who has access to the compensation information of other employees or applicants as a part of such employee's essential job functions discloses the compensation of such other employees or applicants to individuals who do not otherwise have access to such information, unless such disclosure is in response to a formal complaint or charge, in furtherance of an investigation, proceeding, hearing, or action, including an investigation conducted by the employer, or is consistent with the contractor's legal duty to furnish information.
- (4) The contractor will send to each labor union or representative of workers with which he has a collective bargaining agreement or other contract or understanding, a notice to be provided advising the said labor union or workers' representatives of the contractor's commitments under this section, and shall post copies of the notice in conspicuous places available to employees and applicants for employment.
- (5) The contractor will comply with all provisions of Executive Order 11246 of September 24, 1965, and of the rules, regulations, and relevant orders of the Secretary of Labor.

Page **2** of **34** Revised: 2/18/2025

- (6) The contractor will furnish all information and reports required by Executive Order 11246 of September 24, 1965, and by rules, regulations, and orders of the Secretary of Labor, or pursuant thereto, and will permit access to his books, records, and accounts by the administering agency and the Secretary of Labor for purposes of investigation to ascertain compliance with such rules, regulations, and orders.
- (7) In the event of the contractor's noncompliance with the nondiscrimination clauses of this contract or with any of the said rules, regulations, or orders, this contract may be canceled, terminated, or suspended in whole or in part and the contractor may be declared ineligible for further Government contracts or federally assisted construction contracts in accordance with procedures authorized in Executive Order 11246 of September 24, 1965, and such other sanctions may be imposed and remedies invoked as provided in Executive Order 11246 of September 24, 1965, or by rule, regulation, or order of the Secretary of Labor, or as otherwise provided by law.
- (8) The contractor will include the portion of the sentence immediately preceding paragraph (1) and the provisions of paragraphs (1) through (8) in every subcontract or purchase order unless exempted by rules, regulations, or orders of the Secretary of Labor issued pursuant to section 204 of Executive Order 11246 of September 24, 1965, so that such provisions will be binding upon each subcontractor or vendor. The contractor will take such action with respect to any subcontract or purchase order as the administering agency may direct as a means of enforcing such provisions, including sanctions for noncompliance:

*Provided*, however, that in the event a contractor becomes involved in, or is threatened with, litigation with a subcontractor or vendor as a result of such direction by the administering agency, the contractor may request the United States to enter into such litigation to protect the interests of the United States.

The applicant further agrees that it will be bound by the above equal opportunity clause with respect to its own employment practices when it participates in federally assisted construction work: *Provided*, that if the applicant so participating is a state or local government, the above equal opportunity clause is not applicable to any agency, instrumentality or subdivision of such government which does not participate in work on or under the contract.

The applicant agrees that it will assist and cooperate actively with the administering agency and the Secretary of Labor in obtaining the compliance of contractors and subcontractors with the equal opportunity clause and the rules, regulations, and relevant orders of the Secretary of Labor, that it will furnish the administering agency and the Secretary of Labor such information as they may require for the supervision of such compliance, and that it will otherwise assist the administering agency in the discharge of the agency's primary responsibility for securing compliance.

Page **3** of **34** Revised: 2/18/2025

The applicant further agrees that it will refrain from entering into any contract or contract modification subject to Executive Order 11246 of September 24, 1965, with a contractor debarred from, or who has not demonstrated eligibility for, Government contracts and federally assisted construction contracts pursuant to the Executive Order and will carry out such sanctions and penalties for violation of the equal opportunity clause as may be imposed upon contractors and subcontractors by the administering agency or the Secretary of Labor pursuant to Part II, Subpart D of the Executive Order. In addition, the applicant agrees that if it fails or refuses to comply with these undertakings, the administering agency may take any or all of the following actions: Cancel, terminate, or suspend in whole or in part this grant (contract, loan, insurance, guarantee); refrain from extending any further assistance to the applicant under the program with respect to which the failure or refund occurred until satisfactory assurance of future compliance has been received from such applicant; and refer the case to the Department of Justice for appropriate legal proceedings.

#### **DAVIS-BACON ACT**

(The Davis-Bacon Act only applies to the Emergency Management Preparedness Grant Program, Homeland Security Grant Program, Nonprofit Security Grant Program, Tribal Homeland Security Grant Program, Port Security Grant Program, and Transit Security Grant Program for all awarded construction contracts with a value greater than \$2,000.00. It does not apply to other FEMA grant and cooperative agreement programs, including the Public Assistance Program.)

The Agency head shall cause or require the contracting officer to insert in full in any contract in excess of \$2,000 which is entered into for the actual construction, alteration and/or repair, including painting and decorating, of a public building or public work, or building or work financed in whole or in part from Federal funds or in accordance with guarantees of a Federal agency or financed from funds obtained by pledge of any contract of a Federal agency to make a loan, grant or annual contribution (except where a different meaning is expressly indicated), and which is subject to the labor standards provisions of any of the acts listed in § 5.1, the following clauses (or any modifications thereof to meet the particular needs of the agency, Provided, That such modifications are first approved by the Department of Labor):

#### (1) Minimum wages.

(i) All laborers and mechanics employed or working upon the site of the work (or under the United States Housing Act of 1937 or under the Housing Act of 1949 in the construction or development of the project), will be paid unconditionally and not less often than once a week, and without subsequent deduction or rebate on any account (except such payroll

Page **4** of **34** Revised: 2/18/2025

deductions as are permitted by regulations issued by the Secretary of Labor under the Copeland Act (29 CFR part 3)), the full amount of wages and bona fide fringe benefits (or cash equivalents thereof) due at time of payment computed at rates not less than those contained in the wage determination of the Secretary of Labor which is attached hereto and made a part hereof, regardless of any contractual relationship which may be alleged to exist between the contractor and such laborers and mechanics. Contributions made or costs reasonably anticipated for bona fide fringe benefits under section 1(b)(2) of the Davis-Bacon Act on behalf of laborers or mechanics are considered wages paid to such laborers or mechanics, subject to the provisions of paragraph (a)(1)(iv) of this section; also, regular contributions made or costs incurred for more than a weekly period (but not less often than quarterly) under plans, funds, or programs which cover the particular weekly period, are deemed to be constructively made or incurred during such weekly period. Such laborers and mechanics shall be paid the appropriate wage rate and fringe benefits on the wage determination for the classification of work actually performed, without regard to skill, except as provided in § 5.5(a)(4). Laborers or mechanics performing work in more than one classification may be compensated at the rate specified for each classification for the time actually worked therein: Provided, That the employer's payroll records accurately set forth the time spent in each classification in which work is performed. The wage determination (including any additional classification and wage rates conformed under paragraph (a)(1)(ii) of this section) and the Davis-Bacon poster (WH-1321) shall be posted at all times by the contractor and its subcontractors at the site of the work in a prominent and accessible place where it can be easily seen by the workers.

(ii)

- (A) The contracting officer shall require that any class of laborers or mechanics, including helpers, which is not listed in the wage determination and which is to be employed under the contract shall be classified in conformance with the wage determination. The contracting officer shall approve an additional classification and wage rate and fringe benefits therefore only when the following criteria have been met:
- (1) The work to be performed by the classification requested is not performed by a classification in the wage determination; and
- (2) The classification is utilized in the area by the construction industry; and

Page **5** of **34** Revised: 2/18/2025

- (3) The proposed wage rate, including any bona fide fringe benefits, bears a reasonable relationship to the wage rates contained in the wage determination.
- (B) If the contractor and the laborers and mechanics to be employed in the classification (if known), or their representatives, and the contracting officer agree on the classification and wage rate (including the amount designated for fringe benefits where appropriate), a report of the action taken shall be sent by the contracting officer to the Administrator of the Wage and Hour Division, U.S. Department of Labor, Washington, DC 20210. The Administrator, or an authorized representative, will approve, modify, or disapprove every additional classification action within 30 days of receipt and so advise the contracting officer or will notify the contracting officer within the 30-day period that additional time is necessary.
- (C) In the event the contractor, the laborers or mechanics to be employed in the classification or their representatives, and the contracting officer do not agree on the proposed classification and wage rate (including the amount designated for fringe benefits, where appropriate), the contracting officer shall refer the questions, including the views of all interested parties and the recommendation of the contracting officer, to the Administrator for determination. The Administrator, or an authorized representative, will issue a determination within 30 days of receipt and so advise the contracting officer or will notify the contracting officer within the 30-day period that additional time is necessary.
- (D) The wage rate (including fringe benefits where appropriate) determined pursuant to paragraphs (a)(1)(ii) (B) or (C) of this section, shall be paid to all workers performing work in the classification under this contract from the first day on which work is performed in the classification.
- (iii) Whenever the minimum wage rate prescribed in the contract for a class of laborers or mechanics includes a fringe benefit which is not expressed as an hourly rate, the contractor shall either pay the benefit as stated in the wage determination or shall pay another bona fide fringe benefit or an hourly cash equivalent thereof.
- (iv) If the contractor does not make payments to a trustee or other third person, the contractor may consider as part of the wages of any laborer or mechanic the amount of any costs reasonably anticipated in providing bona fide fringe benefits under a plan or program, Provided, That the Secretary of Labor has found, upon the written request of the contractor,

Page **6** of **34** Revised: 2/18/2025

that the applicable standards of the Davis-Bacon Act have been met. The Secretary of Labor may require the contractor to set aside in a separate account asset for the meeting of obligations under the plan or program.

- (2) Withholding. The (write in name of Federal Agency or the loan or grant recipient) shall upon its own action or upon written request of an authorized representative of the Department of Labor withhold or cause to be withheld from the contractor under this contract or any other Federal contract with the same prime contractor, or any other federally-assisted contract subject to Davis-Bacon prevailing wage requirements, which is held by the same prime contractor, so much of the accrued payments or advances as may be considered necessary to pay laborers and mechanics, including apprentices, trainees, and helpers, employed by the contractor or any subcontractor the full amount of wages required by the contract. In the event of failure to pay any laborer or mechanic, including any apprentice, trainee, or helper, employed or working on the site of the work (or under the United States Housing Act of 1937 or under the Housing Act of 1949 in the construction or development of the project), all or part of the wages required by the contract, the (Agency) may, after written notice to the contractor, sponsor, applicant, or owner, take such action as may be necessary to cause the suspension of any further payment, advance, or guarantee of funds until such violations have ceased.
- (3) Payrolls and basic records.
- (i) Payrolls and basic records relating thereto shall be maintained by the contractor during the course of the work and preserved for a period of three years thereafter for all laborers and mechanics working at the site of the work (or under the United States Housing Act of 1937, or under the Housing Act of 1949, in the construction or development of the project). Such records shall contain the name, address, and social security number of each such worker, his or her correct classification, hourly rates of wages paid (including rates of contributions or costs anticipated for bona fide fringe benefits or cash equivalents thereof of the types described in section 1(b)(2)(B) of the Davis-Bacon Act), daily and weekly number of hours worked, deductions made and actual wages paid. Whenever the Secretary of Labor has found under 29 CFR 5.5(a)(1)(iv) that the wages of any laborer or mechanic include the amount of any costs reasonably anticipated in providing benefits under a plan or program described in section 1(b)(2)(B) of the Davis-Bacon Act, the contractor shall maintain records which show that the commitment to provide such benefits is enforceable, that the plan or program is financially responsible, and that the plan or program has been communicated in writing to the laborers or mechanics affected, and records which show the costs anticipated or the actual cost incurred in providing such benefits. Contractors

Page **7** of **34** Revised: 2/18/2025

employing apprentices or trainees under approved programs shall maintain written evidence of the registration of apprenticeship programs and certification of trainee programs, the registration of the apprentices and trainees, and the ratios and wage rates prescribed in the applicable programs.

(ii)

- (A) The contractor shall submit weekly for each week in which any contract work is performed a copy of all payrolls to the (write in name of appropriate federal agency) if the agency is a party to the contract, but if the agency is not such a party, the contractor will submit the payrolls to the applicant, sponsor, or owner, as the case may be, for transmission to the (write in name of agency). The payrolls submitted shall set out accurately and completely all of the information required to be maintained under 29 CFR 5.5(a)(3)(i), except that full social security numbers and home addresses shall not be included on weekly transmittals. Instead the payrolls shall only need to include an individually identifying number for each employee (e.g., the last four digits of the employee's social security number). The required weekly payroll information may be submitted in any form desired. Optional Form WH-347 is available for this purpose from the Wage and Hour Division Web site at http://www.dol.gov/esa/whd/forms/wh347instr.htm or its successor site. The prime contractor is responsible for the submission of copies of payrolls by all subcontractors. Contractors and subcontractors shall maintain the full social security number and current address of each covered worker, and shall provide them upon request to the (write in name of appropriate federal agency) if the agency is a party to the contract, but if the agency is not such a party, the contractor will submit them to the applicant, sponsor, or owner, as the case may be, for transmission to the (write in name of agency), the contractor, or the Wage and Hour Division of the Department of Labor for purposes of an investigation or audit of compliance with prevailing wage requirements. It is not a violation of this section for a prime contractor to require a subcontractor to provide addresses and social security numbers to the prime contractor for its own records, without weekly submission to the sponsoring government agency (or the applicant, sponsor, or owner).
- (B) Each payroll submitted shall be accompanied by a "Statement of Compliance," signed by the contractor or subcontractor or his or her agent who pays or supervises the payment of the persons employed under the contract and shall certify the following:

Page **8** of **34** Revised: 2/18/2025

- (1) That the payroll for the payroll period contains the information required to be provided under § 5.5 (a)(3)(ii) of Regulations, 29 CFR part 5, the appropriate information is being maintained under § 5.5 (a)(3)(i) of Regulations, 29 CFR part 5, and that such information is correct and complete;
- (2) That each laborer or mechanic (including each helper, apprentice, and trainee) employed on the contract during the payroll period has been paid the full weekly wages earned, without rebate, either directly or indirectly, and that no deductions have been made either directly or indirectly from the full wages earned, other than permissible deductions as set forth in Regulations, 29 CFR part 3;
- (3) That each laborer or mechanic has been paid not less than the applicable wage rates and fringe benefits or cash equivalents for the classification of work performed, as specified in the applicable wage determination incorporated into the contract.
- (C) The weekly submission of a properly executed certification set forth on the reverse side of Optional Form WH-347 shall satisfy the requirement for submission of the "Statement of Compliance" required by paragraph (a)(3)(ii)(B) of this section.
- (D) The falsification of any of the above certifications may subject the contractor or subcontractor to civil or criminal prosecution under section 1001 of title 18 and section 231 of title 31 of the United States Code.
- (iii) The contractor or subcontractor shall make the records required under paragraph (a)(3)(i) of this section available for inspection, copying, or transcription by authorized representatives of the (write the name of the agency) or the Department of Labor, and shall permit such representatives to interview employees during working hours on the job. If the contractor or subcontractor fails to submit the required records or to make them available, the Federal agency may, after written notice to the contractor, sponsor, applicant, or owner, take such action as may be necessary to cause the suspension of any further payment, advance, or guarantee of funds. Furthermore, failure to submit the required records upon request or to make such records available may be grounds for debarment action pursuant to 29 CFR 5.12.

(4) Apprentices and trainees -

Page **9** of **34** Revised: 2/18/2025

- (i) Apprentices. Apprentices will be permitted to work at less than the predetermined rate for the work they performed when they are employed pursuant to and individually registered in a bona fide apprenticeship program registered with the U.S. Department of Labor, Employment and Training Administration, Office of Apprenticeship Training, Employer and Labor Services, or with a State Apprenticeship Agency recognized by the Office, or if a person is employed in his or her first 90 days of probationary employment as an apprentice in such an apprenticeship program, who is not individually registered in the program, but who has been certified by the Office of Apprenticeship Training, Employer and Labor Services or a State Apprenticeship Agency (where appropriate) to be eligible for probationary employment as an apprentice. The allowable ratio of apprentices to journeymen on the job site in any craft classification shall not be greater than the ratio permitted to the contractor as to the entire work force under the registered program. Any worker listed on a payroll at an apprentice wage rate, who is not registered or otherwise employed as stated above, shall be paid not less than the applicable wage rate on the wage determination for the classification of work actually performed. In addition, any apprentice performing work on the job site in excess of the ratio permitted under the registered program shall be paid not less than the applicable wage rate on the wage determination for the work actually performed. Where a contractor is performing construction on a project in a locality other than that in which its program is registered, the ratios and wage rates (expressed in percentages of the journeyman's hourly rate) specified in the contractor's or subcontractor's registered program shall be observed. Every apprentice must be paid at not less than the rate specified in the registered program for the apprentice's level of progress, expressed as a percentage of the journeymen hourly rate specified in the applicable wage determination. Apprentices shall be paid fringe benefits in accordance with the provisions of the apprenticeship program. If the apprenticeship program does not specify fringe benefits, apprentices must be paid the full amount of fringe benefits listed on the wage determination for the applicable classification. If the Administrator determines that a different practice prevails for the applicable apprentice classification, fringes shall be paid in accordance with that determination. In the event the Office of Apprenticeship Training, Employer and Labor Services, or a State Apprenticeship Agency recognized by the Office, withdraws approval of an apprenticeship program, the contractor will no longer be permitted to utilize apprentices at less than the applicable predetermined rate for the work performed until an acceptable program is approved.
- (ii) Trainees. Except as provided in 29 CFR 5.16, trainees will not be permitted to work at less than the predetermined rate for the work performed unless they are employed pursuant to and individually registered in a program which has received prior approval, evidenced by formal certification by the U.S. Department of Labor, Employment and Training Administration. The ratio of trainees to journeymen on the job site shall not be greater than

Page **10** of **34** Revised: 2/18/2025

permitted under the plan approved by the Employment and Training Administration. Every trainee must be paid at not less than the rate specified in the approved program for the trainee's level of progress, expressed as a percentage of the journeyman hourly rate specified in the applicable wage determination. Trainees shall be paid fringe benefits in accordance with the provisions of the trainee program. If the trainee program does not mention fringe benefits, trainees shall be paid the full amount of fringe benefits listed on the wage determination unless the Administrator of the Wage and Hour Division determines that there is an apprenticeship program associated with the corresponding journeyman wage rate on the wage determination which provides for less than full fringe benefits for apprentices. Any employee listed on the payroll at a trainee rate who is not registered and participating in a training plan approved by the Employment and Training Administration shall be paid not less than the applicable wage rate on the wage determination for the classification of work actually performed. In addition, any trainee performing work on the job site in excess of the ratio permitted under the registered program shall be paid not less than the applicable wage rate on the wage determination for the work actually performed. In the event the Employment and Training Administration withdraws approval of a training program, the contractor will no longer be permitted to utilize trainees at less than the applicable predetermined rate for the work performed until an acceptable program is approved.

- (iii) Equal employment opportunity. The utilization of apprentices, trainees and journeymen under this part shall be in conformity with the equal employment opportunity requirements of Executive Order 11246, as amended, and 29 CFR part 30.
- (5) Compliance with Copeland Act requirements. The contractor shall comply with the requirements of 29 CFR part 3, which are incorporated by reference in this contract.
- (6) Subcontracts. The contractor or subcontractor shall insert in any subcontracts the clauses contained in 29 CFR 5.5(a)(1) through (10) and such other clauses as the (write in the name of the Federal agency) may by appropriate instructions require, and also a clause requiring the subcontractors to include these clauses in any lower tier subcontracts. The prime contractor shall be responsible for the compliance by any subcontractor or lower tier subcontractor with all the contract clauses in 29 CFR 5.5.
- (7) Contract termination: debarment. A breach of the contract clauses in 29 CFR 5.5 may be grounds for termination of the contract, and for debarment as a contractor and a subcontractor as provided in 29 CFR 5.12.

Page **11** of **34** Revised: 2/18/2025

- (8) Compliance with Davis-Bacon and Related Act requirements. All rulings and interpretations of the Davis-Bacon and Related Acts contained in 29 CFR parts 1, 3, and 5 are herein incorporated by reference in this contract.
- (9) Disputes concerning labor standards. Disputes arising out of the labor standards provisions of this contract shall not be subject to the general disputes clause of this contract. Such disputes shall be resolved in accordance with the procedures of the Department of Labor set forth in 29 CFR parts 5, 6, and 7. Disputes within the meaning of this clause include disputes between the contractor (or any of its subcontractors) and the contracting agency, the U.S. Department of Labor, or the employees or their representatives.
- (10) Certification of eligibility.
- (i) By entering into this contract, the contractor certifies that neither it (nor he or she) nor any person or firm who has an interest in the contractor's firm is a person or firm ineligible to be awarded Government contracts by virtue of section 3(a) of the Davis-Bacon Act or 29 CFR 5.12(a)(1).
- (ii) No part of this contract shall be subcontracted to any person or firm ineligible for award of a Government contract by virtue of section 3(a) of the Davis-Bacon Act or 29 CFR 5.12(a)(1).
- (iii) The penalty for making false statements is prescribed in the U.S. Criminal Code, 18 U.S.C. 1001.
- (b) Contract Work Hours and Safety Standards Act. The Agency Head shall cause or require the contracting officer to insert the following clauses set forth in paragraphs (b)(1), (2), (3), and (4) of this section in full in any contract in an amount in excess of \$100,000 and subject to the overtime provisions of the Contract Work Hours and Safety Standards Act. These clauses shall be inserted in addition to the clauses required by § 5.5(a) or § 4.6 of part 4 of this title. As used in this paragraph, the terms laborers and mechanics include watchmen and guards.

Page **12** of **34** Revised: 2/18/2025

- (1) Overtime requirements. No contractor or subcontractor contracting for any part of the contract work which may require or involve the employment of laborers or mechanics shall require or permit any such laborer or mechanic in any workweek in which he or she is employed on such work to work in excess of forty hours in such workweek unless such laborer or mechanic receives compensation at a rate not less than one and one-half times the basic rate of pay for all hours worked in excess of forty hours in such workweek.
- (2) Violation; liability for unpaid wages; liquidated damages. In the event of any violation of the clause set forth in paragraph (b)(1) of this section the contractor and any subcontractor responsible therefor shall be liable for the unpaid wages. In addition, such contractor and subcontractor shall be liable to the United States (in the case of work done under contract for the District of Columbia or a territory, to such District or to such territory), for liquidated damages. Such liquidated damages shall be computed with respect to each individual laborer or mechanic, including watchmen and guards, employed in violation of the clause set forth in paragraph (b)(1) of this section, in the sum of \$29 for each calendar day on which such individual was required or permitted to work in excess of the standard workweek of forty hours without payment of the overtime wages required by the clause set forth in paragraph (b)(1) of this section.
- (3) Withholding for unpaid wages and liquidated damages. The (write in the name of the Federal agency or the loan or grant recipient) shall upon its own action or upon written request of an authorized representative of the Department of Labor withhold or cause to be withheld, from any moneys payable on account of work performed by the contractor or subcontractor under any such contract or any other Federal contract with the same prime contractor, or any other federally-assisted contract subject to the Contract Work Hours and Safety Standards Act, which is held by the same prime contractor, such sums as may be determined to be necessary to satisfy any liabilities of such contractor or subcontractor for unpaid wages and liquidated damages as provided in the clause set forth in paragraph (b)(2) of this section.
- (4) Subcontracts. The contractor or subcontractor shall insert in any subcontracts the clauses set forth in paragraph (b)(1) through (4) of this section and also a clause requiring the subcontractors to include these clauses in any lower tier subcontracts. The prime contractor shall be responsible for compliance by any subcontractor or lower tier subcontractor with the clauses set forth in paragraphs (b)(1) through (4) of this section.

Page **13** of **34** Revised: 2/18/2025

(c) In addition to the clauses contained in paragraph (b), in any contract subject only to the Contract Work Hours and Safety Standards Act and not to any of the other statutes cited in § 5.1, the Agency Head shall cause or require the contracting officer to insert a clause requiring that the contractor or subcontractor shall maintain payrolls and basic payroll records during the course of the work and shall preserve them for a period of three years from the completion of the contract for all laborers and mechanics, including guards and watchmen, working on the contract. Such records shall contain the name and address of each such employee, social security number, correct classifications, hourly rates of wages paid, daily and weekly number of hours worked, deductions made, and actual wages paid. Further, the Agency Head shall cause or require the contracting officer to insert in any such contract a clause providing that the records to be maintained under this paragraph shall be made available by the contractor or subcontractor for inspection, copying, or transcription by authorized representatives of the (write the name of agency) and the Department of Labor, and the contractor or subcontractor will permit such representatives to interview employees during working hours on the job.

#### **COPELAND "ANTI-KICKBACK" ACT**

(This requirement applies to all prime construction contracts above \$2,000 in situations where the Davis-Bacon Act also applies. Provision shall be included in contracts and subcontracts for compliance with the Copeland "Anti-Kickback" Act. In situations where the Davis-Bacon Act does not apply, neither does the Copeland "Anti-Kickback" Act. As described in section A.4 regarding the Davis-Bacon Act, this provision only applies to certain FEMA grant and cooperative agreement programs. Please reference that list discussed above. Of note, it does not apply to the FEMA Public Assistance Program.)

Compliance with the Copeland "Anti-Kickback" Act.

Contractor. The contractor shall comply with 18 U.S.C. § 874, 40 U.S.C. § 3145, and the requirements of 29 C.F.R. Part 3 as may be applicable, which are incorporated by reference into this contract.

Subcontracts. The contractor or subcontractor shall insert in any subcontracts the clause above and such other clauses as FEMA may by appropriate instructions require, and also a clause requiring the subcontractors to include these clauses in any lower tier subcontracts. The prime contractor shall be responsible for the compliance by any subcontractor or lower tier subcontractor with all of these contract clauses.

Page **14** of **34** Revised: 2/18/2025

Breach. A breach of the contract clauses above may be grounds for termination of the contract, and for debarment as a contractor and subcontractor as provided in 29 C.F.R. § 5.12.

#### CONTRACT WORK HOURS AND SAFETY STANDARDS ACT

(This required contract provision applies to all procurements over \$100,000 that involve the employment of mechanics, laborers, and construction work. These requirements *do not* apply to the purchase of supplies, materials or articles ordinarily available on the open market, or contracts for transportation or transmission of intelligence.)

Compliance with the Contract Work Hours and Safety Standards Act.

- (1) Overtime requirements. No contractor or subcontractor contracting for any part of the contract work which may require or involve the employment of laborers or mechanics shall require or permit any such laborer or mechanic in any workweek in which he or she is employed on such work to work in excess of 40 hours in such workweek unless such laborer or mechanic receives compensation at a rate not less than one and one-half times the basic rate of pay for all hours worked in excess of 40 hours in such workweek.
- (2) Violation; liability for unpaid wages; liquidated damages. In the event of any violation of the clause set forth in paragraph (b)(1) of this section, the contractor and any subcontractor responsible therefor shall be liable for the unpaid wages. In addition, such contractor and subcontractor shall be liable to the United States (in the case of work done under contract for the District of Columbia or a territory, to such District or to such territory), for liquidated damages. Such liquidated damages shall be computed with respect to each individual laborer or mechanic, including watchmen and guards, employed in violation of the clause set forth in paragraph (b)(1) of this paragraph, in the sum of \$27 for each calendar day on which such individual was required or permitted to work in excess of the standard workweek of forty (40) hours without payment of the overtime wages required by the clause set forth in paragraph (b)(1) of this section.
- (3) Withholding for unpaid wages and liquidated damages. The federal agency and/or Jefferson Parish shall upon its own action or upon written request of an authorized representative of the Department of Labor withhold or cause to be withheld, from any moneys payable on account of work performed by the contractor or subcontractor under any such contract or any other Federal contract with the same prime contract, or any other Federally-assisted contract subject to the Contract Work Hours and Safety Standards Act, which is held by the same prime contractor, such sums as may be determined to be necessary to satisfy any liabilities of such contractor or

Page **15** of **34** Revised: 2/18/2025

subcontractor for unpaid wages and liquidated damages as provided in the clause set forth in paragraph (b)(2) of this section.

(4) Subcontracts. The contractor or subcontractor shall insert in any subcontracts the clauses set forth in subparagraph (b)(1) through (4) of this section and also a clause requiring the subcontractors to include these clauses in any lower tier subcontracts. The prime contractor shall be responsible for compliance by any subcontractor or lower tier subcontractor with the clauses set forth in paragraphs (b)(1) through (4) of this section.

Further Compliance with the Contract Work Hours and Safety Standards Act:

- (1) The contractor or subcontractor shall maintain payrolls and basic payroll records during the course of the work and shall preserve them for a period of three years from the completion of the contract for all laborers and mechanics, including guards and watchmen, working on the contract. Such records shall contain the name and address of each such employee, social security number, correct classifications, hourly rates of wages paid, daily and weekly number of hours worked, deductions made, and actual wages paid.
- (2) Records to be maintained under this provision shall be made available by the contractor or subcontractor for inspection, copying, or transcription by authorized representatives of the Department of Homeland Security, the Federal Emergency Management Agency, and the Department of Labor, and the contractor or subcontractor will permit such representatives to interview employees during working hours on the job."

#### RIGHTS TO INVENTIONS MADE UNDER A CONTRACT OR AGREEMENT

(This requirement **does not apply** to the Public Assistance, Hazard Mitigation Grant Program, Fire Management Assistance Grant Program, Crisis Counseling Assistance and Training Grant Program, Disaster Case Management Grant Program, and Federal Assistance to Individuals and Households -Other Needs Assistance Grant Program, as FEMA awards under these programs do not meet the definition of "funding agreement." If FEMA federal award meets definition of "funding agreement" under 37 CFR §401.2(a), for all awarded contracts related to experimental, developmental, or research work type contracts)

(a) Definitions

Page **16** of **34** Revised: 2/18/2025

- (1) *Invention* means any invention or discovery which is or may be patentable or otherwise protectable under Title 35 of the United States Code, or any novel variety of plant which is or may be protected under the Plant Variety Protection Act (7 U.S.C. 2321 *et seq.*).
- (2) Subject invention means any invention of the contractor conceived or first actually reduced to practice in the performance of work under this contract, provided that in the case of a variety of plant, the date of determination (as defined in section 41(d) of the Plant Variety Protection Act, 7 U.S.C. 2401(d)) must also occur during the period of contract performance.
- (3) *Practical Application* means to manufacture in the case of a composition or product, to practice in the case of a process or method, or to operate in the case of a machine or system; and, in each case, under such conditions as to establish that the invention is being utilized and that its benefits are, to the extent permitted by law or government regulations, available to the public on reasonable terms.
- (4) *Made* when used in relation to any invention means the conception or first actual reduction to practice of such invention.
- (5) Small Business Firm means a small business concern as defined at section 2 of Pub. L. 85-536 (15 U.S.C. 632) and implementing regulations of the Administrator of the Small Business Administration. For the purpose of this clause, the size standards for small business concerns involved in government procurement and subcontracting at 13 CFR 121.3-8 and 13 CFR 121.3-12, respectively, will be used.
- (6) Nonprofit Organization means a university or other institution of higher education or an organization of the type described in section 501(c)(3) of the Internal Revenue Code of 1954 (26 U.S.C. 501(c) and exempt from taxation under section 501(a) of the Internal Revenue Code (25 U.S.C. 501(a)) or any nonprofit scientific or educational organization qualified under a state nonprofit organization statute.

#### (b) Allocation of Principal Rights

The *Contractor* may retain the entire right, title, and interest throughout the world to each subject invention subject to the provisions of this clause and 35 U.S.C. 203. With respect to any subject invention in which the *Contractor* retains title, the Federal government shall have a nonexclusive, nontransferable, irrevocable, paid-up license to practice or have practiced for or on behalf of the United States the subject invention throughout the world.

- (c) Invention Disclosure, Election of Title and Filing of Patent Application by Contractor
  - (1) The *contractor* will disclose each subject invention to the *Federal Agency* within two months after the inventor discloses it in writing to *contractor* personnel responsible for patent matters. The disclosure to the agency shall be in the form of a written report and shall identify the *contract* under which the invention was made and the inventor(s). It shall be sufficiently complete in technical detail to convey a clear understanding to the extent

Page **17** of **34** Revised: 2/18/2025

known at the time of the disclosure, of the nature, purpose, operation, and the physical, chemical, biological or electrical characteristics of the invention. The disclosure shall also identify any publication, on sale or public use of the invention and whether a manuscript describing the invention has been submitted for publication and, if so, whether it has been accepted for publication at the time of disclosure. In addition, after disclosure to the *agency*, the *Contractor* will promptly notify the *agency* of the acceptance of any manuscript describing the invention for publication or of any on sale or public use planned by the *contractor*.

- (2) The *Contractor* will elect in writing whether or not to retain title to any such invention by notifying the *Federal agency* within two years of disclosure to the *Federal agency*. However, in any case where publication, on sale or public use has initiated the one year statutory period wherein valid patent protection can still be obtained in the United States, the period for election of title may be shortened by the *agency* to a date that is no more than 60 days prior to the end of the statutory period.
- (3) The *contractor* will file its initial patent application on a subject invention to which it elects to retain title within one year after election of title or, if earlier, prior to the end of any statutory period wherein valid patent protection can be obtained in the United States after a publication, on sale, or public use. The *contractor* will file patent applications in additional countries or international patent offices within either ten months of the corresponding initial patent application or six months from the date permission is granted by the Commissioner of Patents and Trademarks to file foreign patent applications where such filing has been prohibited by a Secrecy Order.
- (4) Requests for extension of the time for disclosure, election, and filing under subparagraphs (1), (2), and (3) may, at the discretion of the *agency*, be granted.
- (d) Conditions When the Government May Obtain Title

The *contractor* will convey to the *Federal agency*, upon written request, title to any subject invention—

- (1) If the *contractor* fails to disclose or elect title to the subject invention within the times specified in (c), above, or elects not to retain title; provided that the *agency* may only request title within 60 days after learning of the failure of the *contractor* to disclose or elect within the specified times.
- (2) In those countries in which the *contractor* fails to file patent applications within the times specified in (c) above; provided, however, that if the *contractor* has filed a patent application in a country after the times specified in (c) above, but prior to its receipt of the written request of the *Federal agency*, the *contractor* shall continue to retain title in that country.

Page **18** of **34** Revised: 2/18/2025

- (3) In any country in which the *contractor* decides not to continue the prosecution of any application for, to pay the maintenance fees on, or defend in reexamination or opposition proceeding on, a patent on a subject invention.
- (e) Minimum Rights to Contractor and Protection of the Contractor Right to File
  - (1) The *contractor* will retain a nonexclusive royalty-free license throughout the world in each subject invention to which the Government obtains title, except if the *contractor* fails to disclose the invention within the times specified in (c), above. The *contractor's* license extends to its domestic subsidiary and affiliates, if any, within the corporate structure of which the *contractor* is a party and includes the right to grant sublicenses of the same scope to the extent the *contractor* was legally obligated to do so at the time the *contract* was awarded. The license is transferable only with the approval of the *Federal agency* except when transferred to the successor of that party of the *contractor's* business to which the invention pertains.
  - (2) The contractor's domestic license may be revoked or modified by the funding Federal agency to the extent necessary to achieve expeditious practical application of the subject invention pursuant to an application for an exclusive license submitted in accordance with applicable provisions at 37 CFR part 404 and agency licensing regulations (if any). This license will not be revoked in that field of use or the geographical areas in which the contractor has achieved practical application and continues to make the benefits of the invention reasonably accessible to the public. The license in any foreign country may be revoked or modified at the discretion of the funding Federal agency to the extent the contractor, its licensees, or the domestic subsidiaries or affiliates have failed to achieve practical application in that foreign country.
  - (3) Before revocation or modification of the license, the *funding Federal agency* will furnish the *contractor* a written notice of its intention to revoke or modify the license, and the *contractor* will be allowed thirty days (or such other time as may be authorized by the *funding Federal agency* for good cause shown by the *contractor*) after the notice to show cause why the license should not be revoked or modified. The *contractor* has the right to appeal, in accordance with applicable regulations in 37 CFR part 404 and *agency* regulations (if any) concerning the licensing of Government-owned inventions, any decision concerning the revocation or modification of the license.

#### (f) Contractor Action to Protect the Government's Interest

(1) The *contractor* agrees to execute or to have executed and promptly deliver to the *Federal agency* all instruments necessary to (i) establish or confirm the rights the Government has throughout the world in those subject inventions to which the *contractor* elects to retain title, and (ii) convey title to the *Federal agency* when requested under paragraph (d) above and to enable the government to obtain patent protection throughout the world in that subject invention.

Page **19** of **34** Revised: 2/18/2025

- (2) The *contractor* agrees to require, by written agreement, its employees, other than clerical and nontechnical employees, to disclose promptly in writing to personnel identified as responsible for the administration of patent matters and in a format suggested by the *contractor* each subject invention made under *contract* in order that the *contractor* can comply with the disclosure provisions of paragraph (c), above, and to execute all papers necessary to file patent applications on subject inventions and to establish the government's rights in the subject inventions. This disclosure format should require, as a minimum, the information required by (c)(1), above. The *contractor* shall instruct such employees through employee agreements or other suitable educational programs on the importance of reporting inventions in sufficient time to permit the filing of patent applications prior to U.S. or foreign statutory bars.
- (3) The *contractor* will notify the *Federal agency* of any decisions not to continue the prosecution of a patent application, pay maintenance fees, or defend in a reexamination or opposition proceeding on a patent, in any country, not less than thirty days before the expiration of the response period required by the relevant patent office.
- (4) The *contractor* agrees to include, within the specification of any United States patent applications and any patent issuing thereon covering a subject invention, the following statement, "This invention was made with government support under (identify the *contract*) awarded by (identify the Federal agency). The government has certain rights in the invention."

#### (g) Subcontracts

- (1) The *contractor* will include this clause, suitably modified to identify the parties, in all subcontracts, regardless of tier, for experimental, developmental or research work. The subcontractor will retain all rights provided for the *contractor* in this clause, and the *contractor* will not, as part of the consideration for awarding the subcontract, obtain rights in the subcontractor's subject inventions.
- (2) In the case of subcontracts, at any tier, when the prime award with the Federal agency was a contract (but not a grant or cooperative agreement), the *agency*, subcontractor, and the contractor agree that the mutual obligations of the parties created by this clause constitute a contract between the subcontractor and the Federal agency with respect to the matters covered by the clause; provided, however, that nothing in this paragraph is intended to confer any jurisdiction under the Contract Disputes Act in connection with proceedings under paragraph (j) of this clause.

#### (h) Reporting on Utilization of Subject Inventions

The *Contractor* agrees to submit on request periodic reports no more frequently than annually on the utilization of a subject invention or on efforts at obtaining such utilization that are being made by the *contractor* or its licensees or assignees. Such reports shall include information regarding the status of development, date of first commercial sale or

Page **20** of **34** Revised: 2/18/2025

use, gross royalties received by the contractor, and such other data and information as the *agency* may reasonably specify. The *contractor* also agrees to provide additional reports as may be requested by the *agency* in connection with any march-in proceeding undertaken by the *agency* in accordance with paragraph (j) of this clause. As required by 35 U.S.C. 202(c)(5), the *agency* agrees it will not disclose such information to persons outside the government without permission of the *contractor*.

#### (i) Preference for United States Industry

Notwithstanding any other provision of this clause, the *contractor* agrees that neither it nor any assignee will grant to any person the exclusive right to use or sell any subject inventions in the United States unless such person agrees that any products embodying the subject invention or produced through the use of the subject invention will be manufactured substantially in the United States. However, in individual cases, the requirement for such an agreement may be waived by the *Federal agency* upon a showing by the *contractor* or its assignee that reasonable but unsuccessful efforts have been made to grant licenses on similar terms to potential licensees that would be likely to manufacture substantially in the United States or that under the circumstances domestic manufacture is not commercially feasible.

#### (j) March-in Rights

The *contractor* agrees that with respect to any subject invention in which it has acquired title, the *Federal agency* has the right in accordance with the procedures in 37 CFR 401.6 and any supplemental regulations of the *agency* to require the *contractor*, an assignee or exclusive licensee of a subject invention to grant a nonexclusive, partially exclusive, or exclusive license in any field of use to a responsible applicant or applicants, upon terms that are reasonable under the circumstances, and if the *contractor*, assignee, or exclusive licensee refuses such a request the *Federal agency* has the right to grant such a license itself if the *Federal agency* determines that:

- (1) Such action is necessary because the *contractor* or assignee has not taken, or is not expected to take within a reasonable time, effective steps to achieve practical application of the subject invention in such field of use.
- (2) Such action is necessary to alleviate health or safety needs which are not reasonably satisfied by the *contractor*, assignee or their licensees;
- (3) Such action is necessary to meet requirements for public use specified by Federal regulations and such requirements are not reasonably satisfied by the *contractor*, assignee or licensees; or
- (4) Such action is necessary because the agreement required by paragraph (i) of this clause has not been obtained or waived or because a licensee of the exclusive right to use or sell any subject invention in the United States is in breach of such agreement.

Page **21** of **34** Revised: 2/18/2025

(k) Special Provisions for Contracts with Nonprofit Organizations

If the *contractor* is a nonprofit organization, it agrees that:

- (1) Rights to a subject invention in the United States may not be assigned without the approval of the *Federal agency*, except where such assignment is made to an organization which has as one of its primary functions the management of inventions, provided that such assignee will be subject to the same provisions as the *contractor*;
- (2) The *contractor* will share royalties collected on a subject invention with the inventor, including Federal employee co-inventors (when the agency deems it appropriate) when the subject invention is assigned in accordance with 35 U.S.C. 202(e) and 37 CFR 401.10;
- (3) The balance of any royalties or income earned by the *contractor* with respect to subject inventions, after payment of expenses (including payments to inventors) incidental to the administration of subject inventions, will be utilized for the support of scientific research or education; and
- (4) It will make efforts that are reasonable under the circumstances to attract licensees of subject invention that are small business firms and that it will give a preference to a small business firm when licensing a subject invention if the *contractor* determines that the small business firm has a plan or proposal for marketing the invention which, if executed, is equally as likely to bring the invention to practical application as any plans or proposals from applicants that are not small business firms; provided, that the *contractor* is also satisfied that the small business firm has the capability and resources to carry out its plan or proposal. The decision whether to give a preference in any specific case will be at the discretion of the *contractor*. However, the *contractor* agrees that the Secretary may review the *contractor's* licensing program and decisions regarding small business applicants, and the *contractor* will negotiate changes to its licensing policies, procedures, or practices with the Secretary when the Secretary's review discloses that the *contractor* could take reasonable steps to implement more effectively the requirements of this paragraph (k)(4).

#### (1) Communication

Any communications to be given hereunder by either party to the other shall be deemed to be duly given if set forth in writing and personally delivered or sent by mail, registered or certified, postage prepaid with return receipt requested, as follows:

Council Chair Jefferson Parish Council 200 Derbigny Street, Suite 6200 Gretna, Louisiana 70053

Written notices hereunder delivered personally shall be deemed communicated as of actual

Page **22** of **34** Revised: 2/18/2025

receipt; mailed notices shall be deemed communicated five (5) days after deposit in the mail, post prepaid, certified, in accordance with this Paragraph.

#### CLEAN AIR ACT AND FEDERAL WATER POLLUTION CONTROL ACT

(For all awarded contracts with a value greater than \$150,000.00)

- (1) The contractor agrees to comply with all applicable standards, orders or regulations issued pursuant to the Clean Air Act, as amended, 42 U.S.C. § 7401 et seq. and the Federal Water Pollution Control Act, as amended, 33 U.S.C. 1251 et seq.
- (2) The contractor agrees to report each violation to Jefferson Parish and understands and agrees that the Jefferson Parish will, in turn, report each violation as required to assure notification to the recipient, Federal Emergency Management Agency, and the appropriate Environmental Protection Agency Regional Office.
- (3) The contractor agrees to include these requirements in each subcontract exceeding \$150,000 financed in whole or in part with federal assistance provided by FEMA.

#### **DEBARMENT AND SUSPENSION**

(Contractor must complete certification and submit prior to award.)

The Contractor represents and warrants that it and its subcontractors are not listed on the governmentwide exclusions in the System for Award Management (SAM), in accordance with the OMB guidelines at 2 CFR 180 that implement Executive Orders 12549 (3 CFR part 1986 Comp., p. 189) and 12689 (3 CFR part 1989 Comp., p. 235), "Debarment and Suspension."

This contract is a covered transaction for purposes of 2 C.F.R. Part 180 and 2 C.F.R. Part 3000. As such, the contractor is required to verify that none of the contractor's principals (defined at 2 C.F.R. § 180.995) or its affiliates (defined at 2 C.F.R. § 180.905) are excluded (defined at 2 C.F.R. § 180.940) or disqualified (defined at 2 C.F.R. § 180.935).

Page **23** of **34** Revised: 2/18/2025

The contractor must comply with 2 C.F.R. Part 180, subpart C and 2 C.F.R. Part 3000, subpart C, and must include a requirement to comply with these regulations in any lower tier covered transaction it enters into.

This certification is a material representation of fact relied upon by (insert name of recipient/subrecipient/applicant). If it is later determined that the contractor did not comply with 2 C.F.R. Part 180, subpart C and 2 C.F.R. Part 3000, subpart C, in addition to remedies available to (insert name of recipient/subrecipient/applicant), the federal government may pursue available remedies, including but not limited to suspension and/or debarment.

The bidder or proposer agrees to comply with the requirements of 2 C.F.R. Part 180, subpart C and 2 C.F.R. Part 3000, subpart C while this offer is valid and throughout the period of any contract that may arise from this offer. The bidder or proposer further agrees to include a provision requiring such compliance in its lower tier covered transactions.

#### BYRD ANTI-LOBBYING AMENDMENT

(Contractor must complete certification and submit prior to award.)

The Contractor certifies, to the best of his or her knowledge and belief that:

- 1. No federally appropriated funds have been paid or will be paid, by or on behalf of the contractor, to any person for influencing or attempting to influence an officer or employee of any agency, a member of Congress, an officer or employee of Congress, or an employee of a member of Congress in connection with the awarding of any federal contract, the making of any federal grant, the making of any federal loan, the entering into of any cooperative agreement, and the extension, continuation, renewal, amendment, or modification of any federal contract, grant, loan, or cooperative agreement.
- 2. If any funds other than federally appropriated funds have been paid or will be paid to any person for influencing or attempting to influence an officer or employee of any agency, a member of Congress, an officer or employee of Congress, or an employee of a member of Congress in connection with this federal contract, grant, loan, or cooperative agreement, the contractor shall complete and submit Standard Form-LLL, "Disclosure Form to Report Lobbying," in accordance with its instructions.

Page **24** of **34** Revised: 2/18/2025

3. Contractor will include language of this certification in all subcontract awards at any tier and require that all recipients of subcontract awards in excess of \$100,000.00 shall certify and disclose accordingly.

#### PROCUREMENT OF RECOVERED MATERIALS

(for all purchase price of items exceeding \$10,000.00 or the value of the quantity acquired during the preceding fiscal year exceeded \$10,000.00)

- (1) In the performance of this contract, the Contractor shall make maximum use of products containing recovered materials that are EPA-designated items unless the product cannot be acquired:
  - i. Competitively within a timeframe providing for compliance with the contract performance schedule;
  - ii. Meeting contract performance requirements; or
  - iii. At a reasonable price.
- (2) Information about this requirement, along with the list of EPA-designated items, is available at EPA's Comprehensive Procurement Guidelines webpage: https://www.epa.gov/smm/comprehensive-procurement-guideline-cpg-program.
- (3) The Contractor also agrees to comply with all other applicable requirements of Section 6002 of the Solid Waste Disposal Act.

# PROHIBITION ON CONTRACTING FOR COVERED TELECOMMUNICTIONS EQUIPMENT OR SERVICES

(for all FEMA declarations and awards)

Prohibition on Contracting for Covered Telecommunications Equipment or Services

(a) Definitions. As used in this clause, the terms backhaul; covered foreign country; covered telecommunications equipment or services; interconnection arrangements; roaming; substantial or essential component; and telecommunications equipment or services have the meaning as defined in FEMA Policy 405-143-1, Prohibitions on Expending FEMA Award Funds for Covered Telecommunications Equipment or Services (Interim), as used in this clause—

Page **25** of **34** Revised: 2/18/2025

#### (b) Prohibitions.

- (1) Section 889(b) of the John S. McCain National Defense Authorization Act for Fiscal Year 2019, Pub. L. No. 115-232, and 2 C.F.R. § 200.216 prohibit the head of an executive agency on or after Aug.13, 2020, from obligating or expending grant, cooperative agreement, loan, or loan guarantee funds on certain telecommunications products or from certain entities for national security reasons.
- (2) Unless an exception in paragraph (c) of this clause applies, the contractor and its subcontractors may not use grant, cooperative agreement, loan, or loan guarantee funds from the Federal Emergency Management Agency to:
  - (i) Procure or obtain any equipment, system, or service that uses covered telecommunications equipment or services as a substantial or essential component of any system, or as critical technology of any system;
  - (ii) Enter into, extend, or renew a contract to procure or obtain any equipment, system, or service that uses covered telecommunications equipment or services as a substantial or essential component of any system, or as critical technology of any system;
  - (iii) Enter into, extend, or renew contracts with entities that use covered telecommunications equipment or services as a substantial or essential component of any system, or as critical technology as part of any system; or
  - (iv) Provide, as part of its performance of this contract, subcontract, or other contractual instrument, any equipment, system, or service that uses covered telecommunications equipment or services as a substantial or essential component of any system, or as critical technology as part of any system.

#### (c) Exceptions.

- (1) This clause does not prohibit contractors from providing—
  - (i) A service that connects to the facilities of a third-party, such as backhaul, roaming, or interconnection arrangements; or
  - (ii) Telecommunications equipment that cannot route or redirect user data traffic or permit visibility into any user data or packets that such equipment transmits or otherwise handles.
- (2) By necessary implication and regulation, the prohibitions also do not apply to:

Page **26** of **34** Revised: 2/18/2025

- (i) Covered telecommunications equipment or services that:
  - i. Are not used as a substantial or essential component of any system; and
  - ii. Are not used as critical technology of any system.
- (ii) Other telecommunications equipment or services that are not considered covered telecommunications equipment or services.

#### (d) Reporting requirement.

- (1) In the event the contractor identifies covered telecommunications equipment or services used as a substantial or essential component of any system, or as critical technology as part of any system, during contract performance, or the contractor is notified of such by a subcontractor at any tier or by any other source, the contractor shall report the information in paragraph (d)(2) of this clause to the recipient or subrecipient, unless elsewhere in this contract are established procedures for reporting the information.
- (2) The Contractor shall report the following information pursuant to paragraph (d)(1) of this clause:
  - (i) Within one business day from the date of such identification or notification: The contract number; the order number(s), if applicable; supplier name; supplier unique entity identifier (if known); supplier Commercial and Government Entity (CAGE) code (if known); brand; model number (original equipment manufacturer number, manufacturer part number, or wholesaler number); item description; and any readily available information about mitigation actions undertaken or recommended.
  - (ii) Within 10 business days of submitting the information in paragraph (d)(2)(i) of this clause: Any further available information about mitigation actions undertaken or recommended. In addition, the contractor shall describe the efforts it undertook to prevent use or submission of covered telecommunications equipment or services, and any additional efforts that will be incorporated to prevent future use or submission of covered telecommunications equipment or services.
- (e) Subcontracts. The Contractor shall insert the substance of this clause, including this paragraph (e), in all subcontracts and other contractual instruments.

Page **27** of **34** Revised: 2/18/2025

#### **DOMESTIC PRERENCES FOR PROCUREMENTS**

(for all FEMA declarations and awards)

As appropriate, and to the extent consistent with law, the contractor should, to the greatest extent practicable, provide a preference for the purchase, acquisition, or use of goods, products, or materials produced in the United States. This includes, but is not limited to iron, aluminum, steel, cement, and other manufactured products.

For purposes of this clause:

Produced in the United States means, for iron and steel products, that all manufacturing processes, from the initial melting stage through the application of coatings, occurred in the United States.

Manufactured products mean items and construction materials composed in whole or in part of non-ferrous metals such as aluminum; plastics and polymer-based products such as polyvinyl chloride pipe; aggregates such as concrete; glass, including optical fiber; and lumber.

### **ACCESS TO RECORDS**

The following access to records requirements applies to this contract:

(1) The contractor agrees to provide Jefferson Parish, the recipient, the FEMA Administrator, the Comptroller General of the United States, or any of their authorized representatives access to any books, documents, papers, and records of the Contractor which are directly pertinent to this contract for the purposes of making audits, examinations, excerpts, and transcriptions.

(2) The Contractor agrees to permit any of the foregoing parties to reproduce by any means whatsoever or to copy excerpts and transcriptions as reasonably needed.

Page **28** of **34** Revised: 2/18/2025

(3) The contractor agrees to provide the FEMA Administrator or his authorized representatives access to construction or other work sites pertaining to the work being completed under the contract.

#### DHS SEAL, LOGO, AND FLAGS

The contractor shall not use the DHS seal(s), logos, crests, or reproductions of flags or likenesses of DHS agency officials without specific FEMA preapproval. The contractor shall include this provision in any subcontracts.

#### COMPLIANCE WITH FEDERAL LAW, REGULATIONS, AND EXECUTIVE ORDERS

This is an acknowledgement that FEMA financial assistance will be used to fund all or a portion of the contract. The contractor will comply with all applicable federal law, regulations, executive orders, FEMA policies, procedures, and directives.

#### NO OBLIGATION BY FEDERAL GOVERNMENT

The Federal Government is not a party to this contract and is not subject to any obligations or liabilities to the non-Federal entity, contractor, or any other party pertaining to any matter resulting from the contract.

# PROGRAM FRAUD AND FALSE OR FRAUDULENT STATEMENTS OR RELATED ACTS

The contractor acknowledges that 31 U.S.C. Chap. 38 (Administrative Remedies for False Claims and Statements) applies to the contractor's actions pertaining to this contract.

#### **AFFIRMATIVE SOCIOECONOMIC STEPS**

If subcontracts are to be let, the prime contractor is required to take all necessary steps identified in 2 C.F.R. § 200.321(b)(1)-(5) to ensure that small and minority businesses, women's business enterprises, and labor surplus area firms are used when possible.

Page **29** of **34** Revised: 2/18/2025

#### **COPYRIGHT**

License and Delivery of Works Subject to Copyright and Data Rights

The Contractor grants to the Jefferson Parish, a paid-up, royalty-free, nonexclusive, irrevocable, worldwide license in data first produced in the performance of this contract to reproduce, publish, or otherwise use, including prepare derivative works, distribute copies to the public, and perform publicly and display publicly such data. For data required by the contract but not first produced in the performance of this contract, the Contractor will identify such data and grant to the Jefferson Parish or acquires on its behalf a license of the same scope as for data first produced in the performance of this contract. Data, as used herein, shall include any work subject to copyright under 17 U.S.C. § 102, for example, any written reports or literary works, software and/or source code, music, choreography, pictures or images, graphics, sculptures, videos, motion pictures or other audiovisual works, sound and/or video recordings, and architectural works. Upon or before the completion of this contract, the Contractor will deliver to the Jefferson Parish data first produced in the performance of this contract and data required by the contract but not first produced in the performance of this contract in formats acceptable by the Jefferson Parish.

#### **CONFLICT OF INTEREST**

Jefferson Parish adheres to the Louisiana Code of Governmental Ethics, contained in Louisiana Revised Statutes Annotated, R.S. 42:1101, et seq. Vendor/Proposer by this submission warrants that there are no "conflicts of interest" related to this procurement that would violate applicable Louisiana Law. Violation of the Louisiana Code of Governmental Ethics may result in rescission of contract, permit or licenses, and the imposition of fines and/or penalties, without contractual liability to the public in accordance with applicable law.

#### GENERAL PROVISION FOR DOMESTIC PREFERENCE FOR PROCUREMENTS

As appropriate, and to the extent consistent with Uniform Guidance of 2 C.F.R. § 200.322, the contractor should, to the greatest extent practicable, provide a preference for the purchase, acquisition, or use of goods, products, or materials produced in the United States. This includes,

Page **30** of **34** Revised: 2/18/2025

but is not limited to iron, aluminum, steel, cement, and other manufactured products. For purposes of this clause:

<u>Produced in the United States means, for iron and steel products, that all manufacturing</u> processes, from the initial melting stage through the application of coatings, occurred in the <u>United States.</u>

Manufactured products mean items and construction materials composed in whole or in part of non-ferrous metals such as aluminum; plastics and polymer-based products such as polyvinyl chloride pipe; aggregates such as concrete; glass, including optical fiber; and lumber.

### **DEPARTMENT OF AGRICULTURE BUY AMERICAN PROVISION (7 C.F.R. § 210.21)**

(This specific requirement applies to contracts for projects receiving federal financial assistance through USDA. Pursuant to Uniform Guidance 2 C.F.R. § 200.322, performance of the provision for domestic preference applies to all contracts funded through federal financial assistance not only for the agricultural commodities)

Jefferson Parish requires that a <u>school food authority</u> purchase, to the maximum extent practicable, domestic commodities or products.

<u>Definition of domestic commodity or product</u>: the term 'domestic commodity or product' means -

- \* An agricultural commodity that is produced in the United States; and
- \* A food product that is processed in the <u>United States</u> substantially using agricultural commodities that are produced in the <u>United States</u>.
- \* Any commodity required by the Federal Grant to be domestically manufactured; parts or equipment to be manufactured in the United States.

Page **31** of **34** Revised: 2/18/2025

The School Food Authority and vendor shall comply with the **Buy American Provision** for all solicitations and contracts that involve the purchase of food, USDA Regulation (7 CFR Part 250 and 7 CFR Part 210). The vendor is required to utilize, to the maximum extent practicable, domestic commodities and products. This requirement pertains to component items. It does not include spices, sauces, etc.

The District participates in the National School Lunch Program and School Breakfast Program and is required to use the nonprofit food service funds, to the maximum extent practical, to buy domestic commodities or products for Program meals. A "domestic commodity or product" is defined as one that is either produced in the U.S. or is processed in the U.S. substantially using agricultural commodities that are produced in the U.S. as provided in 7 CFR Part 210.21(d). Section 12(n) of the National School Lunch Act defines "domestic commodity or product" as an agricultural commodity that is produced in the U.S. and a food product that is processed in the U.S. Substantially means over 51% of the final processed product (by weight or volume) must consist of agricultural commodities that were grown domestically. The Buy American provision must be followed in all procurements where funds are used from the nonprofit food service account, whether directly by an SFA or on its behalf.

Exceptions to the Buy American provision should be used as a last resort; however, an alternative or exception may be approved upon request. To be considered for the alternative or exception, the request must be submitted in writing to a designated official, a minimum of day 14 days in advance of delivery. The request must include the:

Alternative substitute (s) that are domestic and meet the required specifications:

- 1. The product is not produced or manufactured in the U.S. in sufficient and reasonably available quantities of a satisfactory quality; or
- 2. Competitive bids reveal the costs of a U.S. product are significantly higher than the non-domestic product.

Page **32** of **34** Revised: 2/18/2025

Anti-Lobbying Form				
CERTIFICATION OF RESTRICTIONS ON LOBBYING				
l,, hereby certify on (name and title of bidder's official)				
(name and title of bidder's official)				
behalf of that:  (name of bidder)				
(name of bidder)				
(1) No Federal appropriated funds have been paid or will be paid, by or on behalf of the undersigned, to any person for influencing or attempting to influence an officer or employee of any agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with the awarding of any Federal contract, the making of any Federal grant, the making of any Federal loan, the entering into of any cooperative agreement, and the extension, continuation renewal, amendment, or modification of any Federal contract, grant, loan, or cooperative agreement.				
(2) If any funds other than Federal appropriated funds have been paid or will be paid to any person for influencing or attempting to influence an officer or employee of any agency, a Member of Congress, an officer or employee of Congress, or an employe of a Member of Congress in connection with this Federal contract, grant, loan, or cooperative agreement, the undersigned shall complete and submit standard Form LLL, "Disclosure Form to Report Lobbying," in accordance with its instructions.				
(3) The undersigned shall require that the language of this certification be included in the award documents for all sub awards at all tiers (including subcontracts, sub grants and contracts under grants, loans, and cooperative agreements) and that all subrecipients shall certify and disclose accordingly.				
This certification is a material representation of fact upon which reliance is placed when his transaction was made or entered into. Submission of this certification is a prerequisite for making or entering into this transaction imposed by section 1352, title 3° J.S. Code. Any person who fails to file the required certification shall be subject to a cive penalty of not less than \$10,000 and not more than \$100,000 for each such failure.				
Executed this, day of				
By signature of authorized official)				
title of authorized official)				

Page **33** of **34** Revised: 2/18/2025

Debarment/Suspension Form

#### **DEBARMENT/SUSPENSION CERTIFICATION**

#### **Debarment:**

Federal Executive Order (E.O.) 12549 "Debarment" requires that all contractors receiving individual awards, using federal funds, and all subrecipients certify that the organization and its principals are not debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded by any Federal department or agency from doing business with the Federal Government. By signing this document you certify that your organization and its principals are not debarred. Failure to comply or attempts to edit this language may disqualify your bid. Information on debarment is available at the following websites: <a href="https://acquisition.gov/far/index.html">www.sam.gov</a> and <a href="https://acquisition.gov/far/index.html">https://acquisition.gov/far/index.html</a> see section 52.209-6.

Your signature certifies that neither you nor your principal is presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from participation in this transaction by any federal department or agency.

	(	Name and Title of bidder's official)	
		(Name of bidder/company)	
		(Address)	
		(Address)	
PHO	ONE _	FAX	_
EMA	IL		
		Signature	Date

Page **34** of **34** Revised: 2/18/2025

## **Bid Bond**

An Electronic Bid Bond must be submitted with this bid, through one of the respective clearing houses at <a href="https://www.centralbidding.com/bid-bonds/">https://www.centralbidding.com/bid-bonds/</a> To access the bonding companies on Central Bidding, hover over the "Central Bidding" link at the top of the page and select the "Bid Bonds" link.

The electronic bid bond number is to be placed in the required section listed on the standard envelope. Scanned copies of bid bonds will not be accepted with your submission.

