State of Louisiana Department of Transportation and Development

APPROVED MATERIALS LIST

AGGREGATES

Aggregates from the following sources have demonstrated the capability to conform to the quality requirements of Section 1003 of the Department's Standard Specifications for Roads and Bridges, except as noted.

See 'Endnotes' and 'Notes' at the end of each section.

Water Absportion = 0.5%

Updated = 8/22/2017

A. CHERT GRAVEL AND SILICA SANDS

Chert gravels on this list have a Friction Rating of III when used as a coarse aggregate for Asphaltic Concrete. Friction Ratings are defined in Subsection 1003.06

A-1. IN-STATE PRODUCER/SUPPLIERS - BY DISTRICT

A-	1. IIV-2 I	ATE PRODUCER/SUPPLIERS - BY DISTRICT
District 03		
APS00006160	(A309)	Dupont Sand, LLC-Carencro, LA
<u>Material</u>		Approved Uses
Sand Only		Granular Material for Subbase
Carencro		Special Embankment (non-plastic)
Spec. Gravity-S	SSD = 2.62	Asphaltic Concrete
Water Absporti	on = 0.5%	Portland Cement Concrete
Updated = 8/22/2017		
APS00006550	(A308)	L & W Sand Pit, LLC-Carencro, LA
<u>Material</u>		Approved Uses
Sand Only		Granular Material for Subbase
Carencro		Special Embankment (non-plastic)
Spec. Gravity-S		Asphaltic Concrete
Water Absporti	on = 0.5%	Portland Cement Concrete
Updated = 8/22/2017		
APS00007310	(A310)	Vermillion Shell & Limestone Co. IncMaurice, LA
<u>Material</u>		Approved Uses
Sand Only		Granular Material for Subbase
Maurice		Special Embankment (non-plastic)
Spec. Gravity-S		Asphaltic Concrete
Water Absporti	on = 0.5%	Portland Cement Concrete
Updated = 8/22/2017		
APS00011660	(A311)	Perero Co. DBA-DND Landscape - Broussard, LA
<u>Material</u>		Approved Uses
Sand Only		Granular Material for Subbase
Broussard		Special Embankment (non-plastic)
Spec. Gravity-S		Asphaltic Concrete
Water Absporti	on = 0.5%	Portland Cement Concrete
Updated = 8/22/2017		
APS00011760	(A312)	Lafayette Sand & Fill - Lafayette, LA
<u>Material</u>		Approved Uses
Sand Only		Granular Material for Subbase
Carencro		Special Embankment (non-plastic)
Spec. Gravity-S	SSD = 2.62	Asphaltic Concrete

Portland Cement Concrete

				~ ~	
	ist	ric	\+ /		,
	ı 🥆 ı				۱
-	ıvı	ıı	/L '	-	,

	District 03	
	APS00012000	Red Hawk Materials - Maurice, LA
	<u>Material</u>	Approved Uses
	Sand Only	Granular Material for Subbase
	Maurice	Special Embankment (non-plastic)
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete
	Water Absportion = 0.5%	Portland Cement Concrete
	Updated = 8/22/2017	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
	APS00012170	Red Hawk Materials, LLC - Carencro, LA
	<u>Material</u>	Approved Uses
	Sand Only	Granular Material for Subbase
	Carencro	Special Embankment (non-plastic)
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete
	Water Absportion = 0.5%	Portland Cement Concrete
	Updated = 8/22/2017	
	APS00012630	Glenn Lege Construction - Youngsville
	<u>Material</u>	Approved Uses
	Sand Only	Granular Material for Subbase
	Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
	Water Absportion = 0.5%	Asphaltic Concrete
	Updated = 1/12/2024	
	APS00015080	B & D Materials, LLC - Parks, LA
	<u>Material</u>	Approved Uses
	Sand Only	Granular Material for Subbase
	Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
	Water Absportion = 0.5%	Asphaltic Concrete
	Updated = 4/7/2022	Portland Cement Concrete
		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of
		Class F fly ash and GGBFS with a minimum of 50% replacement)
	District 04	
	APS00006830 (A428)	MRH Sand & Gravel-Benton, LA
	<u>Material</u>	Approved Uses
	Gravel	Granular Material for Subbase
Benton		Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.60 Water Absportion = 1.0%		Asphaltic Surface Treatment
		Asphaltic Concrete
	Sand	(Friction Rating = III - Coarse Agg. Only)
	Benton	Portland Cement Concrete
	Spec. Gravity-SSD = 2.62	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
Water Absportion = 0.5%		· · · · · · · · · · · · · · · · · · ·

District 04

APS00007000	(A427)	South Land Sand-Ringgold, LA

<u>Materia</u>	<u>al</u>	Approved Uses
Gravel Only		Base & Surface Course
	Ringgold	Granular Material for Subbase
	Spec. Gravity-SSD = 2.60	Asphaltic Surface Treatment
	Water Absportion = 1.0%	Asphaltic Concrete

Updated = 8/25/2017 (Friction Rating = III - Coarse Agg. Only)

Portland Cement Concrete

APS00011330 (A429) Blount Brothers Construction, Inc. -Shreveport, LA

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Blout Bros. Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete

Updated = 8/22/2017

APS00011910 Hat Creek Dirt Pit - Bossier City, LA

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
Water Absportion = 0.5%	Asphaltic Concrete
Updated = 2/17/2017	Portland Cement Concrete

APS00012310 SiteWurx Sand - Sibley, LA

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Sibley - 164 Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete

Updated = 8/22/2017

APS00012660 Skyplex Trucking -Bentley, LA

<u>Material</u>	Approved Uses	
Sand Only	Granular Material for Subbase	
Wallace Pit	Special Embankment (non-plastic)	
Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
Water Absportion = 0.5%	Portland Cement Concrete	
Updated = 8/22/2017		

District 05

APS00006000 (A509) Century Ready Mix - West Monroe, LA

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Jonesboro Road	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete

			$\sim -$
	ICT.	rict	114
$ \boldsymbol{\cup}$	เอเ	HUL	U.

	District 05		
	APS00007270 (A502)	Martin Marietta - Perryville,LA	
	<u>Material</u>	Approved Uses	
	Gravel	Base & Surface Course	
	Perryville	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.54	Special Embankment (non-plastic)	
	Water Absportion = 1.7%	Asphaltic Surface Treatment	
	Sand	Asphaltic Concrete	
	Perryville	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
	Water Absportion = 0.5%		
	Updated = 8/22/2017		
	APS00014950	Star Silica LLC West Monroe, LA	
	<u>Material</u>	Approved Uses	
	Gravel	Base & Surface Course	
	Spec. Gravity-SSD = 2.52	Granular Material for Subbase	
	Water Absportion = 2.5%	Special Embankment (non-plastic)	
	Sand	Asphaltic Surface Treatment	
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
	Updated = 3/12/2025	Portland Cement Concrete - Gravel Only	
	APS00015510	G & W Sand & Gravel, LLC West Monroe	
	<u>Material</u>	Approved Uses	
	Sand Only	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)	
	Water Absportion = 0.5%	Asphaltic Concrete	
	Updated = 6/20/2023	Portland Cement Concrete	
		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)	
	District 07		
	APS00006130 (A712)	DSD Energy Services-Oakdale, LA	
	<u>Material</u>	Approved Uses	
	Sand Only	Granular Material for Subbase	
	Oakdale Pit	Special Embankment (non-plastic)	
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
	Water Absportion = 0.5%	Portland Cement Concrete	
	Updated = 8/22/2017		
	APS00006520 (A710)	Kinder Sand CoKinder, LA	
<u>Material</u>		Approved Uses	
Sand Only		Granular Material for Subbase	
	Kinder	Special Embankment (non-plastic)	
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
	Water Absportion = 0.5%	Portland Cement Concrete	
Updated = 8/22/2017		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	

Updated = 8/3/2022

District 07	
APS00007320 (A709)	Village Sand, IncKinder, LA
<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Indian Village	Asphaltic Concrete
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	
Updated = 8/22/2017	
APS00012100	Lake Area Materials, LLC - DeRidder
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.54	Granular Material for Subbase
Water Absportion = 1.7%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 3/21/2017	Portland Cement Concrete
APS00012190	Elite Sand - Longville, LA
<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
Water Absportion = 0.5%	Asphaltic Concrete
Updated = 4/13/2017	Portland Cement Concrete
APS00012390	Gator Aggregates - Deridder, LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Pippin Pit	Granular Material for Subbase
Spec. Gravity-SSD = 2.53	Special Embankment (non-plastic)
Water Absportion = 2.2%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Pippin Pit	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	
Updated = 8/22/2017	
APS00014360	Arcosa Aggregates - Anacoco Plant 1391-Merryville
Material	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.55	Granular Material for Subbase
Water Absportion = 1.0%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)

Portland Cement Concrete

Distri	ct 07		
APS00014370		Ard	cosa Aggregates - Indian Village Plant 1284
Materia	al		Approved Uses
Sand C	 Only		Granular Material for Subbase
	Spec. Gravity-SSD = 2.62		Special Embankment (non-plastic)
	Water Absportion = 0.5%		Asphaltic Concrete
Update	d = 7/29/2022		Portland Cement Concrete
APS00014470		Me	erryville Aggregate, LLC - Evans, LA
<u>Materia</u>	<u>al</u>		Approved Uses
Gravel			Base & Surface Course
	Spec. Gravity-SSD = 2.56		Granular Material for Subbase
	Water Absportion = 1.2%		Special Embankment (non-plastic)
Sand			Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.62		Asphaltic Concrete
	Water Absportion = 0.5%		(Friction Rating = III - Coarse Agg. Only)
Update	d = 2/12/2021		Portland Cement Concrete
			(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
APS00014890		So	uth Coast Materials, LLC Longville
<u>Materia</u>	<u>al</u>		Approved Uses
Sand C			Granular Material for Subbase
	Spec. Gravity-SSD = 2.62		Special Embankment (non-plastic)
	Water Absportion = 0.5%		Asphaltic Concrete
Update	d = 5/7/2024		
APS00014960		Ard	cosa Aggregates - West Merryville, LA
<u>Materia</u>	<u>al</u>		Approved Uses
Gravel			Base & Surface Course
	Spec. Gravity-SSD = 2.73		Granular Material for Subbase
	Water Absportion = 1.1%		Special Embankment (non-plastic)
Sand			Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.62		Asphaltic Concrete
	Water Absportion = 0.5%		(Friction Rating = III - Coarse Agg. Only)
Update	d = 2/18/2025		Portland Cement Concrete
APS00015140 A		Ard	cosa Aggregates - Plant LA 1343 - DeRidder
<u>Material</u>			Approved Uses
Gravel			Base & Surface Course
	Spec. Gravity-SSD = 2.57		Granular Material for Subbase
	Water Absportion = 0.7%		Special Embankment (non-plastic)
Sand			Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.62		Asphaltic Concrete
	Water Absportion = 0.5%		(Friction Rating = III - Coarse Agg. Only)
Update	d = 5/4/2022		Portland Cement Concrete

			~~
1)	ıctr	ict	$^{\prime}$
-	เอน	IUL	w

	District 08		
	APS00007150 (A844)	Tanner Heavy Equipment Co-Leesville, LA	
	<u>Material</u>	Approved Uses	
	Sand Only	Granular Material for Subbase	
	Tanner Pit #2	Special Embankment (non-plastic)	
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
	Water Absportion = 0.5%	Portland Cement Concrete	
	Updated = 8/25/2017		
	APS00007300 (A822)	Martin Marietta - Woodworth, LA	
	<u>Material</u>	Approved Uses	
	Gravel	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.54	Special Embankment (non-plastic)	
	Water Absportion = 1.7%	Asphaltic Surface Treatment	
	Sand	Asphaltic Concrete	
	Spec. Gravity-SSD = 2.62	(Friction Rating = III - Coarse Agg. Only)	
	Water Absportion = 0.5%	Portland Cement Concrete	
	Updated = 8/22/2017	(Gravel from this source contains an unusual amount of hematite iron ore, if used in Portland Cement Concrete, the hematite content cannot exceed 2%)	
	APS00011680 (A847)	Larry Grayson & Son Trucking, LLC -Forest Hill, LA	
	<u>Material</u>	Approved Uses	
	Gravel	Granular Material for Subbase	
	Ahtus Melder Rd Pit	Special Embankment (non-plastic)	
	Spec. Gravity-SSD = 2.57	Asphaltic Surface Treatment	
	Water Absportion = 1.0%	Asphaltic Concrete	
	Sand	(Friction Rating = III - Coarse Agg. Only)	
	Ahtus Melder Rd Pit	Portland Cement Concrete	
Spec. Gravity-SSD = 2.62			
	Water Absportion = 0.5%		
	Updated = 8/22/2017		
	APS00011710 (A849)	Diamond B Construction Co.,LLC - Boyce, LA	
	<u>Material</u>	Approved Uses	
	Sand Only	Granular Material for Subbase	
	Hot Wells / Gardener Pit	Special Embankment (non-plastic)	
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
	Water Absportion = 0.5%	Portland Cement Concrete	
	Updated = 8/22/2017		
	APS00011720 (A850)	Diamond B Construction Co., LLC Woodworth, LA	
	<u>Material</u>	Approved Uses	
	Sand Only	Granular Material for Subbase	
	Woodworth Pit	Special Embankment (non-plastic)	
	Spec. Gravity-SSD = 2.65	Asphaltic Concrete	
	Water Absportion = 0.2%	Portland Cement Concrete	
Updated = 5/7/2024		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)	

District (8(
------------	----

APS00014440	Cenla Materials - Forest Hill, LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.55	Granular Material for Subbase
Water Absportion = 1.5%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 8/25/2020	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
APS00016060	Larry Grayson & Son Trucking, LLC #2-Forest Hill
<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)

Water Absportion = 0.5% Updated = 4/14/2025

District 58

711 OUOUUT 100 (71014) OWIIII EIIICIPII303 OUIGIIIDIA, E	APS00007130	(A914)	Swim Enterprises-Columbia,	LA
--	-------------	--------	----------------------------	----

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Columbia	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete
Un detect 0/00/0047	

Asphaltic Concrete

Updated = 8/22/2017

APS00007290 (A913) Martin Marietta - Jena, LA

<u>Material</u>			Approved Uses Base & Surface Course	
	Gravel			
	Jena		Granular Material for Subbase	
	Spec.	Gravity-SSD = 2.55	Special Embankment (non-plastic)	
	Water	Absportion = 1.5%	Asphaltic Surface Treatment	
	Sand		Asphaltic Concrete	
	Jena		(Friction Rating = III - Coarse Agg. Only)	
	Spec.	Gravity-SSD = 2.62	Portland Cement Concrete	
	Water	•	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	

Spec. Gravity-SSD = 2.62

Water Absportion = 0.5%

A-1. IN-STATE PRODUCER/SUPPLIERS - BY DISTRICT

District 58

APS0	0011810	(A916)	Pokey's Materials - Olla, LA
<u>Material</u>			Approved Uses
Gravel			Base & Surface Course
	F.K.A. Amberg	Construction	Granular Material for Subbase
	Spec. Gravity-	SSD = 2.53	Special Embankment (non-plastic)
	Water Absporti	ion = 2.2%	Asphaltic Surface Treatment
Sand			Asphaltic Concrete
	F.K.A. Amberg	Construction	(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-	SSD = 2.62	Portland Cement Concrete
	Water Absporti	ion = 0.5%	
	F.K.A. Amberg	Construction	
Updated	= 2/24/2025		
APS0	0015030		Amberg Construction, LLC Olla
<u>Material</u>			Approved Uses
Gravel			Base & Surface Course
	Spec. Gravity-	SSD = 2.52	Granular Material for Subbase
	Water Absporti	ion = 1.8%	Special Embankment (non-plastic)
Sand			Asphaltic Surface Treatment

Updated = 4/7/2022	Portland Cement Concrete	
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)	

(Friction Rating = III - Coarse Agg. Only)

APS00015090 D & J Construction Co., LLC - Aimwell, LA

Asphaltic Concrete

<u>Material</u>	Approved Uses Granular Material for Subbase	
Sand Only		
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)	
Water Absportion = 0.5%	Asphaltic Concrete	
Updated = 4/7/2022	Portland Cement Concrete	
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)	

District 61

APS00002200 (A628) Bear Industries - Port Allen, LA

Mate	<u>eriai</u>	Approved Uses
Sand	d Only	Asphaltic Concrete
	Port Allen	
	Spec. Gravity-SSD = 2.62	
	Water Absportion = 0.5%	

District 61

APS0	0005950	(A646)	Bunch Sand and Gravel #1 - Clinton, LA
<u>Material</u>			Approved Uses
Gravel			Base & Surface Course
	Pit #1		Granular Material for Subbase
	Spec. Gravity-S	SSD = 2.55	Special Embankment (non-plastic)
	Water Absporti	on = 1.3%	Asphaltic Surface Treatment
Sand			Asphaltic Concrete
	Pit #1		(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-S	SSD = 2.62	Portland Cement Concrete
	Water Absporti	on = 0.5%	
المطملاء ال	7/00/0040		

Updated = 7/26/2018

APS00006180 (A636) Feliciana Farms, Inc.-St. Francisville, LA

<u>Material</u>		Approved Uses
Gravel		Base & Surface Course
	Bayou Sara	Granular Material for Subbase
	Spec. Gravity-SSD = 2.54	Special Embankment (non-plastic)
	Water Absportion = 1.7%	Asphaltic Surface Treatment
Sand		Asphaltic Concrete
	Bayou Sara	(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete
	Water Absportion = 0.5%	

Updated = 8/22/2017

APS00006400 (A632) Hooper Road Dirt Pit-Baton Rouge, LA

<u>Material</u>	Approved Uses	
Sand Only	Granular Material for Subbase	
Baton Rouge	Special Embankment (non-plastic)	
Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
Water Absportion = 0.5%	Portland Cement Concrete	

Updated = 8/22/2017

APS00007010 (A640) Southern Aggregates, LLC-Norwood, LA

<u> Materia</u>	<u>I</u>	Approved Uses
Gravel		Base & Surface Course
	Felps	Granular Material for Subbase
	Spec. Gravity-SSD = 2.53	Special Embankment (non-plastic)
	Water Absportion = 2.2%	Asphaltic Surface Treatment
Sand		Asphaltic Concrete
	Felps	(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete
	Water Absportion = 0.5%	

			A 4
1 1	istr	ıct.	につ
$ \cup$	เอน	ıcı	OΙ

District 61	
APS00011640 (A644)	Fleniken Sand & Gravel Inc - Clinton, LA
<u>Material</u>	Approved Uses
Gravel	Granular Material for Subbase
Acme Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.52	Asphaltic Surface Treatment
Water Absportion = 1.9%	Asphaltic Concrete
Sand	(Friction Rating = III - Coarse Agg. Only)
Acme Pit	Portland Cement Concrete
Spec. Gravity-SSD = 2.62	
Water Absportion = 0.5%	
Updated = 7/26/2018	
APS00011650 (A645)	Dolese Bros-St.HelenaSand&Gravel - Pine Grove, LA
Material	Approved Uses
Gravel	Base & Surface Course
St. Helena S&G Pit	Granular Material for Subbase
Spec. Gravity-SSD = 2.54	Special Embankment (non-plastic)
Water Absportion = 1.6%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
St. Helena S&G Pit	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
Updated = 6/3/2020	
APS00011920	Regional Sand & Gravel - Clinton, LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Highway 960 Pit	Granular Material for Subbase
Spec. Gravity-SSD = 2.50	Special Embankment (non-plastic)
Water Absportion = 3.0%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Highway 960 Pit	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
Updated = 8/22/2017	
APS00012530	Dennis Stewart Equipment Rental,Inc Baton Rouge,LA
<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Joor Road Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete
Updated = 8/22/2017	
APS00012910	South Louisiana Fill Materials, LLC - Darrow, LA
<u>Material</u>	Approved Uses
Sand Only	Asphaltic Concrete
Spec. Gravity-SSD = 2.62	
Water Absportion = 0.5%	
Updated = 1/5/2024	

AGC	GGREGATES APPROVED MATERIALS LIST A-1. IN-STATE PRODUCER/SUPPLIERS - BY DISTRICT			
	District 61			
	APS00014150	Lionel Boudreaux Trucking, LLC - St. Francisville		
	Material	Approved Uses		
	Sand Only	Granular Material for Subbase		
	Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)		
	Water Absportion = 0.5%	Asphaltic Concrete		
	Updated = 10/16/2019	Portland Cement Concrete		
	APS00014180	Ivey Enterprises, LLC - Greenwell Springs, LA		
	<u>Material</u>	Approved Uses		
	Gravel	Base & Surface Course		
	Spec. Gravity-SSD = 2.48	Granular Material for Subbase		
	Water Absportion = 2.7%	Special Embankment (non-plastic)		
	Sand	Asphaltic Surface Treatment		
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete		
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)		
	Updated = 10/16/2019	Portland Cement Concrete		
		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)		
	APS00014850	Superior Sand & Gravel - Plant 1 - Clinton, LA		
	<u>Material</u>	Approved Uses		
	Gravel	Base & Surface Course		
	Spec. Gravity-SSD = 2.57	Granular Material for Subbase		
	Water Absportion = 0.8%	Special Embankment (non-plastic)		
	Sand	Asphaltic Surface Treatment		
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete		
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)		
	Updated = 10/5/2021	Portland Cement Concrete		
		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)		
	APS00014860	Superior Sand & Gravel - Plant 2 - Clinton		
	<u>Material</u>	Approved Uses		
	Gravel	Base & Surface Course		
	Spec. Gravity-SSD = 2.51	Granular Material for Subbase		
	Water Absportion = 2.5%	Special Embankment (non-plastic)		
	Sand	Asphaltic Surface Treatment		

<u>Material</u>		Approved Uses	
Gravel		Base & Surface Course	
	Spec. Gravity-SSD = 2.51	Granular Material for Subbase	
	Water Absportion = 2.5%	Special Embankment (non-plastic)	
Sand		Asphaltic Surface Treatment	
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
Update	d = 10/5/2021	Portland Cement Concrete	

(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)

		~ 4
 istr	ICT.	ムコ
ווכו	11.71	() I

	District 61		
	APS00015000 Material		arriere Construction Co. LLC - Map Pit
			Approved Uses
	Gravel		Base & Surface Course
		vity-SSD = 2.49	Granular Material for Subbase
		sportion = 3.2%	Special Embankment (non-plastic)
	Sand		Asphaltic Surface Treatment
	•	vity-SSD = 2.62	Asphaltic Concrete
		sportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
	Updated = 3/12/20		Portland Cement Concrete - Gravel Only
	APS0001515	0 Ar	cosa Aggregates - Plant LA 1342 - Clinton Pit
	<u>Material</u>		Approved Uses
	Gravel		Base & Surface Course
	•	vity-SSD = 2.52	Granular Material for Subbase
		sportion = 2.2%	Special Embankment (non-plastic)
	Sand	'' OOD 000	Asphaltic Surface Treatment
	· · · · · · · · · · · · · · · · · · ·	vity-SSD = 2.62	Asphaltic Concrete
	Updated = 8/3/202	sportion = 0.5%	(Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete
	•		
	APS00015490		outh Louisiana Fill Materials LLC - Convent
	Material		Approved Uses
	Sand Only		Asphaltic Concrete
	· · · · · · · · · · · · · · · · · · ·	vity-SSD = 2.62	
	Updated = 1/5/202	sportion = 0.5%	
	•		unarian Canad & Cuaval Blant 2 Cuannual Cuara
	APS0001552	.0 50	iperior Sand & Gravel - Plant 3 - Greenwell Sprgs
	Material Cravel		Approved Uses
	Gravel Space Gra	vity-SSD = 2.53	Base & Surface Course Granular Material for Subbase
	•	sportion = 1.9%	Special Embankment (non-plastic)
	Sand	sportion = 1.970	Asphaltic Surface Treatment
		vity-SSD = 2.62	Asphaltic Concrete
	•	sportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
	Updated = 3/12/20	•	Portland Cement Concrete - Gravel Only
	APS0001613		agnolia Sand Gravel Soil - Denham Springs
	Material		Approved Uses
	Gravel		Base & Surface Course
	Spec. Gra	vity-SSD = 2.51	Granular Material for Subbase
	Water Abs	sportion = 2.5%	Special Embankment (non-plastic)
	Water Abs	sportion = 2.5%	Special Embankment (non-plastic) Asphaltic Surface Treatment
	Sand Spec. Gra	vity-SSD = 2.65	Asphaltic Surface Treatment Asphaltic Concrete
	Sand Spec. Gra	vity-SSD = 2.65 sportion = 0.2%	Asphaltic Surface Treatment

			A 4
1 1	istr	ıct.	につ
$ \cup$	เอน	ıcı	OΙ

Approved Uses Gravel Base & Surface Course Spec. Gravity-SSD = 2.51 Granular Material for Subbase Water Absportion = 2.3% Special Embankment (non-plastic) Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.65 Asphaltic Concrete Water Absportion = 0.1% (Friction Rating = III - Coarse Agg. Only) Updated = 2/24/2025 Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) APS00016210 Ivey Dirt & Aggregates - Greenwell Springs Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.65 Special Embankment (non-plastic) Water Absportion = 0.2% Asphaltic Concrete Updated = 12/4/2024		
Gravel Base & Surface Course Spec. Gravity-SSD = 2.51 Granular Material for Subbase Water Absportion = 2.3% Special Embankment (non-plastic) Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.65 Asphaltic Concrete Water Absportion = 0.1% (Friction Rating = III - Coarse Agg. Only) Updated = 2/24/2025 Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) APS00016210 Ivey Dirt & Aggregates - Greenwell Springs Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.65 Special Embankment (non-plastic) Water Absportion = 0.2% Asphaltic Concrete	APS00016140	Convent Minority Material Supplier LLC #2
Spec. Gravity-SSD = 2.51 Granular Material for Subbase Water Absportion = 2.3% Special Embankment (non-plastic) Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.65 Asphaltic Concrete Water Absportion = 0.1% (Friction Rating = III - Coarse Agg. Only) Updated = 2/24/2025 Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) APS00016210 Ivey Dirt & Aggregates - Greenwell Springs Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.65 Special Embankment (non-plastic) Water Absportion = 0.2% Asphaltic Concrete	<u>Material</u>	Approved Uses
Water Absportion = 2.3% Special Embankment (non-plastic) Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.65 Asphaltic Concrete Water Absportion = 0.1% (Friction Rating = III - Coarse Agg. Only) Updated = 2/24/2025 Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) APS00016210 Ivey Dirt & Aggregates - Greenwell Springs Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.65 Special Embankment (non-plastic) Water Absportion = 0.2% Asphaltic Concrete	Gravel	Base & Surface Course
Sand Asphaltic Surface Treatment Spec. Gravity-SSD = 2.65 Water Absportion = 0.1% Updated = 2/24/2025 Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) APS00016210 Ivey Dirt & Aggregates - Greenwell Springs Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.65 Special Embankment (non-plastic) Water Absportion = 0.2% Asphaltic Concrete	Spec. Gravity-SSD = 2.51	Granular Material for Subbase
Spec. Gravity-SSD = 2.65 Water Absportion = 0.1% Updated = 2/24/2025 Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) APS00016210 Ivey Dirt & Aggregates - Greenwell Springs Material Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.65 Special Embankment (non-plastic) Water Absportion = 0.2% Asphaltic Concrete	Water Absportion = 2.3%	Special Embankment (non-plastic)
Water Absportion = 0.1% (Friction Rating = III - Coarse Agg. Only) Updated = 2/24/2025 Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) APS00016210 Ivey Dirt & Aggregates - Greenwell Springs Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.65 Special Embankment (non-plastic) Water Absportion = 0.2% Asphaltic Concrete	Sand	Asphaltic Surface Treatment
Updated = 2/24/2025 Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) APS00016210 Ivey Dirt & Aggregates - Greenwell Springs Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.65 Special Embankment (non-plastic) Water Absportion = 0.2% Asphaltic Concrete	Spec. Gravity-SSD = 2.65	Asphaltic Concrete
(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) APS00016210 Ivey Dirt & Aggregates - Greenwell Springs Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.65 Special Embankment (non-plastic) Water Absportion = 0.2% Asphaltic Concrete	Water Absportion = 0.1%	(Friction Rating = III - Coarse Agg. Only)
mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) APS00016210 Ivey Dirt & Aggregates - Greenwell Springs Material Approved Uses Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.65 Special Embankment (non-plastic) Water Absportion = 0.2% Asphaltic Concrete	Updated = 2/24/2025	Portland Cement Concrete
MaterialApproved UsesSand OnlyGranular Material for SubbaseSpec. Gravity-SSD = 2.65Special Embankment (non-plastic)Water Absportion = 0.2%Asphaltic Concrete		mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of
Sand Only Granular Material for Subbase Spec. Gravity-SSD = 2.65 Special Embankment (non-plastic) Water Absportion = 0.2% Asphaltic Concrete	APS00016210	Ivey Dirt & Aggregates - Greenwell Springs
Spec. Gravity-SSD = 2.65 Special Embankment (non-plastic) Water Absportion = 0.2% Asphaltic Concrete	<u>Material</u>	Approved Uses
Water Absportion = 0.2% Asphaltic Concrete	Sand Only	Granular Material for Subbase
· · · · · · · · · · · · · · · · · · ·	Spec. Gravity-SSD = 2.65	Special Embankment (non-plastic)
Updated = 12/4/2024	Water Absportion = 0.2%	Asphaltic Concrete
	Updated = 12/4/2024	

District 62

APSO	0005700	(AX04)	Accardo Materials, Inc-Franklinton,LA
Materia	<u>I</u>		Approved Uses
Gravel			Base & Surface Course
	Isabel		Granular Material for Subbase
	Spec. Gravity-S	SSD = 2.57	Special Embankment (non-plastic)
	Water Absporti	on = 1.0%	Asphaltic Surface Treatment
Sand			Asphaltic Concrete
	Isabel		(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-S	SSD = 2.62	Portland Cement Concrete
	Water Absporti	on = 0.5%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)

Updated = 8/22/2017

APS00005870 (AY06) Lakeview Sand & Gravel - Bogalusa, LA

<u>Materia</u>	<u>ll</u>	Approved Uses		
Gravel		Base & Surface Course		
	Bogalusa	Granular Material for Subbase		
	Spec. Gravity-SSD = 2.47	Special Embankment (non-plastic)		
	Water Absportion = 3.5%	Asphaltic Surface Treatment		
Sand		Asphaltic Concrete		
	Bogalusa	(Friction Rating = III - Coarse Agg. Only)		
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete		
	Water Absportion = 0.5%			

District 62

APSC	10005990	(AY10)	Cash Sand & Gravel, IncDenham Springs, LA	
<u>Materia</u>	<u>I</u>		Approved Uses	
Gravel			Base & Surface Course	
	Easterly Plant		Granular Material for Subbase	
	Spec. Gravity-S	SSD = 2.54	Special Embankment (non-plastic)	
	Water Absportion	on = 1.5%	Asphaltic Surface Treatment	
Sand			Asphaltic Concrete	
	Easterly Plant		(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-S	SSD = 2.62	Portland Cement Concrete	
	Water Absportion	on = 0.5%		

Updated = 7/26/2018

APS00006060	Crawford Aggregate	Industr-Pine Grove,LA - Jenkins
-------------	--------------------	---------------------------------

<u>Material</u>	Approved Uses		
Gravel	Base & Surface Course		
Jenkins Lane	Granular Material for Subbase		
Spec. Gravity-SSD = 2.54	Special Embankment (non-plastic)		
Water Absportion = 1.7%	Asphaltic Surface Treatment		
Sand	Asphaltic Concrete		
Jenkins Lane	(Friction Rating = III - Coarse Agg. Only)		
Spec. Gravity-SSD = 2.62	Portland Cement Concrete		
Water Absportion = 0.5%	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)		
Updated = 6/3/2020			

APS00006100 (AX71) Daley Sand & Gravel, Inc.-Roseland, LA

<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Roseland	Granular Material for Subbase
Spec. Gravity-SSD = 2.50	Special Embankment (non-plastic)
Water Absportion = 2.5%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Roseland	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend o Class F fly ash and GGBFS with a minimum of 50% replacement)
Docaland	

Roseland

Updated = 3/12/2025

APS00006170 (AY17) Brownstone Sand & Gravel - Franklinton, LA

<u>Materia</u>	<u>ll</u>	Approved Uses		
Gravel		Base & Surface Course		
	Enon Plant - Franklinton	Granular Material for Subbase		
	Spec. Gravity-SSD = 2.54	Special Embankment (non-plastic)		
	Water Absportion = 1.7%	Asphaltic Surface Treatment		
Sand		Asphaltic Concrete		
	Enon Plant - Franklinton	(Friction Rating = III - Coarse Agg. Only)		
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete - Gravel Only		
	Water Absportion = 0.5%			

Updated = 10/26/2021

District 62

APSC	00006190	(AY24)	Florida Parishes Aggregate-Fluker, LA	
<u>Materia</u>	<u>ıl</u>		Approved Uses	
Gravel			Base & Surface Course	
	Kent Pit - Fluke	er	Granular Material for Subbase	
	Spec. Gravity-	SSD = 2.56	Special Embankment (non-plastic)	
	Water Absporti	ion = 1.2%	Asphaltic Surface Treatment	
Sand			Asphaltic Concrete	
	Kent Pit - Fluke	er	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-	SSD = 2.62	Portland Cement Concrete	
	Water Absporti	ion = 0.5%		

Updated = 8/24/2017

APS00006240 (AX91) Gillman Enterprises, LLC-Independence, LA

<u>Mater</u>	<u>ial</u>	Approved Uses		
Grave	l	Base & Surface Course		
	Independence	Granular Material for Subbase		
	Spec. Gravity-SSD = 2.52	Special Embankment (non-plastic)		
	Water Absportion = 2.5%	Asphaltic Surface Treatment		
Sand		Asphaltic Concrete		
	Independence	(Friction Rating = III - Coarse Agg. Only)		
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete		
	Water Absportion = 0.5%			

Updated = 8/24/2017

APS00006350 (AY14) Hard Rock Sand & Gravel LLC - Franklinton, LA - #2

<u>Material</u>		Approved Uses		
Gravel		Base & Surface Course		
#2 - Fra	nklinton	Granular Material for Subbase		
Spec. G	ravity-SSD = 2.54	Special Embankment (non-plastic)		
Water A	bsportion = 1.7%	Asphaltic Surface Treatment		
Sand		Asphaltic Concrete		
#2 - Fra	nklinton	(Friction Rating = III - Coarse Agg. Only)		
Spec. G	ravity-SSD = 2.62	Portland Cement Concrete		
Water A	bsportion = 0.5%			

Updated = 8/24/2017

APS00006360 (AX89) Hard Rock Sand & Gravel, LLC-Mt. Hermon, LA

<u>Materia</u>	<u>l</u>	Approved Uses
Gravel		Base & Surface Course
	Mt. Hermon	Granular Material for Subbase
	Spec. Gravity-SSD = 2.55	Special Embankment (non-plastic)
	Water Absportion = 1.5%	Asphaltic Surface Treatment
Sand		Asphaltic Concrete
	Mt. Hermon	(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete
	Water Absportion = 0.5%	

District 62

APS00006450	(AX/2)	industrial Aggregates, LLC-Franklinton, LA-Pine Cl	
<u>Material</u>		Approved Uses	
Gravel		Base & Surface Course	
Spec. Gravity-S	SSD = 2.53	Granular Material for Subbase	
Water Absporti	ion = 2.2%	Special Embankment (non-plastic)	
Sand		Asphaltic Surface Treatment	
Spec. Gravity-	SSD = 2.62	Asphaltic Concrete	
Water Absporti	ion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
Updated = 8/24/2017		Portland Cement Concrete	

APS00006510 (AX68) K & C Gravel-Independence,LA

<u>Material</u>	Approved Uses	
Sand Only	Granular Material for Subbase	
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)	
Water Absportion = 0.5%	Asphaltic Concrete	
Updated = 8/24/2017	Portland Cement Concrete	

APS00006590 (AY03) Amrize Aggregates -Honey Island

<u>Materia</u>	<u>ll</u>	Approved Uses		
Gravel		Base & Surface Course		
	Honey Island	Special Embankment (non-plastic)		
	Spec. Gravity-SSD = 2.51	Asphaltic Surface Treatment		
	Water Absportion = 2.5%	Asphaltic Concrete		
Sand		(Friction Rating = III - Coarse Agg. Only)		
	Honey Island	Portland Cement Concrete		
	Spec. Gravity-SSD = 2.62			
	Water Absportion = 0.5%			
	Honey Island			

Updated = 3/12/2025

APS00006600 (AY01) Amrize Aggregates - Bogalusa, LA

<u>Materia</u>	<u>l</u>	Approved Uses		
Gravel		Base & Surface Course		
	Isabel	Granular Material for Subbase		
	Spec. Gravity-SSD = 2.52	Special Embankment (non-plastic)		
	Water Absportion = 2.5%	Asphaltic Surface Treatment		
Sand		Asphaltic Concrete		
	Isabel	(Friction Rating = III - Coarse Agg. Only)		
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete		
	Water Absportion = 0.5%			

District 62

APS000	006670	(AX43)	Lon Land Gravel CoMt Hermon, LA
<u>Material</u>			Approved Uses
Gravel			Base & Surface Course
Fra	anklinton		Granular Material for Subbase
Sp	ec. Gravity-S	SD = 2.53	Special Embankment (non-plastic)
Wa	ater Absportic	on = 2.2%	Asphaltic Surface Treatment
Sand			Asphaltic Concrete
Fra	anklinton		(Friction Rating = III - Coarse Agg. Only)
Sp	ec. Gravity-S	SD = 2.62	Portland Cement Concrete
Wa	ater Absportic	on = 0.5%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
Updated =	8/24/2017		
_			

APS00006770 (A135) Mears Sand & Gravel-Denham Springs, LA

<u>Materia</u>	<u>al</u>	Approved Uses		
Gravel		Granular Material for Subbase		
	Dennis Mills	Special Embankment (non-plastic)		
	Spec. Gravity-SSD = 2.53	Asphaltic Surface Treatment		
	Water Absportion = 2.0%	Asphaltic Concrete		
Sand		(Friction Rating = III - Coarse Agg. Only)		
	Dennis Mills	Portland Cement Concrete		
	Spec. Gravity-SSD = 2.62	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)		
	Water Absportion = 0.5%			
Update	d = 6/3/2020			

APS00006850 (AY12) P & J Sand & Gravel, LLC-Independence, LA

<u>Materia</u>	<u>l</u>	Approved Uses		
Gravel		Base & Surface Course		
	Independence	Granular Material for Subbase		
	Spec. Gravity-SSD = 2.48	Special Embankment (non-plastic)		
	Water Absportion = 3.5%	Asphaltic Surface Treatment		
Sand		Asphaltic Concrete		
	Independence	(Friction Rating = III - Coarse Agg. Only)		
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete		
	Water Absportion = 0.5%			

Updated = 8/24/2017

APS00006920 (AX29) Ram Industries-Mt. Hermon, LA

<u>Mater</u>	<u>ial</u>	Approved Uses	
Grave	l	Base & Surface Course	
	Franklinton	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.55	Special Embankment (non-plastic)	
	Water Absportion = 1.5%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
	Franklinton	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
	Water Absportion = 0.5%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	
Updated = 8/24/2017		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	

District 62

APS00	0006990	(AX69)	Smith Sand & Gravel-Franklinton,LA	
<u>Material</u>			Approved Uses	
Gravel			Base & Surface Course	
ı	Franklinton		Granular Material for Subbase	
(Spec. Gravity-S	SSD = 2.52	Special Embankment (non-plastic)	
1	Water Absporti	on = 2.5%	Asphaltic Surface Treatment	
Sand			Asphaltic Concrete	
ſ	Franklinton		(Friction Rating = III - Coarse Agg. Only)	
(Spec. Gravity-S	SSD = 2.62	Portland Cement Concrete	
1	Water Absporti	on = 0.5%		
11	0/04/0047			

Updated = 8/24/2017

APS00007030 (AY26) Southern Aggregates, LLC-DenhamSprings, LA-Plant7

<u>Materia</u>	<u>ll</u>	Approved Uses		
Gravel		Base & Surface Course		
	Plant #7	Special Embankment (non-plastic)		
	Spec. Gravity-SSD = 2.52	Asphaltic Surface Treatment		
	Water Absportion = 1.8%	Asphaltic Concrete		
Sand		(Friction Rating = III - Coarse Agg. Only)		
	Plant #7	Portland Cement Concrete		
	Spec. Gravity-SSD = 2.62			
	Water Absportion = 0.5%			

Updated = 7/26/2018

APS00007140 (AX96) T & D Sand & Gravel, LLC-Independence, LA

<u>Materia</u>	<u>[</u>	Approved Uses		
Gravel		Base & Surface Course		
	Amite	Granular Material for Subbase		
	Spec. Gravity-SSD = 2.53	Special Embankment (non-plastic)		
	Water Absportion = 2.2%	Asphaltic Surface Treatment		
Sand		Asphaltic Concrete		
	Amite	(Friction Rating = III - Coarse Agg. Only)		
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete		
	Water Absportion = 0.5%			

Updated = 8/24/2017

APS00007490 (AB98) Willis Sand & Gravel-Bogalusa, LA

<u>Materia</u>	<u>l</u>	Approved Uses		
Gravel		Granular Material for Subbase		
	Sun	Special Embankment (non-plastic)		
	Spec. Gravity-SSD = 2.52	Asphaltic Surface Treatment		
	Water Absportion = 2.5%	Asphaltic Concrete		
Sand		(Friction Rating = III - Coarse Agg. Only)		
	Sun	Portland Cement Concrete		
	Spec. Gravity-SSD = 2.62			
	Water Absportion = 0.5%			

District 62

	APS00011340 (AY29	BMS, LLC - Amite, LA
	<u>Material</u>	Approved Uses
	Gravel	Base & Surface Course
	Amite Pit	Granular Material for Subbase
	Spec. Gravity-SSD = 2.5	Special Embankment (non-plastic)
	Water Absportion = 2.5%	Asphaltic Surface Treatment
Sand		Asphaltic Concrete
	Amite Pit	(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-SSD = 2.6	Portland Cement Concrete
	Water Absportion = 0.5%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
	Updated = 8/22/2017	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
	APS00011410 (AX75	Hard Rock Sand & Gravel LLC - Franklinton, LA - #1

<u>Material</u>		Approved Uses
	Gravel	Base & Surface Course
	#1 Franklinton	Granular Material for Subbase
	Spec. Gravity-SSD = 2.51	Special Embankment (non-plastic)
	Water Absportion = 2.5%	Asphaltic Surface Treatment
	Sand	Asphaltic Concrete
	#1 Franklinton	(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete
	Water Absportion = 0.5%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
	Updated = 8/24/2017	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)

APS00011460 (AY30) Hunt Gravel - Franklinton, LA

<u>Materia</u>	<u>ll</u>	Approved Uses
Gravel		Base & Surface Course
	Franklinton	Granular Material for Subbase
	Spec. Gravity-SSD = 2.51	Special Embankment (non-plastic)
	Water Absportion = 2.5%	Asphaltic Surface Treatment
Sand		Asphaltic Concrete
	Franklinton	(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete
	Water Absportion = 0.5%	

Updated = 8/24/2017

APS00011520 (AY31) Industrial Mining Plant 5 - Tickfaw, LA

<u>Material</u>		Approved Uses	
Gravel		Base & Surface Course	
	Black Cat Pit	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.50	Special Embankment (non-plastic)	
	Water Absportion = 3.0%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
	Black Cat Pit	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
	Water Absportion = 0.5%		
I la data a	1 0/05/0047		

District 62

	APS00011700 (A	Y34)	Madden Roseland, LA Gravel Pit - Roseland, LA	
	<u>Material</u>		Approved Uses	
	Gravel		Base & Surface Course	
	Formerly Diamond	В	Granular Material for Subbase	
	Spec. Gravity-SSD	= 2.52	Special Embankment (non-plastic)	
	Water Absportion =	2.1%	Asphaltic Surface Treatment	
Sand			Asphaltic Concrete	
	Formerly Diamond I	В	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD	= 2.62	Portland Cement Concrete	
	Water Absportion =	0.5%	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)	
	Formerly Diamond I	В		
	Updated = 1/26/2023			
	APS00011790 (A	Y32)	Southern Aggregates - Amite, LA - #9	
	84 - 4 1		Annual III and	

<u>Material</u>		Approved Uses	
Gravel		Granular Material for Subbase	
	Plant #9	Special Embankment (non-plastic)	
	Spec. Gravity-SSD = 2.52	Asphaltic Surface Treatment	
	Water Absportion = 2.3%	Asphaltic Concrete	
Sand		(Friction Rating = III - Coarse Agg. Only)	
	Plant #9	Portland Cement Concrete	
	Spec. Gravity-SSD = 2.62		
	Water Absportion = 0.5%		

Updated = 8/6/2018

APS00011800 (AY33) Bunch's Sand and Gravel #2 - Greensburg, LA

<u>Materia</u>	<u>l</u>	Approved Uses
Gravel		Granular Material for Subbase
	Pit #2	Special Embankment (non-plastic)
	Spec. Gravity-SSD = 2.53	Asphaltic Surface Treatment
	Water Absportion = 1.8%	Asphaltic Concrete
Sand		(Friction Rating = III - Coarse Agg. Only)
	Pit #2	Portland Cement Concrete
	Spec. Gravity-SSD = 2.62	
	Water Absportion = 0.5%	

Updated = 7/26/2018

APS00011940 Baldwin Redi-Mix Co. Inc.-Greensburg,H&LIsland Pit

<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.53	Granular Material for Subbase
Water Absportion = 1.8%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 7/26/2018	Portland Cement Concrete

			\sim
11	istr	ICT.	K')
	ווכו	11 71	\mathbf{U}

District 62	
APS00012340	River Road Rock - Franklinton, LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Mt. Hermon Pit	Granular Material for Subbase
Spec. Gravity-SSD = 2.53	Special Embankment (non-plastic)
Water Absportion = 2.2%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Mt. Hermon Pit	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
Updated = 8/24/2017	
APS00012420	Tate Construction, LLC - Franklinton, LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Tate Pit	Granular Material for Subbase
Spec. Gravity-SSD = 2.52	Special Embankment (non-plastic)
Water Absportion = 2.5%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Tate Pit	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	
Updated = 8/24/2017	
APS00012510	Industrial Aggregates, LLC - Covington, LA - #2
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Enon Plant #2	Granular Material for Subbase
Spec. Gravity-SSD = 2.55	Special Embankment (non-plastic)
Water Absportion = 1.5%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Enon Plant #2	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
Updated = 8/24/2017	
APS00012620	Industrial Aggregates - Franklinton, LA
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course

<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Pine Cliff Pit	Granular Material for Subbase
Spec. Gravity-SSD = 2.50	Special Embankment (non-plastic)
Water Absportion = 2.5%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Pine Cliff Pit	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	
Updated = 8/24/2017	

			\sim
11	istr	ı∩t	につ
-	เอน	ıcı	UZ

DISTRICT 62	
APS00013080	Northern Sand & Gravel, L.L.C Independence
Material	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.50	Granular Material for Subbase
Water Absportion = 2.4%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 4/29/2020	Portland Cement Concrete
APS00013250	R & S Dozer Service, LLC - Franklinton
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.53	Granular Material for Subbase
Water Absportion = 1.7%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 10/22/2021	Portland Cement Concrete - Gravel Only
APS00013390	L & C Gravel, LLC - Plant #6 - Fluker
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.53	Granular Material for Subbase
Water Absportion = 1.9%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 9/12/2019	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
APS00014300	Southern Aggregates, LLC Plant 31 - Franklinton
<u>Material</u>	Approved Uses
Gravel	Granular Material for Subbase
Spec. Gravity-SSD = 2.55	Special Embankment (non-plastic)
Water Absportion = 1.5%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Spec. Gravity-SSD = 2.62	(Friction Rating = III - Coarse Agg. Only)
Water Absportion = 0.5%	Portland Cement Concrete
Updated = 7/16/2020	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)

			\sim
1)	istr	ICT.	h''
$\boldsymbol{\mathcal{L}}$	ப்பட	ILJ.	UZ

Distri	ct 62	
APS	00014350	Barriere Construction Co., LLC - Independence, LA
<u>Materia</u>	<u>al</u>	Approved Uses
Gravel		Base & Surface Course
	Spec. Gravity-SSD = 2.52	Granular Material for Subbase
	Water Absportion = 2.5%	Special Embankment (non-plastic)
Sand		Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Update	d = 7/15/2020	Portland Cement Concrete
		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
APS	00014410	Arcosa Aggregates - Pearl River Plant 1725
<u>Materia</u>	<u>al</u>	Approved Uses
Gravel		Base & Surface Course
	Spec. Gravity-SSD = 2.48	Granular Material for Subbase
	Water Absportion = 3.3%	Special Embankment (non-plastic)
Sand		Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 8/3/2022		Portland Cement Concrete
APS00014780		Cash Sand & Gravel, Inc Kemp Plant -D.S., LA
		, , , , , , , , , , , , , , , , , , , ,
Materia	<u>al</u>	Approved Uses
<u>Materia</u> Gravel		·
	Spec. Gravity-SSD = 2.52	Approved Uses Base & Surface Course Granular Material for Subbase
Gravel		Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic)
	Spec. Gravity-SSD = 2.52 Water Absportion = 2.1%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment
Gravel	Spec. Gravity-SSD = 2.52 Water Absportion = 2.1% Spec. Gravity-SSD = 2.62	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete
Gravel	Spec. Gravity-SSD = 2.52 Water Absportion = 2.1% Spec. Gravity-SSD = 2.62 Water Absportion = 0.5%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)
Gravel	Spec. Gravity-SSD = 2.52 Water Absportion = 2.1% Spec. Gravity-SSD = 2.62	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete
Gravel	Spec. Gravity-SSD = 2.52 Water Absportion = 2.1% Spec. Gravity-SSD = 2.62 Water Absportion = 0.5%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)
Gravel Sand Update	Spec. Gravity-SSD = 2.52 Water Absportion = 2.1% Spec. Gravity-SSD = 2.62 Water Absportion = 0.5%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of
Gravel Sand Update	Spec. Gravity-SSD = 2.52 Water Absportion = 2.1% Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% d = 10/5/2021	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) Barriere Construction Co. LLC - Miley Pit Approved Uses
Sand Update	Spec. Gravity-SSD = 2.52 Water Absportion = 2.1% Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% d = 10/5/2021	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) Barriere Construction Co. LLC - Miley Pit Approved Uses Base & Surface Course
Sand Update APSO Materia	Spec. Gravity-SSD = 2.52 Water Absportion = 2.1% Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% d = 10/5/2021 00014990 al Spec. Gravity-SSD = 2.51	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) Barriere Construction Co. LLC - Miley Pit Approved Uses Base & Surface Course Granular Material for Subbase
Sand Update APSO Materia Gravel	Spec. Gravity-SSD = 2.52 Water Absportion = 2.1% Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% d = 10/5/2021	Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) Barriere Construction Co. LLC - Miley Pit Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic)
Sand Update APSO Materia	Spec. Gravity-SSD = 2.52 Water Absportion = 2.1% Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% d = 10/5/2021 O0014990 al Spec. Gravity-SSD = 2.51 Water Absportion = 2.2%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) Barriere Construction Co. LLC - Miley Pit Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment
Sand Update APSO Materia Gravel	Spec. Gravity-SSD = 2.52 Water Absportion = 2.1% Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% d = 10/5/2021 O0014990 al Spec. Gravity-SSD = 2.51 Water Absportion = 2.2% Spec. Gravity-SSD = 2.62	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) Barriere Construction Co. LLC - Miley Pit Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete
Sand Update APSO Materia Gravel Sand	Spec. Gravity-SSD = 2.52 Water Absportion = 2.1% Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% d = 10/5/2021 O0014990 al Spec. Gravity-SSD = 2.51 Water Absportion = 2.2% Spec. Gravity-SSD = 2.62 Water Absportion = 0.5%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) Barriere Construction Co. LLC - Miley Pit Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)
Sand Update APSO Materia Gravel Sand	Spec. Gravity-SSD = 2.52 Water Absportion = 2.1% Spec. Gravity-SSD = 2.62 Water Absportion = 0.5% d = 10/5/2021 O0014990 al Spec. Gravity-SSD = 2.51 Water Absportion = 2.2% Spec. Gravity-SSD = 2.62	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) Barriere Construction Co. LLC - Miley Pit Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete

Distr	ict 62	
APS	00015160	Arcosa Aggregates - Plant LA 1349 - Pearl River
<u>Materi</u>	<u>al</u>	Approved Uses
Gravel		Base & Surface Course
	Spec. Gravity-SSD = 2.49	Granular Material for Subbase
	Water Absportion = 3.5%	Special Embankment (non-plastic)
Sand		Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Update	ed = 5/4/2022	Portland Cement Concrete
APS	00015170	Arcosa Aggregates - Plant LA 1341 - Independence
<u>Materi</u>		Approved Uses
Gravel		Base & Surface Course
	Spec. Gravity-SSD = 2.50	Granular Material for Subbase
	Water Absportion = 2.5%	Special Embankment (non-plastic)
Sand		Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Update	ed = 5/4/2022	Portland Cement Concrete
APS	00015200	Arcosa Aggregates - Plant LA 1345 - Franklinton
<u>Materi</u>	<u>al</u>	Approved Uses
Gravel		Base & Surface Course
	Spec. Gravity-SSD = 2.49	Granular Material for Subbase
	Water Absportion = 2.5%	Special Embankment (non-plastic)
Sand		Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Update	ed = 5/4/2022	Portland Cement Concrete
APS	00015210	Arcosa Aggregates - Plant LA 1340 - Denham Springs
<u>Materi</u>	<u>al</u>	Approved Uses
Gravel		Base & Surface Course
	Spec. Gravity-SSD = 2.52	Granular Material for Subbase
	Water Absportion = 2.1%	Special Embankment (non-plastic)
Sand		Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Update	ed = 5/4/2022	Portland Cement Concrete
APS	00015410	Crawford Aggregate Industries - Cross Pit
<u>Materi</u>	<u>al</u>	Approved Uses
Gravel		Base & Surface Course
	Spec. Gravity-SSD = 2.52	Granular Material for Subbase
	Water Absportion = 2.2%	Special Embankment (non-plastic)
Sand		Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Update	ed = 3/12/2025	Portland Cement Concrete
		(Sand from this source is potentially deleterious in Portland Cement Con mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary by Class F fly ash and GGBFS with a minimum of 50% replacement)

Page 25 of 61 - 10/29/2025 2:05:10 PM

			~~
1)	IC TI	こつせ	62
	ווכו	11 71	\mathbf{U}

DISTRICT 62		
APS00015460	Louisiana Aggregate Materials, LLC-DenhamSprings	
<u>Material</u>	Approved Uses	
Gravel	Base & Surface Course	
Spec. Gravity-SSD = 2.51	Granular Material for Subbase	
Water Absportion = 2.5%	Special Embankment (non-plastic)	
Sand	Asphaltic Surface Treatment	
Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
Updated = 2/18/2025	Portland Cement Concrete	
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)	
APS00015650	Accardo Mining, LLC Bogalusa	
<u>Material</u>	Approved Uses	
Gravel	Base & Surface Course	
Spec. Gravity-SSD = 2.19	Granular Material for Subbase	
Water Absportion = 2.3%	Special Embankment (non-plastic)	
Sand	Asphaltic Surface Treatment	
Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
Updated = 3/12/2025	Portland Cement Concrete - Gravel Only	
APS00015670	Candies Excavation, Inc Folsom	
<u>Material</u>	Approved Uses	
Sand Only	Granular Material for Subbase	
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)	
Water Absportion = 0.5%	Asphaltic Concrete	
Updated = 1/12/2024		
APS00015680	A-1 Aggregates - KSB Holdings, LLC - Mt. Hermon	
<u>Material</u>	Approved Uses	
Gravel	Base & Surface Course	
Spec. Gravity-SSD = 2.50	Granular Material for Subbase	
Water Absportion = 2.6%	Special Embankment (non-plastic)	
Sand	Asphaltic Surface Treatment	
Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
Updated = 3/12/2025	Portland Cement Concrete - Gravel Only	
APS00015890	M & M Gravel - Franklinton	
<u>Material</u>	Approved Uses	
Gravel	Base & Surface Course	
Spec. Gravity-SSD = 2.53	Granular Material for Subbase	
Water Absportion = 2.2%	Special Embankment (non-plastic)	
Sand	Asphaltic Surface Treatment	
Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
Updated = 3/12/2025	Portland Cement Concrete - Gravel Only	

District 62

APS00015980	River Road Materials, LLC Franklinton
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.51	Granular Material for Subbase
Water Absportion = 2.2%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = $3/12/2025$	Portland Cement Concrete - Gravel Only
APS00016070	BearCo Construction, LLC Franklinton
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.53	Granular Material for Subbase
Water Absportion = 1.8%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.63	Asphaltic Concrete
Water Absportion = 4.2%	(Friction Rating = III - Coarse Agg. Only)
Updated = 3/12/2025	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
APS00016300	Crawford Aggregate Industries - Lee Brown Pit

<u>Material</u>	Approved Uses		
Gravel	Base & Surface Course		
Spec. Gravity-SSD = 2.52	Granular Material for Subbase		
Water Absportion = 1.8%	Special Embankment (non-plastic)		
Sand	Asphaltic Surface Treatment		
Spec. Gravity-SSD = 2.60	Asphaltic Concrete		
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)		
Updated = 9/23/2025	Portland Cement Concrete - Gravel Only		

A-2. OUT-OF-STATE PRODUCERS/SUPPLIERS

Out of State

APSC	00005730	(ASAN)	Ala	bama Sand and Gravel-Prattville, AL	
<u>Materia</u>	<u>l</u>			Approved Uses	
Gravel				Base & Surface Course	
	Billingsley Pit			Granular Material for Subbase	
	Spec. Gravity-S	SD = 2.63		Special Embankment (non-plastic)	
	Water Absportion	on = 0.8%		Asphaltic Surface Treatment	
Sand				Asphaltic Concrete	
	Billingsley Pit			(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-S	SD = 2.62		Portland Cement Concrete	
	Water Absportion	on = 0.5%			
The date	1 0/04/0047				

Out of State

711 0000007 TO (710717) 7111ation Datin and Diavol, LLO I fill Datingboli, 71	APS00005740	(ASAV)	 Alliance Sand and Gravel, LLC-Phil Campbell, Al
---	-------------	--------	---

<u>Material</u>	Approved Uses
Sand Only	Special Embankment (non-plastic)
Phil Campbell Pit	Asphaltic Concrete
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	

Updated = 8/24/2017

APS00005750 (ASAK) Allstate Deatsville, LLC-Deatsville, AL

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Deatsville Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete

Updated = 8/24/2017

APS00005780 (ABAO) Arkansas Gravel Company, Inc.-Hampton, AR

<u>Material</u>	Approved Uses		
Gravel	Base & Surface Course		
Bradshaw Mine	Granular Material for Subbase		
Spec. Gravity-SSD = 2.56	Special Embankment (non-plastic)		
Water Absportion = 1.2%	Asphaltic Surface Treatment		
Sand	Asphaltic Concrete		
Bradshaw Mine	(Friction Rating = III - Coarse Agg. Only)		
Spec. Gravity-SSD = 2.62	Portland Cement Concrete		
Water Absportion = 0.5%			

Updated = 8/24/2017

APS00005790 (AB76) B & B Gravel & Trucking Co.-Bearden, AR

<u>Material</u>		Approved Uses		
Grav	el	Base & Surface Course		
	Spec. Gravity-SSD = 2.55	Granular Material for Subbase		
	Water Absportion = 1.5%	Special Embankment (non-plastic)		
Sand	1	Asphaltic Surface Treatment		
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete		
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)		
Upda	ated = 8/24/2017	Portland Cement Concrete		

APS00005830 (ASAR) Baldwin Sand & Gravel-Crystal Springs, MS

<u>Material</u>	Approved Uses	
Gravel	Base & Surface Course	
Crystal Springs Pit	Granular Material for Subbase	
Spec. Gravity-SSD	2.57 Special Embankment (non-plastic)	
Water Absportion =	0% Asphaltic Surface Treatment	
Sand	Asphaltic Concrete	
Crystal Springs Pit	(Friction Rating = III - Coarse Agg. Only)	
Spec. Gravity-SSD	2.62 Portland Cement Concrete	
Water Absportion =	(Gravel from this source is potentially deleterious in Portl mixes, requires 30% Class F fly ash or 50% slag to mitigate	
Updated = 8/24/2017	(Sand from this source is potentially deleterious in Portlan mixes, requires 30% Class F fly ash or 50% slag to mitigate	

Out of State

APS00005920 (A	ASAM) Bla	ackwell Aggregates, IncNicholson, MS
<u>Material</u>		Approved Uses
Gravel		Base & Surface Course
Jackson Landing F	Pit	Granular Material for Subbase
Spec. Gravity-SSI	D = 2.48	Special Embankment (non-plastic)
Water Absportion	= 3.5%	Asphaltic Surface Treatment
Sand		Asphaltic Concrete
Jackson Landing F	Pit	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSI	D = 2.62	Portland Cement Concrete
Water Absportion	= 0.5%	
Updated = 8/24/2017		
APS00005930 (A	AB31) Bla	ain Sand & Gravel, IncNatchez, MS
<u>Material</u>		Approved Uses

<u>Materiai</u>		Approved Uses	
Gravel		Granular Material for Subbase	
	Coverhill Pit	Special Embankment (non-plastic)	
	Spec. Gravity-SSD = 2.57	Asphaltic Surface Treatment	
	Water Absportion = 1.0%	Asphaltic Concrete	
Sand		(Friction Rating = III - Coarse Agg. Only)	

Coverhill Pit Portland Cement Concrete

Spec. Gravity-SSD = 2.62 (Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)

Water Absportion = 0.5%

Updated = 8/24/2017

APS00005940 (AA57) Blain Sand & Gravel, Inc.-Crystal Springs, MS

	<u>Material</u>		Approved Uses		
Gravel			Base & Surface Course		
	Spec. Gravity	y-SSD = 2.54	Granular Material for Subbase		
	Water Abspo	ortion = 1.7%	Special Embankment (non-plastic)		
	Sand		Asphaltic Surface Treatment		
	Spec. Gravity	y-SSD = 2.62	Asphaltic Concrete		
	Water Abspo	ortion = 0.5%	(Friction Rating = III - Coarse Agg. Only)		
	Updated = 8/24/2017		Portland Cement Concrete		

APS00006030 Cossatot Rock, LLC-Lockesburg, AR

	<u>Material</u>		Approved Uses		
	Gravel		Base & Surface Course		
	Old Deirks	Hwy Pit	Granular Material for Subbase		
	Spec. Grav	vity-SSD = 2.54	Special Embankment (non-plastic)		
	Water Abs	portion = 1.7%	Asphaltic Surface Treatment		
	Sand		Asphaltic Concrete		
	Old Deirks	Hwy Pit	(Friction Rating = III - Coarse Agg. Only)		
	Spec. Grav	vity-SSD = 2.59	Portland Cement Concrete		
	Water Abs _l	portion = 1.0%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)		
	Updated = 8/24/201	7	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)		

\bigcirc	ıŧ	Ωf	Sta	ıtα
\mathbf{v}	ıι	UI.	Olc	แธ

Updated = 8/24/2017

Out of State			
APS00006110	(AA80)	Dickerson & Bowen Riverside Gravel-Tylertown, MS	
<u>Material</u>		Approved Uses	
Gravel		Base & Surface Course	
McComb		Granular Material for Subbase	
Spec. Gravity-	SSD = 2.46	Special Embankment (non-plastic)	
Water Absport	ion = 4.0%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
McComb		(Friction Rating = III - Coarse Agg. Only)	
Spec. Gravity-	SSD = 2.62	Portland Cement Concrete	
Water Absport	ion = 0.5%		
Updated = 8/24/2017			
APS00006200	(ASAT)	Foley Materials CoPhenix City, AL- Plant 501	
<u>Material</u>		Approved Uses	
Sand Only		Granular Material for Subbase	
Plant 501		Special Embankment (non-plastic)	
Spec. Gravity-		Asphaltic Concrete	
Water Absport	ion = 0.5%	Portland Cement Concrete	
Updated = 8/24/2017			
APS00006210	(ASAJ)	Foley Materials CoPhenix City, AL- Plant 505	
<u>Material</u>		Approved Uses	
Sand Only		Granular Material for Subbase	
Plant 505		Special Embankment (non-plastic)	
Spec. Gravity-		Asphaltic Concrete	
Water Absport	ion = 0.5%	Portland Cement Concrete	
Updated = 8/24/2017			
APS00006230	(ASAI)	Fouke Sand & Gravel, LLC-Fouke, AR	
<u>Material</u>		Approved Uses	
Gravel		Base & Surface Course	
Spec. Gravity-		Granular Material for Subbase	
Water Absport	ion = 0.8%	Special Embankment (non-plastic)	
Sand		Asphaltic Surface Treatment	
Spec. Gravity-		Asphaltic Concrete	
Water Absport	ion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
Updated = 8/24/2017	(15.10)	Portland Cement Concrete	
APS00006260	(ABAK)	Green Brothers Gravel CoHazlehurst, MS	
Material		Approved Uses	
Gravel		Base & Surface Course	
#22	000 050	Granular Material for Subbase	
Spec. Gravity-		Special Embankment (non-plastic)	
Water Absport	1011 = 3.0%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
#22	CCD _ 0.60	(Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete	
Spec. Gravity-		Fortiand Cement Concrete	
Water Absport	1011 = 0.5%		

Page 30 of 61 - 10/29/2025 2:05:10 PM

Spec. Gravity-SSD = 2.62

A-2. OUT-OF-STATE PRODUCERS/SUPPLIERS

Out of State

APS	00006270	(ABAL)	Green Brothers Gravel CoCrystalSprings, MS	
<u>Materia</u>	<u>ıl</u>		Approved Uses	
Gravel			Base & Surface Course	
	#65		Granular Material for Subbase	
	Spec. Gravity-	SSD = 2.50	Special Embankment (non-plastic)	
	Water Absport	ion = 3.0%	Asphaltic Surface Treatment	
Sand			Asphaltic Concrete	
	#65		(Friction Rating = III - Coarse Agg. Only)	

Portland Cement Concrete

Water Absportion = 0.5% Updated = 8/24/2017

APS00006290 (ASAW) Hallet Materials-Porter,TX

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Porter Plant	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.63	Asphaltic Concrete
Updated = 8/24/2017	Portland Cement Concrete

APS00006300 (ASAU) Hammett Gravel Company, Inc.-Bentonia, MS

<u>Material</u>		<u>!</u> !	Approved Uses Base & Surface Course		
	Gravel				
		Yazoo City Operation	Granular Material for Subbase		
		Spec. Gravity-SSD = 2.56	Special Embankment (non-plastic)		
		Water Absportion = 1.2%	Asphaltic Surface Treatment		
	Sand		Asphaltic Concrete		
		Yazoo City Operation	(Friction Rating = III - Coarse Agg. Only)		
		Spec. Gravity-SSD = 2.62	Portland Cement Concrete		
		Water Absportion = 0.5%			

Updated = 8/24/2017

APS00006310 (AA70) Hanson Aggregates-Bearden, AR

<u>Material</u>		<u>ıl</u>	Approved Uses Base & Surface Course	
	Gravel			
		Eagle Mills	Granular Material for Subbase	
		Spec. Gravity-SSD = 2.57	Special Embankment (non-plastic)	
		Water Absportion = 1.0%	Asphaltic Surface Treatment	
	Sand		Asphaltic Concrete	
		Eagle Mills	(Friction Rating = III - Coarse Agg. Only)	
		Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
		Water Absportion = 0.5%		

Out of State

APS00006320 (A092)	Heidelberg Materials - Little River Plant
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Little River F.K.A. Hanson	Granular Material for Subbase
Spec. Gravity-SSD = 2.56	Special Embankment (non-plastic)
Water Absportion = 1.2%	Asphaltic Surface Treatment
Sand	Asphaltic Concrete
Little River F.K.A. Hanson	(Friction Rating = III - Coarse Agg. Only)
Spec. Gravity-SSD = 2.62	Portland Cement Concrete
Water Absportion = 0.5%	
Little River F.K.A. Hanson	
Undated = 3/12/2025	

Updated = 3/12/2025

APS00006420 (AB07) Huey Stockstill, LLC - Picayune, MS - 12 Oaks

Approved Uses Base & Surface Course	
Special Embankment (non-plastic)	
Asphaltic Surface Treatment	
Asphaltic Concrete	
(Friction Rating = III - Coarse Agg. Only)	
Portland Cement Concrete	
(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	

Updated = 8/24/2017

APS00006430 (AB26) Huey P. Stockstill, LLC -Picayune, MS - Pine Grove

	<u>Material</u> Gravel		Approved Uses Base & Surface Course	
		Pine Grove Pit	Granular Material for Subbase	
		Spec. Gravity-SSD = 2.53	Special Embankment (non-plastic)	
		Water Absportion = 2.2%	Asphaltic Surface Treatment	
	Sand		Asphaltic Concrete	
		Pine Grove Pit	(Friction Rating = III - Coarse Agg. Only)	
		Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
		Water Absportion = 0.5%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	
	Updated	d = 8/24/2017	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	

APS00006490 (ABAP) JJ Ferguson Sand & Gravel-Cruger, MS

	<u>Material</u> Gravel		Approved Uses Base & Surface Course	
		Blackhawk Pit	Granular Material for Subbase	
		Spec. Gravity-SSD = 2.54	Special Embankment (non-plastic)	
		Water Absportion = 1.7%	Asphaltic Surface Treatment	
	Sand		Asphaltic Concrete	
		Blackhawk Pit	(Friction Rating = III - Coarse Agg. Only)	
		Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
		Water Absportion = 0.5%	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	

\bigcirc	ıŧ	Ωf	Sta	ıtα
\mathbf{v}	ıι	UI.	Olc	แธ

Out o	f State			
APSO	0006500	(A091)	Johnsville Sand & Gravel-Hermitage, AR	
<u>Materia</u>	<u>l</u>		Approved Uses	
Gravel			Granular Material for Subbase	
	Spec. Gravity-	SSD = 2.55	Special Embankment (non-plastic)	
	Water Absport	ion = 1.5%	Asphaltic Surface Treatment	
Sand			Asphaltic Concrete	
	Spec. Gravity-	SSD = 2.62	(Friction Rating = III - Coarse Agg. Only)	
	Water Absporti	ion = 0.5%	Portland Cement Concrete	
Updated	d = 8/24/2017			
APSC	00006530	(ASAG)	King Sand & Gravel-Kerens, TX	
<u>Materia</u>	<u>I</u>		Approved Uses	
Sand O	nly		Granular Material for Subbase	
	Spec. Gravity-	SSD = 2.62	Special Embankment (non-plastic)	
	Water Absporti	ion = 0.5%	Asphaltic Concrete	
Updated	d = 8/24/2017		Portland Cement Concrete	
APSO	00006540	(AB91)	Krystal Gravel, IncCrystal Springs, MS	
<u>Materia</u>	<u>I</u>		Approved Uses	
Gravel			Base & Surface Course	
	Spec. Gravity-	SSD = 2.53	Granular Material for Subbase	
	Water Absport	ion = 2.2%	Special Embankment (non-plastic)	
Sand			Asphaltic Surface Treatment	
	Spec. Gravity-	SSD = 2.62	Asphaltic Concrete	
			(Edular Dallar III. Orana Ara Orla)	
	Water Absporti	ion = 0.5%	(Friction Rating = III - Coarse Agg. Only)	
Updated	Water Absporti d = 8/24/2017	ion = 0.5%	Portland Cement Concrete	
•		(ASAL)	, , , , , , , , , , , , , , , , , , , ,	
•	d = 8/24/2017 00006680		Portland Cement Concrete	
APSO	d = 8/24/2017 00006680		Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS	
APSC Materia	d = 8/24/2017 00006680	(ASAL)	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase	
APSO Materia Gravel	d = 8/24/2017 00006680 <u>I</u>	(ASAL) SSD = 2.48	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic)	
APSC Materia	d = 8/24/2017 00006680 <u>I</u> Spec. Gravity-3 Water Absport	(ASAL) SSD = 2.48 ion = 3.5%	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment	
APSO Materia Gravel	d = 8/24/2017 00006680 L Spec. Gravity-S Water Absporti	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete	
APSO Materia Gravel	d = 8/24/2017 00006680 L Spec. Gravity-S Water Absporti	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)	
APSO Materia Gravel	d = 8/24/2017 00006680 L Spec. Gravity-S Water Absporti	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete	
APSO Materia Gravel Sand Updated	d = 8/24/2017 00006680 <u>I</u> Spec. Gravity-S Water Absporti Spec. Gravity-S Water Absporti d = 8/24/2017 00006700	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK	
Materia Gravel Sand Updated APSO Materia	d = 8/24/2017 00006680 <u>I</u> Spec. Gravity-S Water Absporti Spec. Gravity-S Water Absporti d = 8/24/2017 00006700	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5%	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses	
APSO Materia Gravel Sand Updated	d = 8/24/2017 00006680 <u>I</u> Spec. Gravity-S Water Absporti Spec. Gravity-S Water Absporti d = 8/24/2017 00006700	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS)	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course	
Materia Gravel Sand Updated APSO Materia	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absportion Spec. Gravity-S Water Absportion d = 8/24/2017 00006700 I Broken Bow Sa	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS) and & Gravel	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course Granular Material for Subbase	
Materia Gravel Sand Updated APSO Materia	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absport Water Absport d = 8/24/2017 00006700 I Broken Bow Sa Spec. Gravity-S	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS) and & Gravel SSD = 2.56	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course Granular Material for Subbase Asphaltic Surface Treatment	
Materia Gravel Sand Updated APSO Materia Gravel	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absportion Spec. Gravity-S Water Absportion d = 8/24/2017 00006700 I Broken Bow Sa	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS) and & Gravel SSD = 2.56	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course Granular Material for Subbase Asphaltic Surface Treatment Asphaltic Concrete	
Materia Gravel Sand Updated APSO Materia	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absporti d = 8/24/2017 00006700 Broken Bow Sa Spec. Gravity-S Water Absporti	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS) and & Gravel SSD = 2.56 ion = 1.2%	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course Granular Material for Subbase Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)	
Materia Gravel Sand Updated APSO Materia Gravel	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absporti d = 8/24/2017 00006700 Broken Bow Sa Spec. Gravity-S Water Absporti	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS) and & Gravel SSD = 2.56 ion = 1.2% and & Gravel	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course Granular Material for Subbase Asphaltic Surface Treatment Asphaltic Concrete	
Materia Gravel Sand Updated APSO Materia Gravel	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absporti d = 8/24/2017 00006700 Broken Bow Sa Spec. Gravity-S Water Absporti d = 8/24/2017 0006700 Broken Bow Sa Spec. Gravity-S Water Absporti	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS) and & Gravel SSD = 2.56 ion = 1.2% and & Gravel SSD = 2.74	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course Granular Material for Subbase Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)	
Materia Gravel Sand Updated APSO Materia Gravel	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absporti d = 8/24/2017 00006700 I Broken Bow Sa Spec. Gravity-S Water Absporti Broken Bow Sa Spec. Gravity-S Water Absporti Broken Bow Sa Spec. Gravity-S Water Absporti	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS) and & Gravel SSD = 2.56 ion = 1.2% and & Gravel SSD = 2.74 ion = 0.4%	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course Granular Material for Subbase Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)	
Materia Gravel Sand Updated APSO Materia Gravel	d = 8/24/2017 00006680 I Spec. Gravity-S Water Absporti d = 8/24/2017 00006700 Broken Bow Sa Spec. Gravity-S Water Absporti d = 8/24/2017 0006700 Broken Bow Sa Spec. Gravity-S Water Absporti	(ASAL) SSD = 2.48 ion = 3.5% SSD = 2.62 ion = 0.5% (ABAS) and & Gravel SSD = 2.56 ion = 1.2% and & Gravel SSD = 2.74 ion = 0.4%	Portland Cement Concrete Marion Clay & Gravel, LLC-Columbia, MS Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete Martin Marietta Aggregates-Eagletown, OK Approved Uses Base & Surface Course Granular Material for Subbase Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)	

Out of State

APS00006720	(ASAX)	Martin Marietta Aggregates-Garwood,TX
<u>Material</u>		Approved Uses
Gravel		Base & Surface Course
Garwood Plant		Granular Material for Subbase
Spec. Gravity-S	SSD = 2.57	Special Embankment (non-plastic)
Water Absporti	on = 1.0%	Asphaltic Surface Treatment
Sand		Asphaltic Concrete
Garwood Plant		(Friction Rating = III - Coarse Agg. Only)
Updated = 8/24/2017		Portland Cement Concrete
APS00006780	(ABAC)	Memphis Stone & Gravel CoNesbit, MS

<u>Material</u>	Approved Uses	
Sand Only	Granular Material for Subbase	
Anderson Plant	Special Embankment (non-plastic)	
Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
Water Absportion = 0.5%	Portland Cement Concrete	
Updated = 8/24/2017		

(ABAD) Memphis Stone & Gravel Co.-Senatobia, MS APS00006790

<u>Material</u>	Approved Uses	
Sand Only	Granular Material for Subbase	
Perry Plant	Special Embankment (non-plastic)	
Spec. Gravity-SSD = 2.62	Asphaltic Concrete	
Water Absportion = 0.5%	Portland Cement Concrete	
11 1 2 1 0/04/004		

Updated = 8/24/2017

(ASAQ) ODDEE Smith Constr.Inc.-Brookhaven, MS APS00006840

<u>Material</u> Gravel		<u> </u>	Approved Uses	
			Base & Surface Course	
		Oddee California Camp Pit	Granular Material for Subbase	
		Spec. Gravity-SSD = 2.56	Special Embankment (non-plastic)	
		Water Absportion = 1.2%	Asphaltic Surface Treatment	
	Sand		Asphaltic Concrete	
		Oddee California Camp Pit	(Friction Rating = III - Coarse Agg. Only)	
	Updated	d = 8/24/2017	Portland Cement Concrete	

APS00006860 (A018) Perkinston Sand & Gravel-Perkinston, MS

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
Water Absportion = 0.5%	Asphaltic Concrete
Updated = 8/24/2017	Portland Cement Concrete

APS00006910 (ASAF) R & R Logging & Gravel-Columbia, MS

<u>Material</u>	Approved Us	Approved Uses	
Gravel	Base & Surfac	e Course	
Spec. Gravity-SSD	= 2.49 Granular Mate	rial for Subbase	
Water Absportion =	= 3.5% Special Emba	nkment (non-plastic)	
Sand	Asphaltic Surf	ace Treatment	
Spec. Gravity-SSD	= 2.62 Asphaltic Con	crete	
Water Absportion =	= 0.5% (Friction Ratin	g = III - Coarse Agg. Only)	
Updated = 8/24/2017	Portland Cem	ent Concrete	

Out of State

APS00006930	(ASAP) Riverside Sand & Gravel-Tylertown, MS
Material	Approved Uses

Sand Only Granular Material for Subbase

NW St. Paul Pit Special Embankment (non-plastic)

Spec. Gravity-SSD = 2.62 Asphaltic Concrete

Water Absportion = 0.5% Portland Cement Concrete

Updated = 8/24/2017

APS00006980 (ASAY) Simpson Materials Co.-Valley Park, MO

<u>Material</u>	Approved Uses	
Gravel	Base & Surface Course	
Ranken Site	Granular Material for Subbase	
Spec. Gravity-SSD = 2.51	Special Embankment (non-plastic)	
Water Absportion = 2.5%	Asphaltic Surface Treatment	
Sand	Asphaltic Concrete	
Ranken Site	(Friction Rating = III - Coarse Agg. Only)	
Updated = 8/28/2017	Portland Cement Concrete	

APS00007160 (AB15) Texas Crushed Stone Co., Inc.-Georgetown, TX

<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Stone	Granular Material for Subbase
(Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.48	Asphaltic Surface Treatment
Water Absportion = 3.6%	Asphaltic Concrete
Updated = 3/12/2025	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(excluding bridge decks)
	Riprap & Stone Revetment

APS00007170 (AB27) The Fordyce Co-Victoria, TX

<u>Material</u>	Approved Uses	
Gravel	Base & Surface Course	
Briggs Plant	Granular Material for Subbase	
Spec. Gravity-SSD = 2.74	Special Embankment (non-plastic)	
Water Absportion = 0.8%	Asphaltic Surface Treatment	
Sand	Asphaltic Concrete	
Briggs Plant	(Friction Rating = III - Coarse Agg. Only)	
Spec. Gravity-SSD = 2.62	Portland Cement Concrete	
Water Absportion = 0.5%	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	

Out of State

APS00007210 (ASAF	l) Triangle A	Aggregates, LL	C-Jackson, AL
-------------------	---------------	----------------	---------------

<u>Material</u>		Approved Uses	
Grave	I	Base & Surface Course	
	Couch - Triangle Pit	Granular Material for Subbase	
	Spec. Gravity-SSD = 2.61	Special Embankment (non-plastic)	
	Water Absportion = 0.8%	Asphaltic Surface Treatment	
Sand		Asphaltic Concrete	
	Couch - Triangle Pit	(Friction Rating = III - Coarse Agg. Only)	
	Spec. Gravity-SSD = 2.63	Portland Cement Concrete	

Updated = 8/28/2017

APS00007250 (ASAE) Trinity Materials-West Lockesburg, AR

<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.56	Granular Material for Subbase
Water Absportion = 1.2%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 8/28/2017	Portland Cement Concrete

APS00007510 (ASAA) Wooten Sand & Gravel-Fouke, AR

<u>Material</u>		Approved Uses
	Gravel	Base & Surface Course
	Spec. Gravity-SSD = 2.60	Granular Material for Subbase
	Water Absportion = 1.0%	Special Embankment (non-plastic)
	Sand	Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
	Updated = 8/24/2017	Portland Cement Concrete

APS00011350 (ASAS) Eastern Oklahoma Quarries, LLC - Spiro, OK

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Spiro Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete

Updated = 8/24/2017

APS00011360 (ASAZ) Shale Support Holdings, LLC - Nicholson, MS

	<u>Material</u> Gravel		Approved Uses Granular Material for Subbase	
		Nicholson Pit	Special Embankment (non-plastic)	
		Spec. Gravity-SSD = 2.49	Asphaltic Surface Treatment	
		Water Absportion = 3.5%	Asphaltic Concrete	
	Sand		(Friction Rating = III - Coarse Agg. Only)	
		Nicholson Pit	Portland Cement Concrete	
		Spec. Gravity-SSD = 2.63	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	
Updated = 8/28/2017		d = 8/28/2017	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)	

A-2. OUT-OF-STATE PRODUCERS/SUPPLIERS

Οu	ıt	Ωf	St	ate
\sim	IL.	VI.	$\mathbf{O}_{\mathbf{L}}$	alt

APS00011380	(ASBA)	South Gate Aggregates, LLC - Nicholson, MS
<u>Material</u>		Approved Uses
Gravel		Base & Surface Course
Burge Pit		Granular Material for Subbase
Spec. Grav	ity-SSD = 2.47	Special Embankment (non-plastic)
Water Absp	ortion = 3.5%	Asphaltic Surface Treatment
Sand		Asphaltic Concrete
Burge Pit		(Friction Rating = III - Coarse Agg. Only)
Spec. Grav	ity-SSD = 2.63	Portland Cement Concrete
Updated = 8/28/201	7	(Gravel from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
APS00011450	(ASBC)	Huey P. Stockstill, LLC- Nicholson, MS

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Santa Rosa Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.63	Asphaltic Concrete
Updated = 8/24/2017	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)

APS00011470 (ASBB) Eastern Oklahoma Quarries - Garland, AR

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Chieftan Sand Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.63	Asphaltic Concrete
Water Absportion = 0.8%	Portland Cement Concrete
Updated = 8/24/2017	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)

APS00011630 (ASBE) Heidelberg Materials - Bristol Plant

<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Bristol Plant F.K.A. Hanson	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.63	Portland Cement Concrete
Updated = 5/22/2023	

Hammett & Green Aggregates - Vicksburg, MS (ASBF) APS00011690

<u> wateria</u>	<u>1</u>	Approved Uses
Gravel		Base & Surface Course
	Henry Mine Pit	Granular Material for Subbase
	Spec. Gravity-SSD = 2.56	Special Embankment (non-plastic)
	Water Absportion = 1.2%	Asphaltic Surface Treatment
Sand		Asphaltic Concrete
	Henry Mine Pit	(Friction Rating = III - Coarse Agg. Only)
	Spec. Gravity-SSD = 2.62	Portland Cement Concrete
	Water Absportion = 0.5%	

Updated = 1/8/2019

Spec. Gravity-SSD = 2.63

Updated = 1/16/2018

A-2. O	UT-OF-STATE PRODUCERS/SUPPLIERS
Out of State	
APS00012160	Dickerson & Bowen Co., Inc - Brookhaven, MS
<u>Material</u>	Approved Uses
Gravel Only	Base & Surface Course
D & B Brookhaven Pit	Granular Material for Subbase
Spec. Gravity-SSD = 2.53	Asphaltic Surface Treatment
Water Absportion = 2.2%	Asphaltic Concrete
Updated = 8/28/2017	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete
APS00012380	LeHigh Hanson - Garwood, TX
<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Arena Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	Portland Cement Concrete
Updated = 8/24/2017	
APS00012890	D & J Construction Company, LLC - West Monroe
<u>Material</u>	Approved Uses
Sand Only	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
Water Absportion = 0.5%	Asphaltic Concrete
Updated = 1/16/2018	Portland Cement Concrete
APS00012930	Regional Sand & Gravel, LLC #2 - Clinton
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.54	Granular Material for Subbase
Water Absportion = 1.5%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 7/26/2018	Portland Cement Concrete
	(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
APS00012980	Gulf Coast Sand & Gravel - Jackson, AL
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.59	Granular Material for Subbase
Water Absportion = 1.2%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment

Asphaltic Concrete

Portland Cement Concrete

(Friction Rating = III - Coarse Agg. Only)

A-2. OUT-OF-STATE PRODUCERS/SUPPLIERS

\bigcirc	14	٥f	Sta	+~
\cup	uι	OΓ	Old	นษ

APS(00013340	Heritage Sand and Gravel - Columbia, MS
<u>Materia</u>	<u>al</u>	Approved Uses
Gravel		Base & Surface Course
	Spec. Gravity-SSD = 2.50	Granular Material for Subbase
	Water Absportion = 3.0%	Special Embankment (non-plastic)
Sand		Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Update	d = 4/7/2020	Portland Cement Concrete
		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
APS(00014030	Sierra FRAC Sand - Plain Dealing
<u>Materia</u>	<u>al</u>	Approved Uses
Sand O	nly	Granular Material for Subbase
	Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
	Water Absportion = 0.5%	Asphaltic Concrete
Update	d = 11/15/2018	Portland Cement Concrete
APS	00014570	Arkansas Granufill Supply - Hot Springs, AR
<u>Materia</u>	<u>al</u>	Approved Uses
Sand O	nly	Asphaltic Concrete
	Spec. Gravity-SSD = 2.59	Supplemental Fines (screenings) for Asphaltic Concrete
	Water Absportion = 1.5%	
Update	d = 10/5/2021	
APS(00014750	Rock Island Sand and Gravel - Harrell Pit-Hampton
<u>Materia</u>	<u>al</u>	Approved Uses
Gravel		Base & Surface Course
	Spec. Gravity-SSD = 2.58	Granular Material for Subbase
	Water Absportion = 1.0%	Special Embankment (non-plastic)
Sand		Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.62	Asphaltic Concrete
	Water Absportion = 1.0%	(Friction Rating = III - Coarse Agg. Only)
Update	d = 10/5/2021	Portland Cement Concrete
		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend c Class F fly ash and GGBFS with a minimum of 50% replacement)
APS(00014970	Gulf Coast Sand - Nicholson, MS
<u>Materia</u>	<u>al</u>	Approved Uses
Gravel		Base & Surface Course
	Spec. Gravity-SSD = 2.48	Granular Material for Subbase
	Water Absportion = 2.9%	Special Embankment (non-plastic)
Sand		Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.68	Asphaltic Concrete
	Water Absportion = 0.1%	(Friction Rating = III - Coarse Agg. Only)
	d = 1/27/2022	Portland Cement Concrete
Update	//	

Spec. Gravity-SSD = 2.62

Water Absportion = 0.5%

Updated = 5/13/2025

A-2. Ol	JT-OF-STATE PRODUCERS/SUPPLIERS
Out of State	
APS00015010	Island Sand & Gravel - Crossett, AR
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.51	Granular Material for Subbase
Water Absportion = 1.8%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.64	Asphaltic Concrete
Water Absportion = 0.2%	(Friction Rating = III - Coarse Agg. Only)
Updated = 3/12/2025	Portland Cement Concrete - Gravel Only
APS00015130	Amrize Aggs - Cave-In-Rock, IL - Transition Ledge
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Stone	Granular Material for Subbase
(Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.65	Asphaltic Surface Treatment
Water Absportion = 1.3%	Asphaltic Concrete
Updated = 9/29/2025	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
	Riprap & Stone Revetment
APS00015180	Arcosa Aggregates - Plant 1347 - Hattiesburg, MS
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.53	Granular Material for Subbase
Water Absportion = 2.2%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.62	Asphaltic Concrete
Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Updated = 5/4/2022	Portland Cement Concrete
APS00015190	Arcosa Aggregates - Plant 1348 - Columbia, MS
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Spec. Gravity-SSD = 2.53	Granular Material for Subbase
Water Absportion = 2.2%	Special Embankment (non-plastic)
Sand	Asphaltic Surface Treatment

Asphaltic Concrete

Portland Cement Concrete

(Friction Rating = III - Coarse Agg. Only)

A-2. OUT-OF-STATE PRODUCERS/SUPPLIERS

\sim	1	- 1		٠	1 -
()	ΙIŤ	of	. ~	·tΩ	ιτΩ
\sim	uι	- OI		ıc	

Out c	of Otale	
APS	00015540	Hammett Gravel Company, Inc Red Mountain Plant
<u>Materia</u>	<u>al</u>	Approved Uses
Gravel		Base & Surface Course
	Spec. Gravity-SSD = 2.50	Granular Material for Subbase
	Water Absportion = 3.1%	Special Embankment (non-plastic)
Sand		Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.64	Asphaltic Concrete
	Water Absportion = 0.5%	(Friction Rating = III - Coarse Agg. Only)
Update	d = 3/12/2025	Portland Cement Concrete
		(Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
APS	00015780	RockCo Mining, LLC Courtland, MS
<u>Materia</u>	<u>al</u>	Approved Uses
Gravel		Base & Surface Course
	Spec. Gravity-SSD = 2.54	Granular Material for Subbase
	Water Absportion = 1.6%	Special Embankment (non-plastic)
Sand		Asphaltic Surface Treatment
	Spec. Gravity-SSD = 2.65	Asphaltic Concrete
	Water Absportion = 0.4%	(Friction Rating = III - Coarse Agg. Only)
Update	d = 3/12/2025	Portland Cement Concrete - Gravel Only
APS(00015900	Huey P. Stockstill, LLC Boone Mine
APS(Approved Uses
	<u>al</u>	
<u>Materia</u>	Spec. Gravity-SSD = 2.45	Approved Uses Base & Surface Course Granular Material for Subbase
<u>Materia</u> Gravel	<u>al</u>	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic)
<u>Materia</u>	Spec. Gravity-SSD = 2.45 Water Absportion = 3.6%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment
<u>Materia</u> Gravel	Spec. Gravity-SSD = 2.45 Water Absportion = 3.6% Spec. Gravity-SSD = 2.64	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete
Materia Gravel Sand	Spec. Gravity-SSD = 2.45 Water Absportion = 3.6% Spec. Gravity-SSD = 2.64 Water Absportion = 0.1%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)
Materia Gravel Sand	Spec. Gravity-SSD = 2.45 Water Absportion = 3.6% Spec. Gravity-SSD = 2.64	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete
Materia Gravel Sand	Spec. Gravity-SSD = 2.45 Water Absportion = 3.6% Spec. Gravity-SSD = 2.64 Water Absportion = 0.1%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only)
Materia Gravel Sand Update	Spec. Gravity-SSD = 2.45 Water Absportion = 3.6% Spec. Gravity-SSD = 2.64 Water Absportion = 0.1%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of
Materia Gravel Sand Update APSO Materia	Spec. Gravity-SSD = 2.45 Water Absportion = 3.6% Spec. Gravity-SSD = 2.64 Water Absportion = 0.1% d = 3/12/2025	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) West Side Complex - Hayes Quarry Approved Uses
Materia Gravel Sand Update APSO Materia Gravel	Spec. Gravity-SSD = 2.45 Water Absportion = 3.6% Spec. Gravity-SSD = 2.64 Water Absportion = 0.1% d = 3/12/2025	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) West Side Complex - Hayes Quarry Approved Uses Base & Surface Course
Sand Update APSO Materia Gravel Sand	Spec. Gravity-SSD = 2.45 Water Absportion = 3.6% Spec. Gravity-SSD = 2.64 Water Absportion = 0.1% d = 3/12/2025	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) West Side Complex - Hayes Quarry Approved Uses Base & Surface Course Granular Material for Subbase
Materia Gravel Sand Update APSO Materia Gravel	Spec. Gravity-SSD = 2.45 Water Absportion = 3.6% Spec. Gravity-SSD = 2.64 Water Absportion = 0.1% d = 3/12/2025 00016400	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) West Side Complex - Hayes Quarry Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic)
Sand Update APSO Materia Gravel Sand	Spec. Gravity-SSD = 2.45 Water Absportion = 3.6% Spec. Gravity-SSD = 2.64 Water Absportion = 0.1% d = 3/12/2025 00016400 al (Limestone)	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) West Side Complex - Hayes Quarry Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment
Sand Update APSO Materia Gravel Sand	Spec. Gravity-SSD = 2.45 Water Absportion = 3.6% Spec. Gravity-SSD = 2.64 Water Absportion = 0.1% d = 3/12/2025 00016400 al (Limestone) Spec. Gravity-SSD = 2.52	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) West Side Complex - Hayes Quarry Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete
Materia Gravel Sand Update APSO Materia Gravel Sand Stone	Spec. Gravity-SSD = 2.45 Water Absportion = 3.6% Spec. Gravity-SSD = 2.64 Water Absportion = 0.1% d = 3/12/2025 00016400 al (Limestone) Spec. Gravity-SSD = 2.52 Water Absportion = 3.2%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) West Side Complex - Hayes Quarry Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only)
Materia Gravel Sand Update APSO Materia Gravel Sand Stone	Spec. Gravity-SSD = 2.45 Water Absportion = 3.6% Spec. Gravity-SSD = 2.64 Water Absportion = 0.1% d = 3/12/2025 00016400 al (Limestone) Spec. Gravity-SSD = 2.52	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = III - Coarse Agg. Only) Portland Cement Concrete (Sand from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) West Side Complex - Hayes Quarry Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete

AGGREGATES APPROVED MATERIALS LIST

NOTES:

Note A-1:

Source approval samples of gravel and sand are obtained by personnel of the Materials and District Laboratories. The source is defined as the pit or quarry which produces the aggregate being evaluated. All aggregate which does not pass through the 4.75mm (No. 4) sieve shall be source approved prior to use. Certain aggregates may be approved for restricted use. A complete source approval analysis shall be run on each aggregate source.

Note A-2:

All material, regardless of prior approval, shall be sampled in accrodance with the Materials Sampling Manual and tested for conformance to the appropriate specifications. Any deviation in performance from the original sample submitted may result in removal of the material from the approved list.

Note A-3:

A specific gravity value of 2.62 (SSD) may be used for all in-state silica sands used for portland cement concrete.

Note A-4:

Because absorption has been found to correlate with the type and specific gravity of silica sands and chert gravels, the water absorption factors given in the following table may be used:

Out of State

APS00005770

APS00005710	(ABBC) Agrecasa Del Caribe-San Pedro Sula, HON	
<u>Material</u>	Approved Uses	
_		

Stone	Base & Surface Course	
(Limestone)	Granular Material for Subbase	
Spec. Gravity-SSD = 2.63	Special Embankment (non-plastic)	
Water Absportion = 1.6%	Asphaltic Surface Treatment	
Updated = 6/24/2022	Asphaltic Concrete	
	(Friction Rating = IV - Coarse Agg. Only)	
	Portland Cement Concrete	
	(may be used on bridge decks)	

Riprap & Stone Revetment (ABBY) APAC - Brickey's Stone-Bloomsdale, MO - Burlington

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Burlington Formation	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.64	Asphaltic Surface Treatment
Water Absportion = 1.4%	Asphaltic Concrete
Updated = 6/24/2022	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete
	(may be used on bridge decks)
	Riprap & Stone Revetment

APS00005900 (AB25) Arcosa Lightweight - Erwinville, LA

<u>Material</u>	Approved Uses	
Lightweight Aggregate	Special Embankment (non-plastic)	
(Expanded Clay)	Asphaltic Surface Treatment	
Spec. Gravity-SSD = 1.65	(Type B, C, & D applications only)	
Water Absportion = 16.3%	Asphaltic Concrete	
Updated = 12/8/2021	(excluding wearing surfaces)	
	(Friction Rating = I - Coarse Agg. Only)	
	Portland Cement Concrete	

APS00005960 (ABBU) Arcosa Aggregates - Grand Rivers, KY-StLouis

<u>Material</u>	Approved Uses		
Stone	Base & Surface Course		
(Siliceous Limestone)	Granular Material for Subbase		
St. Louis Formation	Special Embankment (non-plastic)		
Spec. Gravity-SSD = 2.69	Asphaltic Surface Treatment		
Water Absportion = 0.5%	Asphaltic Concrete		
Updated = 10/20/2021	(Friction Rating = IV - Coarse Agg. Only)		
	Riprap & Stone Revetment		

Out of State

Updated = 6/24/2022

Out of State			
	APS00005970 (AB	BK) To	exas Materials - Burnet.TX
	<u>Material</u>		Approved Uses
	Stone		Base & Surface Course
	(Limestone)		Granular Material for Subbase
	F.K.A OldCastle Mate	rials -	Special Embankment (non-plastic)
	Spec. Gravity-SSD = 2	2.78	Asphaltic Surface Treatment
	Water Absportion = 0.	.7%	Asphaltic Concrete
	Updated = 1/12/2024		(Friction Rating = IV - Coarse Agg. Only)
			Portland Cement Concrete
			(excluding bridge decks)
			Riprap & Stone Revetment
	APS00006080 (ABI	BN) C	rystal Hill Quarry-North Little Rock, AR
	<u>Material</u>		Approved Uses
	Stone		Base & Surface Course
	(Sandstone)		Granular Material for Subbase
	Granite Mountain Qua	arries	Special Embankment (non-plastic)
	Spec. Gravity-SSD = 2	2.62	Asphaltic Surface Treatment
	Water Absportion = 0.9%		Asphaltic Concrete
	Updated = 9/24/2024		(Friction Rating = II - Coarse Agg. Only)
			Riprap & Stone Revetment
	APS00006250 (A03	33) G	ranite Mountain Quarries-Little Rock, AR
	<u>Material</u>		Approved Uses
	Stone		Base & Surface Course
	(Granite)		Granular Material for Subbase
	Syenite Granite		Special Embankment (non-plastic)
	Spec. Gravity-SSD = 2		Asphaltic Surface Treatment
	Water Absportion = 0.	.9%	Asphaltic Concrete
	Updated = 2/16/2024		(Friction Rating = II - Coarse Agg. Only)
			Portland Cement Concrete
			Riprap & Stone Revetment
	APS00006340 (A07	77) H	anson Aggregates-Perch Hill Plant-Chico,TX
	<u>Material</u>		Approved Uses
	Stone		Base & Surface Course
	(Limestone)		Granular Material for Subbase
	Perch Hill Plant		Special Embankment (non-plastic)
	Spec. Gravity-SSD = 2	2.68	Asphaltic Surface Treatment
	Water Absportion = 0.	.8%	Asphaltic Concrete

(Friction Rating = IV - Coarse Agg. Only)

Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment

	ь. о	THER AGGREGATE MATERIALS
APS00006370	(AA90) Ha	astie Mining Company-Cave-in-Rock,IL
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Sandstone)		Granular Material for Subbase
Hastie Mining	Company Quarry	Special Embankment (non-plastic)
Spec. Gravity-	SSD = 2.66	Asphaltic Surface Treatment
Water Absport	ion = 0.8%	Asphaltic Concrete
Updated = 8/24/2017		(Friction Rating = I - Coarse Agg. Only)
		Portland Cement Concrete
		Riprap & Stone Revetment
APS00006440	(AA91) Ide	eal Domicana, SA-Santo Domingo, DR
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Limestone)		Granular Material for Subbase
Spec. Gravity-	SSD = 2.61	Special Embankment (non-plastic)
Water Absport	ion = 1.3%	Asphaltic Surface Treatment
Updated = 8/25/2017		Portland Cement Concrete
APS00006480	(ABBO) Ja	maica Aggregates Limited dba Amrize
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Crushed Alluv	vial Stone)	Granular Material for Subbase
Spec. Gravity-	SSD = 2.72	Special Embankment (non-plastic)
Water Absport	ion = 1.0%	Asphaltic Surface Treatment
Updated = 8/25/2017		Asphaltic Concrete
		(Friction Rating = III - Coarse Agg. Only)
		Portland Cement Concrete
		Riprap & Stone Revetment
APS00006560	(ABAN) Ar	nrize Aggregates - Cave-In-Rock, IL - SandStone
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Sandstone)		Granular Material for Subbase
Spec. Gravity-		Special Embankment (non-plastic)
Water Absport	ion = 0.8%	Asphaltic Surface Treatment
Updated = 6/3/2020		Asphaltic Concrete
		(Friction Rating = I - Coarse Agg. Only)
		Portland Cement Concrete
		(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
		Riprap & Stone Revetment

Out of State

APS00006570	(ABAM) A	Amrize Aggregates - Cave-In-Rock, IL - Sil. Limest
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Siliceous Lim	estone)	Granular Material for Subbase
Ledge 8 - 10		Special Embankment (non-plastic)
Spec. Gravity-	SSD = 2.68	Asphaltic Surface Treatment
Water Absport	tion = 0.7%	Asphaltic Concrete
Updated = $6/24/2022$		(Friction Rating = III - Coarse Agg. Only)
		Portland Cement Concrete
		(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of

(may be used on bridge decks)

Class F fly ash and GGBFS with a minimum of 50% replacement)

Riprap & Stone Revetment
APS00006580 (ABCA) Amrize Aggregates - Fredonia, KY

	,	· · · · · · · · · · · · · · · · · · ·
<u>Materi</u>	<u>al</u>	Approved Uses
Stone		Base & Surface Course
	(Siliceous Limestone)	Granular Material for Subbase
	Spec. Gravity-SSD = 2.69	Special Embankment (non-plastic)
	Water Absportion = 0.7%	Asphaltic Surface Treatment
Update	ed = 6/24/2022	Asphaltic Concrete
		(Friction Rating = III - Coarse Agg. Only)
		Portland Cement Concrete
		(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
		(may be used on bridge decks)
		Riprap & Stone Revetment

APS00006690 (AA86) Martin Marietta Aggregates-Bahamas, BAH

<u>Material</u>	Approved Uses	
Stone	Base & Surface Course	
(Porous Limestone)	Granular Material for Subbase	
Spec. Gravity-SSD = 2.38	Special Embankment (non-plastic)	
Water Absportion = 3.9%	Asphaltic Surface Treatment	
Updated = 8/25/2017	Asphaltic Concrete	
	(Friction Rating = III - Coarse Agg. Only)	
	Portland Cement Concrete	
	Riprap & Stone Revetment	

\cap	+	of.	Sta	+~
Ou	L	ΟI	Sia	ιe

APS00006710 (AA92)	Martin Marietta Aggregates-Cove, AR
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Rhyolite)	Granular Material for Subbase
Traprock	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.66	Asphaltic Surface Treatment
Water Absportion = 0.7%	Asphaltic Concrete
Undated = $7/20/2022$	(Friction Rating = II - Coarse Agg, Only)

APS00006730	(ABAW)	Martin Marietta	Aggregates-Malvern,	AR - SandStone
711 000000100	(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	mai uni manotta	riggiogatoo marroni,	7 11 C Garrage 10110

Riprap & Stone Revetment

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Sandstone)	Granular Material for Subbase
Jones Mill Pit	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.53	Asphaltic Surface Treatment
Water Absportion = 2.2%	Asphaltic Concrete
Updated = 8/25/2017	(Friction Rating = II - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment

Out of State

APS00006740 (ABAX) Martin Marietta Aggregates-Malvern, AR - Granite

<u>Materi</u>	<u>al</u>	Approved Uses
Stone		Base & Surface Course
	(Granite)	Granular Material for Subbase
	Jones Mill Pit	Special Embankment (non-plastic)
	Spec. Gravity-SSD = 2.58	Asphaltic Surface Treatment
	Water Absportion = 0.9%	Asphaltic Concrete
Update	ed = 2/16/2024	(Friction Rating = III - Coarse Agg. Only)
		Portland Cement Concrete
		Riprap & Stone Revetment

APS00006750 (AA39) Martin Marietta Aggregates-Mulgrave, NS

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Granite)	Granular Material for Subbase
Spec. Gravity-SSD = 2.70	Special Embankment (non-plastic)
Water Absportion = 0.9%	Asphaltic Surface Treatment
Updated = 2/16/2024	Asphaltic Concrete
	(excluding OGFC and coarse mix)
	(Friction Rating = I - Coarse Agg. Only)
	Portland Cement Concrete
	(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
	Riprap & Stone Revetment

	В.	OTHER AGGREGATE MATERIALS
APS00006760	(AA51)	Martin Marietta Aggregates-Sawyer,OK
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Sandstone)		Granular Material for Subbase
Spec. Gravity-	SSD = 2.52	Special Embankment (non-plastic)
Water Absport	tion = 2.3%	Asphaltic Surface Treatment
Updated = $6/3/2020$		Asphaltic Concrete
		(Friction Rating = I - Coarse Agg. Only)
		Portland Cement Concrete
		(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate) Riprap & Stone Revetment
4 DO00000000	(AD40)	
APS00006880	(AB13)	Pine Bluff Sand & Gravel-Delaware, AR
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Sandstone)		Granular Material for Subbase
River Mountain	•	Special Embankment (non-plastic)
Spec. Gravity-		Asphaltic Surface Treatment
Water Absport	tion = 1.0%	Asphaltic Concrete
Updated = 11/10/2020		(Friction Rating = I - Coarse Agg. Only)
		Portland Cement Concrete
		(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires 30% Class F fly ash or 50% slag to mitigate)
		Riprap & Stone Revetment
APS00006890	(ABBS)	Pine Bluff Sand & Gravel-Salem,KY
Material	,	Approved Uses
Stone		Base & Surface Course
(Siliceous Lim	estone)	Granular Material for Subbase
Cumberland R	•	Special Embankment (non-plastic)
Spec. Gravity-	SSD = 2.68	Asphaltic Surface Treatment
Water Absport	tion = 0.8%	Asphaltic Concrete
Updated = 10/28/2021		(Friction Rating = III - Coarse Agg. Only)
		Riprap & Stone Revetment
Out of State		
APS00007160	(AB15)	Texas Crushed Stone Co., IncGeorgetown, TX
<u>Material</u>	(- /	Approved Uses
Gravel		Base & Surface Course
Stone		Granular Material for Subbase
(Limestone)		Special Embankment (non-plastic)
Spec. Gravity-	SSD = 2.48	Asphaltic Surface Treatment
Water Absport		Asphaltic Concrete
Updated = 3/12/2025		(Friction Rating = IV - Coarse Agg. Only)
•		Portland Cement Concrete
		(excluding bridge decks)
		Diagram 9 Otana Davistanant

Riprap & Stone Revetment

APS00007180	(A056)	Tower Rock Stone Co-St.Genevieve, MO- Limestn Zn8
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Limestone)		Granular Material for Subbase
Spec. Gravity	r-SSD = 2.64	Special Embankment (non-plastic)
Water Abspor	rtion = 1.6%	Asphaltic Surface Treatment
Updated = 5/21/2018		Asphaltic Concrete
		(Friction Rating = III - Coarse Agg. Only)
		Portland Cement Concrete
		Riprap & Stone Revetment
APS00007190	(A079)	Tower Rock Stone Co-St.Genevieve, MO- Oolitic
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Oolitic Stone	·)	Granular Material for Subbase
Spec. Gravity	r-SSD = 2.47	Special Embankment (non-plastic)
Water Abspor	rtion = 4.8%	Asphaltic Surface Treatment
Updated = 8/25/2017		Asphaltic Concrete
		(Friction Rating = III - Coarse Agg. Only)
		Portland Cement Concrete
		Riprap & Stone Revetment
Out of State		
APS00007260	(AB61)	Martin Marietta - Bridgeport TX
	· · ·	3-1
<u>Material</u>	(-)	Approved Uses
	(-)	• •
<u>Material</u>		Approved Uses
Material Stone	(- ,	Approved Uses Base & Surface Course
Material Stone (Limestone)	,	Approved Uses Base & Surface Course Granular Material for Subbase
Material Stone (Limestone) Bridgeport	7-SSD = 2.64	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic)
Material Stone (Limestone) Bridgeport Spec. Gravity	7-SSD = 2.64	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment
Material Stone (Limestone) Bridgeport Spec. Gravity Water Abspor	7-SSD = 2.64	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete
Material Stone (Limestone) Bridgeport Spec. Gravity Water Abspor	7-SSD = 2.64	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only)
Material Stone (Limestone) Bridgeport Spec. Gravity Water Abspor	7-SSD = 2.64	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete
Material Stone (Limestone) Bridgeport Spec. Gravity Water Abspor	7-SSD = 2.64	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks)
Material Stone (Limestone) Bridgeport Spec. Gravity Water Abspor Updated = 6/24/2022	r-SSD = 2.64 rtion = 1.3%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment
Material Stone (Limestone) Bridgeport Spec. Gravity Water Absport Updated = 6/24/2022	r-SSD = 2.64 rtion = 1.3%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses Base & Surface Course
Material Stone (Limestone) Bridgeport Spec. Gravity Water Absport Updated = 6/24/2022 APS00007340 Material	r-SSD = 2.64 rtion = 1.3%	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses
Material Stone (Limestone) Bridgeport Spec. Gravity Water Absport Updated = 6/24/2022 APS00007340 Material Stone (Limestone) Calera Quarry	r-SSD = 2.64 rtion = 1.3% (A042)	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses Base & Surface Course
Material Stone (Limestone) Bridgeport Spec. Gravity Water Absport Updated = 6/24/2022 APS00007340 Material Stone (Limestone) Calera Quarry Spec. Gravity	7-SSD = 2.64 rtion = 1.3% (A042)	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses Base & Surface Course Granular Material for Subbase
Material Stone (Limestone) Bridgeport Spec. Gravity Water Absport Updated = 6/24/2022 APS00007340 Material Stone (Limestone) Calera Quarry Spec. Gravity Water Absport	7-SSD = 2.64 rtion = 1.3% (A042)	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete
Material Stone (Limestone) Bridgeport Spec. Gravity Water Absport Updated = 6/24/2022 APS00007340 Material Stone (Limestone) Calera Quarry Spec. Gravity	7-SSD = 2.64 rtion = 1.3% (A042)	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only)
Material Stone (Limestone) Bridgeport Spec. Gravity Water Absport Updated = 6/24/2022 APS00007340 Material Stone (Limestone) Calera Quarry Spec. Gravity Water Absport	7-SSD = 2.64 rtion = 1.3% (A042)	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete
Material Stone (Limestone) Bridgeport Spec. Gravity Water Absport Updated = 6/24/2022 APS00007340 Material Stone (Limestone) Calera Quarry Spec. Gravity Water Absport	7-SSD = 2.64 rtion = 1.3% (A042)	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks)
Material Stone (Limestone) Bridgeport Spec. Gravity Water Absport Updated = 6/24/2022 APS00007340 Material Stone (Limestone) Calera Quarry Spec. Gravity Water Absport	7-SSD = 2.64 rtion = 1.3% (A042)	Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete (may be used on bridge decks) Riprap & Stone Revetment Vulcan Materials Co-Calera, AL Approved Uses Base & Surface Course Granular Material for Subbase Special Embankment (non-plastic) Asphaltic Surface Treatment Asphaltic Concrete (Friction Rating = IV - Coarse Agg. Only) Portland Cement Concrete

\cap	ııt	$\cap f$	State
\sim	uι	OI.	State

APS00007350 (AA95)	Vulcan Materials Co-Cancun, MEX
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.38	Special Embankment (non-plastic)
Water Absportion = 3.7%	Asphaltic Surface Treatment
Updated = 6/24/2022	Asphaltic Concrete
	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete
	(may be used on bridge decks)
	Riprap & Stone Revetment

APS00007380 (ABBQ) Vulcan Materials Co-Grand Rivers, KY- Ft Payne

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Siliceous Limestone)	Granular Material for Subbase
Ft. Payne Formation	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.68	Asphaltic Surface Treatment
Water Absportion = 0.2%	Asphaltic Concrete
Updated = 10/29/2021	(Friction Rating = III - Coarse Agg. Only)
	(Friction Rating = II for ADT <= 20,000 - Coarse Agg. Only)

APS00007390 (ABBP) Vulcan Materials Co-Grand Rivers, KY- Warsaw

<u>Mat</u>	<u>terial</u>	Approved Uses	
Stor	ne	Base & Surface Course	
	(Limestone)	Granular Material for Subbase	
	Warsaw Formation	Special Embankment (non-plastic)	
	Spec. Gravity-SSD = 2.67	Asphaltic Surface Treatment	
	Water Absportion = 0.9%	Asphaltic Concrete	
Upd	dated = 10/29/2021	(Friction Rating = IV - Coarse Agg. Only)	
		Riprap & Stone Revetment	

Out of State

APS00007430 (ABBT) Vulcan Materials Co-Tuscumbia, AL- Pride Quarry

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.60	Special Embankment (non-plastic)
Water Absportion = 1.9%	Asphaltic Surface Treatment
Updated = 6/24/2022	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
	(may be used on bridge decks)
	Riprap & Stone Revetment

	B.	OTHER AGGREGATE MATERIALS
APS00007450	(AB19)	Vulcan Materials Co-Trinity, AL
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Limestone)		Granular Material for Subbase
Trinity Plant		Special Embankment (non-plastic)
Spec. Gravity-	SSD = 2.65	Asphaltic Surface Treatment
Water Absport	ion = 1.2%	Asphaltic Concrete
Updated = 10/25/2017		(Friction Rating = IV - Coarse Agg. Only)
		Portland Cement Concrete
		(excluding bridge decks)
		Riprap & Stone Revetment
APS00007480	(ABAY)	Warren Paving-Salem, KY - Upper Warsaw Formation
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Siliceous Lime	estone)	Granular Material for Subbase
Slats Lucas Q	uarry	Special Embankment (non-plastic)
Spec. Gravity-	SSD = 2.69	Asphaltic Surface Treatment
Water Absport	ion = 0.4%	Asphaltic Concrete
Updated = 10/20/2021		(Friction Rating = III - Coarse Agg. Only)
		(Friction Rating = II for ADT <10,000 - Coarse Agg. Only)
		Riprap & Stone Revetment
APS00007500	(AB78)	Winn Materials, IncClarksville, TN
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Siliceous Lime	estone)	Granular Material for Subbase
Spec. Gravity-		Special Embankment (non-plastic)
Water Absport	ion = 0.6%	Asphaltic Surface Treatment
Updated = 10/28/2021		Asphaltic Concrete
		(Friction Rating = IV - Coarse Agg. Only)
		Riprap & Stone Revetment
APS00007520	(AB04)	Delta Materials - Marble Falls, TX
<u>Material</u>		Approved Uses
Stone		Base & Surface Course
(Sandstone)		Granular Material for Subbase
Spec. Gravity-		Special Embankment (non-plastic)
Water Absport	ion = 2.1%	Asphaltic Surface Treatment
Updated = 8/25/2017		Asphaltic Concrete
		(Friction Rating = I - Coarse Agg. Only)
		Portland Cement Concrete
		Riprap & Stone Revetment

Updated = 11/9/2018

	B. OTHER AGGREGATE MATERIALS	
APS00011430 (ABC	D) APAC - Brickey's Stone-Bloomsdale, MO - Plattin	
Material	Approved Uses	
Stone	Base & Surface Course	
(Limestone)	Granular Material for Subbase	
Plattin Formation	Special Embankment (non-plastic)	
Spec. Gravity-SSD = 2.6		
Water Absportion = 2.0%		
Updated = 7/26/2018	(Friction Rating = IV - Coarse Agg. Only)	
·	Portland Cement Concrete	
	(excluding bridge decks)	
	Riprap & Stone Revetment	
Out of State		-
APS00011620 (ABC) Central Stone Co - Farmington, MO	_
<u>Material</u>	Approved Uses	
Stone	Base & Surface Course	
(Granite)	Granular Material for Subbase	
Butler Hill Granite Quarr	Special Embankment (non-plastic)	
Spec. Gravity-SSD = 2.6	2 Asphaltic Surface Treatment	
Water Absportion = 0.3%	Asphaltic Concrete	
Updated = 2/16/2024	(Friction Rating = IV - Coarse Agg. Only)	
	Portland Cement Concrete	
	(excluding bridge decks)	
	Riprap & Stone Revetment	
APS00011870	Amrize Aggregates-Smithland, KY-Three Rivers-S1	_
<u>Material</u>	Approved Uses	
Stone	Base & Surface Course	
(Siliceous Limestone)	Granular Material for Subbase	
3RvrQry-Bench S1-Pit#	Special Embankment (non-plastic)	
Spec. Gravity-SSD = 2.6	7 Asphaltic Surface Treatment	
Water Absportion = 1.0%	Asphaltic Concrete	
Updated = 5/20/2020	(Friction Rating = III - Coarse Agg. Only)	
	Riprap & Stone Revetment	
APS00012130	Tower Rock Stone Co-St.Genevieve, MO- Limestn Zn12	
<u>Material</u>	Approved Uses	
Stone	Base & Surface Course	
(Limestone)	Granular Material for Subbase	
Ledge 12	Special Embankment (non-plastic)	
Spec. Gravity-SSD = 2.6	•	
Water Absportion = 0.8%	Asphaltic Concrete	

(Friction Rating = IV - Coarse Agg. Only)

Riprap & Stone Revetment

\bigcirc ı	ıŧ	$\cap f$	State
\mathcal{O}_{U}	11	UΙ	Olaic

APS00012300	Vulcan Materials Co-West Loachapoka, AL
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Granite)	Granular Material for Subbase
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)
Water Absportion = 0.4%	Asphaltic Surface Treatment
Updated = 2/16/2024	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(excluding bridge decks)
	Riprap & Stone Revetment

APS00012320	Arcosa Aggregates - Grand Rivers,KY-Warsaw
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Siliceous Limestone)	Granular Material for Subbase
Warsaw Formation	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.65	Asphaltic Surface Treatment
Water Absportion = 1.1%	Asphaltic Concrete
Updated = 11/10/2020	(Friction Rating = IV - Coarse Agg. Only)
	Riprap & Stone Revetment

APS00012600 Martin Marietta - MMR - Hondo, TX

<u>N</u>	<u>laterial</u>	Approved Uses
S	tone	Base & Surface Course
	(Limestone)	Granular Material for Subbase
	Medina Rock & Rail Quarry	Special Embankment (non-plastic)
	Spec. Gravity-SSD = 2.53	Asphaltic Surface Treatment
	Water Absportion = 2.2%	Asphaltic Concrete
U	pdated = 8/29/2017	(Friction Rating = IV - Coarse Agg. Only)
		Riprap & Stone Revetment

Out of State

APS00012680	warren Paving-Salem, KY-Lower High Calcium Ledge
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Lower Warsaw Formation	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.67	Asphaltic Surface Treatment
Water Absportion = 0.7%	Asphaltic Concrete
Updated = 6/24/2022	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(may be used on bridge decks)
	Riprap & Stone Revetment

APS00012880	Amrize Aggregates-Smithland, KY-Three Rivers-S2	
<u>Material</u>	Approved Uses	
Stone	Base & Surface Course	
(Siliceous Limestone)	Granular Material for Subbase	
Spec. Gravity-SSD = 2.69	Special Embankment (non-plastic)	
Water Absportion = 0.8%	Asphaltic Surface Treatment	
Updated = 5/20/2020	Asphaltic Concrete	
	(excluding OGFC and coarse mix)	
	(Friction Rating = III - Coarse Agg. Only)	
	Riprap & Stone Revetment	

Out of State

Α	PS00012960	APAC R4 ObrusS.A. D.C.V Boca Del Rio, Mexico
Ma	<u>aterial</u>	Approved Uses
St	one	Base & Surface Course
	(Granite)	Granular Material for Subbase
	Spec. Gravity-SSD = 2.89	Special Embankment (non-plastic)
	Water Absportion = 1.5%	Asphaltic Surface Treatment
Up	odated = 2/16/2024	Asphaltic Concrete
		(Friction Rating = IV - Coarse Agg. Only)
		Portland Cement Concrete
		Ripran & Stone Revetment

and I A Dandones C A Calitia Cto Comento	
aras I A Pongerosa S A - Collinasin Formin -	1
•	eras LA Ponderosa S.A OoliticStnFormtn -

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.71	Special Embankment (non-plastic)
Water Absportion = 1.2%	Asphaltic Surface Treatment
Updated = 2/21/2024	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment
	Stone (Limestone) Spec. Gravity-SSD = 2.71 Water Absportion = 1.2%

APS00014110	Rogers Group - Lacey's Springs Quarry

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.70	Special Embankment (non-plastic)
Water Absportion = 0.7%	Asphaltic Surface Treatment
Updated = 2/14/2020	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment

APS00014340	Amrize Aggregates-Smithland, KY-Upper Fredonia	
<u>Material</u>	Approved Uses	
Stone	Base & Surface Course	
(Siliceous Limestone)	Granular Material for Subbase	
Spec. Gravity-SSD = 2.70	Special Embankment (non-plastic)	
Water Absportion = 1.0%	Asphaltic Surface Treatment	
Updated = 10/21/2020	Asphaltic Concrete	
	(Friction Rating = IV - Coarse Agg. Only)	
	Riprap & Stone Revetment	

Out of State

APS00014530	Martin Marietta - Mili Creek - Granite	
<u>Material</u>	Approved Uses	
Stone	Base & Surface Course	
(Granite)	Granular Material for Subbase	
Spec. Gravity-SSD = 2.74	Special Embankment (non-plastic)	
Water Absportion = 1.0%	Asphaltic Surface Treatment	
Updated = 2/16/2024	Asphaltic Concrete	
	(Friction Rating = IV - Coarse Agg. Only)	
	Portland Cement Concrete	
	Riprap & Stone Revetment	

APS00014540 Martin Marietta - Mill Creek - Limestone

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Dolomitic Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.81	Special Embankment (non-plastic)
Water Absportion = 0.4%	Asphaltic Surface Treatment
Updated = 5/31/2022	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment

APS00014560 Shorline Aggregates Inc. - South Brook Quarry

<u>Material</u>	<u>Materia</u>	
Stone	Stone	
(Granite)		
Spec. Gravity-SSD = 2.71		
Water Absportion = 0.5%		
Updated = 2/16/2024	Update	
(Granite) Spec. Gravity-SSD = 2.71 Water Absportion = 0.5%		

\bigcirc	ıŧ		State
\mathcal{O}	Jι	UI	Siait

APS00014700	Heidelberg Materials-Servtex Quarry-New Braunfels
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
F.K.A. Hanson Aggregates	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.57	Asphaltic Surface Treatment
Water Absportion = 2.0%	Asphaltic Concrete
Updated = 5/22/2023	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
	(excluding bridge decks)
	Riprap & Stone Revetment

APS00014710	Arcosa Lightweight - Livingston, AL	
<u>Material</u>	Approved Uses	
Lightweight Aggregate	Special Embankment (non-plastic)	
(Expanded Clay)	Asphaltic Surface Treatment	
Spec. Gravity-SSD = 1.07	Asphaltic Concrete	
Water Absportion = 20.8%	(Friction Rating = I - Coarse Agg. Only)	
Updated = 12/8/2021	Portland Cement Concrete	

Out of State

APS00014740	Heidelberg Materials - Burnet Quarry	
<u>Material</u>	Approved Uses	
Stone	Base & Surface Course	
(Siliceous Limestone)	Granular Material for Subbase	
F.K.A. Hanson Aggregates -	Special Embankment (non-plastic)	
Spec. Gravity-SSD = 2.78	Asphaltic Surface Treatment	
Water Absportion = 0.6%	Asphaltic Concrete	
Updated = 5/22/2023	(Friction Rating = IV - Coarse Agg. Only)	
	Portland Cement Concrete	
	(excluding bridge decks)	
	Riprap & Stone Revetment	

APS00014900	Neely's Landing LLC Jackson, MO	
<u>Material</u>	Approved Uses	
Stone	Base & Surface Course	
(Siliceous Limestone)	Granular Material for Subbase	
Spec. Gravity-SSD = 2.62	Special Embankment (non-plastic)	
Water Absportion = 1.0%	Asphaltic Surface Treatment	
Updated = 10/20/2021	Asphaltic Concrete	
	(Friction Rating = III - Coarse Agg. Only)	
	Portland Cement Concrete	
	Riprap & Stone Revetment	

Out o	of State	ļ
-------	----------	---

APS00014980	Arcosa Lightweight - Streetman Plant
<u>Material</u>	Approved Uses
Lightweight Aggregate	Asphaltic Surface Treatment
(Expanded Shale)	Asphaltic Concrete
Spec. Gravity-SSD = 1.65	(Friction Rating = I - Coarse Agg. Only)
Water Absportion = 14.1%	Portland Cement Concrete
Updated = 12/2/2022	

APS00015020	APAC Brickey Stone - Bloomdale - Kimmswick
APSOCITION	APAL. Brickey Stone - Bioomogie - Kimmswick
/ \l \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	7 1 7 10 DITORCY CLOTTC DICCITIAGIC TAITHINGWICK

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.67	Special Embankment (non-plastic)
Water Absportion = 1.3%	Asphaltic Surface Treatment
Updated = 6/24/2022	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(may be used on bridge decks)
	Riprap & Stone Revetment

APS00015110 Amrize Aggregates-Cave-In-Rock, IL-Dolomite Ledge

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Dolomitic Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.67	Special Embankment (non-plastic)
Water Absportion = 1.1%	Asphaltic Surface Treatment
Updated = 6/24/2022	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
	(may be used on bridge decks)
	Riprap & Stone Revetment

APS00015120 Amrize Aggrs-Cave-In-Rock, IL-Upper St. Gen Ledge

<u>M</u>	<u>laterial</u>	Approved Uses
S	tone	Base & Surface Course
	(Limestone)	Granular Material for Subbase
	Spec. Gravity-SSD = 2.67	Special Embankment (non-plastic)
	Water Absportion = 0.9%	Asphaltic Surface Treatment
U	lpdated = 6/24/2022	Asphaltic Concrete
		(Friction Rating = IV - Coarse Agg. Only)
		Portland Cement Concrete
		(may be used on bridge decks)
		Riprap & Stone Revetment

Updated = 2/16/2024

B. OTHER AGGREGATE MATERIALS	
Out of State	
APS00015130	Amrize Aggs - Cave-In-Rock, IL - Transition Ledge
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Stone	Granular Material for Subbase
(Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.65	Asphaltic Surface Treatment
Water Absportion = 1.3%	Asphaltic Concrete
Updated = 9/29/2025	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement) Riprap & Stone Revetment
APS00015230	Shoreline Agg., Inc Point Rousse Quarry
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Granite)	Granular Material for Subbase
Spec. Gravity-SSD = 2.79	Special Embankment (non-plastic)
Water Absportion = 0.4%	Asphaltic Surface Treatment
Updated = 2/16/2024	Asphaltic Concrete
	(Friction Rating = III - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment
APS00015310	Hastie Mining and Trucking #2 - Cave-In-Rock, IL
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Siliceous Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.69	Special Embankment (non-plastic)
Water Absportion = 1.0%	Asphaltic Surface Treatment
Updated = 6/13/2025	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	Riprap & Stone Revetment
APS00015390	Matco Aggregates LLC Actopan Quarry - Basalt
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Granite)	Granular Material for Subbase
Spec. Gravity-SSD = 2.87	Special Embankment (non-plastic)
Water Absportion = 2.1%	Asphaltic Surface Treatment

Asphaltic Concrete

Portland Cement Concrete Riprap & Stone Revetment

(Friction Rating = IV - Coarse Agg. Only)

Updated = 9/15/2023

B. OTHER AGGREGATE MATERIALS

Out of State	
APS00015610	CEMEX 4200 Balcones Quarry - New Braunfels,TX
Material	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.58	Special Embankment (non-plastic)
Water Absportion = 1.5%	Asphaltic Surface Treatment
Updated = 8/12/2025	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
	(may be used on bridge decks)
	Riprap & Stone Revetment
APS00015630	Amrize Aggrs-Cave-In-Rock, IL - Downeys Bluff Led
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.67	Asphaltic Surface Treatment
Water Absportion = 1.1%	Asphaltic Concrete
Updated = 9/15/2023	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(Stone from this source is potentially deleterious in Portland Cement Concrete mixes, requires mitigation by 30% Class F fly ash, 50% slag, or ternary blend of Class F fly ash and GGBFS with a minimum of 50% replacement)
	Riprap & Stone Revetment
APS00015640	Coastal Industrial Resources, LLC-Gibralgar Quarry
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.65	Asphaltic Surface Treatment
Water Absportion = 1.6%	Asphaltic Concrete
Updated = 9/15/2023	(Friction Rating = IV - Coarse Agg. Only)
	Riprap & Stone Revetment
APS00015720	GCA Materials - May Pen, Jamaica
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.65	Asphaltic Surface Treatment
Water Absportion = 2.0%	Asphaltic Concrete

(Friction Rating = IV - Coarse Agg. Only)

Riprap & Stone Revetment

Spec. Gravity-SSD = 2.66

Water Absportion = 1.6%

Updated = 6/11/2025

В.	OTHER AGGREGATE MATERIALS
Out of State	
APS00015790	Cemex Materials Newfoundland, Inc Canada
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Dolomitic Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.75	Asphaltic Surface Treatment
Water Absportion = 0.4%	Asphaltic Concrete
Updated = 11/13/2023	(Friction Rating = IV - Coarse Agg. Only)
	Riprap & Stone Revetment
APS00015840	Souter Limestone and Minerals, LLC Gore, OK
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Granular Material for Subbase
Spec. Gravity-SSD = 2.67	Special Embankment (non-plastic)
Water Absportion = 0.7%	Asphaltic Surface Treatment
Updated = 1/12/2024	Asphaltic Concrete
	(Friction Rating = IV - Coarse Agg. Only)
	Portland Cement Concrete
	(may be used on bridge decks)
15000015050	Riprap & Stone Revetment
APS00015850	Amrize, IncThree Rivers Quarry -Smithland, KY S3
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.66	Asphaltic Surface Treatment
Water Absportion = 1.0%	Asphaltic Concrete
Updated = 1/29/2024	(Friction Rating = IV - Coarse Agg. Only)
A D000045040	Riprap & Stone Revetment
APS00015940	Two Countries Materials S.A. DE CV - Mexico
<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.68 Water Absportion = 2.0%	Asphaltic Surface Treatment Asphaltic Concrete
Updated = 3/14/2024	Riprap & Stone Revetment
APS00016010	Tajo Chirripo S.A Limon
	•
Material Stone	Approved Uses Base & Surface Course
(Basalt Rock)	Special Embankment (non-plastic)
(Dasait Nock)	Special Embandment (non plastic)

Asphaltic Surface Treatment

Riprap & Stone Revetment

(Friction Rating = IV - Coarse Agg. Only)

Asphaltic Concrete

APS00016120	Antoine Rock Quarry - Delight, AR	
<u>Material</u>	Approved Uses	
Stone	Riprap & Stone Revetment	
(Limestone)		
Updated = 9/10/2024		

Out of State

APS00016400	West Side Complex - Hayes Quarry
<u>Material</u>	Approved Uses
Gravel	Base & Surface Course
Sand	Granular Material for Subbase
Stone	Special Embankment (non-plastic)
(Limestone)	Asphaltic Surface Treatment
Spec. Gravity-SSD = 2.52	Asphaltic Concrete
Water Absportion = 3.2%	(Friction Rating = IV - Coarse Agg. Only)
Updated = 10/3/2025	Riprap & Stone Revetment
	Bedding Material

APS00016410	Southland Resources, Inc.	
<u>Material</u>	Approved Uses	
Stone	Base & Surface Course	
(Sandstone)	Special Embankment (non-plastic)	
Spec. Gravity-SSD = 2.62	Asphaltic Surface Treatment	
Water Absportion = 1.9%	Riprap & Stone Revetment	
Updated = 7/24/2025		

APS00016440	Amriza Aga Smithland	Throa Divora Middle Frederia
AP300010440	Aminze AggSmilmand	Three Rivers-Middle Fredonia

<u>Material</u>	Approved Uses
Stone	Base & Surface Course
(Limestone)	Special Embankment (non-plastic)
Spec. Gravity-SSD = 2.64	Asphaltic Surface Treatment
Water Absportion = 1.7%	Riprap & Stone Revetment

Updated = 10/3/2025

NOTES:

Note B-1:

Refer to Subsections 501.02 and 1003.06 for definition and application of Friction Ratings.

Note B-2:

All material, regardless of prior approval, shall be sampled in accrodance with the Materials Sampling Manual and tested for conformance to the appropriate specifications. Any deviation in performance from the original sample submitted may result in removal of the material from the approved list.

REFERENCE:

DOTD Standard Specifications and Special Provisions, Section 1003

DOTD Supplemental Specifications

DOTD Maintenance Specifications

No information contained in this list is to be used for promotional purposes.