



STATE OF LOUISIANA  
DEPARTMENT OF TRANSPORTATION AND DEVELOPMENT  
TECHNICAL SPECIFICATIONS FOR

**TRACTOR/LOADER/BACKHOE COMBINATION, 4 WHEEL DRIVE**

**SERIES NO. 866-000**

**REV. 12/1/2025**

**EQUIPMENT SPECIFICATION 866-000B**

**GENERAL**

This specification sets forth the minimum requirements for a 4 wheel drive tractor/loader/backhoe combination.

Equipment shall be new, a production model of current manufacture, and must meet all state and Federal safety and emission standards in effect at time of order.

**REPRESENTATIVE SPECIFICATIONS**

A Caterpillar 420 and John Deere 310, with appropriate options and standard features, was used to develop these specifications and establish equivalency evaluation criteria.

Equipment of similar style, type, character, quality, features, and purpose conforming to the following detailed requirements/specifications will be considered. For evaluation purposes, bidders proposing an exception/equivalent option/feature to those specified herein, may be required to provide manufacturer/product information (catalogue sheets, detailed specifications, pictures, etc.). This information will be evaluated against the minimum requirements of this specification. Proposed submittals that are determined not to be equivalent to the established criteria will be rejected.

**LOUISIANA AUTHORIZED DEALER(S)**

Proposed item(s) must be from a manufacturer who has at least one (1) authorized dealer within the State of Louisiana where parts and service can be obtained. Authorized dealer(s) must have properly trained technicians plus all other resources necessary to perform warranty and repair services in complete accordance with the manufacturer's requirements. A letter certifying the ability to meet this requirement, inclusive of the company name(s) and address(es) of the Louisiana authorized dealer(s), should be supplied with the bid submittal and may be required prior to award.

**DELIVERY & ACCEPTANCE**

Vendor shall perform a test run of each unit to verify that all features and capabilities are operating properly at time of delivery. Documentation of testing may be required prior to acceptance by the Department.

Unit(s) must be delivered completely assembled (including all components, accessories, etc.) and ready for operation without any additional preparation including, but not limited to, ensuring all fluid levels are at their full mark, **fuel tank(s) level is at least ¼ of tank**, all necessary lubrication has been performed, etc.

Any unit delivered under this specification is subject to rejection if there is evidence of poor workmanship, by either the vendor or the original manufacturer. Noted defects and/or nonconformance findings may be corrected by the vendor. Corrections must be completed and approved by the Equipment Engineer or his representative prior to final acceptance.

Unit(s) shall be delivered “**on the ground**;” DOTD will not unload nor provide any unloading equipment to the vendor/delivery driver in order to offload the unit(s).

**NOTE:** The Department will have space available for equipment to be unloaded.

**EACH UNIT MUST BE SUPPLIED WITH THE FOLLOWING DOCUMENTATION AT TIME OF DELIVERY:**

1. Dealer's Service Policy
2. Owner's/Operator's Manual(s)
  - a. One (1) Hardcopy
  - b. One (1) Digital Copy
    - i. Acceptable Formats: PDF delivered via USB “Flash Drive”, or E-mail
3. Service Manual(s)
  - a. One (1) Hardcopy
  - b. One (1) Digital Copy
    - i. Acceptable Formats: PDF delivered via USB “Flash Drive”, or E-mail
4. Build Sheet(s) – as applicable
  - a. One (1) Hardcopy
  - b. Build sheets should be written in plain language (not company specific codes) and include, at a minimum, all standard & optional features of the delivered unit.

**NOTE:** Invoices will not be processed for payment until the unit(s) have been inspected by the Equipment Engineer or their representative and deemed in compliance with the specifications.

**BID SUBMITTALS**

Any additions, deletions, or variations from the specifications should be noted in the "Bidder's Exceptions" page of this specification. Exceptions that are noted to be less than a minimum requirement will not be accepted.

Any additions, deletions or variations from the manufacturer's standard published specifications should be noted on the "Bidder's Exceptions" page of this specification. Unless otherwise noted, any items appearing in the manufacturer's standard published specifications furnished by the Bidder are assumed to be included in the Bidder's submittal.

Bidder should note on their submittal any installation(s) to the equipment that will be performed by the vendor instead of the manufacturer.

Failure to note any specification exceptions, manufacturer specification alterations, and/or vendor installations prior to award may result in rejection of the equipment at the time of delivery.

**THE NUMBER OF DELIVERY DAYS AFTER RECEIPT OF ORDER (ARO) MAY BE USED AS A FACTOR IN THE AWARD.**

## EQUIPMENT SPECIFICATIONS

### NOTICE TO BIDDERS

Bidder should review the detailed "Equipment Specification" completely and respond to the compliance question at the end of each section by marking "X", in the space provided, for "Yes" or "No". Mark "Yes" to indicate that the equipment bid meets the section exactly as specified. Mark "No" if there are exceptions to any part of that section. Exceptions/deviations to any part of the specification are to be detailed on the "Bidder's Exceptions" page of this specification.

**IN ORDER TO BE CONSIDERED FOR AWARD, BIDDER SHOULD RETURN THIS SPECIFICATION, COMPLETED IN FULL, WITH THEIR BID SUBMITTAL.**

**Note: All values listed below are minimums unless noted otherwise.**

**1. General Description:** These specifications describe a 4 wheel drive rubber tired combination backhoe loader equipped with roll over protection and a sunshade.

Comply:    Yes    No

**1.2. Engine**

  1.2.1. 87 HP

  1.2.2. Turbocharged diesel

  1.2.3. Liquid cooled

Comply:    Yes    No

**1.3. Transmission:** Four (4) speeds forward and three (3) speeds reverse

Comply:    Yes    No

**1.4. Front Axle:** Mechanical front wheel drive

Comply:    Yes    No

**1.5. Hydraulic Pump**

  1.5.1. High volume

  1.5.2. 28 GPM

Comply:    Yes    No

**1.6. Steering:** Hydrostatic power steering

Comply:    Yes    No

## EQUIPMENT SPECIFICATIONS

### 1.7. Loader

- 1.7.1. 1 CY, front end
- 1.7.2. 5,780 lbs. Full height lifting capacity
- 1.7.3. Approximately 8' dumping height
- 1.7.4. Complete with bucket and controls
- 1.7.5. Loader to include reversible bolt-on cutting edge

Comply:    Yes    No

### 1.8. Electrical System

- 1.8.1. 12 volt
- 1.8.2. Maintenance free battery: 850 CCA battery
- 1.8.3. Battery disconnect switch

Comply:    Yes    No

### 1.9. Backhoe

- 1.9.1. 17'9" Reach from swing pivot
- 1.9.2. 2,000 lbs. lifting capacity
- 1.9.3. Complete with joystick controls
- 1.9.4. 24" basic digging bucket

Comply:    Yes    No

### 1.10. Seat: Reversible, two-way

Comply:    Yes    No

### 1.11. Tires

- 1.11.1. 19.5 LX 24, 8ply, tractor type rear
- 1.11.2. 11L-16, 8 ply front

Comply:    Yes    No

### 1.12. Accessories

- 1.12.1. Include all accessories needed for normal operation
- 1.12.2. Reversible outrigger feet
- 1.12.3. Tachometer
- 1.12.4. Hour meter
- 1.12.5. Headlights
- 1.12.6. Tail stop lights
- 1.12.7. Seat belt
- 1.12.8. Backup alarm
- 1.12.9. Horn
- 1.12.10. Fire extinguisher

## EQUIPMENT SPECIFICATIONS

**1.12.11.** SMV triangle

Comply:    Yes    No

**1.13.** Warranty

**1.13.1.** One year full coverage at nearest authorized location

Comply:    Yes    No

# BIDDER'S EXCEPTIONS

**Instructions:** Bidder should note all exceptions in space provided below. List the detail number from the aforementioned specification in the column to the left and the exception in the column to the right. Responses may be typed or hand-written. Handwritten responses must be legible. If additional space is needed, please print a duplicate copy of this sheet. "Bidder's Exceptions" page(s) should be returned with the bid submittal.

## Examples:

1.6 Engine has 325 horsepower

1.18.3      Batteries have 2000 CCA combined.

2.2.8 Crossmembers are 4" channel on 12" centers.